

POWER SUPPLY CONNECTION STRUCTURE DEVICE

NOTICE OF COPYRIGHT

[0001] A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to any reproduction by anyone of the patent disclosure, as it appears in the United States Patent and Trademark Office patent files or records, but otherwise reserves all copyright rights whatsoever.

BACKGROUND OF THE PRESENT INVENTION

FIELD OF INVENTION

[0002] The present invention relates to a power supply connection structure device, and more particularly to a power supply connection structure device which is safe to use, waterproof, and prevents electric shock to an individual.

DESCRIPTION OF RELATED ARTS

[0003] A power supply connection structure device is generally electrically connected to a power supply so that an electrical appliance is supplied with electric power for working. A conventional power supply connection structure device can be a lamp socket, a three-hole power cord, or an electric socket. The lamp socket, which is a two-phase power connection device, generally includes two plug columns which are respectively electrically connected to the live wire and the neutral wire. The lamp socket is electrically connected to a lamp for supplying electric power to the lamp. The three-hole power cord, which is a three-phase power connection device generally having three plugholes for coupling with the live wire, neutral wire and the ground wire respectively,

is electrically connected to an electrical appliance for providing power supply. The three-hole power cord is widely used with office equipments, such as computers and printers, household electrical appliances, such as rice cookers and electric water heaters. The two-hole and three-hole electric sockets are also common in our daily lives. However, there are still some potential safety hazards for the conventional power supply connection structure device, especially the problem of waterproof and electric shock to an individual. For example, a curious child may pull off a fluorescent tube of a household desk lamp from its socket and may touch the socket with his or her hands. As for a conventional power cord, they may hold conductive objects such as metal nails, and copper wires, and insert them into the plugholes. These behaviors are very dangerous that may result an electric shock to an individual. On the other hand, since the current power supply connection structure device has no waterproofing capability or feature, when water unintentionally gets into the power supply connection structure device such as a three-hole power cord, the device could be electrically connected to the power source, that is when a person is in contact with the device, an electric shock to the person is easy to take place. Therefore, a power supply device which is waterproof and prevents electric shock to an individual for ensuring its safe use is a common demand in the market.

SUMMARY OF THE PRESENT INVENTION

[0004] The main object of the present invention is to provide a power supply connection structure device which is waterproof, prevents electric shock to an individual, and is safe to use.

[0005] Another object of the present invention is to provide a power supply connection structure device, which comprises a first electrical connection unit, a second electrical connection unit, and a control unit, wherein when only the first electrical connection unit and the second electric connecting unit are connected to the power source, or either the first electrical connection unit or the second electrical connection unit is individually connected to the power source, the electric circuit between the device and the power

source is not electrically connected. However, only when the control unit connects the first electrical connection unit and the second electrical connection unit to the power source, the electric circuit between the first and second electrical connection units and the power source is electrically connected, so that the power supply connection structure device can be used for power supply.

[0006] Another object of the present invention is to provide a power supply connection structure device, wherein the connection of the electric circuit is under control of the control unit. In other words, only when the first and second electrical connection units, and the control unit cooperate, the power supply connection structure device is able to connect to the power source, so that electric shock to an individual is prevented.

[0007] Another object of the present invention is to provide a power supply connection structure device, which is used for electrically connecting an electrical appliance to the power source, wherein the first and second electrical connection units can be the live wire connecting unit and the neutral wire connecting unit respectively while the control unit controls the electrical connection between the live wire connecting unit and the live wire of the power source, and the electrical connection between, the neutral wire connecting unit and the neutral wire of the power source, the live wire connecting unit and the neutral wire connecting unit, are not directly connected to the power source, so that the power supply connection structure device of the present invention can safely electrically connect the electrical appliance to the household or industrial AC power supply.

[0008] Another object of the present invention is to provide a power supply connection structure device, wherein the control unit comprises two micro-switches, when the control unit is activated, the two micro-switches connect the live wire connecting unit and the neutral wire connecting unit to the live wire and the neutral wire respectively, so that the power supply connection structure device is electrically connected to the power source. Therefore, by means of the two micro-switches, only when the control unit is activated, the power supply connection structure device is able to connect with the power source, so that the power supply connection structure device is safe to use.

[0009] Another object of the present invention is to provide a power supply connection structure device, which can be a three-hole power cord, wherein the first electric connection unit includes a live wire plughole and a live wire connection terminal and the second electric connection unit includes a neutral wire plughole and a neutral wire connection terminal. The three-hole power cord further has a ground wire plughole, so that the live wire plughole, the neutral wire plughole and the ground wire plughole are adapted for coupling with the live wire, the neutral wire and the ground wire respectively. The three-hole power cord further comprises an electric circuit arrangement which includes a live wire access terminal, a neutral wire access terminal, and a ground wire access terminal, wherein the control unit electrically connects the live wire connection terminal to the live wire access terminal, and electrically connects the neutral wire connection terminal to the neutral wire access terminal by the two micro-switches, so that, by introducing the control unit, the three-hole power cord is safe to use.

[0010] Another object of the present invention is to provide a power supply connection structure device, wherein the power supply connection structure device can be a three-hole power cord, wherein the control unit, which can be provided at the ground wire plughole, comprises an insulation push member and two actuation members. When the insulation push member is pressed, the two actuation members close the two micro-switches respectively, so that the live wire connection terminal is electrically connected to the live wire access terminal while the neutral wire connection terminal is electrically connected to the neutral wire access terminal. Therefore, when a conductive object is inserted and received in the live wire plughole or the neutral wire plughole, or when there are conductive objects inserting into both of the live wire plughole and the neutral wire plughole, or when there are conductive objects inserting into the ground wire plughole, the electric circuit will not be connected, so that the safe use of the three-hole power cord is ensured.

[0011] Another object of the present invention is to provide a power supply connection structure device, which can be a three-hole power cord, wherein the control unit may further comprise a waterproof seal provided at the insulation member and the inner walls

around the live wire plughole and the neutral wire plughole are also waterproof. The three-hole power cord further comprises a partition arrangement, which has a central hole for receiving the waterproof seal and three communication holes for the live wire connection terminal, the neutral wire connection terminal and the ground wire connection terminal to sealedly pass therethrough respectively. Therefore, even when the live wire plughole, the neutral wire plughole and the ground wire plughole are all filled with water, the water will not pass through the partition arrangement to have contact with the electric circuit arrangement, so that the three-hole power cord is provided with a waterproof effect, and thus electric shock to an individual is prevented.

10 [0012] Another object of the present invention is to provide a power supply connection structure device, which can be a lamp socket for electrically connecting a lamp to a power source, wherein the first electric connection unit and the second electric connection unit can be respectively a live wire plug column and a neutral wire plug column. When one of the live wire plug column and the neutral wire plug column is pressed, or both of the live wire plug column and the neutral wire plug column are pressed, the electric circuit will not connect. The electric circuit will only connect when the control unit is activated, so that it is safe to use and electric shock to an individual is prevented.

20 [0013] Another object of the present invention is to provide a power supply connection structure device, which can be an electric socket for electrically connecting an electrical appliance to a power source, wherein the first electric connection unit and the second electric connection unit can be a live wire connection unit and a neutral connection unit respectively, and that when a conductive object is inserted and received in one of or both of the plugholes of the live wire connection unit and a neutral connection unit, the electric circuit will not be connected. The electric circuit will only connect when the control unit is activated, so that it is safe to use and electric shock to an individual is prevented.

[0014] Another object of the present invention is to provide a power supply connection structure device, which can be an electric socket, wherein the control unit, which is provided at the ground wire plughole, further provides a hook releasing mechanism, and

that only when a plug pin of a standard plug is inserted and received in the ground wire plughole, the push member will be pushed to actuate the micro-switches, so that the operation safety will further be ensured.

[0015] Another object of the present invention is to provide a power supply connection structure device, wherein the structure is simple, the manufacturing cost is low, and it is suitable for mass production.

[0016] Additional advantages and features of the invention will become apparent from the description which follows, and may be realized by means of the instrumentalities and combinations particular point out in the appended claims.

[0017] According to the present invention, the foregoing and other objects and advantages are attained by a power supply connection structure device for electrically connecting an electrical appliance to a power source, comprising a first electric connection unit, a second electric connection unit, and a control unit which shifts between an idle state, in which the first and second electric connection units are not connected to the power source, and an activation state, in which the control unit electrically connect the first and second control units to the power source, so as to electrically connect the power supply connection structure device, the power source and the electrical appliance to form an electric circuit, thereby the power source provide a power supply to the electrical appliance.

[0018] Preferably, the first electric connection unit is a live wire connection unit while the second electric connection unit is a neutral wire connection unit.

[0019] Preferably, the power supply connection structure device further comprises an electric circuit arrangement which includes a live wire access terminal and a neural wire access terminal. The control unit comprises two micro-switches, wherein when the control unit is in the activation state, one of the two micro-switches electrically connects the live wire connection unit with the live wire access terminal, and the other micro-switch electrically connects the neutral wire connection unit with the neutral wire access

terminal, thereby the power supply connection structure device, the electrical appliance and the power source are electrically connected to form an electric circuit.

[0020] Preferably, the power supply connection structure device is embodied as a three-hole power cord, wherein the first electric connection unit is a live wire connection unit having a live wire plughole and including a live wire connection terminal, and the
5 second electric connection unit is a neutral wire connection unit having a neutral wire plughole and including a neutral wire connection terminal. The power supply connection structure device further comprises a ground wire connection unit which has a ground wire plughole and includes a ground wire connection terminal, wherein when three plug
10 pins of the electrical appliance are respectively inserted and received in the live wire plughole, the neutral wire plughole and the ground wire plughole, the three plug pins of the electrical appliance are electrically connected to the live wire connection terminal, the neutral wire connection terminal and the ground wire connection terminal respectively.

[0021] Preferably, the power supply connection structure device is embodied as a lamp
15 socket, wherein the electrical appliance is a lighting lamp and the first electric connection unit is a live wire plug column while the second electric connection unit is a neutral wire plug column.

[0022] Preferably, the power supply connection structure device is embodied as a socket, wherein the first electric connection unit is a live wire connection unit having a
20 live wire plughole and including a live wire connection terminal, and the second electric connection unit is a neutral wire connection unit having a neutral wire plughole and including a neutral wire connection terminal. The power supply connection structure device further comprises a ground wire connection unit which has a ground wire plughole and includes a ground wire connection terminal, wherein when three plug pins of the
25 electrical appliance are respectively inserted and received in the live wire plughole, the neutral wire plughole and the ground wire plughole, the three plug pins of the electrical appliance are electrically connected to the live wire connection terminal, the neutral wire connection terminal and the ground wire connection terminal respectively.

[0023] Preferably, the control unit is coupled with the ground wire connection unit.

[0024] Preferably, the control unit comprises a push member and two actuation members, wherein the two actuation members are parallelly and spacedly coupled to the push member. The two micro-switches are respectively coupled to the two actuation members in such a manner that when the two actuation members are driven by the push member to move, the two micro-switches are respectively driven by the two actuation members to switch on. Thereby, the electric circuits between the live and neutral wire connection terminals, and the live and neutral wire access terminals are respectively connected.

[0025] Preferably, the control unit further comprises a reposition arrangement, wherein the two actuation members return to their original positions by means of the reposition arrangement, so that the two micro-switches are respectively driven to switch off by the two actuation members.

[0026] Preferably, the reposition arrangement comprises two springs each having a first end coupled to one of the activation members and a second end coupled to the electric circuit arrangement.

[0027] Preferably, each of the activation members comprises an actuation arm and a drive arm extended from the actuation arm, wherein the actuation arm is driven by the push member and the reposition arrangement to reciprocate. Each of the micro-switches comprises a resilient element and an electric connection element which is an electric conductive element. Each of the micro-switches operates as a switch for electrically connecting the electric circuits between the live and neutral wire connection terminals, and the live and neutral wire access terminals respectively. When the push member is pressed, the actuation arm is pressed by the push member to drive the drive arm to bias against the resilient element, wherein the resilient element forces the electric connection element to move, so as to allow the electric connection elements to electrically connect the electric circuits between the live and neutral wire connection terminals, and the live and neutral wire access terminals respectively.

[0028] Preferably, the control unit further comprises a retention pivot and a retention element pivotally and rotatably coupled to the retention pivot in such a manner that an opening is formed between the retention element and the push member. The retention element is detachably mounted to the push member, wherein when a plug pin is inserted
5 into the opening, the push member is detached from the retention element, so as to drive the activation members to switch on the micro-switches.

[0029] Preferably, the width of the opening is substantially the same as the width of a plug pin of a plug of the electrical appliance.

[0030] Preferably, the retention element comprises a retainer arm and an actuator arm
10 extended from the retainer arm, wherein the actuator arm is detachably coupled with the push member.

[0031] Preferably, the actuator arm provides a groove and the push member provides a hook adapted for detachably engaging with the groove in such manner that the actuator arm is detachably coupled with the push member.

[0032] Preferably, the power supply connection structure device comprises a housing
15 defining a receiving cavity for receiving the control unit and the electric circuit arrangement. The housing comprises a partition arrangement, wherein the live wire plug hole, the neutral wire plughole and the ground wire plughole are formed at a first side of the partition arrangement, and that the electric circuit arrangement is provided at an
20 opposed second side of the partition arrangement. The partition arrangement has a central hole which couples with the control unit, and three communication holes for the live wire connection terminal, the neutral wire connection terminal and the ground wire connection terminal to pass therethrough respectively and to enable the live wire connection terminal, the neutral wire connection terminal and the ground wire connection
25 terminal to be sealedly formed with the partition arrangement.

[0033] Preferably, the control unit further comprises a seal provided in the ground wire plughole, wherein the seal is provided with a positioning member for mounting the push

member, wherein a receiving compartment is formed between the seal and the positioning member. The push member comprises a push arm and a retention arm extended from the push arm and the positioning member comprises a pad body having a positioning hole, wherein the retention arm is capable of inserting into the receiving compartment through the positioning hole.

[0034] Preferably, the seal, the positioning member and the push member are made of waterproof silicon dioxide.

[0035] Preferably, the control unit comprises an activation arm and a stopper arm. The push member is formed with a slot, wherein a first end of the stopper arm is detachably engaged in the slot and a second end of the stopper arm is connected to the activation arm in such a manner that the stopper arm is driven by the activation arm to displace, wherein when coupling with the lighting lamp, the activation arm is pressed to drive the stopper arm to move, so as to detach from the push member, so that the push member applies an pressing force to the activation members to switch on the micro-switches.

[0036] Preferably, each of the micro-switches is a metal resilient plate, wherein the control unit comprises a push member and the micro-switches are coupled to the push member in such a manner that the micro-switches switch on in response to a driving operation of the push member so as to electrically connect the electric circuit between the live wire connection unit and the live wire access terminal, and the electric circuit between the neutral wire connection unit and the neutral wire access terminal respectively.

[0037] According to another aspect of the present invention, the present invention provides a method of manufacturing a power supply connection structure device which comprises the following steps.

[0038] (a) Provide a housing having a live wire plughole, a neutral wire plughole and a ground wire plughole thereon and defining a receiving cavity therein.

[0039] (b) Couple a live wire connecting terminal, a neutral wire connecting terminal and a ground wire connecting terminal with the live wire plughole, the neutral wire plughole and the ground wire plughole respectively, and dispose an electric circuit arrangement in the receiving cavity, wherein the electric circuit arrangement comprises a live wire access terminal and a neutral wire access terminal.

[0040] (c) Configure a control unit comprising two micro-switches, wherein when the two micro-switches switch on, one of the two micro-switches electrically connects the live wire connection terminal with the live wire access terminal and the other micro-switch electrical connects the neutral wire connection terminal with the neutral wire access terminal, so that an electric circuit between the power supply connection structure device, a power source and an electrical appliance is connected.

[0041] According to another aspect of the present invention, the present invention provides a method for electrically connecting an electrical appliance to a power source via a power source connection structure device, wherein the method comprises the following steps.

[0042] (i) Receive three plug pins of the electrical appliance in a live wire plughole, a neutral wire plughole and a ground wire plughole respectively for electrically connecting the three plug pins to a live wire connecting terminal, a neutral wire connecting terminal and a ground wire connecting terminal respectively.

[0043] (ii) Drive two actuation members to switch on two micro-switches when one of the three plug pins pushes a push member of a control unit, so as to electrically connect the live wire connection terminal with the live access terminal and to electrically connect the neutral wire connection terminal with the neutral wire access terminal respectively, so that an electric circuit between the power supply connection structure device, the power source, and the electrical appliance is connected.

[0044] The present invention is advantageous in that the two electric connection units are not directly connected to the power source, but is under control of the control unit, so

that when both of the two electric connection units and the control unit are in operation, the electric circuit can be connected, and thus electric shock to an individual is prevented. In addition, the introduction of the partition arrangement and the waterproof seal of the control unit enable a waterproof effect of the power supply connection structure device of the present invention.

[0045] Still further objects and advantages will become apparent from a consideration of the ensuing description and drawings.

[0046] These and other objectives, features, and advantages of the present invention will become apparent from the following detailed description, the accompanying drawings, and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0047] Fig. 1 is a perspective view of a power supply connection structure device according to a first preferred embodiment of the present invention.

[0048] Fig. 2 is an exploded view of the power supply connection structure device according to the above first preferred embodiment of the present invention.

[0049] Fig. 3 is a rear view of the power supply connection structure device according to the above first preferred embodiment of the present invention.

[0050] Fig. 4 is a schematic view illustrating the power supply connection structure device in an idle state according to the above first preferred embodiment of the present invention.

[0051] Fig. 5 is a schematic view illustrating the power supply connection structure device in an activation state according to the above first preferred embodiment of the present invention.

[0052] Fig. 6 is a schematic view illustrating the partition arrangement of the power supply connection structure device according to the above first preferred embodiment of the present invention.

5 [0053] Fig. 7 an exploded view illustrating the control unit of the power supply connection structure device according to the above first preferred embodiment of the present invention.

[0054] Fig. 8 is a perspective view of a power supply connection structure device according to a second preferred embodiment of the present invention.

10 [0055] Fig. 9 is an exploded view of the power supply connection structure device according to the above second preferred embodiment of the present invention.

[0056] Fig. 10 is a schematic view illustrating the power supply connection structure device in an activation state according to the above second preferred embodiment of the present invention.

15 [0057] Fig. 11 is a perspective view of a power supply connection structure device according to an alternative mode of the above second preferred embodiment of the present invention.

[0058] Fig. 12 is an exploded view of the power supply connection structure device according to the alternative mode of the above second preferred embodiment of the present invention.

20 [0059] Fig. 13 a schematic view illustrating the power supply connection structure device in an activation state according to the alternative mode of the above second preferred embodiment of the present invention.

[0060] Fig. 14 is a perspective view of a power supply connection structure device according to another alternative mode of the above second preferred embodiment of the present invention.

5 [0061] Fig. 15 is a sectional view of the power supply connection structure device according to another alternative mode of the above second preferred embodiment of the present invention.

[0062] Fig. 16 is a schematic view illustrating the partition arrangement of the housing of the power supply connection structure device according to another alternative mode of the above second preferred embodiment of the present invention.

10 [0063] Fig. 17 is a perspective view of a power supply connection structure device according to a third preferred embodiment of the present invention.

[0064] Fig. 18 is an exploded view of the power supply connection structure device according to the above third preferred embodiment of the present invention.

15 [0065] Fig. 19 is a schematic view illustrating the plug pin of an electrical appliance being about to insert into the plughole of the power supply connection structure device according to the above third preferred embodiment of the present invention.

[0066] Fig. 20 is a schematic view illustrating the plug pin of an electrical appliance being inserted into the plughole of the power supply connection structure device according to the above third preferred embodiment of the present invention.

20 [0067] Fig. 21 is a perspective view of a power supply connection structure device according to another alternative mode of the above third preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0068] The following description is disclosed to enable any person skilled in the art to make and use the present invention. Preferred embodiments are provided in the following description only as examples and modifications will be apparent to those skilled in the art. The general principles defined in the following description would be applied to other embodiments, alternatives, modifications, equivalents, and applications without departing from the spirit and scope of the present invention.

[0069] Referring to Figs. 1 to 7 of the drawings, a power supply connection structure device, which is used for electrically connecting an electrical appliance to a power source, according to a first preferred embodiment of the present invention is illustrated. The power supply connection structure device comprises a first electric connection unit **10**, a second electric connection unit **20** and a control unit **30**. When the control unit **30** is in an activation state, the control unit **30** electrically connects the first and second electric connection units **10** and **20** to the power source, so that an electric circuit between the power supply connection structure device, the electrical appliance and the power source is connected, and thus the power source can supply electric power to the electrical appliance.

[0070] The first and second electric connection units **10** and **20** are arranged for electrically connecting to the power source for forming the electric circuit. The power source may be a DC electric power source, so that the first and second electric connection units **10** and **20** are respectively arranged for electrically connecting to the positive and negative electrodes of the DC electric power source. According to this preferred embodiment of the present invention, the power source is an AC electric power source, and the first and second electric connection units **10** and **20** are respectively a live wire connection unit and a neutral wire connection unit.

[0071] The power supply connection structure device further comprises an electric circuit arrangement **40** which may be embodied as an electric circuit board and includes a live wire access terminal **41** and a neutral wire access terminal **42**. The control unit **30**

controls two micro-switches **32**. When the control unit **30** is in the activation state, the two micro-switches **32** electrically connect the live wire connection unit **10** with the live wire access terminal **41**, and the neutral wire connection unit **20** with the neutral wire access terminal **42** respectively, so that the power supply connection structure device, the electrical appliance and the power source are electrically connected with each other to form an electric circuit.

[0072] More specifically, the power supply connection structure device of this preferred embodiment of the present invention can be, but not limited to, a three-hole power cord which is widely used with office equipments, such as computers, and printers, and household electrical appliances, such as rice cookers and electric water heaters. The first electric connection unit **10** is a live wire connection unit having a live wire plughole **11** and including a live wire connection terminal **12** electrically connected to the live wire plughole 11. The second electric connection unit **20** is a neutral wire connection unit having a neutral wire plughole **21** and including a neutral wire connection terminal **22** electrically connected to the neutral wire plughole 21. Accordingly, the three-hole power cord, which is a three-phase electric power cord, further comprises a ground wire connection unit **50** which has a ground wire plughole **51** and includes a ground wire connection terminal **52** electrically connected to the ground wire plughole 51. Thus, when three plug pins of an electrical appliance are respectively inserted and received in the live wire plughole **11**, the neutral wire plughole **21** and the ground wire plughole **51**, the plug pins of the electrical appliance are respectively electrically connected to the live wire connection terminal **12**, the neutral wire connection terminal **22** and the ground wire connection terminal **52**.

[0073] According to this preferred embodiment, the power supply connection structure device can be embodied as the three-hole power cord, wherein when the control unit is in the activation state, the control unit **30** electrically connects the live wire connection unit **10** and the neutral wire connection unit **20** to the power source, so that the electric circuit between the power supply connection structure device, the electrical appliance and the

power source is connected, and thus the power source can supply electric power to the electrical appliance.

[0074] Accordingly, the three-hole power cord also comprises the electric circuit arrangement **40** which includes the live wire access terminal **41** and the neutral wire access terminal **42**. The control unit **30** controls the two micro-switches **32**. When the control unit **30** is in the activation state, one of the two micro-switches **32** electrically connect the live wire connection unit **10** with the live wire access terminal **41**, and the other micro-switch **32** electrically connects the neutral wire connection unit **20** with the neutral wire access terminal **42**, so that the electric circuit between the power supply connection structure device, the electrical appliance and the power source is in electrical connection state.

[0075] More specifically, as shown in Figs. 4 and 5 of the drawings, when the control unit **30** is an idle state, even though the plug pins are inserted and received in the live wire plughole **11** and the neutral wire plughole **21** respectively and the plug pins are electrically connected to the live wire connection terminal **12** and the neutral wire connection terminal **22** respectively, as long as the live wire connection terminal **12** and the neutral wire connection terminal **22** are not electrically connected to the live wire access terminal **41** and the neutral wire access terminal **42** of the electric circuit arrangement **40** respectively, the electric circuit thereof is not electrically connected.

[0076] When the control unit **30** is in the activation state, the live wire connection terminal **12** and the neutral wire connection terminal **22** are electrically connected with the plug pins, and the control unit **30** is arranged to electrically switch on the two micro-switches **31** provided respectively between the live and neutral wire connection terminals **12** and **22** and between the live and neutral wire access terminals **41** and **42** of the electric circuit arrangement **40**, so that the electric circuit between the power supply connection structure device and the electrical appliance is electrically connected. When the power source is electrically connected to the power supply connection structure device, the electrical appliance is supplied with electrical power for operation.

[0077] It is worth mentioning that the mechanism for the control unit **30** to switch on or switch off the two micro-switches can be embodied in various ways. According to this preferred embodiment of the present invention, as shown in Fig. 2 of the drawings, the control unit **30**, which is coupled to the ground wire connection unit **50**, comprises a push member **32** and two actuation members **33** which are capable of providing reciprocating movement. The two actuation members **33** are parallelly and spacedly coupled to the push member **32**. The two micro-switches **31** are respectively coupled to the two actuation members **33**, so that when the two actuation members **33** are driven by said push member **32** to move, the two micro-switches **31** are respectively driven by the two actuation members **33** to switch on, so that the live and neutral wire connection terminals **12** and **22**, and the live and neutral wire access terminals **41** and **42** are electrically connected. It is worth mentioning that the push member **32** can be embodied as a push shaft in this preferred embodiment.

[0078] It is worth mentioning that the control unit **30** further comprises a reposition arrangement **34**. The two actuation members **33** return to their original positions by means of the reposition arrangement **34**, so that the two micro-switches **31** are respectively driven to the switch off state by the two actuation members **33**.

[0079] More specifically, the reposition arrangement **34** is embodied as a resilient arrangement comprising two springs **341**. A first end of each spring **341** is connected to an actuation member **33** and a second end thereof can be connected to the electric circuit arrangement **40** or the housing. Therefore, when a plug pin of the electrical appliance, which is a ground wire connection plug pin in this preferred embodiment, is inserted and received in the ground wire plughole **51**, the push member **32** presses the two actuation members **33** and the two springs are compressed, so that the two micro-switches are switched on to electrically connect the live wire connection terminal **12** with the live wire access terminal **41** and to electrically connect the neutral wire connection terminal **22** with the neutral wire access terminal respectively. When the plug pin of the electrical appliance is removed from the ground wire plughole **51**, the push member **32** is released, and the two springs **341** restore to their original positions respectively, so that the two

actuation members **33** are driven to return to their original positions respectively, and then the two micro-switches **31** are in the switch off state, wherein the live wire connection terminal **12** is electrically disconnected with the live neutral wire access terminal **41** and the neutral wire connection terminal **22** is also electrically disconnected with the neutral wire access terminal **42**.

[0080] In other words, the merely electrical connection between the plug pins of the electrical appliance and the live and neutral wire connection terminals **12** and **22** is not able to switch, i.e. to electrically connect, the electric circuit between the electrical appliance and the power supply connection structure device of the present invention. Only when the control unit **30**, which is coupled to the ground wire connection unit **50**, is activated to switch on the two micro-switches, the electric circuit between the electrical appliance and the power supply connection structure device of the present invention is switched and electrically connected. It is worth mentioning that the push member **32** and the actuation members **33** are preferred to be made of insulation materials.

[0081] Referring to Figs. 4 and 5 of the drawings, more specifically, each of the actuation members **33** comprises an actuation arm **331** and a drive arm **332** extended from the actuation arm **331**. The actuation arm **331** is driven by the push member **32** and the reposition arrangement **34** to reciprocate. Each of the micro-switches **31** may comprise a resilient element **311** which can be a spring and an electric connection element **312** which can be an electric conductive element. One of the micro-switches **31** operates as a switch to electrically connect the live wire connection terminal **12** with the live wire access terminal **41** and the other micro-switch **31** also operates as a switch to electrically connect the neutral wire connection terminal **22** with the live and neutral wire access terminal **42**.

[0082] In other words, when the push member **32** is pressed, the actuation arms **331** are driven by the push member **32** to drive the drive arms **332** to respectively press the resilient elements **311**, and then the resilient elements **311** respectively drive the electric connection elements **312** to move, so as to electrically connect the live wire connection

terminal 12 with the live wire access terminal 41 and to electrically connect the neutral wire connection terminal 22 with the neutral wire access terminal 42 respectively.

[0083] Referring to Fig. 3 of the drawings, the electric circuit arrangement 40 further comprises a first electric connection arrangement 43 which is electrically coupled to the live and neutral wire connection terminals 12 and 22 and is electrically connected to a first indication lamp. When the three-hole power cord is electrically connected to the power source and the electrical appliance, and the plug pins of the electrical appliance are respectively inserted and received in the live and neutral wire plugholes 11 and 21, the first indication lamp will illuminate when the first electric connection arrangement 43 is electrically connected without the operation of the control unit 30. The electric circuit arrangement 40 further comprises a second electric connection arrangement 44 which is coupled to the live and neutral wire access terminals 41 and 42 of the electric circuit arrangement 40, and a second indication lamp is electrically connected to the second electric connection arrangement 44, so that when the control unit 30 is operated to switch on the micro-switches 31, the second indication lamp will illuminate when the second electric connection arrangement 40 is electrically connected with the power source.

[0084] For example, the first indication lamp can be a green signal lamp while the second indication lamp can be a red signal lamp. When there are electric conductive objects inserting into the live and neutral wire plugholes 11 and 21, the green signal lamp will provide a green light illumination, but the electric circuit between the device and the power source is not connected, so that electric shock to an individual is prevented. When the live and neutral wire plugholes 11 and 21 receive inserting electric conductive objects and simultaneously that there is a rigid object pushing the push member 32 for switching on the two micro-switches 31, the electric circuit between the device and the power source will be electrically connected and the red signal lamp will provide a red light illumination.

[0085] In other words, in comparison with the conventional three-hole power cord, the three-hole power cord of the present invention is provided with an additional control unit 30. Only under the operation of the control unit 30, the three-hole power cord can

electrically connect to the live and neutral wires, so that the electric circuit between the power source, the three-hole power cord, and the electrical appliance can be electrically connected, and thus the electrical appliance is able to be provided with power supply. Because of the arrangement of the control unit **30**, when a child inserts electric
5 conductive objects into the live and neutral wire plugholes **11** and **21**, the electric circuit will not be connected, so that electric shock to any individual is prevented. In addition, the control unit **30** is coupled to the ground wire connection unit, providing a compact and integral structure.

[0086] It is worth mentioning that the power supply connection structure device is
10 provided with a waterproof ability. Referring to Fig. 6 of the drawings, the power supply connection structure device, i.e. the three-hole power cord, comprises a housing **60** defining a receiving cavity **61** for receiving the control unit **30** and the electric circuit arrangement **40**.

[0087] The housing **60** comprises a partition arrangement **62**, wherein the live wire
15 plughole **11**, the neutral wire plughole **21**, and the ground wire plughole **51** are formed at a first side of the partition arrangement **62**, while the electric circuit arrangement **40** is provided at a second side of the partition arrangement **62** opposing to the first side thereof. The partition arrangement **62** has a central hole **621** for coupling with the control unit **31**, and three communication holes **622** for the live wire connection terminal **12**, the
20 neutral wire connection terminal **22**, and the ground wire connection terminal **52** to sealedly pass therethrough.

[0088] Referring to Fig. 7 of the drawings, the control unit **30** further comprises a seal
35 provided in the ground wire plughole **51**. Preferably, the seal **35** is made of waterproof silicon dioxide. The seal **35** can be connected to a positioning member **36** for
25 mounting the push member **32**. A receiving compartment **351** is formed between the seal **35** and the positioning member **36**.

[0089] More specifically, the push member **32** comprises a push arm **311** and a retention arm **322** extended from the push arm **311**. The positioning member **36** can be a

positioning pad comprising a pad body **361** having a positioning hole **362**, and the retention arm **322** can be inserted into the receiving compartment **351** through the positioning hole **362**. When a plug pin of the electrical appliance is inserted and received in the ground wire plughole **51**, the plug pin presses the retention arm **322** to move inwardly, so that the push arm **321** applies a pushing force to the two actuation members **33** so as to respectively switch on the two micro-switches **31**.

[0090] Since the end portion of the seal **35** adjacent to the ground wire plughole is sealed, even though the three-hole power cord is immersed in water, water will not pass through the central hole **621** of the partition arrangement **62** and reach the opposing side adjacent to the electric circuit arrangement **40**. In addition, the inner walls around the live wire plughole **11**, the neutral wire plughole **21** and the ground wire plughole **51** are all formed with waterproof materials such as plastic materials. The live wire connecting terminal **12**, the neutral wire connecting terminal **22** and the ground wire connecting terminal **52** pass through the communicating holes respectively and are sealedly coupled with the partition arrangement **62**, and thus when the live wire plughole **11**, the neutral wire plughole **21** and the ground wire plughole **51** are all filled with water, the water will not pass through the partition arrangement **62** and have contact with the electric circuit arrangement **40**, so that the three-hole power cord is provided with a waterproof effect, and thus electric shock to any individual is prevented.

[0091] Accordingly, a manufacturing method of the power supply connection structure device of the present invention, adapted for electrically connecting the electrical appliance to the power source, and embodied as the three-hole power cord, comprises the following steps.

[0092] (a) Provide a housing **60** having a live wire plughole **11**, a neutral wire plughole **21** and a ground wire plughole **51** thereon and defining a receiving cavity **61** therein.

[0093] (b) Couple a live wire connecting terminal **12**, a neutral wire connecting terminal **22** and a ground wire connecting terminal **52** with the live wire plughole **11**, the neutral wire plughole **21** and the ground wire plughole **51** respectively, and dispose an

electric circuit arrangement **40** in the receiving cavity **61**, wherein the electric circuit arrangement **40** comprises a live wire access terminal **41** and a neutral wire access terminal **42**.

[0094] (c) Configure a control unit **30** comprising two micro-switches **31**, wherein
5 when the two micro-switches **31** are switched on, one of the two micro-switches **31** electrically connects the live wire connection terminal **12** with the live neutral wire access terminal **41** and the other micro-switch **31** electrical connects the neutral wire access terminal **22** with the neutral wire access terminal, so that the electric circuit between the power supply connection structure device, the power source, and the
10 electrical appliance is electrically connected.

[0095] In the step (c), the control unit **30**, which is coupled to the ground wire connection unit **50**, comprises a push member **32** and two actuation members **33** which are capable of moving reciprocatingly. The two actuation members **33** are parallelly and spacedly coupled to the push member **32**. The two micro-switches **31** are respectively
15 coupled to the two actuation members **33**, so that when the two actuation members **33** are driven by said push member **32** to move, the two micro-switches **31** are respectively driven by the two actuation members **33** to switch on. The control unit **30** further comprises a reposition arrangement **34**. The two actuation members **33** return to their original positions by means of the reposition arrangement **34**, so that the two micro-
20 switches **31** are respectively driven to switch off by the two actuation members **33**.

[0096] More specifically, the reposition arrangement **34** is a resilient arrangement comprising two springs **341**. A first end of each spring **341** is connected to an actuation member **33** and a second end thereof can be connected to the electric circuit arrangement **40** or the housing. Therefore, when the push member **32** presses the two actuation
25 members **33**, the two springs are compressed, so that the two micro-switches are switched on to electrically connect the live wire connection terminal **12** with the live wire access terminal **41** and to electrically connect the neutral wire connection terminals **22** with the neutral wire access terminals **42** respectively.

[0097] In the step (c), the control unit **30** further comprises a seal **35** provided in the ground wire plughole **51**. Preferably, the seal **35** is made of waterproof silicon dioxide. The seal **35** can be connected to a positioning member **36** for mounting the push member **32**. A receiving compartment **351** may be formed between the seal **35** and the positioning member **36**. The push member **32** comprises a push arm **311** and a retention arm **322** extended from the push arm **311**. The positioning member **36** can be a positioning pad comprising a pad body **361** having a positioning hole **362**, and the retention arm **322** can be inserted and received in the receiving compartment **351** through the positioning hole **362**. When a plug pin of the electrical appliance is inserted and received in the ground wire plughole **51**, the plug pin press the retention arm **322** to move inwardly, so that the push arm **321** applies a pushing force to the two actuation members **33** so as to switch on the two micro-switches **31**.

[0098] Therefore, when the power supply connection structure device of the present invention is embodied as the three-hole power cord, a method for electrically connecting an electrical appliance to a power source is provided, wherein the method comprises the following steps.

[0099] (i) Receive three plug pins of the electrical appliance in the live wire plughole **11**, the neutral wire plughole **21** and the ground wire plughole **51** respectively for electrically connecting the three plug pins to the live wire connecting terminal **12**, the neutral wire connecting terminal **22** and the ground wire connecting terminal **52** respectively.

[00100] (ii) Drive two actuation members **33** to switch on the two micro-switches **31** when one of the three plug pins pushes the push member **32** of the control unit **30**, so as to electrically connect the live wire connection terminal **12** with the live wire access terminal **41** and to electrically connect the neutral wire connection terminal **22** with the neutral wire access terminal **42** respectively, so that the electric circuit between the power supply connection structure device, the power source, and the electrical appliance is connected.

[00101] When the three plug pins of the electrical appliance get out of the live wire plughole **11**, the neutral wire plughole **21**, and the ground wire plughole **51** respectively, the push member **32** will return to its original position under the control of the reposition arrangement **34**.

5 [00102] Referring to Figs. 8 to 10 of the drawings, the power supply connection structure device according to a second preferred embodiment of the present invention embodied as a lamp socket, which is a two-phase power supply connection structure device for electrically connecting a lighting lamp to a power source which can be an AC electric power source, is illustrated. The power supply connection structure device of the
10 second preferred embodiment comprises a first electric connection unit **10A**, a second electric connection unit **20A** and a control unit **30A**. When the control unit **30A** is in an activation state, the control unit **30A** electrically connects the first and second electric connection units **10A** and **20A** to the power source, so that the electric circuit between the power supply connection structure device, the lighting lamp and the power source is
15 connected, and thus the power source supplies electric power to the lighting lamp.

[00103] Referring to Fig. 9 of the drawings, the first and second electric connection units **10A** and **20A** are respectively a live wire plug column and a neutral wire plug column which are pressed to electrically connect to a live wire connection terminal **12A** and a neutral connection terminal **22A** respectively. The power supply connection
20 structure device further comprises an electric circuit arrangement **40A** including a live wire access terminal **41A** and a neutral wire access terminal **42A**. The control unit **30A** controls two micro-switches **32A**. When the control unit **30A** is in the activation state, the two micro-switches **32A** electrically connect the live wire connection unit **10A** with the live wire access terminal **41A**, and electrically connect the neutral wire connection
25 unit **20A** with the neutral wire access terminal **42A**, so that the electric circuit between the power supply connection structure device, the lighting lamp and the power source is connected.

[00104] Referring to Figs. 11 to 13 of the drawings, according to an alternative mode of the present invention, the control unit **30B** further comprises a push member **32B** and two

actuation members **33B** which are capable of providing reciprocating movement. The two actuation members **33B** are parallelly and spacedly coupled to the push member **32B**. The two micro-switches **31B** are respectively coupled to the two actuation members **33B** in such a manner that when the two actuation members **33B** are driven by said push member **32B** to move, the two micro-switches **31B** are respectively driven by the two actuation members **33B** to switch on, so that the live wire connection terminal **12B** is electrically connected with the live wire access terminal **41B** and the neutral wire connection terminal **22B** is electrically connect with the live and neutral wire access terminal **42B** respectively. It is worth mentioning that the push member **32B** can be embodied as a push shaft in this second preferred embodiment.

[00105] It is worth mentioning that the control unit **30B** further comprises a reposition arrangement **34B**, as shown in Fig.12 of the drawings. The two actuation members **33B** return to their original positions by means of the reposition arrangement **34B**, so that the two micro-switches **31B** are respectively driven to be switched off by the two actuation members **33B**. The first and second electric connection unit **10B** and **20B**, i.e. the live wire plug column and the neutral wire plug column, are also respectively coupled to a spring member **70B**.

[00106] More specifically, the reposition arrangement **34B** is a resilient arrangement comprising two springs **341B**. A first end of each spring **341B** is connected to an actuation member **33B** and a second end thereof can be connected to the electric circuit arrangement **40B** or the housing. Therefore, when the plugholes of the lighting lamp are respectively coupled with the first and second plug columns, the push member **32B** presses the two actuation members **33B** and the two springs are compressed, so that the two micro-switches are switched on to electrically connect the live wire connection terminal **12B** with the live wire access terminal **41B** and to electrically connect the neutral wire connection terminal **22B** with the neutral wire access terminal **42B** respectively. When the lighting lamp is detached from the lamp socket, the push member **32B** is released and the two springs **341B** restore to their original positions respectively, wherein the two actuation members **33B** are driven to return to their original positions

respectively, and then the two micro-switches **31B** are switched off, so that the live wire connection terminal **12B** is electrically disconnected with the live wire access terminal **41B** and the neutral wire connection terminal **22B** is also electrically disconnected with the neutral wire access terminal **42B**.

5 [00107] Referring to Figs. 14 to 16 of the drawings, a control unit **30C** according to another preferred embodiment of the present invention is illustrated. The control unit **30C** comprises an activation mechanism. More specifically, the control unit comprises an activation arm **37C** and a stopper arm **38C**. The push member **32C** has a slot **323C**, wherein a first end of the stopper arm **38C** is detachably coupled in the slot **323C**. A
10 second end of the stopper arm **38C** can be vertically connected to the activation arm **37C** in such a manner that the stopper arm **38C** can be driven by the activation arm **37C** to displace. Therefore, when coupling with the lighting lamp, the activation arm **37C** is pressed to drive the stopper arm to move to detach from the push member **32C**, so that the push member **32C** applies an pressing force to the activation members **33C** to switch
15 on the micro-switches, so that a safe use of the lamp socket is further ensured and electric shock to any individual is prevented.

[00108] In addition, the lamp socket **60C** comprises a housing **60C** which includes a partition arrangement **62C** made of waterproof material. The electric circuit arrangement **40C** and the plug columns of the lamp socket are provided at two opposing sides of the
20 partition arrangement **62C**. In addition, the housing **60C** may further comprise a plurality of waterproof silicon dioxide seal **63C** for preventing water from having access to the side of the lamp socket which is adjacent to the electric circuit arrangement **40C**, so that the lamp socket is provided with a waterproof ability.

[00109] Referring to Figs. 17 to 20 of the drawings, a power supply connection structure device embodied as an electric socket according to a third preferred embodiment of the
25 present invention is illustrated. Preferably, the electric socket can be a three-hole electric socket. The power supply connection structure device comprises a first electric connection unit **10D**, a second electric connection unit **20D** and a control unit **30D**. When the control unit **30D** is in an activation state, the control unit **30D** electrically

connects the first and second electric connection units **10D** and **20D** to the power source, so that the electric circuit between the power supply connection structure device, the electrical appliance and the power source is connected, and thus the power source supplies electric power to the electrical appliance.

5 [00110] The first electric connection unit **10D** is a live wire connection unit having a live wire plughole **11D** and including a live wire connection terminal **12D**. The second electric connection unit **20D** is a neutral wire connection unit having a neutral wire plughole **21D** and including a neutral wire connection terminal **22D**. Accordingly, the three-hole electric socket, which is a three-phase electric socket, further comprises a
10 ground wire connection unit **50D** which has a ground wire plughole **51D** and includes a ground wire connection terminal **52D**. Thus, as shown in Fig. 20 of the drawings, when the plug pins of the electrical appliances are respectively inserted and received in the live wire plughole **11D**, the neutral wire plughole **21D** and the ground wire plughole **51D**, the plug pins of the electrical appliances are electrically connected to the live wire
15 connection terminal **12D**, the neutral wire connection terminal **22D** and the ground wire connection terminal **52D** respectively.

[00111] The first and second electric connection units **10D** and **20D** are arranged for electrically connecting to the power source for forming the electric circuit. The power source may be a DC electric power source, so that the first and second electric connection
20 units **10D** and **20D** are respectively arranged for electrically connecting to the positive and negative electrodes of the DC electric power source. According to this preferred embodiment of the present invention, the power source is an AC electric power source, and the first and second electric connection units **10D** and **20D** are respectively a live wire connection unit and a neutral wire connection unit.

25 [00112] In this embodiment, the power supply connection structure device further comprises an electric circuit arrangement **40D** which may be embodied as an electric circuit board and includes a live wire access terminal **41D** and a neutral wire access terminal **42D**. The control unit **30D** controls two micro-switches **32D**. When the control unit **30** is in the activation state, one of the two micro-switches **32D** electrically connects

the live wire connection unit **10D** with the live wire access terminal **41D**, and the other micro-switch **32D** electrically connects the neutral wire connection unit **20D** with the neutral wire access terminal **42D**, so that the electric circuit between the power supply connection structure device, the electrical appliance and the power source is connected.

5 [00113] The first electric connection unit **10D** is a live wire connection unit having a live wire plughole **11D** and including a live wire connection terminal **12D**. The second electric connection unit **20D** is a neutral wire connection unit having a neutral wire plughole **21D** and including a neutral wire connection terminal **22D**. Accordingly, the three-hole electric socket, which is a three-phase electric socket, further comprises a
10 ground wire connection unit **50D** which has a ground wire plughole **51D** and includes a ground wire connection terminal **52D**. Thus, when the plug pins of the electrical appliances are respectively inserted and received in the live wire plughole **11D**, the neutral wire plughole **21D** and the ground wire plughole **51D**, the plug pins of the electrical appliances are respectively electrically connected to the live wire connection
15 terminal **12D**, the neutral wire connection terminal **22D** and the ground wire connection terminal **52D**.

[00114] Accordingly, the three-hole electric socket further comprises an electric circuit arrangement **40D** which includes a live wire access terminal **41D** and a neutral wire access terminal **42D**. The control unit **30D** controls two micro-switches **32D**. When the
20 control unit **30D** is in the activation state, one of the two micro-switches **32D** electrically connects the live wire connection unit **10D** with the live wire access terminal **41D**, and the other micro-switch **32D** electrically connects the neutral wire connection unit **20D** with the neutral wire access terminal **42D** (similar to the above first preferred embodiment), so that the electric circuit between the power supply connection structure
25 device, the electrical appliance and the power source is connected.

[00115] More specifically, as shown in Figs. 19 and 20 of the drawings, when the control unit **30D** is an idle state, and the plug pins are merely inserted and received in the live wire plughole **11D** and the neutral wire plughole **21D**, the plug pins are respectively electrically connected to the live wire connection terminal **12D** and the neutral wire

connection terminal **22D**. However, the live wire connection terminal **12D** and the neutral wire connection terminal **22D** are not respectively electrically connected to the live wire access terminal **41D** and the neutral wire access terminal **42D** of the electric circuit arrangement **40D**, so that the electric circuit between the power supply connection structure device, the electrical appliance and the power source is not electrically connected.

[00116] When the control unit **30D** is in the activation state, the live wire connection terminal **12D** and the neutral wire connection terminal **22D** are respectively electrically connected to the plug pins, and the control unit **30D** is arranged for switching on the two micro-switches **31D** between the live and neutral wire connection terminals **12D** and **22D**, and the live and neutral wire access terminals **41D** and **42D** of the electric circuit arrangement **40D** respectively, so that the electric circuit between the power supply connection structure device and the electrical appliance is connected. When the power source is electrically connected to the power supply connection structure device, the electrical appliance is supplied with electric power for operation.

[00117] It is worth mentioning that the mechanism for the control unit **30D** to switch on or switch off the two micro-switches **31D** can be embodied in various ways. According to this preferred embodiment of the present invention, as shown in Figs. 17-20 of the drawings, the control unit **30D** coupled to the ground wire connection unit **50D** comprises a push member **32D** and two actuation members **33D** which are capable of providing reciprocating movement. The two actuation members **33D** are parallelly and spacedly coupled to the push member **32D**. The two micro-switches **31D** are respectively coupled to the two actuation members **33D**, so that when the two actuation members **33D** are driven by said push member **32D** to move, the two micro-switches **31D** are respectively driven by the two actuation members **33D** to switch on, so that the live wire connection terminal **12D** is electrically connected to the live wire access terminal **41D** and the neutral wire connection terminal **22D** is electrically connected with the neutral wire access terminal **42D**. It is worth mentioning that the push member **32D** can be embodied as a push shaft in this preferred embodiment.

[00118] It is worth mentioning that the control unit **30D** provides a hook releasing mechanism. More specifically, the control unit **30D** further comprises a retention pivot **37D** and a retention element **38D** pivotally and rotatably coupled to the retention pivot **37D** in such a manner that an opening **39D** is formed between the retention element **38D** and the push member **32D**. In addition, the retention element **38D** is detachably mounted to push member **32D**, so that when a plug pin is inserted and received in the opening **39D**, the push member **32D** is detached from the retention element **38D**, so as to drive the activation members **33D** to switch on the micro-switches **32A** respectively. The retention element **38D** rotates with respect to the retention pivot **37D** and enables the plug pin to electrically connect to the ground wire connection terminal **52D** at the ground wire connection plughole **51D**.

[00119] Preferably, the width of the opening **39D** can be substantially the same as the width of a plug pin of a plug. In other words, the opening **39D** just allows a plug pin of a plug inserting into the ground wire plughole **51D** for pushing away the retention element **38D** to detach the push member **32D** from the retention element **38D**, wherein the pressing force from the plug pin of the plug can be applied to the activation members **33D** to switch on the micro-switches **31D** respectively.

[00120] Referring to Figs. 19 and 20 of the drawings, the retention element **38D** comprises a retainer arm **381D** and an actuator arm **382D** extended from the retainer arm **381D**. The actuator arm **382D** is detachably coupled with the push member **32D**. The detachable mounting manner can be achieved via various structures. According to this preferred embodiment, the actuator arm **382D** has a groove **383D**. Correspondingly, the push member **32D** is provided with a hook **323D** which is adapted for detachably engaging with the groove **383D**, so that the actuator arm **382D** is detachably mounted with the push member **32D**. When the plug pin of the plug is inserted and received in the opening **39D**, the plug pin forces the hook **323D** to leave the groove **383D**, and the push member **32D** which is pressed by the plug pin pushes inwardly to switch on the micro-switches **31D**.

[00121] Alternatively, the actuator arm **382D** is provided with the hook while the push member **32D** has the groove, so that the actuator arm **382D** is also detachably mounted with the push member **32D**. It is worth mentioning that the hook and the actuator arm **382D** may define a predetermined angle with respect to each other, so that there is no influence for the plug pin of the plug to pass through the opening **39D** to electrically connect to the ground wire connection terminal.

[00122] In addition, the retainer arm **381D** may be provided with a guide arm **384D**, and the push member **32D** has a guide surface **324D** for guiding the plug pin of the plug to slide into the opening **39D**. The retainer arm **381D** may be further provided with a metal resilient plate for retracting the retention element **38D** to its original position.

[00123] Similar to the above first preferred embodiment, the control unit **30D** further comprises a reposition arrangement **34D**. The two actuation members **33D** return to their original positions by means of the reposition arrangement **34D**, so that the two micro-switches **31D** can be respectively driven to switch off by the two actuation members **33D** respectively.

[00124] More specifically, the reposition arrangement **34D** is a resilient arrangement comprising two springs **341D**. A first end of each spring **341D** is connected to an actuation member **33D** and a second end thereof can be connected to the electric circuit arrangement **40D** or the housing. Therefore, when a plug pin of the electrical appliance, which is a ground wire connection plug pin according to this preferred embodiment, is inserted and received in the ground wire plughole **51D**, wherein the push member **32D** presses the two actuation members **33D** and the two springs **341D** are compressed, so that the two micro-switches **31D** are switched on to electrically connect the live wire connection terminal **12D** with the live wire access terminal **41D** and to electrically connects the neutral wire connection terminal **22D** with the neutral wire access terminal **42D** respectively. When the plug pin of the electrical appliance is removed from the ground wire plughole **51D**, the push member **32D** is released and the two springs **341D** restore to their original positions respectively, wherein the two actuation members **33D** are driven to return to their original positions respectively, and then the two micro-

switches **31D** are switched off, so that the live wire connection terminal **12D** is electrically disconnected with the live wire access terminal **41D** and the neutral wire connection terminal **22D** is electrically disconnected with the neutral wire access terminal **42D**.

5 [00125] In other words, the electrical connection between the plug pins of the electrical appliance and the live and neutral wire connection terminals **12D** and **22D** are able to electrically connect the electrical appliance with the power supply connection structure device of the present invention. Only when the control unit **30D** which is coupled to the ground wire connection unit **50D** is activated to switch on the two micro-switches, the
10 electric circuit between the electrical appliance and the power supply connection structure device of the present invention can be electrically connected.

[00126] Accordingly, the push member **32D** and the actuation members **33D** are made of insulation materials. Each of the actuation members comprises an actuation arm **331D** and a drive arm **332D** extended from the actuation arm **331D**. The actuation arm **331D** is
15 driven by the push member **32D** and the reposition arrangement **34D** to reciprocate. Each of the micro-switches **31D** may comprise a resilient element **311D**, which can be a spring, and an electric connection element **312D**, which can be an electric conductive element. One of the micro-switches **31D** operates as a switch to electrically connect the live wire connection terminal **12D** with the live wire access terminal **41D** and the other
20 micro-switch also operates as a switch to electrically connect the neutral wire connection terminal **22D** with the neutral wire access terminal **42D**.

[00127] In other words, when the push member **32D** is pressed, the actuation arm **331D** is driven by the push member **32D** to drive the drive arm **332D** to press the resilient element **311D**, and then the resilient element **311D** drives the electric connection element
25 **312D** to move, so as to electrically connect the live wire connection terminal **12D** with the live wire access terminal **41D** and to electrically connect the neutral wire connection terminal **22D**, and the neutral wire access terminal **42D**.

[00128] Referring to Fig. 21 of the drawings, according to an alternative mode of the above third preferred embodiment of the present invention, the structure is similar to the power supply connection structure device of the above third preferred embodiment of the present invention. The difference is that the push member **32E** directly pushes the micro-
5 switches **31E** to connect the electric circuit. More specifically, each of the micro-switches can be a metal resilient plate and may provide a retaining function by the plastic metal resilient plate. More specifically, when the plug pin of the plug gets out of the plug hole of the electric socket, the push member **32D** return to its original position by means of the resilient retracting ability of the metal resilient plate.

10 [00129] One skilled in the art will understand that the embodiments of the present invention as shown in the drawings and described above is exemplary only and not intended to be limiting.

[00130] It will thus be seen that the objects of the present invention have been fully and effectively accomplished. The embodiments have been shown and described for the
15 purposes of illustrating the functional and structural principles of the present invention and is subject to change without departure from such principles. Therefore, this invention includes all modifications encompassed within the spirit and scope of the following claims.

WHAT IS CLAIMED IS:

1. A power supply connection structure device for electrically connecting an electrical appliance to a power source, comprising:

a first electric connection unit;

5 a second electric connection unit; and

a control unit being shifted between an idle state and an activation state, wherein in said idle state, said first and second electric connection units are not electrically connected to said power source, and that in said activation state, said control unit electrically connects said first and second control units to said power source, so as to
10 electrically connect an electric circuit between said power supply connection structure device, the power source and the electrical appliance, thereby said power source supplies a power supply to said electrical appliance.

2. The power supply connection structure device, as recited in claim 1, wherein said first electric connection unit is a live wire connection unit and said second
15 electric connection unit is a neutral wire connection unit.

3. The power supply connection structure device, as recited in claim 2, wherein said power supply connection structure device further comprises an electric circuit arrangement including a live wire access terminal and a neural wire access terminal, wherein said control unit comprises two micro-switches arranged in such a
20 manner that when said control unit is in said activation state, one of said two micro-switches electrically connects said live wire connection unit with said live wire access terminal, and said other micro-switch electrically connects said neutral wire connection unit with said neutral wire access terminal, thereby said electric circuit between said power supply connection structure device, the electrical appliance and the power source
25 is connected.

4. The power supply connection structure device, as recited in claim 3, wherein said power supply connection structure device is a three-hole power cord, wherein said first electric connection unit is a live wire connection unit having a live wire plughole and including a live wire connection terminal, wherein said second electric
5 connection unit is a neutral wire connection unit having a neutral wire plughole and including a neutral wire connection terminal, wherein said power supply connection structure device further comprises a ground wire connection unit which has a ground wire plughole and includes a ground wire connection terminal, wherein when said live wire plughole, said neutral wire plughole and said ground wire plughole receive three plug
10 pins of the electrical appliance respectively, the three plug pins of the electrical appliance are electrically connected to said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal respectively.

5. The power supply connection structure device, as recited in claim 3, wherein said power supply connection structure device is a lamp socket while the
15 electrical appliance is a lighting lamp, wherein said first electric connection unit is a live wire plug column while said second electric connection unit is a neutral wire plug column.

6. The power supply connection structure device, as recited in claim 3, wherein said power supply connection structure device is an electric socket, wherein said
20 first electric connection unit is a live wire connection unit having a live wire plughole and including a live wire connection terminal, wherein said second electric connection unit is a neutral wire connection unit having a neutral wire plughole and including a neutral wire connection terminal, wherein said power supply connection structure device further comprises a ground wire connection unit which has a ground wire plughole and includes
25 a ground wire connection terminal, wherein when said live wire plughole, said neutral wire plughole and said ground wire plughole receive the three plug pins of the electrical appliance respectively, the three plug pins of the electrical appliance are electrically connected to said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal respectively.

7. The power supply connection structure device, as recited in claim 4 or 6, wherein said control unit is coupled with said ground wire connection unit.

8. The power supply connection structure device, as recited in claim 5, wherein said control unit comprises a push member and two actuation members, wherein
5 said two actuation members are parallelly and spacedly coupled to said push member, wherein said two micro-switches are respectively coupled to said two actuation members in such a manner that when said two actuation members are driven by said push member to move, said two micro-switches are respectively driven by said two actuation members to switch on to electrically connect said live wire connection terminal and said neutral
10 wire connection terminal with said live wire access terminal and said neutral wire access terminal respectively.

9. The power supply connection structure device, as recited in claim 7, wherein said control unit comprises a push member and two actuation members, wherein said two actuation members are parallelly and spacedly coupled to said push member, wherein
15 said two micro-switches are respectively coupled to said two actuation members in such a manner that when said two actuation members are driven by said push member to move, said two micro-switches are respectively driven by said two actuation members to switch on to electrically connect said live wire connection terminal and said neutral wire connection terminal with said live wire access terminal and said neutral wire access
20 terminal respectively.

10. The power supply connection structure device, as recited in claim 9, wherein said control unit further comprises a reposition arrangement, wherein said two actuation members return to original positions thereof by means of said reposition arrangement, wherein said two micro-switches are respectively driven to switch off by
25 said two actuation members.

11. The power supply connection structure device, as recited in claim 10, wherein said reposition arrangement comprises two springs each having a first end

coupled to one of said activation members and a second end coupled to said electric circuit arrangement.

12. The power supply connection structure device, as recited in claim 8, wherein said reposition arrangement comprises two springs each having a first end
5 coupled to one of said activation members and a second end coupled to said electric circuit arrangement.

13. The power supply connection structure device, as recited in claim 11, wherein each of said activation member comprises an actuation arm and a drive arm extended from said actuation arm, wherein said actuation arm is driven by said push
10 member and said reposition arrangement to reciprocate, wherein each of said micro-switches comprises a resilient element and an electric connection element which is an electric conductive element, wherein one of said micro-switches operates as a switch for electrically connecting said live wire connection terminal with said live wire access terminal, and said other micro-switch also operates as a switch for electrically connecting
15 said neutral wire connection terminal with said live and neutral wire access terminal, wherein when said push member is pressed, said actuation arm is pressed by said push member to drive said drive arm to bias against said resilient element, wherein said resilient element forces said electric connection element to move, so as to allow said electric connection elements to electrically connect said live wire connection terminal
20 and said neutral wire connection terminal with said live wire access terminal and said neutral wire access terminal respectively.

14. The power supply connection structure device, as recited in claim 13, wherein said control unit further comprises a retention pivot and a retention element pivotally and rotatably coupled to said retention pivot in such a manner that an opening is
25 formed between said retention element and said push member, wherein said retention element is detachably mounted to push member, wherein when one of the plug pins is inserted into said opening, said push member is detached from said retention element, so as to drive said activation members to switch on said micro-switches.

15. The power supply connection structure device, as recited in claim 14, wherein a width of said opening is substantially the same as a width of the plug pin of a plug of the electrical appliance.

16. The power supply connection structure device, as recited in claim 15,
5 wherein said retention element comprises a retainer arm and an actuator arm extended from said retainer arm, wherein said actuator arm is detachably coupled with said push member.

17. The power supply connection structure device, as recited in claim 16,
10 wherein said actuator arm has a groove and said push member is provided with a hook adapted for detachably engaging with said groove in such a manner that said actuator arm is detachably coupled with said push member.

18. The power supply connection structure device, as recited in claim 2,
15 wherein said power supply connection structure device comprises a housing defining a receiving cavity for receiving said control unit and said electric circuit arrangement, wherein said housing further comprises a partition arrangement, wherein said live wire plug hole, said neutral wire plughole and said ground wire plughole are disposed at a first side of said partition arrangement, wherein said electric circuit arrangement is disposed at an opposing second side of said partition arrangement, wherein said partition arrangement has a central hole which couples with said control unit, and three
20 communication holes for said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal to pass therethrough respectively and enable said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal to be sealedly formed with said partition arrangement.

19. The power supply connection structure device, as recited in claim 11,
25 wherein said power supply connection structure device comprises a housing defining a receiving cavity for receiving said control unit and said electric circuit arrangement, wherein said housing further comprises a partition arrangement, wherein said live wire plug hole, said neutral wire plughole and said ground wire plughole are disposed at a first

side of said partition arrangement, wherein said electric circuit arrangement is disposed at an opposing second side of said partition arrangement, wherein said partition arrangement has a central hole which couples with said control unit, and three communication holes for said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal to pass therethrough respectively and enable said live wire connection terminal, said neutral wire connection terminal and said ground wire connection terminal to be sealedly formed with said partition arrangement.

20. The power supply connection structure device, as recited in claim 19, wherein said control unit further comprises a seal provided in said ground wire plughole, wherein said seal is provided with a positioning member for mounting said push member, wherein a receiving compartment is formed between said seal and said positioning member, wherein said push member comprises a push arm and a retention arm extended from said push arm, wherein said positioning member comprises a pad body having a positioning hole, wherein said retention arm is capable of inserting into said receiving compartment through said positioning hole.

21. The power supply connection structure device, as recited in claim 20, wherein said seal, said positioning member and said push member are made of waterproof silicon dioxide.

22. The power supply connection structure device, as recited in claim 12, wherein said control unit comprises an activation arm and a stopper arm, wherein said push member has a slot and a first end of said stopper arm is detachably engaged in said slot, wherein a second end of said stopper arm is connected to said activation arm in such a manner that said stopper arm is driven by said activation arm to displace, wherein when coupling with said lighting lamp, said activation arm is pressed to drive said stopper arm to move to detach from said push member, so that said push member applies an pressing force to said activation members to switch on said micro-switches.

23. The power supply connection structure device, as recited in claim 6, wherein each of said micro-switches is a metal resilient plate, wherein said control unit

comprises a push member, wherein said micro-switches are coupled to said push member in such a manner that said micro-switches switch on in response to a driving operation of said push member to electrically connect said live wire connection unit with said live wire access terminal, and to electrically connect said neutral wire connection unit with said neutral wire access terminal respectively.

24. A method of manufacturing a power supply connection structure device, comprising:

(a) providing a housing having a live wire plughole, a neutral wire plughole and a ground wire plughole thereon and defining a receiving cavity therein;

(b) coupling a live wire connecting terminal, a neutral wire connecting terminal and a ground wire connecting terminal with said live wire plughole, said neutral wire plughole and said ground wire plughole respectively, and disposing an electric circuit arrangement in said receiving cavity, wherein said electric circuit arrangement comprises a live wire access terminal and a neutral wire access terminal; and

(c) configuring a control unit comprising two micro-switches, wherein when said two micro-switches are switched on, one of said two micro-switches electrically connects said live wire connection terminal with said live wire access terminal, and said other micro-switch electrically connects said neutral wire connection terminals with said neutral wire access terminal, so that an electric circuit between said power supply connection structure device, a power source and an electrical appliance is connected.

25. A method for electrically connecting an electrical appliance to a power source via a power source connection structure device, wherein the method comprises the following steps:

(i) receiving three plug pins of said electrical appliance into a live wire plughole, a neutral wire plughole and a ground wire plughole of said power source connection structure device respectively for electrically connecting said three plug pins to

a live wire connecting terminal, a neutral wire connecting terminal and a ground wire connecting terminal of said power source connection structure device respectively; and

- (ii) pushing a push member of a control unit of said power source connection structure device by one of said three plug pins so as to drive two actuation members to switch on two micro-switches of said power source connection structure device, so as to electrically connect said live wire connection terminal and said neutral wire connection terminal with a live wire access terminal and a neutral wire access terminal of said power source connection structure device respectively, so that an electric circuit between said power supply connection structure device, said power source and said electrical appliance is connected.