

(19) World Intellectual Property Organization
International Bureau



162162

(43) International Publication Date
17 October 2002 (17.10.2002)

PCT

(10) International Publication Number
WO 02/081882 A1

(51) International Patent Classification⁷: **F02B 47/02**

(21) International Application Number: PC1/JP02/03473

(22) International Filing Date: 8 April 2002 (08 04 2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2001-109177 6 April 2001 (06 04 2001) JP
2001-217286 17 July 2001 (17 07 2001) JP

(71) Applicant (for all designated States except US): **MITSUBISHI HEAVY INDUSTRIES, LTD.** [JP/JP] 5-1 Marunouchi 2-chome, Chiyoda-ku, Tokyo 100-8315 (JP)

(72) Inventors; and

(75) Inventors/Applicants (for US only): **YUKI, Akihiro** [JP/JP], C/O YOKOHAMA Research & Development Center, MITSUBISHI HEAVY INDUSTRIES, LTD. 8-1, Sachura 1-chome Kanazawa-ku Yokohama-shi, Kanagawa 236-8515 (JP) **SHIMADA, Takafumi** [JP/JP] C/O YOKOHAMA Research & Development Center, MITSUBISHI HEAVY INDUSTRIES, LTD. 8-1, Sachura

1-chome, Kanazawa-ku Yokohama-shi, Kanagawa 236-8515 (JP) **ITOU, Kuninori** [JP/JP], C/O YOKOHAMA Research & Development Center MITSUBISHI HEAVY INDUSTRIES, LTD. 8-1, Sachura 1-chome, Kanazawa-ku, Yokohama-shi, Kanagawa 236-8515 (JP) **ISHIDA, Hiroyuki** [JP/JP], C/O NAGASAKI Research & Development Center, MITSUBISHI HEAVY INDUSTRIES, LTD. 717-1, Fukahori-machi 5-chome, Nagasaki-shi, Nagasaki 851-6392 (JP)

(74) Agent: **TAKAHASHI, Masahisa**, Room 1003, Ambassador Roppongi Buildings, 16-13, Roppongi 3-chome, Minato-ku Tokyo 106-0032 (JP)

(81) Designated States (national): CN, ID, JP, KR, SG, US

(84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR)

Published:

— with international search report

For two-letter codes and other abbreviations refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette

(54) Title: METHOD OF OPERATING INTERNAL COMBUSTION ENGINE INJECTED WITH CRITICAL WATER

(57) Abstract: The object of the invention is to provide an operating method of an internal combustion engine with critical water injection, in which the advantage of critical water is positively utilized to increase engine efficiency and output in addition to the reduction of the emission of nitrogen oxide and CO. It is characterized in that sub- or super-critical water of above 250 °C and above 10 MPa is injected during the compression or combustion stroke of the internal combustion engine by starting the injection before the fuel ignites in the compression stroke, particularly the injection is done so that said critical water interferes with the fuel spray injected into the combustion chamber, and the injection period is in the range of -90 °C ~ +30 °C from the top dead center crank position

WO 02/081882 A1