



(51) International Patent Classification:
E21B 17/10 (2006.01) *E21B 37/02* (2006.01)

(21) International Application Number:
PCT/GB2010/001512

(22) International Filing Date:
10 August 2010 (10.08.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0913979.1 10 August 2009 (10.08.2009) GB
12/709,948 22 February 2010 (22.02.2010) US

(71) Applicant (for all designated States except US): **DOMAIN LICENCES LIMITED**; Jipfa Building, 3rd Floor, Main Street, Tortola (VG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **JENNER, Andrew** [GB/DE]; Brüsseler Strasse 29, 49377 Vechta (DE).

(74) Agents: **KILBURN & STRODE LLP** et al.; 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: DOWNHOLE DEVICE




FIG. 3

(57) Abstract: A stop collar or like device is formed in one piece to have a portion for a tool to be attached. Movement of the tool allows the collar to be drawn tightly into engagement onto a pipe or other tubular member. A bow centraliser has alternate bows longitudinally offset to reduce initial insertion force. The centraliser may be formed to have end bands of the type used in the stop collar.