

**A REGULATION-COMPLIANT HOLDING DEVICE FOR STORING OR
TRANSPORTING A NON-COMPLIANT CONTAINER**

Technical Field

[0001] A method of storing and/or transporting a container is provided. A holding device for containing a container is also provided. According to an embodiment, the container does not meet United States transportation regulations; whereas the holding device meets or exceeds the United States transportation regulations. According to another embodiment, the container contains a subterranean formation fluid sample.

Summary

[0002] According to an embodiment, a method of storing or transporting a sample comprises: inserting a sample container into a holding device, wherein the sample container contains the sample, wherein the sample container does not meet United States transportation regulations, wherein the holding device meets or exceeds United States transportation regulations, and wherein the holding device comprises a chamber and an opening; and storing or transporting the holding device.

[0003] According to another embodiment, a holding device for containing a container comprises: a chamber; and an opening, wherein the holding device meets or exceeds United States transportation regulations, wherein the container contains a sample, and wherein United States transportation regulations require the sample to be stored or transported according to the United States transportation regulations.

Brief Description of the Figures

[0004] The features and advantages of certain embodiments will be more readily appreciated when considered in conjunction with the accompanying figures. The figures are not to be construed as limiting any of the preferred embodiments.

[0005] **Fig. 1A** is a diagram of a sample container including a sample receptacle.

[0006] **Fig. 1B** is a diagram of the sample container further including a pressurization compartment.

[0007] **Figs. 2A and 2B** are diagrams according to certain embodiments of a holding device including a chamber for containing the sample container.

Detailed Description

[0008] As used herein, the words "comprise," "have," "include," and all grammatical variations thereof are each intended to have an open, non-limiting meaning that does not exclude additional elements or steps.

[0009] It should be understood that, as used herein, "first," "second," "third," etc., are arbitrarily assigned and are merely intended to differentiate between two or more valves, seals, etc., as the case may be, and does not indicate any sequence. Furthermore, it is to be understood that the mere use of the term "first" does not require that there be any "second," and the mere use of the term "second" does not require that there be any "third," etc.

[0010] As used herein, a "fluid" is a substance having a continuous phase that tends to flow and to conform to the outline of its container when the substance is tested at a temperature of 71 °F (22 °C) and a pressure of one atmosphere

"atm" (0.1 megapascals "MPa"). A fluid can be a liquid or gas. A fluid can have only one phase or more than one phase. In the oil and gas industry, a fluid having only one phase is commonly referred to as a single-phase fluid and a fluid having more than one phase is commonly referred to as a multi-phase fluid. If a single-phase fluid is subjected to sufficient changes in pressure or temperature, then the fluid system can become unstable. As used herein, the term "unstable" means that a single-phase fluid undergoes a phase separation, causing the single-phase fluid to become a multi-phase fluid.

[0011] Many countries, such as the United States ("U.S."), have governmental agencies that regulate the storage and/or transportation of certain substances. An example of an agency in the U.S. that regulates storage and/or transportation of the substances is the Department of Transportation ("DOT"). Examples of classes of substances that are currently regulated by the DOT can include, but are not limited to: explosives; flammable materials; corrosive materials; certain gases; radioactive materials; and hazardous materials, such as infectious materials and pressurized material. Each class can include several unique substances.

[0012] It is common for a governmental agency to impose requirements for the containers that regulated substances are to be stored or transported in. Container requirement examples include, but are not limited to: the container must be labeled in a manner to clearly identify the class of the substance located within the container; the container must be made of a specific type of material depending on which class of substance is to be placed in the container; the container material may have to be a certain thickness depending on the substance class; and in some instances, the container may not be filled with more than a certain volume of the substance. One

class of substances may have its own unique container requirements; whereas, another class of substances may have different container requirements. In order to ensure compliance with governmental regulations, the substance should be identified as belonging to a regulated class of substances. Then, the regulations for that class of substances can be evaluated to determine the appropriate specifications for the container the substance is to be placed in.

[0013] In the oil and gas industry it is often desirable to take a sample of a subterranean formation fluid, also referred to as a reservoir fluid. The reservoir fluid is generally a single-phase fluid. A formation fluid belongs to a class of substances regulated in the U.S. by the DOT. There are a variety of instruments that can be used to collect a sample of formation fluids. One such instrument is the ARMADA® sampling system, marketed by Halliburton Energy Services, Inc. In order to collect a sample, the sampling system is placed into a wellbore at a desired location. The sampling system functions to collect a sample of the formation fluids (the desirable fluid) at that location. The sampling system is then returned to the surface where the sample can be retrieved from the system. In some instances, fluids other than the desired fluid will be collected along with the desired fluid. For example, if oil is the desired reservoir fluid to be collected, water (the undesired fluid) may also be collected along with the oil. It is to be understood that any reference herein to "the sample" is meant to apply to the desired fluid. For example, if an embodiment specifies the stability of the sample, then such embodiment is meant to pertain only to the stability of the desired fluid and is not meant to apply to the stability of any undesired fluid that may be collected along with the desired fluid.

[0014] Reservoirs are typically located in the range of a few hundred feet (shallow reservoirs) to a few tens of thousands of feet (ultra-deep reservoirs). In order to produce oil or gas, a wellbore is drilled into a reservoir or adjacent to a reservoir. A wellbore can extend several hundreds of feet below the earth's surface or several hundreds of feet below the surface of a body of water in off-shore drilling. There can be a difference in temperature at different depths of the formation. For example, as the depth of a wellbore increases below the earth's surface, the temperature generally increases. Moreover, as the depth of a wellbore increases below the surface of a body of water, the temperature generally decreases. A collected formation sample can be subjected to changes in temperature as the sample is carried through the hundreds to thousands of feet to the surface; thus, causing the desired fluid to become unstable.

[0015] To avoid destabilizing the fluid, some sampling systems include a separate compartment whereby the sample can be pressurized. One way to pressurize a sample is to inject a gas, such as nitrogen, into a pressurization compartment. The compartment can be pressurized to a desired pressure with the injected gas based on the anticipated temperature change. The increased pressure helps maintain the sample as a stable fluid.

[0016] It is common to collect a sample of a substance in a container. In some instances the container may not meet governmental regulations and can be called a non-compliant container. Because these containers are non-compliant, the sample must be removed from the non-compliant container and transferred into a compliant container. However, it may be undesirable to transfer the sample to a new container. For example, transferring the sample may expose people to

possible injury or health risks, and compromise the sample itself due to a failed transfer process. It is also inefficient and less convenient to transfer a sample into a compliant container.

[0017] Thus, there is a need for a holding device that meets or exceeds U.S. transportation regulations whereby a non-compliant container can be inserted into the compliant holding device for storage and/or transportation.

[0018] A novel holding device that meets or exceeds U.S. regulations comprising a chamber and an opening can be used for storing or transporting a sample container, wherein the sample container does not meet the U.S. regulations.

[0019] According to an embodiment, a holding device for containing a container comprises: a chamber; and an opening, wherein the holding device meets or exceeds United States transportation regulations, wherein the container contains a sample, and wherein United States transportation regulations require the sample to be stored or transported according to the United States transportation regulations.

[0020] According to another embodiment, a method of storing or transporting a sample comprises: inserting a sample container into a holding device, wherein the sample container contains the sample, wherein the sample container does not meet United States transportation regulations, wherein the holding device meets or exceeds United States transportation regulations, and wherein the holding device comprises a chamber and an opening; and storing or transporting the holding device.

[0021] Any discussion of the embodiments regarding the holding device, the sample container, or any components thereof, is intended to apply to the apparatus embodiments and the method embodiments. Any discussion of a particular component of the holding device or the sample container (e.g., a

valve) is meant to include the singular form of the component and also the plural form of the component, without the need to continually refer to the component in both the singular and plural form throughout. For example, if a discussion involves "the valve **203**," it is to be understood that the discussion pertains to one valve (singular) and two or more valves (plural).

[0022] Turning to the Figures. **Figs. 1A and 1B** are diagrams of a sample container **200**. According to an embodiment, the sample container **200** does not meet United States transportation regulations. As can be seen in **Fig. 1B**, the sample container **200** comprises a sample receptacle **201**. The sample receptacle **201** will have two ends; a first end and a second end. The sample receptacle **201** can include a first opening. The sample receptacle **201** can also include a second opening. The openings can be located at the first and second ends. The sample receptacle **201** can contain a sample. The sample can be introduced into the sample receptacle **201** via the first and/or second openings. The sample can be a substance, such as a solid, liquid, gas, or combinations thereof. According to an embodiment, the sample is a substance that is regulated by a U.S. agency. According to another embodiment, the sample is a substance that is regulated by the U.S. DOT. According to another embodiment, the sample is a subterranean formation fluid. According to another embodiment, the sample container **200** is part of the ARMADA® sampling system, marketed by Halliburton Energy Services, Inc.

[0023] The sample container **200** can further comprise a valve **203**. The valve **203** can be a one-way valve. As used herein, the term "one-way valve" means a device that allows a fluid to enter a space within an enclosed area in one direction, but does not independently allow the fluid to exit

the space in a reverse direction. Of course, a one-way valve may have a release mechanism whereby a person can activate the mechanism thereby causing at least some of the fluid within the sample retaining space to flow out of the enclosed area. However, the one-way valve should be designed such that any fluid that enters the space will not freely flow back out of that space without external intervention. The valve **203** can be positioned in an opening of the sample receptacle **201**. The valve **203** can be located at the first end or the second end of the sample receptacle **201**, or one valve **203** can be located at the first end and another valve **203** can be located at the second end. A sample can be introduced into the sample receptacle **201** via the valve **203** positioned in the opening of the sample receptacle **201**. In this manner, the sample can be contained inside the sample receptacle **201** until a time when it is desirable to remove the sample from the sample receptacle **201**.

[0024] As can be seen in **Fig. 1A**, the sample container **200** can further include a pressurization compartment **202**. The pressurization compartment **202** will have two ends; a first end and a second end. The pressurization compartment **202** can include one or more openings. The opening(s) are preferably located at the end(s) of the pressurization compartment **202**. According to an embodiment, the pressurization compartment **202** is detachably connected to the sample receptacle **201**. The first end of the pressurization compartment **202** can be detachably connected to the first end of the sample receptacle **201**, thus forming a center of the sample container **200**. The sample container **200** can now include the sample receptacle **201** having an outermost end (the second end) and the pressurization compartment **202** having an outermost end (the second end). As used herein, the term "outermost" means the location(s) that is the farthest away from the center of an object.

[0025] According to an embodiment, the pressurization compartment **202** is capable of receiving a pressurization medium, such as a gas. The pressurization compartment **202** can also include a valve **203**. The valve **203** can be located in an opening of the pressurization compartment **202**. The valve **203** can be located at the first and/or second end of the pressurization compartment **202**. The valve **203** can be a one-way valve. The pressurization medium can be introduced into the pressurization compartment **202** via the valve **203** located in the opening. The pressurization medium can be introduced such that a desired pressure is maintained in the pressurization compartment **202**. For example, a sufficient volume of the pressurization medium can be introduced to maintain the desired pressure in the pressurization compartment **202**. There may be a variety of reasons for including a pressurization compartment **202**. One reason may be when the sample is a single-phase fluid, the sample can be subjected to temperature changes, and it is desirable to maintain the sample as a stable fluid. The pressurization compartment **202** can be connected to the sample receptacle **201** in a manner such that a pressure, for example gas pressure, from the pressurization compartment **202** maintains the sample located within the sample receptacle **201** as a stable fluid. According to another embodiment, the desired pressure in the pressurization compartment **202** is at least a sufficient pressure to maintain the sample as a stable fluid.

[0026] The sample receptacle **201** can be detachably connected at the first end to the first end of the pressurization compartment **202**. When the sample container **200** does not include the pressurization compartment **202**, a sample can be introduced into the sample receptacle **201** via the first end comprising an opening and/or the second end comprising an opening of the sample receptacle **201**. The sample can be

introduced into the first end of the sample receptacle **201** via the valve **203** or into the second end of the receptacle **201** via a valve **203** (not shown). When the sample container **200** includes the pressurization compartment **202**, a sample can be introduced into the sample receptacle **201** via the second end of the sample receptacle **201** via a valve **203** (not shown).

[0027] The sample container **200** can further comprise a first seal **204**. The first seal **204** can be positioned adjacent to the sample receptacle **201**. As depicted in **Fig. 1B**, the first seal **204** can be positioned at the second end of the sample receptacle **201** opposite of the valve **203**. The second end of the sample receptacle **201** can include an opening. According to an embodiment, the seal is designed such that once in place, a sample located within the sample receptacle **201** is not capable of independently exiting the sample receptacle **201**. By including the first seal **204** at this second end, the sample can be contained within the sample receptacle **201**. The sample receptacle **201** can further include a second seal **205**. As can be seen in **Fig. 1B**, the second seal **205** can be positioned at the first end of the sample receptacle **201**. According to an embodiment, the second seal **205** is positioned at the first end of the sample receptacle **201** adjacent to the valve **203**. If the sample receptacle **201** includes both a first and second seal **204/205**, then preferably, the second seal **205** is positioned at the end of the sample receptacle **201** opposite the end of the sample receptacle **201** that includes the first seal **204**. By including the first and second seals **204/205**, any sample located within the sample receptacle **201** can be contained. As can be seen in **Fig. 1A**, the second seal **205** can be positioned adjacent to the pressurization compartment **202**. According to this embodiment, the second seal **205** can be positioned at the second end of the pressurization compartment **202** adjacent to the valve

203. When the sample container **200** includes both, the sample receptacle **201** and the pressurization compartment **202**, the first seal **204** can be used to seal the outermost end of the sample receptacle **201** and the second seal **205** can be used to seal the outermost end of the pressurization compartment **202**. Of course, according to this embodiment, the first end of the sample receptacle **201** will be detachably connected to the first end of the pressurization compartment **202** to form a center of the sample container **200**.

[0028] The seals **204/205** can be permanently attached, removably attached, and combinations thereof to the sample container **200**. By way of example, the first seal **204** can be removably attached to the sample receptacle **201** and the second seal **205** can be removably attached to the pressurization compartment **202**. In this manner, once a sample has been collected and is located inside the sample receptacle **201**, the sample can be contained within the sample receptacle **201** by attaching the first seal **204** to the outermost end (the second end) of the sample receptacle **201** and by attaching the second seal **205** to the outermost end (the second end) of the pressurization compartment **202**. By way of another example, the first seal **204** can be permanently attached to the second end of the sample receptacle **201** and the second seal **205** can be removably attached to the first end of the sample receptacle **201**. In this manner, once a sample has been collected and is located inside the sample receptacle **201**, the sample can be contained within the sample receptacle **201** via the permanently attached first seal **204** and by attaching the second seal **205** to the first end of the sample receptacle **201**. By way of another example, the first seal **204** and the second seal **205** can be removably attached to the sample receptacle **201**. In this manner, once a sample has been collected and is located inside

the sample receptacle **201**, the first seal **204** can be attached to the outermost end (the second end) of the sample receptacle **201**, the sample receptacle **201** can be disconnected from the pressurization compartment **202**, and the second seal **205** can then be attached to the first end of the sample receptacle **201**.

[0029] **Figs. 2A and 2B** are diagrams of the holding device **100** according to certain embodiments. According to an embodiment, the holding device **100** meets or exceeds United States ("U.S.") transportation regulations. In another embodiment, the sample container **200** does not meet U.S. transportation regulations, but the holding device **100** meets or exceeds U.S. transportation regulations.

[0030] The holding device **100** comprises a chamber **105** and an opening. In an embodiment, the holding device **100** is capable of completely surrounding the sample container **200**. The shape of the chamber **105** can be selected such that the holding device **100** is capable of completely surrounding the sample container **200**. The sample container **200** may be a variety of shapes, as such the chamber **105** may also be a variety of shapes. The shape of the chamber **105** and the shape of the sample container **200** can be the same, similar, or different. Examples of possible shapes of the sample container **200** and the chamber **105** include, but are not limited to, circular, rounded, orbicular, elliptical, cylinoidal, cylindrical, polygonal, frustrum, or conical. In an embodiment, the size of the chamber **105** is selected such that the holding device is capable of completely surrounding the sample container **200**.

[0031] The methods include the step of inserting the sample container **200** into the holding device **100**. The sample container **200** can fit in a variety of ways inside the holding device **100**. For example, the sample container **200** can fit closely inside the holding device **100**. For a close fit, the

shape and size of the chamber **105** can be selected such that the sample container **200** has limited vertical or lateral movement inside the holding device **100**. By way of another example, the sample container **200** can fit loosely inside the holding device **100**. For a loose fit, the shape and size of the chamber **105** can be selected such that an annulus **104** exists between the sample container **200** and the holding device **100**. As used herein, the term "annulus" means the space between two objects, one inside the other. For example, an annulus **104** can exist between the inside of the chamber **105** and the outside of the sample container **200**. As used herein, the term "inside" means the inner perimeter or circumference of an object. As used herein, the term "outside" means the outer perimeter or circumference of an object. By way of another example, an annulus **104** can exist between one or more of the outermost ends of the sample container **200** and the ends of the holding device **100**.

[0032] The holding device **100** also includes two ends. In an embodiment, at least one of the ends is the opening. Preferably, the sample container **200** is capable of being placed inside the holding device **100** via the opening. The holding device **100** can further comprise a first end seal **101**. The first end seal **101** can be permanently attached or removably attached to a first end of the chamber **105**. The holding device **100** can also include a second end seal **102**. The second end seal **102** can be permanently attached or removably attached to a second end of the chamber **105**. If the first end seal **101** is permanently attached to the first end of the chamber **105**, then preferably, the second end of the chamber **105** is the opening. Moreover, if the first end seal **101** is permanently attached to the first end of the chamber **105**, then preferably, the second end seal **102** is removably attached to the second end of the chamber **105**.

[0033] The first and/or second end seals **101/102** can include an opening. As can be seen in **Fig. 2A**, the sample container **200**, comprising the sample receptacle **201** and the pressurization compartment **202**, is positioned inside the holding device **100**. As can be seen in **Fig. 2B**, the sample receptacle **201** can be detached from the pressurization compartment **202** and the sample container **200** can then be positioned inside the holding device **100**. Although not shown in **Figs. 2A and 2B**, the sample container **200** can include the second seal **205**.

[0034] The holding device **100** can further include a holding device valve **103**. In an embodiment, the holding device valve **103** is positioned adjacent to the end seal **101/102** within the opening. The holding device valve **103** can be a one-way valve. The holding device **100** can be connected to a pressurization delivery source. The delivery source can contain a pressurization medium and be equipped with a pump. The pressurization medium (shown in **Fig. 2B** as dots within the annulus **104**) can be a gas, for example, nitrogen. The holding device **100** can be operatively connected to the delivery source such that the pressurization medium can be pumped into the holding device **100** via the opening and the holding device valve **103**. In an embodiment, the holding device **100** is capable of being filled with the pressurization medium to a desired pressure. An example of when it may be useful to pressurize the holding device **100** is when the sample container **200** does not include the pressurization compartment **202**. In this example, the sample is not pressurized and may not remain as a stable fluid if subjected to changes in temperature. As such, it may be desirable to pressurize the holding device **100**. In an embodiment, the holding device **100** is pressurized to a desired pressure. The desired pressure can be a sufficient pressure to maintain the sample as a stable fluid.

[0035] As can be seen in **Fig. 2A**, the shape and size of the chamber **105** may be such that only a very small annulus **104** or no annulus **104** exists between the inside of the chamber **105** and the outside of the sample container **200**. If it is desirable to pressurize the holding device **100**, then the shape and size of the chamber **105** can be designed to provide an annulus **104**. For example, the length of the chamber **105** may be increased to provide an annulus **104** between at least one end of the holding device **100** and at least one of the outermost ends of the sample container **200**. As can be seen in **Fig. 2B**, the size of the perimeter or circumference of the chamber **105** may be increased to provide an annulus **104** between the inside of the chamber **105** and the outside of the sample container **200**. The sample container **200** can also include a pressurization adapter **206**. According to an embodiment, the pressurization adapter **206** is positioned at a location on the sample container **200** such that the pressurization adapter **206** helps to create an annulus **104** between the container and the holding device. For example, the pressurization adapter **206** can be positioned at the first end of the sample container **200** adjacent to the first seal **204**. By way of another example, the pressurization adapter **206** can be positioned at the second end of the sample container **200**. In the preceding example, the pressurization adapter **206** can be adjacent to a valve **203** or a second seal **205** (not shown in **Figs. 2A and 2B**). The size of the chamber is preferably sufficient to accommodate the entire length of the sample container **200** including the pressurization adapter **206**.

[0036] The pressurization adapter **206** can include at least one protrusion. The at least one protrusion can be used to help create an annulus **104** between the container **200** and the holding device **100**. The first end seal **101** can contain at least one appropriately-sized opening to accommodate the at

least one protrusion. In this manner, the at least one protrusion is capable of being inserted into the at least one opening such that a seal is created at that end of the holding device.

[0037] In an embodiment, a method of storing or transporting a substance comprises: inserting the sample container **200** into the holding device **100** and storing or transporting the holding device. The methods can further include the step of collecting a sample prior to the step of inserting. The sample can be collected in the sample receptacle **201**. If the sample container **200** also includes a pressurization compartment **202**, then the methods can also include the step of pressurizing the pressurization compartment **202** prior to the step of inserting. If the sample container **200** also includes a pressurization compartment **202**, then the methods can also include the step of separating the sample receptacle **201** from the pressurization compartment **202** prior to the step of inserting. The methods can further include the step of pressurizing the holding device **100** after the step of inserting. The methods can further include the step of pressurizing the pressurization compartment **202** and/or the holding device **100** to a desired pressure. According to an embodiment, the desired pressure is a pressure sufficient to maintain the sample as a stable fluid.

[0038] Therefore, the present invention is well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular embodiments disclosed above are illustrative only, as the present invention may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown,

other than as described in the claims below. It is, therefore, evident that the particular illustrative embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the present invention. While compositions and methods are described in terms of "comprising," "containing," or "including" various components or steps, the compositions and methods also can "consist essentially of" or "consist of" the various components and steps. Whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range is specifically disclosed. In particular, every range of values (of the form, "from about a to about b," or, equivalently, "from approximately a to b,") disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values. Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. Moreover, the indefinite articles "a" or "an", as used in the claims, are defined herein to mean one or more than one of the element that it introduces. If there is any conflict in the usages of a word or term in this specification and one or more patent(s) or other documents that may be incorporated herein by reference, the definitions that are consistent with this specification should be adopted.

WHAT IS CLAIMED IS:

1. A method of storing or transporting a sample comprising:
inserting a sample container into a holding device,
wherein the sample container contains the sample,
wherein the sample container does not meet United States transportation regulations,
wherein the holding device meets or exceeds United States transportation regulations, and
wherein the holding device comprises a chamber and an opening; and
storing or transporting the holding device.
2. The method according to Claim 1, wherein the sample container comprises a sample receptacle.
3. The method according to Claim 2, wherein the sample container further includes a pressurization compartment, wherein the pressurization compartment is detachably connected to the sample receptacle.
4. The method according to Claim 3, further comprising the step of separating the sample receptacle from the pressurization compartment prior to the step of inserting.
5. The method according to Claim 3, further comprising the step of pressurizing the pressurization compartment prior to the step of inserting.
6. The method according to Claim 5, wherein the pressurization compartment is pressurized to a desired pressure.

7. The method according to Claim 1, wherein the sample container further comprises a valve.
8. The method according to Claim 1, wherein the sample container further comprises a seal.
9. The method according to Claim 8, wherein the seal is permanently attached or removably attached to the sample container.
10. The method according to Claim 1, wherein the holding device is capable of completely surrounding the sample container.
11. The method according to Claim 1, wherein the sample container is capable of fitting closely inside the holding device or fitting loosely inside the holding device.
12. The method according to Claim 11, wherein the shape and size of the chamber is selected such that the sample container has limited vertical or lateral movement inside the holding device after insertion into the holding device.
13. The method according to Claim 11, wherein the shape and size of the chamber is selected such that an annulus exists between the sample container and the holding device after insertion into the holding device.
14. The method according to Claim 1, wherein the holding device further comprises an end seal.

15. The method according to Claim 14, wherein the end seal is permanently attached or removably attached to an end of the chamber.

16. The method according to Claim 1, wherein the holding device further comprises a holding device valve.

17. The method according to Claim 1, further comprising the step of collecting the sample prior to the step of inserting.

18. The method according to Claim 1, further comprising the step of pressurizing the holding device after the step of inserting.

19. The method according to Claim 18, wherein the holding device is pressurized to a desired pressure.

20. A holding device for containing a container comprising:
a chamber; and
an opening,

wherein the holding device meets or exceeds United States transportation regulations,
wherein the container contains a sample, and
wherein United States transportation regulations require the sample to be stored or transported according to the United States transportation regulations.