

Description

Title of Invention: METHOD AND SYSTEM FOR AN- NOUNCEMENT TIME OF IDLE TIMEOUT FOR POWER SAVING OPERATIONS IN WIRELESS NETWORKS

Technical Field

- [1] The present invention relates in general to wireless communication, and in particular, to power saving operations in wireless networks.

Background Art

- [2] A beacon frame is commonly used to set timing allocations and to communicate management information in a wireless communication network including multiple wireless devices. A beacon frame may provide communication schedule timing allocations to the wireless devices in the network for wireless communication over radio frequency (RF) channels.
- [3] The 60 GHz RF band can provide a higher data communication rate (e.g., by a factor of 10) in comparison to the IEEE 802.11n wireless communication standard. However, beacon transmissions usually operate at a much lower rate due to their broadcast nature, thus creating significant control overhead to 60 GHz wireless communication networks.

Disclosure of Invention

Solution to Problem

- [4] Embodiments of the invention provide wireless communication over a wireless communication medium.

Advantageous Effects of Invention

- [5] Embodiments of the present invention allow announcement time(AT) period operations to suit power saving STAs, and allow AT operations to be more traceable to both STAs and the coordinator.

Brief Description of Drawings

- [6] FIG. 1A shows a block diagram of a wireless communication system implementing power saving, according to an embodiment of the present invention.
- [7] FIG. 1B shows an example beacon interval (BI) transmission schedule for Announcement Time (AT) of idle timeout for power saving operations, according to an embodiment of the invention.
- [8] FIG. 2 shows an example relationship between time out periods for various AT idle timeout policies, for power saving operations, according to an embodiment of the invention.

- [9] FIG.3 shows an example dynamic/active list of wireless stations to be polled during the AT, for power saving operations, according to an embodiment of the invention.
- [10] FIG. 4A shows a modified millimeter-wave (mmWave) non-PCP STA Capability Information element, for power saving operations, according to an embodiment of the invention.
- [11] FIG. 4B shows an example mmW BSS Parameter Configuration field, for power saving operations, according to an embodiment of the invention.
- [12] FIG. 5A shows an example AT Idle Timeout information element (IE), for power saving operations, according to an embodiment of the invention.
- [13] FIG. 5B shows an example mmWave Operation element, for power saving operations, according to an embodiment of the invention.
- [14] FIG. 6 shows a flowchart of an operational process of a wireless station in a wireless communication system, for power saving operations, according to an embodiment of the invention.
- [15] FIG. 7 shows a flowchart of an operational process of a coordinator in a wireless communication system on conjunction with wireless station operation of FIG. 6, for power saving operations, according to an embodiment of the invention.
- [16] FIG. 8 shows a more detailed block diagram of a wireless communication system implementing power saving, according to an embodiment of the present invention.
- [17] FIG. 9 is a high level block diagram showing an information processing system comprising a computer system useful for implementing an embodiment of the present invention.

Best Mode for Carrying out the Invention

- [18] Embodiments of the invention provide wireless communication over a wireless communication medium. In one embodiment, the invention provides a process comprising generating a schedule which indicates when a wireless communication station may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period. The AT period comprises a period after a beacon transmission in a beacon interval.
- [19] In another embodiment, the present invention provides a wireless coordinator station, comprising a scheduling module configured for generating a power saving schedule indicating when a wireless communication station may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval.
- [20] In another embodiment, the present invention provides a wireless communication station, comprising a power saving module configured for receiving a power saving

schedule and entering the wireless communication station into a power saving state accordingly, wherein the schedule indicates when the wireless communication station may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval.

[21] In another embodiment, the present invention provides a wireless communication system, comprising a wireless coordinator station comprising a scheduling module configured for generating a schedule indicating when one or more wireless communication stations may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval. The wireless communication system further comprises at least one wireless communication station comprising a power saving module configured for receiving a power saving schedule from the coordinator station over a wireless communication medium, and entering into a power saving state accordingly.

[22] These and other features, aspects, and advantages of the present invention will become understood with reference to the following description, appended claims, and accompanying figures.

Mode for the Invention

[23] Embodiments of the present invention provide Announcement Time (AT) of idle timeout for power saving operations in a wireless network. As shown in FIG. 1A, an embodiment of a wireless communication network 5 according to the present invention includes multiple (m) electronic wireless devices such as wireless communication stations 7 comprising wireless transmitter and/or receiver devices, and a wireless coordinator station 6, implementing a frame structure for data communication over a wireless communication medium (e.g., radio frequency band). One or more of the wireless stations 7 may comprise power saving wireless stations.

[24] In one example, such a frame structure (marked by beacon frames) is implemented via a Media Access Control (MAC) layer and a physical (PHY) layer. In a wireless transmitter, a MAC layer receives a MAC Service Data Unit (MSDU) and attaches a MAC header thereto, in order to construct a MAC Protocol Data Unit (MPDU). The MAC header includes information such as a source address (SA) and a destination address (DA). The MPDU is a part of a PHY Service Data Unit (PSDU) and is transferred to a PHY layer in the transmitter to attach a PHY header (i.e., PHY preamble) thereto to construct a PHY Protocol Data Unit (PPDU). The PHY header includes parameters for determining a transmission scheme including a coding/modulation scheme. Before transmission as a packet from the wireless transmitter to a

wireless receiver over a wireless communication medium (e.g., a radio frequency channel), a preamble is attached to the PPDU, wherein the preamble can include channel estimation and synchronization information.

- [25] A beacon frame may contain reduced information, wherein most of the schedule allocation and management information of a beacon frame are moved to a later time called the Announcement Time (AT) period where unicast frames may be transmitted at a higher data rate.
- [26] One implementation of the present invention comprises a method and system to bound and indicate the Announcement Time (AT) transmission schedule for each power saving (PS) wireless station (STA) present in the wireless communication network 5, to facilitate power saving. According to an embodiment of the present invention disclosed herein, the starting time of the AT is indicated in the beacon frame and the end time (and/or length) for the AT is also indicated. This results in a bounded awake time for power sensitive wireless stations (STAs) in the wireless communication network, and improves power saving (PS) operations.
- [27] In one embodiment of the invention, an awake wireless station may enter a power saving state (or doze off) by reducing electrical power consumption therein (e.g., by reducing communication). In the awake state, a wireless station consumes more power than in a power saving state.
- [28] In one implementation, the present invention improves power saving operations in case a coordinator station does not send additional frames or in case of frame losses during the AT. Specifically, in one embodiment of the invention, the AT transmission schedule comprising a power saving schedule, is indicated to the power saving wireless stations (PS-STAs) in real-time during the AT, using an AT idle timeout process. Such a process is applicable for PS-STAs to determine their wake up periods in their Awake Beacon Intervals (BIs).
- [29] When the schedule allocations are transmitted by the wireless coordinator (e.g., wireless coordinator device/station 6) in the wireless communication network (e.g., wireless network 5) during an AT, in case of frame losses during the AT, or in case the coordinator does not transmit additional frames to PS-STAs, then the coordinator can use an AT idle timeout process to indicate idle timeout and the PS-STAs can determine when each PS-STA may enter a power saving state without staying awake for the rest of the beacon interval (BI). The coordinator maintains and uses a dynamic STA list to determine its AT transmission sequence. This list categorizes and separates the STAs based on their power sensitivity levels. The coordinator dynamically updates the STA list based on a parameter setup as the AT continues.
- [30] An AT is present in a BI where the duration of the AT is not pre-known to the STAs at the time the BI enters the AT phase. The coordinator transmits directed frames to

STAs during the AT and STAs stay in an awake state to receive/respond to these frames during a part of the AT known by both the coordinator and each STA. A directed frame comprises a frame of information sent from the coordinator to an STA using directional transmission such as a beamforming transmission. The directed frame sent by the coordinator to an STA includes specific timing or schedule that instructs when the STA may enter a doze (i.e., power saving) state. Further, the schedule may indicate for how long the STA may stay in the doze state (i.e., indicating when the STA should awake).

- [31] Embodiments of the present invention allow indicating and determining whether an STA may enter a power saving (doze off) state based on the AT idle interval while dwelling in the awake state. In one implementation, an idle timeout clock/timer is reset when an STA receives a directed frame from the coordinator. In another implementation, the idle timeout clock/timer is reset when a set of predefined events that are commonly observable to both the STA and the coordinator take place (e.g., when the STA receives or overhears a valid frame from the coordinator). In other implementations, upon the reception of a pre-determined triggering frame from the coordinator, the STA starts a new awake policy that is either conveyed in the received frame or previously agreed upon with the coordinator.
- [32] In one example, N idle timeout policies are assigned to M levels of power sensitive STAs, wherein less power sensitive STAs obtain loosely bounded or unbounded timeout policies, and more power sensitive STAs obtain tightly bounded timeout policies. The coordinator maintains a dynamic policy-based STA list to determine the transmission sequence during the AT. Absence of a transmission is used as an indication of no allocations/requests from the coordinator. Different AT starting points are assigned for different levels of power sensitive STAs. The coordinator adaptively announces/adjusts AT Idle Timeout policies of the STAs.
- [33] FIG. 1B shows an example transmission schedule 10 for announcement time of idle timeout for power saving operations, according to an embodiment of the invention. When a beacon frame (Beacon) is present in a BI, the BI typically starts with beacon transmissions and a directional transmission training phase, such as a beamforming training phase for wireless communication between wireless stations. Antenna training for beamforming provides increased signal quality (high directional antenna beamforming gain) and an extended communication range by steering the transmitted signal in a narrow direction.
- [34] When an AT is present in a BI, an AT period follows immediately after a beamforming training period and ends at the time data transmissions starts. In an Awake BI of a power saving STA, the power saving STA remains in the awake state during the beacon time period (BT), and may doze (i.e., enter power saving state)

during the beamforming training period. Embodiments of the present invention enable an STA to dynamically determine whether it may doze off at a specific time within the AT to reduce power consumption. As such, the STA need not stay awake during the entire AT, or in the worst case for the remainder of the BI.

- [35] In one embodiment, the coordinator employs N Announcement Time idle timeout policies P1, P2, ..., PN for different levels of STA power sensitivity. Without loss of generality, assume that P1 indicates a policy for highly power sensitive STAs and PN indicates a policy for low or non-power sensitive STAs. Each policy Pj (wherein j=1, 2, ..., N) is characterized by two parameters: Sj and Wj, wherein Sj represents the starting time in the AT and Wj represents the idle timeout interval for Pj policy STAs.
- [36] The Beacon frame indicates the starting times S1, S2, ... SN for corresponding P1, P2, ..., PN policy STAs. As an example, FIG. 1B illustrates the behavior of a P2 policy STA in three different scenarios, showing an AT in a BI and the behavior of a P2 policy STA in its Awake BI.
- [37] The P2 policy STA is a PS-STA and wakes up during the beacon time (BT) in its Awake BI to receive Beacon frames from the coordinator and learn about the AT starting time for P2 policy class STAs. The P2 policy STA enters a doze state at the end of the BT and wakes up at the designated AT starting time S2. At time S2, the P2 policy STA starts an idle countdown timer with a value W2 indicating an idle timeout interval time. At the end of the countdown, the STA may enter a power saving state for the remainder of the AT period.
- [38] In a first example scenario according to the invention (i.e., Scenario 1 in FIG. 1B), as the P2 policy STA remains idle and does not receive any directed frames from the coordinator by the end of the idle timeout interval W2, the P2 policy STA may enter a doze state. The coordinator should not send any frames directed to this P2 policy STA for the remainder of the AT period. In the case that a directed frame from the coordinator is lost, the P2 policy STA will be unable to send a response or acknowledge (ACK) frame to the coordinator. Both the coordinator and the P2 policy STA keep a countdown timer running with the W2 value, and the P2 policy STA may enter the doze state at the end of the idle timeout interval W2 without causing confusion to the coordinator.
- [39] Beacon frames are generally broadcast frames sent in a BT period, while directed (i.e., unicast) frames transmitted in the AT period are only between coordinator and an intended receiver (i.e., one-to-one communication).
- [40] In a second example scenario according to the invention (i.e., Scenario 2 in FIG. 1B), the P2 policy STA receives a request frame Rq from the coordinator (PCP) before the end of the idle timeout interval W2 and the P2 policy STA responds with a response frame Rs (e.g., an ACK). In one embodiment, the request frame Rq comprises a

directed (unicast) frame sent from the coordinator to a STA. The directed frame sent by the coordinator provides a specific timing or schedule that instructs when, and optionally for how long, the P2 policy STA may enter the doze state, wherein the P2 policy STA operates accordingly. For the example shown in FIG. 1B, the coordinator instructs the P2 policy STA to remain awake for the duration of the AT.

- [41] In a third example scenario according to the invention (i.e., Scenario 3 in FIG. 1B), the coordinator may not instruct the P2 policy STA explicitly about a timing or schedule indicating when the P2 policy STA may doze. Instead, upon successful reception of a directed frame from the coordinator, the P2 policy STA resets its timer to W2 (or a different value W2' known to both the coordinator and the STA), and starts the timeout countdown process again.
- [42] A directed frame includes management information and is sent during the AT period, typically involving request and response frames between a coordinator and a receiver station STA. In one embodiment of the invention shown in FIG. 1B, said transmission schedule 10 includes a power saving schedule providing specific timing or schedule that instructs when the STA may enter a doze (i.e., power saving) state. Further, the schedule may indicate for how long the STA may stay in the doze state (i.e., indicating when the STA should awake or exit the power saving mode).
- [43] The power saving (PS) schedule is not required to be contained in a directed frame. In one embodiment, the PS schedule information (in this case, the value of a timeout W) is transmitted in a Beacon time (BT) or AT period, and this information continues to be applicable over multiple Beacon Intervals (BIs) until the PCP sends out new values of W. as such, the PS schedule is determined based on: (1) the AT period idle timeout process which is pre-agreed by both the PCP and each PS-STA and, (2) the value of W set by the PCP.
- [44] In another implementation, the PS-STA timeout W2 need not stop only upon the reception of a directed frame from the coordinator, but may stop upon any set of events that are commonly observable by both the coordinator and the PS-STA. For example, the PS-STA may stop the timeout interval W2 upon overhearing any valid frames sent from the coordinator.
- [45] In other implementations, the values of the starting times S1, S2, ..., SN may not have any specific order. Further, as shown by example chart 20 in FIG. 2, the values of the timeout interval window sizes W1, W2, ..., WN follow the following order in relation (1), assuming P1 represents a most tightly bounded AT policy:
- [46] $W1 \leq W2 \leq \dots \leq WN$. (1)
- [47] The maximum value of WN is bounded by the end of the BI, meaning a PN policy STA should remain awake for as long as the rest of the BI. This is usually the case for non-power sensitive STAs.

- [48] In another implementation, the coordinator may specify an aggregate of multiple AT idle timeout policies and timers for a class of STAs (e.g., timeout when either a directed frame based timer (using W_x) or a valid frame based timer (using W_y) expires).
- [49] The coordinator maintains a dynamic active list of STAs to which it intends to send directed frames during the AT. An example of such a dynamic active list 30 kept by the coordinator is shown in FIG. 3. The coordinator categorizes the list of STAs based on the AT timeout policy ($P_1, P_2, \dots, P_N$) that the STAs use. At the beginning of an AT phase, the coordinator sets a timeout value t_i for an STA_i to the idle timeout value W_j , wherein j is the index of the policy P_j that STA_i belongs to, and i is an integer as the index of wireless stations.
- [50] For each STA_i in the active list 30, there is an associated parameter t_i which represents the upcoming timeout time for STA_i . The example in FIG. 3 for eight wireless stations, wherein $i = 1, 2, \dots, 8$, illustrates that the list 30 includes: $STA_1 (t_1)$, $STA_5 (t_5)$, $STA_3 (t_3)$, $STA_8 (t_8)$, $STA_6 (t_6)$, $STA_2 (t_2)$, $STA_4 (t_4)$ and $STA_7 (t_7)$. If for a station STA_i , the value t_i is larger than the current time, then that STA_i is removed from the active list 30 of the coordinator.
- [51] The coordinator dynamically updates/refreshes the active list 30 and timeout value t_i during the AT. As time passes during the AT, additional STAs are removed from the list upon timeout (meaning upon t_i being larger than the current time). If the coordinator has conveyed a timing/schedule to an STA_i , that STA_i may be removed from the list, provided that the coordinator has no additional frames directed to the STA_i during the AT. If the coordinator does not have information and/or communication schedule allocations for a STA_i , the coordinator may directly take that STA_i out from the active list without sending any frame to that STA_i .
- [52] An example application of the present invention for Wireless Gigabit Alliance (WiGig) is described hereinbelow. WiGig applies to multi-gigabit speed wireless communications technology operating over the 60 GHz radio frequency band. WiGig is an industry-led effort to define a wireless digital network interface specification for wireless signal transmission on the 60 GHz frequency band for wireless local area networks and wireless local area network devices such as consumer electronics (CE) and other electronic devices including wireless radios.
- [53] Without embodiments of the present invention, when a non-coordinator STA misses a Service Period (SP) schedule information in a BI, that STA stays awake for the duration of the BI in case the coordinator sends a frame to that STA later. If the SP schedule information is sent during the AT period which a power saving STA misses, that STA has no knowledge of when the AT ends and stays awake for the duration of the BI. This is undesirable for PS-STAs.

- [54] According to an embodiment of the invention for a WiGig wireless local area network, to utilize the AT idle timeout, an “AT Idle Timeout” field is added to the millimeter-wave (mmWave) non-PCP (i.e., non Personal Basic Service Set (PBSS) Control Point) STA Capability Information, as shown in FIG. 4A. PCP is equivalent to the coordinator such a coordinator 6 in Fig. 1A in the PBSS. A PS-STA sets this AT Idle Timeout field to indicate to the PCP that it wants to use the proposed AT timeout method.
- [55] In addition, according to the invention, an AT Idle Timeout Information Element (IE) 50 is defined as shown by example in FIG. 5A, which is sent by the PCP (coordinator) to specify the parameters of the policies. The PCP is equivalent to the coordinator in the PBSS. In its simplest form, only 2-levels of policies are used, where the starting times $S1 = S2 =$ AT starting times for PS-STAs (P1) and non-PS-STAs (P2), respectively. In this case, W2 is unbounded within the BI unless otherwise specified. The only parameter that needs to be set is the value of W1, which is specified by the value of the AT Timeout Window field in the AT Idle Timeout IE.
- [56] The PCP may send the AT Idle Timeout IE 50 as a power saving schedule to an associated STA with its AT Idle Timeout field setting to “1” in the mmWave (mmW) non-PCP STA Capability Information. If an STA which sets the AT Idle Timeout field in the “mmW non-PCP STA Capability Information” (and receives the AT Idle Timeout IE if applicable), does not receive any frame at AT idle timeout time into the AT, the STA may enter the doze state. At the AT idle timeout time, if the PCP does not complete a successful request/response dialog with the STA, the PCP should not send directed frames to this STA for the rest of the AT.
- [57] According to another embodiment of the invention, to utilize the AT idle timeout, an “MinBIHeaderDuration” field is added to the WiGig millimeter-wave (mmWave) Basic Service Set (BSS) Parameter Configuration field 41 of the mmWave Operation information element, as shown by example in FIG. 4B. The PCP uses this field to specify the parameters of the policies for a power saving schedule, according to an embodiment of the invention. In its simplest form, only 2-levels of policies are used, wherein the starting times $S1 = S2 =$ AT starting times for power saving STAs (i.e., policy P1) and non-power saving STAs (i.e., policy P2), respectively. In this case, W2 is unbounded within the BI unless otherwise specified. The only parameter that needs to be set is the value of W1, which is specified by the value of the MinBIHeaderDuration field.
- [58] FIG. 5B shows an example mmWave Operation element 51 according to an embodiment of the invention. If a power saving STA does not receive any frame from the PCP at MinBIHeaderDuration time into the AT, the power saving STA may enter the doze state. By the MinBIHeaderDuration time, if the PCP does not complete a

successful request/response dialog with this STA, the PCP should not send directed frames to this STA for the rest of the AT. As noted, the PCP is equivalent to the coordinator in the PBSS.

[59] FIG. 6 shows a flowchart of an example process 60, according to an embodiment of the present invention, for operation of a P_n class STA in the wireless communication network in conjunction with a coordinator, wherein $n = 1, 2, \dots N$. The process 60 comprises the following process blocks:

[60] *Block 61:* Wake up at the start of Awake BI.

[61] *Block 62:* Receive Beacon, update S_n and W_n if available.

[62] *Block 63:* Wake up at the AT starting time S_n.

[63] *Block 64:* Set local timer to W_n and start timer for down counting.

[64] *Block 65:* Incoming frame? If yes, proceed to block 66, or else proceed to block 69.

[65] *Block 66:* Respond or ACK to the incoming frame.

[66] *Block 67:* Received explicit schedule in the frame for communication over the wireless communication? If yes, proceed to block 68, else proceed to block 70.

[67] *Block 68:* Follow schedule for the rest of the BI. End.

[68] *Block 69:* Timer timeout? If yes, proceed to block 71, or else proceed to block 65.

[69] *Block 70:* Reset / refresh the local timer according to the defined policy. The reset/refresh value may depend on the implementation. Proceed to block 65.

[70] *Block 71:* May doze for the rest of the BI for power saving. End.

[71] FIG. 7 shows a flowchart of an example process 80, according to an embodiment of the present invention, for operation of the coordinator station in the wireless communication network. The process 80 comprises the following process blocks:

[72] *Block 81:* Categorize STAs in a dynamic active list and initialize local timer.

[73] *Block 82:* Is the empty STA active list? If yes, proceed to block 89, or else proceed to block 83.

[74] *Block 83:* Choose an STA from the active list and transmit a directional frame to the chosen STA.

[75] *Block 84:* Reset the timeout value (t_i) of STA i or remove from the active list if the timeout value is smaller than current time.

[76] *Block 85:* Update timer for other STAs on the active list.

[77] *Block 86:* Any STA timeout? If yes, proceed to block 87, or else proceed to block 88.

[78] *Block 87:* Remove timeout STA(s) from the active list. Proceed to block 88.

[79] *Block 88:* AT is about to end? If yes, proceed to block 89, or else proceed to block 82.

[80] *Block 89:* End.

[81] As such, embodiments of the present invention allow AT period operations to suit power saving STAs, and allow AT operations to be more traceable to both STAs and

the coordinator. Dynamic control of the AT by the coordinator provides efficiency. Service Period (SP) schedule information communication overhead to power saving STAs is reduced. An expedited AT transmission schedule is employed by the coordinator for power saving stations. Multi-level PS-based time-bounded differentiated services are provided during the AT.

- [82] The length of the idle timeout interval is variable rather than a fixed time window for all STAs. Wireless channel access based on the AT period comprises a polling period wherein the coordinator manages wireless channel access (non-contention) for STAs for accessing the shared wireless channel. Request and response frames are communicated between the coordinator and an STA during the AT period for managing wireless channel.
- [83] FIG. 8 shows a block diagram of an example wireless communication network system 200, implementing an embodiment of the present invention. The system 200 includes a wireless transmitter station 202 (such as STA1 in Fig. 1A) and a wireless receiver station 204 (such as STA2 in FIG. 1A), for wireless data communication, such as wireless transmission of audio/video information over a radio frequency channel 201. The system 200 also includes a wireless coordinator device 235 (such as coordinator 6 in FIG. 1A) that facilitates communications in the network. The stations 202 and 204 may be power saving STAs as described herein.
- [84] The transmitter 202 includes a PHY layer 206, a MAC layer 208, and an application layer 210. The MAC layer 208 includes a power saving module 209 which implements a power saving process according to embodiments of the invention disclosed herein, such as process 60 described above in relation to Fig. 6. The power saving module 209 also implements a countdown timer as needed. The PHY layer 206 includes a radio frequency (RF) communication module 207 for transmitting/receiving signals under control of a baseband process module 230. The baseband process module 230 allows communicating control information and other information.
- [85] The application layer 210 includes an audio/visual (A/V) pre-processing module 211 for packetizing video streams, which are then converted to MAC packets by the MAC layer 208. The application layer 210 further includes an AV/C control module 212 which sends stream transmission requests and control commands to reserve radio frequency channel time blocks for transmission of packets. In one embodiment, the transmitter 202 further includes hardware processor, memory, logic, integrated circuits, etc. (not shown) as part of the PHY layer, configured according to embodiments of the present invention.
- [86] The wireless receiver station 204 includes a PHY layer 214, a MAC layer 216, and an application layer 218. The MAC layer 216 includes a power saving module 217 which implements a power saving process such as process 60 described above in

relation to Fig. 6, according to an embodiment of the invention. The PHY layer 214 includes a RF communication module 213 which transmits/receives signals under control of a baseband process module 231. The application layer 218 includes an A/V post-processing module 219 for de-packetizing the video information in the MAC packets into streams, received by the MAC layer 216. The de-packetizing is reverse of the packetization by A/V pre-processing module 211 in the application layer 210 of wireless transmitter station 202. The application layer 218 further includes an AV/C control module 220 which handles stream control and channel access. Beamforming transmissions may be performed over multiple channels. The MAC/PHY layers may perform antenna training and beaming switching control for directional transmission such as beamforming communications. In one embodiment, the receiver 204 further includes hardware processor, memory, logic, integrated circuits, etc. (not shown) as part of the PHY layer, configured according to embodiments of the present invention.

[87] Similarly, the wireless coordinator station 235 also includes a MAC layer 236 and a PHY layer 238. The MAC layer 236 includes a scheduling module 239 which implements a scheduling saving process according to embodiments of the invention disclosed herein, such as process 80 described above in relation to Fig. 7. The scheduling module 239 also implements a countdown timer as needed. The PHY layer 238 includes similar components as those in the transmitter 202 and the receiver 204.

[88] As such, in one example, each of the STAs 202, 204 implements the process 60 in their MAC layers 208, 216, respectively. Further, the coordinator 235 implements the process 80 in the MAC layer 236. In one example, the wireless system 200 comprises a wireless local area network (WLAN) such as an IEEE 802.11 WLAN, but is enhanced according to embodiments of the present invention as described herein.

[89] An example implementation of the present invention in the system 200 for mmWave wireless communication such as for a 60 GHz radio frequency band wireless network is useful with WiGig applications (e.g., all client types, including A/V equipment, network devices, PCs and handhelds). An example WiGig network utilizes a 60 GHz-band mmWave technology to support a physical (PHY) layer data transmission rate of multi-Gbps (gigabits per second).

[90] As is known to those skilled in the art, the aforementioned example architectures described above, according to the present invention, can be implemented in many ways, such as program instructions for execution by a processor, as software modules, microcode, as computer program product on computer readable media, as logic circuits, as application specific integrated circuits, as firmware, as consumer electronic devices, etc., in wireless devices, in wireless transmitters/receivers, in wireless networks, etc. Further, embodiments of the invention can take the form of an entirely hardware embodiment, an entirely software embodiment, or an embodiment containing

both hardware and software elements.

- [91] FIG. 9 is a high level block diagram showing an information processing system comprising a computer system 100 useful for implementing an embodiment of the present invention. The computer system 100 includes one or more processors 101, and can further include an electronic display device 102 (for displaying graphics, text, and other data), a main memory 103 (e.g., random access memory (RAM)), a storage device 104 (e.g., hard disk drive), a removable storage device 105 (e.g., a removable storage drive, a removable memory module, a magnetic tape drive, an optical disk drive, a computer readable medium having stored therein computer software and/or data), a user interface device 106 (e.g., keyboard, touch screen, keypad, pointing device), and a communication interface 107 (e.g., a modem, a network interface [such as an Ethernet card], a communications port, or a PCMCIA slot and card). The communication interface 107 allows software and data to be transferred between the computer system and external devices. The system 100 further includes a communications infrastructure 108 (e.g., a communications bus, cross-over bar, or network) to which the aforementioned devices/modules 101 through 107 are connected.
- [92] Information transferred via communications interface 107 may be in the form of signals such as electronic, electromagnetic, optical, or other signals capable of being received by communications interface 107, via a communication link that carries signals and may be implemented using wire or cable, fiber optics, a phone line, a cellular phone link, an radio frequency (RF) link, and/or other communication channels. Computer program instructions representing the block diagram and/or flowcharts herein may be loaded onto a computer, programmable data processing apparatus, or processing devices to cause a series of operations performed thereon to produce a computer implemented process.
- [93] Embodiments of the present invention have been described with reference to flowchart illustrations and/or block diagrams of methods, apparatus (systems) and computer program products according to embodiments of the invention. Each block of such illustrations/diagrams, or combinations thereof, can be implemented by computer program instructions. The computer program instructions when provided to a processor produce a machine, such that the instructions, which execute via the processor, create means for implementing the functions/operations specified in the flowchart and/or block diagram. Each block in the flowchart /block diagrams may represent a hardware and/or software module or logic, implementing embodiments of the present invention. In alternative implementations, the functions noted in the blocks may occur out of the order noted in the figures, concurrently, etc.
- [94] The terms "computer program medium," "computer usable medium," "computer readable medium," and "computer program product," are used to generally refer to

media such as main memory, secondary memory, removable storage drive, a hard disk installed in hard disk drive, and signals. These computer program products are means for providing software to the computer system. The computer readable medium allows the computer system to read data, instructions, messages or message packets, and other computer readable information from the computer readable medium. The computer readable medium, for example, may include non-volatile memory, such as a floppy disk, ROM, flash memory, disk drive memory, a CD-ROM, and other permanent storage. It is useful, for example, for transporting information, such as data and computer instructions, between computer systems. Computer program instructions may be stored in a computer readable medium that can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions stored in the computer readable medium produce an article of manufacture including instructions which implement the function/act specified in the flowchart and/or block diagram block or blocks.

[95] Furthermore, the computer readable medium may comprise computer readable information in a transitory state medium such as a network link and/or a network interface, including a wired network or a wireless network, that allows a computer to read such computer readable information. Computer programs (i.e., computer control logic) are stored in main memory and/or secondary memory. Computer programs may also be received via a communications interface. Such computer programs, when executed, enable the computer system to perform the features of the present invention as discussed herein. In particular, the computer programs, when executed, enable the multi-core processor to perform the features of the computer system. Such computer programs represent controllers of the computer system.

[96] Though the present invention has been described with reference to certain versions thereof; however, other versions are possible. Therefore, the spirit and scope of the appended claims should not be limited to the description of the preferred versions contained herein.

[97]

Claims

- [Claim 1] A method of wireless communication over a wireless communication medium, comprising:
generating a schedule indicating when one or more wireless communication stations may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period; wherein the AT period comprises a period after a beacon transmission in a beacon interval.
- [Claim 2] The method of claim 1, wherein:
generating a schedule indicating when a wireless communication station may enter a power saving state in an AT period, further comprises indicating the length of time the wireless communication station may remain in the power saving state.
- [Claim 3] The method of claim 1, further comprising:
wirelessly providing the schedule from a coordinator to a power saving wireless communication station in a wireless network in real-time during the AT period; and
each power saving wireless station utilizing the schedule to determine a wake up schedule in a Beacon Interval (BI).
- [Claim 4] The method of claim 3, further comprising:
generating a schedule indicating when a wireless communication station may enter a power saving state in an announcement time (AT) period, by assigning timeout policies to multiple levels of power sensitive wireless communication stations.
- [Claim 5] The method of claim 4, further comprising:
the coordinator maintaining a dynamic, policy-based, list of wireless communication stations to determine said schedule, wherein the dynamic list categorizes and separates the wireless communication stations based on their power sensitivity levels.
- [Claim 6] The method of claim 5, further comprising:
the coordinator dynamically updating the dynamic list based on a parameter setup during each AT period.
- [Claim 7] The method of claim 6, further comprising:
assigning N idle timeout policies to M levels of power sensitive power saving wireless stations;
wherein a less power sensitive wireless communication station obtains a loosely bounded or unbounded timeout policy, and a more power

sensitive wireless communication station obtains a tightly bounded timeout policy.

[Claim 8]

The method of claim 3, further comprising:

in case of a frame loss during the AT period, or in case the coordinator does not send additional frames to the power saving wireless communication stations, the coordinator utilizing a countdown timeout timer based on the idle timeout interval to indicate idle timeout; and the power saving wireless stations determining when each power saving station may enter a power saving state without staying awake for at least a portion of the remainder of a beacon interval (BI).

[Claim 9]

The method of claim 8, wherein:

an AT period is present in a BI where the duration of the AT period is unknown to the wireless stations at the time the BI enters the AT period.

[Claim 10]

The method of claim 9, further comprising:

the coordinator wirelessly transmitting directed frames to one or more wireless communication stations during the AT period and each wireless communication station remaining awake to receive, and respond to, the directed frames during a portion of the AT period known by both the coordinator and each individual wireless communication station.

[Claim 11]

The method of claim 10, further comprising:

a power saving wireless station utilizing a countdown timeout timer based on the idle timeout interval in the schedule; and resetting the timer to idle timeout interval when the power saving wireless station receives a directed frame from the coordinator.

[Claim 12]

The method of claim 10, further comprising:

a power saving wireless station utilizing a countdown timeout timer based on an idle timeout interval in the schedule; and resetting the timer when a set of predefined events that are commonly observable to both the power saving wireless station and the coordinator occur.

[Claim 13]

The method of claim 10, further comprising:

a power saving wireless station utilizing a countdown timeout timer based on an idle timeout interval in the schedule; and upon reception of a directed frame from the coordinator, a power saving wireless station starting a new awake policy that is either conveyed in the received frame or is previously agreed upon with the

coordinator.

[Claim 14]

The method of claim 1, further comprising:
assigning different AT period timeout interval starting points for different levels of power sensitive wireless stations;
adaptively adjusting AT period idle time out policies to one or more power saving wireless stations.

[Claim 15]

The method of claim 3, wherein:
the wireless communication medium comprises a mmWave wireless channel;
the wireless communication stations and the coordinator are configured to wirelessly communicate in a wireless local area network via the wireless communication medium.

[Claim 16]

A wireless coordinator station, comprising:
a scheduling module configured for generating a schedule indicating when a wireless communication station may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval; and
a physical layer configured for wireless communication with one or more wireless communication stations over a wireless communication medium.

[Claim 17]

The wireless coordinator station of claim 16, wherein:
the scheduling module is further configured for indicating the length of time a wireless communication station may remain in the power saving state.

[Claim 18]

The wireless coordinator station of claim 16, wherein:
the schedule is wirelessly provided to a power saving wireless communication station in a wireless network in real-time during the AT period, such that each power saving wireless station may utilize the schedule to determine a wake up schedule in a Beacon Interval (BI).

[Claim 19]

The wireless coordinator station of claim 18, wherein:
the scheduling module is further configured for generating a schedule indicating when a wireless communication station may enter a power saving state in an announcement time (AT) period, by assigning timeout policies to multiple levels of power sensitive wireless communication stations.

[Claim 20]

The wireless coordinator station of claim 19, wherein:
the scheduling module is further configured for maintaining a dynamic,

policy-based, list of one or more wireless communication stations to determine said schedule, wherein the dynamic list categorizes and separates wireless communication stations based on their power sensitivity levels.

[Claim 21] The wireless coordinator station of claim 20, wherein:
the scheduling module is further configured for dynamically updating the dynamic list based on a parameter setup during each AT period.

[Claim 22] The wireless coordinator station of claim 21, wherein:
N idle timeout policies are assigned to M levels of power sensitive power saving wireless communication stations such that a less power sensitive wireless communication station receives a loosely bounded or unbounded timeout policy, and a more power sensitive wireless communication station receives a tightly bounded timeout policy.

[Claim 23] The wireless coordinator station of claim 18, wherein:
the scheduling module is further configured such that, in case of a frame loss during the AT period or in case the wireless coordinator station does not send additional frames to the power saving wireless communication stations, the wireless coordinator station utilizes a countdown timeout timer based on the idle timeout interval to indicate idle timeout;
whereby one or more power saving wireless communication stations may determine when each power saving communication station may enter a power saving state without staying awake for at least a portion of the remainder of a beacon interval (BI).

[Claim 24] The wireless coordinator station of claim 23, wherein:
an AT period is present in a BI where the duration of the AT period is unknown to a wireless communication station at the time the BI enters the AT period.

[Claim 25] The wireless coordinator station of claim 24, wherein:
the wireless coordinator station wirelessly transmits directed frames to one or more wireless communication stations during the AT period, such that each wireless communication station may remain awake to receive, and respond to, the directed frames during a portion of the AT period known by both the wireless coordinator station and each individual wireless communication station.

[Claim 26] The wireless coordinator station of claim 16, wherein: different AT period timeout interval starting points are assigned for different levels of power sensitive wireless communication stations, and the scheduling

module is further configured for adaptively adjusting AT period idle time out policies to one or more power saving wireless communication stations.

[Claim 27] The wireless coordinator station of claim 16, wherein:
the wireless communication medium comprises a mmWave wireless channel;
each wireless communication station and the wireless coordinator station are configured to wirelessly communicate in a wireless network via the wireless communication medium.

[Claim 28] A wireless communication station, comprising:
a power saving module configured for receiving a transmission schedule comprising power saving schedule and entering the wireless communication station into a power saving state accordingly, wherein the schedule indicates when the wireless communication station may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval; and
a physical layer configured for wireless communication over a wireless communication medium.

[Claim 29] The wireless communication station of claim 28, wherein:
the schedule further indicates the length of time the wireless communication station may remain in the power saving state.

[Claim 30] The wireless communication station of claim 28, wherein:
the wireless communication station wirelessly receives the schedule from a wireless coordinator station in a wireless network in real-time during the AT period, such that the power saving module utilizes the schedule to determine a wake up schedule in a Beacon Interval (BI).

[Claim 31] The wireless communication station of claim 30, wherein:
the schedule further indicates when the wireless communication station may enter a power saving state in an announcement time (AT) period, utilizing timeout policies assigned to multiple levels of power sensitive wireless communication stations.

[Claim 32] The wireless communication station of claim 31, wherein:
N idle timeout policies are assigned to M levels of power sensitive power saving wireless communication stations such that a less power sensitive wireless communication station receives a loosely bounded or unbounded timeout policy, and a more power sensitive wireless communication station receives a tightly bounded timeout policy.

- [Claim 33] The wireless communication station of claim 30, wherein:
power saving module is configured to enter a power saving state without staying awake for at least a portion of the remainder of a beacon interval (BI).
- [Claim 34] The wireless communication station of claim 33, wherein:
an AT period is present in a BI where the duration of the AT period is unknown to a wireless communication station at the time the BI enters the AT period.
- [Claim 35] The wireless communication station of claim 34, wherein:
the power saving module is configured such that the wireless communication station remains awake to receive, and respond to, directed frames from the coordinator station during a portion of the AT period known by both the coordinator station and the wireless communication station.
- [Claim 36] The wireless communication station of claim 35, wherein:
the power saving module is configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and resetting the timer to the idle timeout interval when the power saving wireless station receives a directed frame from the coordinator station.
- [Claim 37] The wireless communication station of claim 35, wherein:
the power saving module is further configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and resetting timer when a set of predefined events that are commonly observable to both the power saving wireless station and the coordinator station occur.
- [Claim 38] The wireless communication station of claim 35, wherein:
the power saving module is further configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and upon reception of a directed frame from the coordinator station, starting a new awake policy that is either conveyed in the received frame or is previously agreed upon with the coordinator station.
- [Claim 39] The wireless communication station of claim 28 wherein: different AT period timeout interval starting points are assigned for different levels of power sensitive wireless communication stations;
the wireless communication medium comprises a mmWave wireless channel, and the wireless communication station is configured to wirelessly communicate in a wireless local area network via the

wireless communication medium.

[Claim 40]

A wireless communication system, comprising:
a wireless coordinator station comprising a scheduling module configured for generating a schedule indicating when one or more wireless communication stations may enter a power saving state in an announcement time (AT) period, based on an idle timeout interval in the AT period, wherein the AT period comprises a period after a beacon transmission in a beacon interval; and
at least one wireless communication station comprising a power saving module configured for receiving a power saving schedule from the coordinator station over a wireless communication medium, and entering into a power saving state accordingly.

[Claim 41]

The wireless communication system of claim 40, wherein:
the scheduling module is further configured for indicating the length of time a wireless communication station may remain in the power saving state.

[Claim 42]

The wireless communication system of claim 40, wherein:
the schedule is wirelessly provided to a power saving wireless communication station in a wireless network in real-time during the AT period, such that each power saving wireless station may utilize the schedule to determine a wake up schedule in a Beacon Interval (BI).

[Claim 43]

The wireless communication system of claim 42, wherein:
the scheduling module is further configured for generating a schedule indicating when a wireless communication station may enter a power saving state in an announcement time (AT) period, by assigning timeout policies to multiple levels of power sensitive wireless communication stations.

[Claim 44]

The wireless communication system of claim 43, wherein:
the scheduling module is further configured for maintaining a dynamic, policy-based, list of one or more wireless communication stations to determine said schedule, wherein the dynamic list categorizes and separates wireless communication stations based on their power sensitivity levels.

[Claim 45]

The wireless communication system of claim 44, wherein:
the scheduling module is further configured for dynamically updating the dynamic list based on a parameter setup during each AT period.

[Claim 46]

The wireless communication system of claim 45, wherein:
N idle timeout policies are assigned to M levels of power sensitive

power saving wireless communication stations such that a less power sensitive wireless communication station receives a loosely bounded or unbounded timeout policy, and a more power sensitive wireless communication station receives a tightly bounded timeout policy.

[Claim 47]

The wireless communication system of claim 42, wherein:
the scheduling module is further configured such that, in case of a frame loss during the AT period or in case the wireless coordinator station does not send additional frames to power saving wireless communication stations, the wireless coordinator station utilizes a countdown timeout timer based on the idle timeout interval to indicate idle timeout;

whereby the power saving wireless communication station determines when to enter a power saving state without staying awake for at least a portion of the remainder of a beacon interval (BI).

[Claim 48]

The wireless communication system of claim 47, wherein:
an AT period is present in a BI where the duration of the AT period is unknown to a wireless communication station at the time the BI enters the AT period.

[Claim 49]

The wireless communication system of claim 48, wherein:
the wireless coordinator station wirelessly transmits directed frames to one or more wireless communication stations during the AT period, and wherein the power saving module is configured such that the wireless communication station remains awake to receive, and respond to, directed frames from the coordinator station during a portion of the AT period known by both the coordinator station and the wireless communication station.

[Claim 50]

The wireless communication system of claim 49, wherein:
the power saving module is configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and resetting the timer to idle timeout interval when the power saving wireless station receives a directed frame from the coordinator station.

[Claim 51]

The wireless communication system of claim 49, wherein:
the power saving module is further configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and resetting timer when a set of predefined events that are commonly observable to both the power saving wireless station and the coordinator station occur.

[Claim 52]

The wireless communication system of claim 49, wherein:

the power saving module is further configured for utilizing a countdown timeout timer based on the idle timeout interval in the schedule, and upon reception of a directed frame from the coordinator station, starting a new awake policy that is either conveyed in the received frame or is previously agreed upon with the coordinator station.

[Claim 53] The wireless communication system of claim 40, wherein: different AT period timeout interval starting points are assigned for different levels of power sensitive wireless communication stations.

[Claim 54] The wireless communication system of claim 53, wherein: the scheduling module is further configured for adaptively adjusting AT period idle time out policies to one or more power saving wireless communication stations.

[Claim 55] The wireless communication system of claim 40, wherein: the wireless communication medium comprises a mmWave wireless channel;
the wireless coordinator station and said at least one wireless communication station are configured to wirelessly communicate in a wireless network via the wireless communication medium.

[Claim 56] The wireless communication system of claim 55, wherein: the mmWave wireless channel comprise a 60 GHz radio frequency band.

[Claim 57] The wireless communication system of claim 56, wherein: the wireless network comprises a wireless local area network.