

Electrical switch with resilient contact arm

This invention relates to an electrical switch.

Many forms of electrical switch are known, and a common form comprises a housing carrying a first, fixed contact and a second, movable contact in the form of a resilient contact arm secured to the housing at one end, and an actuator member mounted on the housing and operable to urge the resilient contact arm from a first position out of engagement with the fixed contact into a second position in engagement with the fixed contact.

In such known switches the actuator member can be a push-button, a slider member or a rotary member, being mounted on the housing in dependence upon its particular manner of operation.

Whatever the manner of operation of the actuator member, it is desirable for the actuator member to be easily operable, and for there to be a high contact force between the fixed and movable contacts in the closed condition of the switch.

In U.S. Patent Specification No. 4,081,632 there is described a switch as set out above in which, on operation of the switch, the resilient contact arm is brought into engagement intermediate its ends, with a fixed part of the switch whereby the effective resilient length of the contact arm is reduced as the contact arm moves from its first position to its second position.

This known switch gives the advantages of ease of operation together with a high contact force as mentioned above, but has the disadvantage that in view of the form of the resilient contact arm, this being a single limb cantilever member, and the need to provide a fixed part in the switch for engagement by the resilient contact arm intermediate its ends, the switch cannot be made of relatively small size.

In US—A—4097702 there is disclosed an electrical switch comprising a first, fixed contact and a second, movable contact in the form of a resilient contact arm secured at one end, and an actuator member operable to urge the resilient contact arm from a first position out of engagement with the fixed contact into a second position in engagement with the fixed contact, the resilient contact arm extending from its secured end as a single inner limb and then dividing into two outer limbs one of which is engaged by the actuator member and the other of which engages the fixed contact on operation of the actuator member, the arrangement being such that on operation of the actuator member, initially the whole resilient contact arm deflects by bending of the single inner limb until said other outer limb engages the fixed contact whereafter the two outer limbs of the resilient contact arm are deflected towards each other thereby to increase the contact force between said other outer limb and the fixed contact.

This known switch is mechanically operated and is not designed for manual operation, and thus there is no provision for tactile operation of the switch.

According to this invention a switch as set out in the penultimate paragraph is characterised in that the fixed contact and the resilient contact arm and the actuator member are carried by a housing, said one outer limb being shaped such that during movement of the actuator member, deflection of the two outer limbs of the resilient contact arm towards each other passes through a maximum and then decreases whereby an over-centre action for the actuator member is achieved.

In the switch of this invention ease of operation of the actuator member is achieved in that initially the whole resilient contact arm is deflected by bending of the single inner limb thereof, this bending offering little resistance to movement of the actuator member, while a high final contact force is achieved by the subsequent movement of the outer limbs of the resilient contact member towards each other while one limb is in contact with the fixed contact, these advantages being obtained in a manner which enables the switch to be of relatively small size and which provides for tactile operation.

Electrical switches according to this invention will now be described by way of example with reference to the drawings, in which:—

Figure 1 is a diagrammatic sectional view through a first switch in a first condition;

Figure 2 is a view similar to Figure 1 but with the first switch in a second condition;

Figure 3 is a diagrammatic sectional view through the first switch at right angles to the views of Figures 1 and 2;

Figure 4 is a view similar to Figure 1 but through a second switch;

Figure 5 is a view similar to Figure 2 but through the second switch;

Figure 6 is a view similar to Figure 1 but through a third switch; and

Figure 7 is a view similar to Figure 1 but through a fourth switch.

The switch shown in Figures 1 to 3 comprises a housing 1 moulded from electrically insulating plastics material in the form of an open rectanguloid box. The base 2 of the housing 1 carries a first fixed metal contact 3 having a contact head 4 located within the housing 1, and a pin portion 5 projecting from the base 2 of the housing 1 for receipt, for example, in a hole in a substrate such as a printed circuit board (not shown). Also secured to the base 2 is a second contact 6 stamped and formed from resilient sheet metal, and having a pin portion 7 projecting from the base 2 similarly to and spaced from the pin portion 5 of the fixed contact 3, and having within the

housing 1 a movable resilient contact arm 8. The contact arm 8 comprises a single inner L-shaped limb 9 extending from the pin portion 7, which inner limb 9 divides into two outer limbs 10 and 11 joined by a cross limb 12 to give a U-shape.

The housing 1 is closed by a cover 13 having a slot 14 therein, and an actuator member 15 is positioned in the slot 14 for movement from a first position, shown in Figure 1, in which a head 16 of the actuator member 15 located within the housing 1 is positioned substantially over the pin portion 7 of the second contact 6, and a second position, shown in Figure 2, in which the head 16 is positioned substantially over the fixed contact 3. The top, outer part of the actuator member 15 is shown broken away, but can be of any convenient form suitable for effecting the necessary sliding movement of the actuator member 15 along the slot 14 between the two positions described.

As clearly shown in Figure 1, the upper (as seen in the drawings) outer limb 10 of the contact arm 8 presents an outer edge which has a first portion 17 which slopes from the end of the inner arm 9 towards the cover 13, and a second portion 18 which extends parallel to the cover 13 (and thus to the base 2), to the free end of the limb 10.

In the first condition of the switch shown in Figure 1, the head 16 of the actuator member 15 is resting on the inner limb 9 of the contact arm 8, the lower outer limb 11 is out of contact with the fixed contact head 4, and the resilient contact arm 8 is unflexed.

As the actuator member 15 is slid along the slot 14 towards the second position shown in Figure 2, the head 16 engages the first portion 17 of the edge of the upper outer limb 10 of the contact arm 8, and initially the whole contact arm 8 is resiliently deflected by bending of the inner limb 9 until the lower outer limb 11 comes into engagement with the head 4 of the fixed contact 3. (Figure 2 shows the inner limb 9 in this flexed condition). Thereafter, further movement of the head 16 along the edge portion 17 causes the two outer limbs 10 and 11 of the contact arm 8 to be resiliently deflected towards each other, thereby to increase the contact force between the lower outer limb 11 and the head 4 of the fixed contact 3.

The head 16 then passes over the ridge 19 between the edge portions 17 and 18 of the upper outer limb 10 and passes on to the edge portion 18 which, due to the bending of the inner limb 9 is now sloping away from the cover 13 in the direction away from the ridge 19, as shown in Figure 2, until the switch is in a second condition as shown in Figure 2 in which electrical connection between the post portions 5 and 7 of the contacts 3 and 8 is maintained.

Due to the above described manner of operation of the switch, an over-centre action is achieved for the actuator member 15 giving a

user a positive feel indicating correct operation of the switch. The resistance to movement of the actuator member 15 felt by a user increases as the head 16 passes along the edge portion 17 of the upper outer limb 10 until the head 16 passes over the ridge 19 whereafter the force decreases again as the head 16 passes along the edge portion 18 of the upper outer limb 10.

The maximum contact force between the lower outer limb 11 and head 4 of the fixed contact 3, and the maximum deflection of the outer limb 10 and 11 towards each other, occurs as the head 16 of the actuator member 15 passes over the ridge 19, after which the outer limbs 10 and 11 relax slightly. This action causes a slight beneficial sliding action between the lower outer limb 11 and the head 4 of the fixed contact 3.

A similar over-centre action is felt as the actuator member 15 is returned to the first position shown in Figure 1, the lower outer limb 11 coming out of contact with the head 4 of the fixed contact 3 during this movement.

As shown in Figure 3, the housing 1 and cover 13 can be moulded together with a plurality of similar structures in strip form whereby a multiple switch can be produced. Preferably adjacent housings and covers are separated by a line of weakness 20 whereby a single or strip of any required number of housings and covers can be broken from a longer strip.

Referring now to Figures 4 and 5, the switch here shown is similar to that shown in Figures 1 to 3, and corresponding parts have the same reference numerals.

In the switch shown in Figures 1 and 2 the area of contact between the fixed contact 3 and the resilient contact arm 11 is exposed to the surrounding atmosphere, and while this may normally be acceptable, there are occasions when it is desirable for the contact area to be protected from the surrounding atmosphere, the switch then being a so-called gas-tight switch.

Thus, in the switch shown in Figures 4 and 5, the wall 21 of the housing 1 adjacent the fixed contact 3 is formed with a thickened portion 22 through which the fixed contact 3 extends, and with a slot 23 which receives a body 24 of resilient electrically insulating material. The body 24 is received in the slot 23 on the surface of the thickened portion 22 of the wall 21, and envelopes both the contact head 4 of the fixed contact 3, and also the contact head 25 of the lower outer limb 11 of the contact arm 8. The body 24 can be pre-formed and mounted on the housing 1 prior to mounting of the contacts 3 and 8 thereon, or the body 24 can be formed in situ on the housing 1 by, for example, injection of a room-temperature curing paste, or by a moulding operation, either before or after the contacts 3 and 8 are mounted thereon.

On first operation of the switch from the condition of Figure 4 to that of Figure 5 the contact head 25 of the outer limb 11 is urged

through the material of the body 24, and the contact head 25 is therefore preferably sharp to facilitate such penetration. On return of the switch to the condition of Figure 1 the material of the body 24 relaxes to fill the space between the contact heads 4 and 25, thereby retaining the sealing of the contact position at all times.

The switch shown in Figures 4 and 5 can be part of a multiple switch arrangement, as shown in Figure 3, formed from a plurality of such switches arranged in a row with their housings 1 integrally formed, in which case the body 24 of resilient electrically insulating material can be a single body common to all of the switches of the row.

Referring now to Figure 6, the switch here shown is similar to that shown in Figures 1 and 2, and corresponding parts have the same reference numbers.

The essential differences between the switch of Figure 6 and that of Figures 1 and 2 are that in the switch of Figure 6 the housing 1 is of one-piece construction, not having a separate lid (13) as used in Figures 1 and 2, and that the actuator member 15 in Figure 6 is retained in the housing 1 by an extension of the single inner limb 9 of the resilient contact 6. The fixed contact 3 is also mounted differently in that it is inserted from the side rather than from the bottom of the housing. The housing 1 can thus be moulded in one piece, with all the necessary cores moving horizontally of the housing 1 as seen in the drawing.

The housing 1 is open to one side (left-hand side in Figure 6) and the actuator member 15 is introduced into the housing from this side. The contact 6 is then mounted on the housing 1 from the open side thereof, the extension on the single inner limb 9 of the contact 6 engaging behind the actuator member 15 which is thus retained in the housing 1 thereby.

Referring now to Figure 7, the switch here shown is similar to that shown in Figure 6, but includes a body 24 of resilient electrically insulating material as shown in the switch of Figures 4 and 5. The housing 1 is again of one-piece construction, with the actuator member 15 being retained in place by the contact 6.

The switches of Figures 6 and 7 have the advantage that they are easy to manufacture and assemble, and are thus relatively cheap, while still retaining the advantages of the switches of Figures 1 and 2; or Figures 3 and 4 respectively.

Claim

An electrical switch comprising a first, fixed contact (3) and a second, movable contact in the form of a resilient contact arm (6) secured at one end, and an actuator member (15) operable to urge the resilient contact arm (6) from a first position out of engagement with the fixed contact (3) into a second position in engagement with the fixed contact (3), the resilient

contact arm (6) extending from its secured end as a single inner limb (9) and then dividing into two outer limbs (10, 11) one (10) of which is engaged by the actuator member (15) and the other (11) of which engages the fixed contact (3) on operation of the actuator member (15), the arrangement being such that on operation of the actuator member (15), initially the whole resilient contact arm (9, 10, 11) deflects by bending of the single inner limb (9) until said other outer limb (11) engages the fixed contact (3) whereafter the two outer limbs (10, 11) of the resilient contact arm (9, 10, 11) are deflected towards each other thereby to increase the contact force between said other outer limb (11) and the fixed contact (3), characterised in that the fixed contact (3) and the resilient contact arm (9, 10, 11) and the actuator member (15) are carried by a housing (1), said one outer limb (10) being shaped such that during movement of the actuator member (15), deflection of the two outer limbs (10, 11) of the resilient contact arm (9, 10, 11) towards each other passes through a maximum and then decreases whereby an over-centre action for the actuator member (15) is achieved.

Revendication

Interrupteur électrique comprenant un premier contact fixe (3) et un second contact mobile sous la forme d'une lame de contact élastique (6) fixée à une extrémité, et un élément d'actionnement (15) pouvant être manoeuvré pour déplacer la lame de contact élastique (6) d'une première position éloignée du contact fixe (3) vers une seconde position appliquée contre le contact fixe (3), la lame de contact élastique (6) s'étendant à partir de son extrémité fixée sous la forme d'une branche intérieure unique (9), puis se divisant en deux branches extérieures (10, 11) dont une première (10) est engagée par l'élément d'actionnement (15) et la seconde (11) porte contre le contact fixe (3) lors d'une manoeuvre de l'élément d'actionnement (15), l'agencement étant tel que, lors d'une manoeuvre de l'élément d'actionnement (15), la totalité de la lame de contact élastique (9, 10, 11) dévie initialement par flexion de la branche intérieure unique (9) jusqu'à ce que ladite seconde branche extérieure (11) porte contre le contact fixe (3), après quoi les deux branches extérieures (10, 11) de la lame de contact élastique (9, 10, 11) sont déviées l'une vers l'autre afin d'accroître la force de contact entre ladite seconde branche extérieure (11) et le contact fixe (3), caractérisé en ce que le contact fixe (3) et la lame de contact élastique (9, 10, 11) et l'élément d'actionnement (15) sont portés par un boîtier (1), ladite première branche extérieure (10) étant configurée de manière que, pendant un mouvement de l'élément d'actionnement (15), une déviation des deux

through the material of the body 24, and the contact head 25 is therefore preferably sharp to facilitate such penetration. On return of the switch to the condition of Figure 1 the material of the body 24 relaxes to fill the space between the contact heads 4 and 25, thereby retaining the sealing of the contact position at all times.

The switch shown in Figures 4 and 5 can be part of a multiple switch arrangement, as shown in Figure 3, formed from a plurality of such switches arranged in a row with their housings 1 integrally formed, in which case the body 24 of resilient electrically insulating material can be a single body common to all of the switches of the row.

Referring now to Figure 6, the switch here shown is similar to that shown in Figures 1 and 2, and corresponding parts have the same reference numbers.

The essential differences between the switch of Figure 6 and that of Figures 1 and 2 are that in the switch of Figure 6 the housing 1 is of one-piece construction, not having a separate lid (13) as used in Figures 1 and 2, and that the actuator member 15 in Figure 6 is retained in the housing 1 by an extension of the single inner limb 9 of the resilient contact 6. The fixed contact 3 is also mounted differently in that it is inserted from the side rather than from the bottom of the housing. The housing 1 can thus be moulded in one piece, with all the necessary cores moving horizontally of the housing 1 as seen in the drawing.

The housing 1 is open to one side (left-hand side in Figure 6) and the actuator member 15 is introduced into the housing from this side. The contact 6 is then mounted on the housing 1 from the open side thereof, the extension on the single inner limb 9 of the contact 6 engaging behind the actuator member 15 which is thus retained in the housing 1 thereby.

Referring now to Figure 7, the switch here shown is similar to that shown in Figure 6, but includes a body 24 of resilient electrically insulating material as shown in the switch of Figures 4 and 5. The housing 1 is again of one-piece construction, with the actuator member 15 being retained in place by the contact 6.

The switches of Figures 6 and 7 have the advantage that they are easy to manufacture and assemble, and are thus relatively cheap, while still retaining the advantages of the switches of Figures 1 and 2; or Figures 3 and 4 respectively.

Claim

An electrical switch comprising a first, fixed contact (3) and a second, movable contact in the form of a resilient contact arm (6) secured at one end, and an actuator member (15) operable to urge the resilient contact arm (6) from a first position out of engagement with the fixed contact (3) into a second position in engagement with the fixed contact (3), the resilient

contact arm (6) extending from its secured end as a single inner limb (9) and then dividing into two outer limbs (10, 11) one (10) of which is engaged by the actuator member (15) and the other (11) of which engages the fixed contact (3) on operation of the actuator member (15), the arrangement being such that on operation of the actuator member (15), initially the whole resilient contact arm (9, 10, 11) deflects by bending of the single inner limb (9) until said other outer limb (11) engages the fixed contact (3) whereafter the two outer limbs (10, 11) of the resilient contact arm (9, 10, 11) are deflected towards each other thereby to increase the contact force between said other outer limb (11) and the fixed contact (3), characterised in that the fixed contact (3) and the resilient contact arm (9, 10, 11) and the actuator member (15) are carried by a housing (1), said one outer limb (10) being shaped such that during movement of the actuator member (15), deflection of the two outer limbs (10, 11) of the resilient contact arm (9, 10, 11) towards each other passes through a maximum and then decreases whereby an over-centre action for the actuator member (15) is achieved.

Revendication

Interrupteur électrique comprenant un premier contact fixe (3) et un second contact mobile sous la forme d'une lame de contact élastique (6) fixée à une extrémité, et un élément d'actionnement (15) pouvant être manoeuvré pour déplacer la lame de contact élastique (6) d'une première position éloignée du contact fixe (3) vers une seconde position appliquée contre le contact fixe (3), la lame de contact élastique (6) s'étendant à partir de son extrémité fixée sous la forme d'une branche intérieure unique (9), puis se divisant en deux branches extérieures (10, 11) dont une première (10) est engagée par l'élément d'actionnement (15) et la seconde (11) porte contre le contact fixe (3) lors d'une manoeuvre de l'élément d'actionnement (15), l'agencement étant tel que, lors d'une manoeuvre de l'élément d'actionnement (15), la totalité de la lame de contact élastique (9, 10, 11) dévie initialement par flexion de la branche intérieure unique (9) jusqu'à ce que ladite seconde branche extérieure (11) porte contre le contact fixe (3), après quoi les deux branches extérieures (10, 11) de la lame de contact élastique (9, 10, 11) sont déviées l'une vers l'autre afin d'accroître la force de contact entre ladite seconde branche extérieure (11) et le contact fixe (3), caractérisé en ce que le contact fixe (3) et la lame de contact élastique (9, 10, 11) et l'élément d'actionnement (15) sont portés par un boîtier (1), ladite première branche extérieure (10) étant configurée de manière que, pendant un mouvement de l'élément d'actionnement (15), une déviation des deux



branches extérieures (10, 11) de la lame de contact élastique (9, 10, 11), l'une vers l'autre, passe par un maximum, puis diminue afin qu'une action de genouillère soit obtenue pour l'élément d'actionnement (15).

Patentanspruch

Elektrischer Schalter, der einen ersten festen Kontakt (3) und einen zweiten, beweglichen Kontakt in Form eines elastischen Kontaktarmes (6) besitzt, der an dem einen Ende befestigt ist, sowie ein Betätigungselement (15), das betätigbar ist, um den elastischen Kontaktarm (6) aus einer ersten Stellung, in der er sich außer Eingriff mit dem festen Kontakt (3) befindet, in eine zweite Stellung zu bewegen, in der er mit dem festen Kontakt (3) in Eingriff tritt, wobei sich der elastische Kontaktarm (6) von seinem befestigten Ende ausgehend als einzelner innerer Schenkel (9) erstreckt und sich dann in zwei äußere Schenkel (10, 11) aufteilt, von denen der eine (10) mit dem Betätigungselement (15) in Eingriff steht und der andere (11) mit dem festen Kontakt (3) bei einer

Betätigung des Betätigungselementes (15) in Eingriff tritt, wobei die Anordnung so getroffen ist, daß bei Betätigung des Betätigungselementes (15) zunächst sich der gesamte elastische Kontaktarm (9, 10, 11) dadurch verformt, daß der einzelne innere Schenkel (9) solange gebogen wird, bis der äußere Schenkel (11) mit dem festen Kontakt (3) in Eingriff tritt, worauf die beiden äußeren Schenkel (10, 11) des elastischen Kontaktarmes (9, 10, 11) aufeinander zu verbogen werden, wodurch die Kontaktkraft zwischen dem äußeren Schenkel (11) und dem festen Kontakt (3) vergrößert wird, dadurch gekennzeichnet, daß der feste Kontakt (3) und der elastische Kontaktarm (9, 10, 11) und das Betätigungselement (15) von einem Gehäuse (1) getragen sind und daß der eine äußere Schenkel (10) so geformt ist, daß während einer Bewegung des Betätigungselementes (15) die Verbiegung der beiden äußeren Schenkel (10, 11) des elastischen Kontaktarmes (9, 10, 11) aufeinander zu ein Maximum durchläuft und dann wieder abnimmt, wodurch eine Sprungwirkung für das Betätigungselement (15) erzielt wird.

