

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 July 2007 (19.07.2007)

PCT

(10) International Publication Number
WO 2007/081323 A1

(51) International Patent Classification:
B60C 1/00 (2006.01) **B32B 25/08** (2006.01)

(74) Agent: **CHENG, Lee**; RADER, FISHMAN & GRAUER
PLLC, 1233 20TH STREET, N.W., Suite 501, Washington,
District Of Columbia 20036 (US).

(21) International Application Number:
PCT/US2006/000588

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 10 January 2006 (10.01.2006)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants (*for all designated States except US*):
THE YOKOHAMA RUBBER CO., LTD. [JP/JP];
36-11, Shimbashi 5-chome, Minato-ku, Tokyo 105-8685
(JP). **EXXONMOBIL CHEMICAL PATENTS INC.**
[US/US]; 13501 Katy Freeway, Houston, Texas 77079
(US).

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **SOEDA, Yoshihiro**
[JP/JP]; C/O THE YOKOHAMA RUBBER CO., LTD.,
HIRATSUKA FACTORY, 2-1, Oiwake, Hiratsuka-shi,
Kanagawa 254-8601 (JP). **MORROKA, Naoyuki** [JP/JP];
C/O THE YOKOHAMA RUBBER CO., LTD., HIRAT-
SUKA FACTORY, 2-1, Oiwake, Hiratsuka-shi, Kanagawa
254-8601 (JP). **HARA, Yuichi** [JP/JP]; C/O THE YOKO-
HAMA RUBBER CO., LTD., HIRATSUKA FACTORY,
2-1, Oiwake, Hiratsuka-shi, Kanagawa 254-8601 (JP).
TSOU, Andy Haishung [US/US]; 3007 Prairie Knoll
Court, Houston, Texas 77059 (US).

Published:

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: LAMINATE OF THERMOPLASTIC POLYMER COMPOSITION HAVING LOW AIR PERMEABILITY AND PNEUMATIC TIRE USING SAME AS INNER LINER

(57) Abstract: A laminate (C) of a thermoplastic polymer composition comprising: a thermoplastic resin composition (A) having an permeation coefficient of 10×10^{-12} cc•cm/cm²•sec•cmHg or less, laminated with a thermoplastic polymer composition (B) having a melt viscosity of 500 - 2000 Pa•s and a Young's modulus at a room temperature of 1 - 400 MPa, wherein the thickness of a layer of the thermoplastic resin composition (A) is 0.05 - 10 μm and the air permeation coefficient of the laminate (C) of 20×10^{-12} cc • cm/cm² • sec • cmHg or less, and a pneumatic tire using the above laminate (C) as an inner liner.



WO 2007/081323 A1