

FIRE COLLAR

FIELD OF THE INVENTION

This invention relates to a device for
5 preventing fire from spreading from one side of a
partition to another by way of pipework or ducting in the
partition. In particular, the invention is primarily
concerned with a new form of fire damper and a fire
collar for location in a concrete slab separating the
10 floors and walls of multi-floor buildings.

BACKGROUND OF THE INVENTION

A common type of fire collar comprises a metal
collar which is fastened around a concrete slab-
15 penetrating plastics material pipe in the region where it
traverses the slab; the collar enclosing an intumescent
material. When a fire on one side of the concrete slab
reaches a sufficient intensity to melt the pipe where it
penetrates the slab, it also causes the intumescent
20 material to expand and seal off the void left by the
melted pipe. In this way, a barrier is formed to prevent
the spread of the fire to the other side of the concrete
slab.

A major problem with this type of fire collar
25 is that the time taken for the intumescent material to
form a seal can be too long in rapidly advancing fires
with the result that the fire can still spread to the
other side of the partition.

A recent attempt to overcome this problem is a
30 fire damper comprising a tubular insert having a grid of
intumescent material formed across the circumference of
the pipe or duct. However, although such an arrangement
enables very quick sealing to occur, it has the
disadvantage that it slows down the passage of fluid
35 along the pipe or duct. Such a slowdown is amplified by
the number of concrete slabs which the pipe or duct
traverses to the extent that complete blockage of the
fluid can ultimately occur.

OBJECT OF THE INVENTION

It is therefore an object of the invention to provide a new form of fire collar/fire damper which obviates the aforementioned disadvantages or at least provides the public with a useful alternative.

SUMMARY OF THE INVENTION

According to the present invention in its broadest form, there is provided a housing for fitting into pipework or ducting at the location the pipework or ducting traverses a partition, which housing incorporates a damper arrangement and a heat detector, wherein the damper arrangement is designed to normally enable unimpeded fluid flow through the pipework or ducting but to seal off the pipework or ducting when the heat detector reacts to a preset temperature value.

By "fluid" is intended to mean gases, such as air-conditioning air, waste gases, and liquids such as liquid wastes and water.

DETAILED DESCRIPTION OF THE INVENTION

Preferably, the damper arrangement incorporates a cylinder or ball valve having an internal passageway which is of the same or similar diameter to that of the pipework or ducting in which it is fitted. The cylinder or ball valve is arranged so as to be rotatable about an axis so that it can rotate between a normal open position where passage of fluid through the pipework or ducting is unimpeded to a position, generally at right angles to the open position, where passage of fluid is prevented.

Rotation of the cylinder or ball valve can be achieved by mechanical and/or electrical means. Mechanical rotation can be, for instance, by the use of a spiral spring retained in a recess formed in an exterior wall of the housing, having its outer end held by the housing and its inner end held by the cylinder or ball valve. In its normal configuration, the spring is under tension but it cannot rotate the ball or cylinder to a

closed position until the heat detector reacts to a preset temperature value. The closed position can be established by a pin located in the housing wall which meets a stop when rotation through 90° has been made.

5 In one form of the invention, the heat detector can be formed from a material which has the dual properties of, firstly, being capable of bonding or interlocking with an element of the damper arrangement and the housing and, secondly, being able to yield its
10 bond or lock when it is heated to a predetermined temperature value. These properties enable the heat detector to be designed and located in such a manner that it will normally ensure that the damper arrangement is held open but when a predetermined, ie. preset,
15 temperature is reached, it will yield enabling the damper arrangement to close.

Suitable heat detector materials are lead and its alloys, plastics materials and various composites. Typically, the temperature at which such materials yield
20 will be in the range of 60°-120°C, depending upon the particular application, so as to meet governmental or local council requirements.

The heat detector material can be located, for instance, in the interior perimeter of the housing where
25 an element of the damper arrangement has an adjacency when in an open configuration. Thus, in the case of a ball valve, a circular seal of heat detector material, such as a ring of lead can be located between the housing and the ball valve at both the inlet and outlet sides.

30 In another form, the heat detector material can comprise an alloy pad formed on the end of a bearing shaft which extends through the wall of the housing to a location within the damper arrangement, preferably at a location which does not impede the flow of fluid through
35 the housing. A spiral spring retained in a recess on the outer side of the housing connects the shaft to the housing. The spring is normally held under compression and is only released from compression when the alloy pad

yields upon being heated to the preset temperature, thereby enabling the shaft and damper to rotate to a closed position.

In yet another form of the invention, the heat
5 detector can be a thermocouple. The thermocouple can be connected by way of appropriate circuitry to a solenoid which can retract a pin extending between the housing and the damper arrangement, to permit the damper arrangement to close when the thermocouple detects a predetermined
10 temperature value. Such a situation also permits the damper to be reset to an open configuration as well as the simultaneous operation of other fire collars within the partition.

In order to test the integrity of the fire
15 collar/damper arrangement, testing means can be provided which enable the damper to be moved between its open and closed configurations. Such testing means can be automatic or manual. An automatic testing means can comprise a motor which drives, for instance, the
20 aforementioned bearing shaft so as to rotate the attached damper. A manual testing means can consist of a simple lever fitted to the bearing shaft.

The fire collar according to the invention is ideally fabricated from ceramic materials but other
25 materials such as fibre-reinforced concrete, metal and the like can also be used depending upon the specific usage. Preferably, the damper arrangement incorporates a cylinder or ball made from plastics material having an intumescent material embedded between inner and outer
30 layers of the plastics material. The intumescent material expands when the cylinder or ball has rotated to its closed position, thereby providing an additional fire-stop feature.

Usage of the fire collar/fire damper can range
35 across a large number of fields from plumbing to ventilation and air-conditioning installations.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a top view of a fire collar according to the invention showing a closed damper arrangement;

5 Figure 2 is a top view of the fire collar shown in Figure 1 with the damper arrangement open;

 Figure 3 is an end view of the fire collar shown in Figure 1;

10 Figure 4 is a side view of the fire collar shown in Figure 1;

 Figure 5 is a side view of a fire collar according to another aspect of the present invention;

 Figure 6 is a side view of a fire collar according to yet another aspect of the present invention;

15 Figure 7 is an end view of a fire damper assembly accordingly to still yet another aspect of the present invention; and

 Figure 8 is a side view of the fire damper assembly of Figure 7.

20

DESCRIPTION OF PREFERRED EMBODIMENTS

Preferred embodiments of the invention will now be described with reference to the drawings, in each of which like reference numerals refer to like parts.

25 Referring firstly to Figures 1-4, the fire collar comprises a ceramic housing 10 having a partially spherical ceramic ball valve 11, that is, the ball valve has two opposing sectors removed as can be seen in Figure 3, centrically located therein. The ceramic housing may
30 be formed by heat welding two hemispheres together after the ball valve 11 has been located therein.

 The spherical ball valve 11 has a passageway 12 extending from one side to the other with a diameter which corresponds to the diameter of the housing inlet 13 and outlet 14. The housing inlet 13 and outlet 14, in
35 turn, have diameters which do not impede the flow of fluid there through from attached pipework or ducting. There is thus unimpeded fluid flow through the fire

collar.

A recess 24 is formed in the outer wall of the housing and a stainless steel spiral spring 15 is located therein. The spiral spring has one end 16 bent so as to be retained within a hub of the housing and the other end 17 cranked for retention by the ball valve 11.

Two rings 18, 19 of lead alloy are bonded between the housing and the ball valve, and additionally seal the end of the small gap 20 between the ball valve and its seat. The gap 20 can be maintained by small ridges formed on the surface of the ball valve. Such a gap is useful for preventing binding between the ball valve and its seat such as could potentially occur over time.

Elastomeric seals 21, 22 enable quick secure fractional attachment to a plastics material ventilation pipe extending from a toilet or similar odour producing facility.

The fire collar depicted in Figures 1-4 is designed to be located within a concrete slab of a high rise building. In use, the fire collar will maintain the open configuration shown, for instance, in Figure 2 until such time as a fire occurs on either side of the concrete slab. When the fire reaches the ventilation-hydraulic pipe at the point of attachment to the fire collar, and the temperature climbs to the pre-set value, the lead alloy ring seals 18, 19 melt and the ball valve is then free to rotate under the tension of the spiral spring 15.

Rotation continues until the passageway 12 in the ball valve is in alignment with the inlet 13 and outlet 14 at which point a stop pin 23 in the ball valve quadrant prevents further rotation.

Referring to Figure 5, the fire collar comprises a two-part plastics material housing 50, 51 whose components press-fit together so as to enclose a partially spherical hollow plastics material ball 52 having opposed openings so as to provide a through passageway for fluid when in an open configuration. The

ball 52 includes an intumescent material which is encased within the walls of the ball.

The ball 52 is rotatable between an open and a closed position upon integrally formed pivots 53, 54 which are housed in recesses formed in the wall of the housing. Under normal, in use, conditions, the ball is retained in an open position by two rings of lead 55, 56 contained in annular recesses in the housing at the entry and at sides of the ball.

The ball 53 is held under tension in its open position by virtue of a flat coil spring 57. The spring is tensioned to rotate the ball through ninety degrees when the lead rings 55, 56 yield at a preset temperature.

Continued rotation of the ball 53 is prevented by a stop 58 formed by a wall of the housing.

The fire collar can be readily connected to the pipework by means of cylindrical connecting elements 59a, 59b.

Figure 6 is a modified version of the fire collar shown in Figure 5. This version enables the fire collar to be tested at desired intervals to ensure that the ball can be rotated and has not become jammed or otherwise inoperable. The main difference from the Figure 5 version is that the heat detector component comprises an alloy pad 60 formed on the end of a square drive shaft 61. A secondary internal drive shaft 62 also joins with this alloy pad and connects to a pulley 63, which is rotatable by means of an actuating cable 64 connected to a motor 65.

In general use, the motor is actuated to rotate the fireball 66 between an open and closed position and back again, to test the integrity of the system at desired time intervals.

During a fire, the alloy pad 60 yields and the fireball 66 rotates under the action of a coil spring 67, as the mechanical connection between the square drive shaft 61 and the internal drive shaft 62 is disengaged.

Figures 7 and 8 show a general damper

arrangement which is based upon the same principal of operation as the Figure 6 embodiment.

The damper arrangement comprises a rotating damper 70 in which a heat detecting metal alloy pad 71 is
5 located with the same type of coil spring 72 and testing
73 set-up as described with Figure 6.

The damper is connected to ducting at 74, 75 and is pivotal at 76. Intumescent material is located at 77, 78 and intumescent lip seals are positioned at 79,
10 80.

The function of this damper is similar to that of the previous embodiment.

1. A fire damper including:
a housing having an inlet adapted to connect to an inlet conduit and an outlet adapted to connect to an outlet conduit;
a damping member in said housing adapted to move from an open position in which the damping member allows fluid to flow from said inlet to said outlet to a closed position in which said damping member inhibits flow from said inlet to said outlet, said damping member having a passage therethrough with a passage inlet and a passage outlet, said passage inlet and said passage outlet being adapted to align with the inlet and outlet of said housing respectively when said damping member is in the open position and said damping member including an intumescent material.
2. A fire damper according to Claim 1, wherein said damping member is mounted for rotation about an axis extending across said housing.
3. A fire damper according to Claim 2 including biasing means for biasing said damping member to the closed position.
4. A fire damper according to Claim 3, wherein said biasing means includes a spiral spring wound about said axis.
5. A fire damper according to Claim 4, wherein said damping member is mounted on a shaft which is supported for rotation in said housing about said axis.
6. A fire damper according to Claim 4, wherein said spiral spring is mounted between said damping member and said housing.
7. A fire damper according to Claim 3 including retaining means for retaining said damping member in the open position against the bias of said biasing means, said retaining means being adapted to release said damping member in response to heat whereby said biasing means can force said damping member to the closed position.
8. A fire damper according to Claim 7, wherein at least a portion of said retaining means is located in said housing and said portion is adapted to yield in response to said housing or fluid in said housing reaching a predetermined temperature.
9. A fire damper according to Claim 1, wherein at least a portion of said retaining means is located in said housing and said at least a portion is adapted to yield in response to said housing or fluid in said housing reaching a predetermined temperature.
10. A fire damper according to Claim 9, wherein said at least a portion of said retaining means is located adjacent said passage inlet.

11. A fire damper according to Claim 10, wherein said at least a portion of said retaining means is a ring which engages with said housing and said damping member so as to retain said damping member in the open position.
12. A fire damper according to Claim 11, wherein said retaining means is adapted to yield within a temperature range of 60 degrees Celsius and 120 degrees Celsius.
13. A fire damper according to Claim 12, wherein said retaining means is formed substantially of lead or a lead alloy or composite.
14. A fire damper according to Claim 17, wherein said retaining means releasably secures said damping member to said housing and is adapted to release said damping member in response to the ambient air reaching a predetermined temperature.
15. A fire damper according to Claim 14 including heat detection means adapted to detect temperature and actuate said retaining means.
16. A fire damper according to Claim 15, wherein said damping member is mounted on a shaft which is supported for rotation in said housing about said axis.
17. A fire damper according to Claim 16, wherein said shaft is a first shaft and said retaining means drivingly connects said first shaft to a second shaft.
18. A fire damper according to Claim 17, wherein said second shaft is drivingly connected to a drive motor.
19. A fire damper according to Claim 1, wherein said damping member is a cylinder valve or a ball valve.
20. A fire damper according to Claim 19, wherein said intumescent material of said damping member is encased by a plastics material.
21. A fire damper according to Claim 20, wherein said plastics material is molded about said intumescent material.
22. A fire damper including:
 - a housing having an inlet adapted to connect to an inlet conduit and an outlet adapted to connect to an outlet conduit;
 - a damping member in said housing adapted to move from an open position in which the damping member allows fluid to flow from said inlet to said outlet to a closed position in which said damping member inhibits flow from said inlet to said outlet;
 - biasing means for biasing said damping member towards the closed position;
 - retaining means for retaining said damping member in the open position, and at least a portion of said retaining means being located in said housing and being adapted to yield upon

fluid in said housing reaching a predetermined temperature so as to release said damping member.

23. A fire damper according to Claim 22, wherein said damping member has a passage therethrough with a passage inlet and a passage outlet, said passage inlet and said passage outlet being adapted to align with the inlet and outlet of said housing respectively when said damping member is in the open position.

24. A fire damper according to Claim 23, wherein said damping member is mounted for rotation about an axis extending across said housing.

25. A fire damper according to Claim 24, wherein said biasing means includes a spiral spring wound about said axis.

26. A fire damper according to Claim 25, wherein said spiral spring is mounted between said damping member and said housing.

27. A fire damper according to Claim 24, wherein said damping member is mounted on a shaft which is supported for rotation in said housing about said axis.

28. A fire damper according to Claim 23, wherein said at least a portion of said retaining means is located adjacent said passage inlet.

29. A fire damper according to Claim 28, wherein said at least a portion of said retaining means is a ring which engages with said housing and said damping member so as to retain said damping member in the open position.

30. A fire damper according to any one of Claims 22 to 29, wherein said retaining means is adapted to yield within a temperature range of 60 degrees Celsius and 120 degrees Celsius.

31. A fire damper according to Claim 30, wherein said retaining means is formed substantially of lead or a lead alloy or composite.

32. A fire damper according to Claim 22, wherein said retaining means releasably secures said damping member to said housing.

33. A fire damper according to Claim 32 including heat detection means adapted to detect temperature and actuate said retaining means.

34. A fire damper according to Claim 27, wherein said shaft is a first shaft and said retaining means drivingly connects said first shaft to a second shaft.

35. A fire damper according to Claim 34, wherein said second shaft is drivingly connected to a drive motor.

36. A fire damper according to Claim 22, wherein said damping member is a cylinder valve or a ball valve.

37. A fire damper including:

a housing having an inlet adapted to connect to an inlet conduit and an outlet adapted to connect to an outlet conduit;

a damping member having a flow passage therethrough defined at least in part by first and second spaced apart opposed wall portions, said damping member being mounted in said housing for at least partial rotation from an open position in which said flow passage aligns with said inlet and said outlet to a closed position in which said first wall portion closes said inlet and said second wall portion closes said outlet;

biasing means operatively connected to said housing for biasing said damping member towards the closed position;

retaining means for retaining said damping member in the open position, said retaining means being adapted to release said damping member in response to heat; and

a quantity of intumescent material in said housing and adapted to form a seal between said damping member and said housing upon expansion when said damping member is in the closed position.

38. A fire damper according to Claim 37, wherein said biasing means includes a spiral spring.

39. A fire damper according to Claim 38, wherein said spiral spring is mounted between said damping member and said housing.

40. A fire damper according to Claim 37, wherein at least a portion of said retaining means is located in said housing.

41. A fire damper according to Claim 40, wherein said at least a portion of said retaining means is a ring which engages with said housing and said damping member so as to retain said damping member in the open position.

42. A fire damper according to Claim 37, wherein said retaining means is adapted to yield within a temperature range of 60 degrees Celsius and 120 degrees Celsius.

43. A fire damper according to Claim 42, wherein said retaining means is formed substantially of lead or a lead alloy or composite.

44. A fire damper according to Claim 37, wherein said retaining means includes a pin which releasably secures said damping member to said housing and is adapted to release said damping member in response to the ambient air reaching a predetermined temperature.

45. A fire damper according to Claim 44 including heat detection means adapted to detect temperature and actuate said pin.

46. A fire damper according to Claim 37, wherein said damping member is mounted on a first shaft and said retaining means drivingly connects said first shaft to a second shaft which is drivingly connected to a drive motor.