



(51) International Patent Classification:
B29C 35/08 (2006.01) *B29D 11/00* (2006.01)
F21V 29/02 (2006.01)

(21) International Application Number:
PCT/US2009/038327

(22) International Filing Date:
26 March 2009 (26.03.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/072,540 1 April 2008 (01.04.2008) US

(71) Applicant (for all designated States except US): **NO-VARTIS AG** [CH/CH]; Lichtstrasse 35, CH-4056 Basel (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **MORGAN, Courtney, Flem** [US/US]; 3215 Summer View Drive, Alpharetta, GA 30022 (US).

(74) Agent: **HU, Sheng-Hsin**; Ciba Vision Corporation, Patent Department, 11460 Johns Creek Parkway, Duluth, GA 30097 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ULTRAVIOLET OUTPUT STABILIZATION BY FLUORESCENT BULB TEMPERATURE MONITORING




FIG. 2

(57) Abstract: A controller measures a temperature at which an ultraviolet (UV) fluorescent lamp is operating and, in response, controls heat transfer between a heat-generating portion of the fluorescent lamp power supply circuitry, such as the ballast, and the interior of the curing chamber to maintain the fluorescent lamps operating at a stable temperature.



Declarations under Rule 4.17:

Published:

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))* — *with international search report (Art. 21(3))*