

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
19 October 2006 (19.10.2006)

PCT

(10) International Publication Number
WO 2006/108216 A1

(51) International Patent Classification:
B29C 63/32 (2006.01)

(21) International Application Number:
PCT/AU2006/000474

(22) International Filing Date: 10 April 2006 (10.04.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2005901859 14 April 2005 (14.04.2005) AU

(71) Applicant (for all designated States except US): **RIB LOC AUSTRALIA PTY LIMITED** [AU/AU]; 587 Grand Junction Road, Gepps Cross, S.A. 5094 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BATEMAN, Ian, Roger** [AU/AU]; 3 Short Street, Marino, S.A. 5049 (AU). **MAYMAN, Craig, Anthony** [AU/AU]; 23 Yurilla Drive, Bellevue Height, S.A. 5050 (AU).

(74) Agent: **MADDERNS**; Level 1, 64 Hindmarsh Square, Adelaide, S.A. 5000 (AU).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: UNDERGROUND AND PARTLY SUBMERGED PIPE WINDING APPARATUS AND METHOD



(57) Abstract: An apparatus and method for lining an underground conduit is disclosed. The apparatus (10) comprises: an annular frame (40) having a crown portion (42) and a base portion (49); a strip guide disposed around and supported by the annular frame (40), the guide arranged to guide a strip (12) around a helical path; a pair of strip pinch rollers mounted to the frame (40) at a position circumferentially about halfway between the crown portion (42) and the base portion (49); a drive assembly mounted to the frame for driving the strip (12) downwards into the helical path in a winding direction so as to present an incoming first edge to an adjacent second edge of a wound convolution of the strip; a liquid remover mounted to the frame, the liquid remover arranged to prevent liquid that has adhered to and ascended with the second edge from descending down towards the incoming first edge; and an extruder (80) mounted to the frame (40) for extruding a molten bead of plastic onto the strip (12) at a position just before said overlap.

WO 2006/108216 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.