

Description

The present invention relates to a coin dispensing apparatus for use in coin exchangers, coin operated gaming machines or the like and more particularly to such a coin dispensing apparatus comprising a hopper for holding a supply of coins or tokens in bulk and a rotary disc for dispensing coins one at a time and in predetermined quantities.

Hitherto, such a coin dispensing apparatus is known as disclosed in Japanese Patent Application Publication No. 62-45,588 (U.S. Patent Specification No. 4,589,433). As shown in Fig. 10, such a known coin dispensing apparatus comprises a hopper for holding a supply of coins in bulk and a rotary disc 3 rotatably disposed at one side within the hopper 1 at an angle to the horizontal. The rotary disc 3 has a central circular stage 4 provided at the central portion thereof and a plurality of coin transporting pins 5 arranged in a peripheral portion 3a around the central circular stage 4 such as to receive one coin between two sequential transporting pins 5 spaced apart in the peripheral direction of the rotary disc 3. The coin dispensing apparatus further comprises a delivery guide 7 and an outlet chute 6 which are fixed to a stationary frame at an upper delivery portion 3b. The delivery guide 7 extends from the outlet chute 13 to an upper periphery 4a of the central stage across the peripheral portion 3a of the rotary disc 3 in the upper delivery portion 3b and has a tunnel passage for passing the transporting pin 5. Thus, when the rotary disc is rotated, a coin is transported from the bottom portion of the hopper 1 to the outlet chute 6 at the upper delivery portion 3b by each of the transporting pins 5 which project from the surface of the rotary disc 3 and pass through the tunnel passage in the delivery guide 7.

Aforementioned coin dispensing apparatus of prior art has a disadvantage in that the size of the coin transporting pin is limited since a large transporting pin can carry two or more coins at a time so that a coin counting device usually provided at the front of the outlet chute would make a miscount or the inlet of the outlet chute would be jammed with coins and further the dimension of the tunnel passage in the delivery guide must be increased. On the other hand, in order to improve function of picking up a coin from a gutter formed at a lower portion of the hopper, it is desirable to make the length of the coin transporting pin large sufficient to efficiently pickup the coin from the gutter.

In order to improve coin dispensing efficiency it is also desired to make the length of the coin agitating members protruded from the surface of the central stage of the rotary disc as long as possible and/or to locate on the central stage away

from the center axis of the rotary disc in the radial direction, but the coin agitating members are also limited owing to the same reasons as for the coin transporting pin.

The object of the present invention is to improve the function of picking up coins from the bottom portion in a hopper by use of a long transporting pin without miscounting and jamming coins in the upper delivery portion.

Another object of the present invention is to improve the coin dispensing efficiency by providing unique means for agitating coins in the lower portion of a hopper without miscounting and jamming coins in the upper delivery portion and increasing load for agitating coins.

According to one aspect of the present invention, in a coin dispensing apparatus comprising a hopper for holding a supply of coins or tokens in bulk, a rotary disc rotatably disposed within the hopper and provided with a central circular stage, a plurality of coin transporting pins which are protruded in a peripheral portion around the central circular stage and spaced apart in the peripheral direction of the rotary disc, and a coin delivery guide extended across the peripheral portion of the rotary disc for guiding coins on the peripheral portion to an outlet chute, a carrier having a plurality of coin transporting pins spaced apart in the circumferential direction is rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude the pins extended through the rotary disc from the surface of the peripheral portion of the rotary disc in a minimum amount at a position of the delivery guide and in a maximum amount at a coin picking up position.

According to another aspect of the present invention, in a coin dispensing apparatus comprising a hopper for holding a supply of coins in bulk, a rotary disc rotatably disposed within the hopper and provided with a central circular stage, a plurality of coin transporting pins which are protruded in a peripheral portion around the central circular stage and spaced apart in the peripheral direction of the rotary disc, and a coin delivery guide extended across the peripheral portion of the rotary disc for guiding coins on the peripheral delivery portion to an outlet chute, a carrier having a plurality of coin agitating members spaced apart in the circumferential direction is rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude coin agitating members extended through the rotary disc from the surface of the central circular stage of the rotary disc in a minimum amount at a position of the delivery portion and in a maximum amount at a coin picking up position.

According to a preferred embodiment of the present invention the rotary disc is rotatably disposed at one side within the hopper at an angle to the horizontal.

According to a preferred embodiment of the present invention, the carrier has a plurality of coin transporting pins spaced apart in the circumferential direction and extended through the peripheral portion of the rotary disc and a plurality of coin agitating members spaced apart in the circumferential direction and extended through the central circular stage of the rotary disc.

Fig. 1 is a sectional view illustrating an embodiment of the coin dispensing apparatus according to the present invention;

Fig. 2 is a front view of the embodiment shown in Fig. 1;

Fig. 3 is a front view similar to Fig. 2 illustrating another embodiment of the present invention;

Fig. 4 is a sectional view illustrating other embodiment of the present invention;

Fig. 5 is a front view of the embodiment shown in Fig. 4;

Fig. 6 is a sectional view illustrating other embodiment of the present invention;

Fig. 7 is a front view of the embodiment shown in Fig. 6;

Fig. 8 is a sectional view illustrating other embodiment of the present invention;

Fig. 9 is a front view of the embodiment shown in Fig. 8; and

Fig. 10 is a perspective view of the illustrative coin dispensing apparatus of prior art.

Referring to Figs. 1 and 2 illustrating a first embodiment of the coin dispensing apparatus according to the present invention, a hopper 1 is connected to a stationary supporting plate 10 which is fixedly mounted on a conventional supporting stand in a position inclined to the horizontal in a known manner. The supporting plate 10 is provided with a rotary disc supporting surface 11 for supporting a rotary disc 3 with a central circular stage 4 and a carrier supporting surface 12 inclined relative to the rotary disc supporting surface 11 for supporting a disc shaped carrier 8. A rotating shaft 2 is driven by means of a motor 13 and is extended through a central hole 14 in the supporting plate 10. A plurality of rotary disc supporting balls 16 are spaced from each other in the circumferential direction and rotatably retained by means of a retainer ring 15 and then positioned in a circular race 17 formed in the supporting surface 11 on the supporting plate 10. A plurality of carrier supporting balls 21 are also spaced from each other in the circumferential direction and rotatably retained by means of a retainer ring 20 and then positioned in a circular race 22 formed in the supporting surface 12 on the supporting plate 10. The rotary disc 3

and the carrier 8 are rotatably supported on the rotating shaft 2 at their central holes, respectively. The carrier 8 is provided with a plurality of coin transporting pins 5 which are protruded from the surface toward the rotary disc 3 and spaced apart in the circumferential direction. The coin transporting pins 5 are respectively inserted in holes 9 which are formed in a peripheral portion 3a of the rotary disc 3 and spaced apart in the circumferential direction by the same space as that between the coin transporting pins. A spring 26 is interposed between the rotary disc 3 and the carrier 8 and a spring 25 is interposed between the rotary disc 3 and a washer 27 which is fixed to the top of the rotating shaft 2 by means of a screw 28 to thereby urge the central portions of the rotary disc 3 and the carrier 8 towards the stationary supporting plate 10 by means of springs 26 and 25, respectively to rotatably support the rotary disc 3 and the carrier 8 on the supporting plate through the balls 16 and 21, respectively.

The rotating shaft 2 is provided with a driving pin 30 which is laterally extended from the shaft, while the rotary disc 3 is provided with a driven pin 31 which is protruded from the under surface of the rotary disc such as to be drivingly engaged with the driving pin 30, whereby the rotary disc 3 is driven by the rotating shaft 2. A plurality of screws 32 are threaded in tapped holes in the central circular stage 4 and the rotary disc 3 and extended through bearings 34 at holes 33 formed in the carrier 8 to thereby drivingly connect the carrier 8 to the rotary disc 3.

In operation, when the rotary disc 3 is rotated by the rotating shaft 2, the carrier 8 is integrally rotated with the rotary disc 3, but in an inclined position in respect to the rotary disc 3. Accordingly, the coin transporting pins 5 extend from the surface of the lower peripheral portion of the rotary disc 3 into the bottom portion of the hopper 1 in a maximum protrusion amount at a coin picking up position which is substantially diametrically opposed to the position of the delivery guide 7 at the upper delivery portion 3b and the protrusion amount of the coin transporting pins subsequently decreases to a protrusion amount corresponding to a thickness of one coin at the front of the outlet chute 6 as the rotary disc 3 is rotated and the coin transporting pins 5 approach to the outlet chute 6 at the upper delivery portion 3b. When the coin transporting pin 5 reaches to the position of the delivery guide 7 at the upper delivery portion 3b, the coin transporting pin 5 is substantially withdrawn in the hole 9 as shown in Fig. 1. The coin transporting pin 5 is again extended from the surface of the peripheral portion 3a of the rotary disc 3 after passing the position of the delivery guide 7 and the extrusion amount of the pin 5 subsequently

increases to the maximum amount.

According to the present invention, it is able to effect a high picking up and agitating efficiency by the coin transporting pin 5, without any interference with the delivery guide 7 and the miscounting and jamming of coins at the upper delivery portion, so that the coin dispensing efficiency and the reliability in the operation of the coin dispensing apparatus are remarkably improved.

In the aforementioned embodiment, the rotary disc 3 is arranged within the hopper 1 at an angle to the horizontal, but the rotary disc 3 may be arranged to rotate in a horizontal position.

Fig. 3 shows another embodiment, wherein the coin transporting pin 5 has a large dimension in the radial direction.

Figs. 4 and 5 show a third embodiment of the present invention. In this embodiment, a plurality of rod shaped agitating members 35 are secured to the inclined carrier 8 such as to extend through holes 36 and 37 formed in the rotary disc 3 and the central circular stage 4.

Figs. 6 and 7 show other embodiment which is similar to the embodiment shown in Figs. 4 and 5, wherein the coin agitating members 35 are extended in the radial direction of the central circular stage 4.

Figs. 8 and 9 show other embodiment of the present invention which is similar to the embodiment shown in Figs. 4 and 5 except of providing the coin transporting pins 5 integrally on the surface of the peripheral portion 3a of the rotary disc 3.

Claims

1. A coin dispensing apparatus comprising a hopper (1) for holding a supply of coins in bulk, a rotary disc (3) rotatably disposed within the hopper and provided with a central circular stage (4), a plurality of coin transporting pins (5) which are protruded in a peripheral portion (3a) around the central circular stage (4) and spaced apart in the peripheral direction of the rotary disc (3), a coin delivery guide (7) extended across the peripheral portion of the rotary disc for guiding coins on the peripheral delivery portion (3b) to an outlet chute (8) characterized by a carrier (8) having a plurality of coin transporting pins (5) spaced apart in the circumferential direction, said carrier (8) being rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude the pins (5) which are extended through the rotary disc (3) from the surface of the peripheral portion (3a) of the rotary disc (3) in a minimum amount at a position of the delivery guide (7) and in a

maximum amount at a coin picking up position.

2. Apparatus claimed in claim 1, wherein the rotary disc (3) is rotatably disposed at one side within the hopper (1) at an angle to the horizontal.
3. Apparatus claimed in claim 1, wherein the carrier (8) is provided with a plurality of agitating members (35) spaced apart in the circumferential direction such as to extend through the central circular stage (4) of the rotary disc (3).
4. A coin dispensing apparatus comprising a hopper (1) for holding a supply of coins in bulk, a rotary disc (3) rotatably disposed within the hopper and provided with a central circular stage (4), a plurality of coin transporting pins (5) which are protruded in a peripheral portion (3a) around the central circular stage (4) and spaced apart in the peripheral direction of the rotary disc (3), a coin delivery guide (7) extended across the peripheral portion of the rotary disc for guiding coins on the peripheral delivery portion (3b) to an outlet chute (8) characterized by, a carrier (8) having a plurality of coin agitating members (35) spaced apart in the circumferential direction, said carrier (8) being rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude the coin agitating members (35) extended through the rotary disc (3) from the surface of the central circular stage (4) of the rotary disc (3) in a minimum amount at a position of the delivery portion and in a maximum amount at a coin picking up position.
5. Apparatus claimed in claim 4, wherein the rotary disc (3) is rotatably disposed at one side within the hopper (1) at an angle to the horizontal.

Patentansprüche

1. Münzenabgabevorrichtung mit einem Vorrats-trichter (1) zum Halten eines Vorrats an Münzen als Haufen, einer drehbaren Scheibe (3), die in dem Vorrats-trichter drehbar angeordnet und mit einer zentralen kreisförmigen Stufe (4) versehen ist, einer Anzahl von Münzentransportstiften (5), die in einem Umfangsteil (3a) um die zentrale kreisförmige Stufe (4) vorstehen und in Umfangsrichtung von der drehbaren Scheibe (3) beabstandet sind, einer Münzenabgabeführung (7), die sich über den Umfangsbereich der drehbaren Scheibe erstreckt, um Münzen auf dem periphären Abgabebereich



increases to the maximum amount.

According to the present invention, it is able to effect a high picking up and agitating efficiency by the coin transporting pin 5, without any interference with the delivery guide 7 and the miscounting and jamming of coins at the upper delivery portion, so that the coin dispensing efficiency and the reliability in the operation of the coin dispensing apparatus are remarkably improved.

In the aforementioned embodiment, the rotary disc 3 is arranged within the hopper 1 at an angle to the horizontal, but the rotary disc 3 may be arranged to rotate in a horizontal position.

Fig. 3 shows another embodiment, wherein the coin transporting pin 5 has a large dimension in the radial direction.

Figs. 4 and 5 show a third embodiment of the present invention. In this embodiment, a plurality of rod shaped agitating members 35 are secured to the inclined carrier 8 such as to extend through holes 36 and 37 formed in the rotary disc 3 and the central circular stage 4.

Figs. 6 and 7 show other embodiment which is similar to the embodiment shown in Figs. 4 and 5, wherein the coin agitating members 35 are extended in the radial direction of the central circular stage 4.

Figs. 8 and 9 show other embodiment of the present invention which is similar to the embodiment shown in Figs. 4 and 5 except of providing the coin transporting pins 5 integrally on the surface of the peripheral portion 3a of the rotary disc 3.

Claims

1. A coin dispensing apparatus comprising a hopper (1) for holding a supply of coins in bulk, a rotary disc (3) rotatably disposed within the hopper and provided with a central circular stage (4), a plurality of coin transporting pins (5) which are protruded in a peripheral portion (3a) around the central circular stage (4) and spaced apart in the peripheral direction of the rotary disc (3), a coin delivery guide (7) extended across the peripheral portion of the rotary disc for guiding coins on the peripheral delivery portion (3b) to an outlet chute (8) characterized by a carrier (8) having a plurality of coin transporting pins (5) spaced apart in the circumferential direction, said carrier (8) being rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude the pins (5) which are extended through the rotary disc (3) from the surface of the peripheral portion (3a) of the rotary disc (3) in a minimum amount at a position of the delivery guide (7) and in a

maximum amount at a coin picking up position.

2. Apparatus claimed in claim 1, wherein the rotary disc (3) is rotatably disposed at one side within the hopper (1) at an angle to the horizontal.
3. Apparatus claimed in claim 1, wherein the carrier (8) is provided with a plurality of agitating members (35) spaced apart in the circumferential direction such as to extend through the central circular stage (4) of the rotary disc (3).
4. A coin dispensing apparatus comprising a hopper (1) for holding a supply of coins in bulk, a rotary disc (3) rotatably disposed within the hopper and provided with a central circular stage (4), a plurality of coin transporting pins (5) which are protruded in a peripheral portion (3a) around the central circular stage (4) and spaced apart in the peripheral direction of the rotary disc (3), a coin delivery guide (7) extended across the peripheral portion of the rotary disc for guiding coins on the peripheral delivery portion (3b) to an outlet chute (8) characterized by, a carrier (8) having a plurality of coin agitating members (35) spaced apart in the circumferential direction, said carrier (8) being rotatably supported at the rear side of the rotary disc to rotate at an angle to the rotary disc such as to extrude the coin agitating members (35) extended through the rotary disc (3) from the surface of the central circular stage (4) of the rotary disc (3) in a minimum amount at a position of the delivery portion and in a maximum amount at a coin picking up position.
5. Apparatus claimed in claim 4, wherein the rotary disc (3) is rotatably disposed at one side within the hopper (1) at an angle to the horizontal.

Patentansprüche

1. Münzenabgabevorrichtung mit einem Vorrats-trichter (1) zum Halten eines Vorrats an Münzen als Haufen, einer drehbaren Scheibe (3), die in dem Vorrats-trichter drehbar angeordnet und mit einer zentralen kreisförmigen Stufe (4) versehen ist, einer Anzahl von Münzentransportstiften (5), die in einem Umfangsteil (3a) um die zentrale kreisförmige Stufe (4) vorstehen und in Umfangsrichtung von der drehbaren Scheibe (3) beabstandet sind, einer Münzenabgabeführung (7), die sich über den Umfangsbereich der drehbaren Scheibe erstreckt, um Münzen auf dem peripheren Abgabebereich



- reich (3b) zu einer Ausgabeschütte (8), zu führen, **gekennzeichnet** durch einen Träger (8) der eine Anzahl von Münztransportstiften (5) aufweist, die in Umfangsrichtung beabstandet sind, wobei der Träger (8) drehbar an der Rückseite der drehbaren Scheibe gehalten ist, um sich unter einem Winkel zur drehbaren Scheibe in der Weise zu drehen, daß die Stifte herausgedrückt werden, die sich durch die drehbare Scheibe (3) von der Oberfläche des peripheren Bereichs (3a) der drehbaren Scheibe (3) in einer minimalen Weise an einer Stelle der Abgabeführung (7) und in einer maximalen Weise an der Stelle der Münzaufnahme erstrecken.
2. Vorrichtung nach Anspruch 1, wobei die drehbare Scheibe (3) drehbar an einer Seite in dem Vorratstrichter (1) unter einem Winkel zur Horizontalen angeordnet ist.
3. Vorrichtung nach Anspruch 1, wobei der Träger (8) mit einer Anzahl von Rührelementen (35) versehen ist, die in Umfangsrichtung derart beabstandet sind, daß sie sich durch die zentrale kreisförmige Stufe (4) der drehbaren Scheibe (3) erstrecken.
4. Münzenabgabevorrichtung mit einem Vorratstrichter (1) zum Halten eines Vorrats an Münzen als Haufen, einer drehbaren Scheibe (3), die in dem Vorratstrichter drehbar angeordnet und mit einer zentralen kreisförmigen Stufe (4) versehen ist, einer Anzahl von Münztransportstiften (5), die in einem Umfangsteil (3a) um die zentrale kreisförmige Stufe (4) vorstehen und in Umfangsrichtung von der drehbaren Scheibe (3) beabstandet sind, einer Münzenabgabeführung (7), die sich über den Umfangsbereich der drehbaren Scheibe erstreckt, um Münzen auf dem peripheren Abgabebereich (3b) zu einer Ausgabeschütte (8), zu führen, **gekennzeichnet** durch einen Träger (8) der eine Anzahl von Münzenrührelemente (35) aufweist, die in Umfangsrichtung beabstandet sind, wobei der Träger (8) drehbar an der Rückseite der drehbaren Scheibe gehalten ist, um sich unter einem Winkel zur drehbaren Scheibe in der Weise zu drehen, daß die Münzenrührelemente (35) herausgedrückt werden, die sich durch die drehbare Scheibe (3) von der zentralen kreisförmigen Stufe (4) der drehbaren Scheibe (3) in einer minimalen Weise an einer Stelle der Abgabeführung (7) und in einer maximalen Weise an der Stelle der Münzaufnahme erstrecken.

5. Vorrichtung nach Anspruch 4, wobei die drehbare Scheibe (3) an einer Seite in dem Vorratstrichter (1) unter einem Winkel zur Horizontalen drehbar angeordnet ist.

Revendications

1. Appareil pour distribuer des pièces comprenant une trémie (1) pour contenir des pièces en vrac, un disque rotatif (3) disposé à tourner à l'intérieur de la trémie et prévu avec un palier circulaire central (4), une pluralité de broches de transport de pièce (5) qui dépassent dans une partie périphérique (3a) autour du palier circulaire central (4) et qui sont espacées dans la direction périphérique du disque rotatif (3), un guide pour délivrer les pièces (7) qui se prolonge à travers la partie périphérique du disque rotatif pour guider les pièces sur la partie de déchargement périphérique (3b) vers une goulotte de sortie (8) caractérisé par un support (8) comportant une pluralité de broches de transport de pièce (5) espacées dans la direction circonférentielle, ledit support (8) étant supporté à tourner sur l'extrémité arrière du disque rotatif pour tourner d'un certain angle par rapport au disque rotatif de manière à extruder les broches (5) qui sortent à travers le disque rotatif (3) à partir de la surface de la partie périphérique (3a) du disque rotatif (3) d'une faible valeur à l'emplacement du guide de déchargement (7) et d'une valeur plus importante à une position de prélèvement des pièces.
2. Appareil selon la revendication 1, dans lequel le disque rotatif (3) est disposé à tourner sur un côté à l'intérieur de la trémie (1) à un certain angle par rapport à l'horizontale.
3. Appareil selon la revendication 1, dans lequel le support (8) est prévu avec une pluralité d'éléments d'agitation (35) espacés dans la direction circonférentielle d'une manière telle à se prolonger à travers le palier circulaire central (4) du disque rotatif (3).
4. Appareil pour distribuer des pièces comprenant une trémie (1) pour contenir des pièces en vrac, un disque rotatif (3) disposé à tourner à l'intérieur de la trémie et prévu avec un palier circulaire central (4), une pluralité de broches de transport de pièce (5) qui dépassent dans une partie périphérique (3a) autour du palier circulaire central (4) et qui sont espacées dans la direction périphérique du disque rotatif (3), un guide pour délivrer les pièces (7) qui se prolonge à travers la partie périphérique



du disque rotatif pour guider les pièces sur la partie de déchargement périphérique (3b) vers une goulotte de sortie (8), caractérisé par un support (8) comportant une pluralité d'éléments d'agitation de pièce (35) espacés dans la direction circonférentielle, ledit support (8) étant supporté à tourner sur le côté arrière du disque rotatif pour tourner d'un certain angle par rapport au disque rotatif de façon à extruder les éléments d'agitation de pièce (35) qui se prolongent à travers le disque rotatif (3) à partir de la surface du palier circulaire central (4) du disque rotatif (3) d'une valeur minimale à un emplacement de la partie de déchargement et d'une valeur maximale à une position de prélèvement de pièces.

5

10

15

5. Appareil selon la revendication 4, dans lequel le disque rotatif (3) est disposé à tourner sur un côté à l'intérieur de la trémie (1) à un certain angle par rapport à l'horizontale.

20

25

30

35

40

45

50

55

6