

APPARATUS AND METHOD FOR RELEASING TENSION MEMBERS FOR USE IN ANCHOR METHOD

Technical Field

5 The present invention relates to an apparatus and method for releasing tension members for use in an anchor method to provide soft ground reinforcement for civil engineering projects, and more particularly, to an apparatus and method for releasing tension members for use in an anchor method, in which both ends of the tension member are firmly and stably held by anchors, where all or some of the wires consisting of several strands are cut, and at least one end of the cut
10 wires is hit to release and draw the tension member.

Background Art

 Generally, an anchor method is used to reinforce soft ground by drilling a hole into the ground, inserting an anchor member composed of a grout-feeding hose and a tension member
15 into the drilled hole, pouring grout into the anchor member through the grout-feeding hose, curing the grout with the anchor member, fastening an anchor with one end of the tension member, and drawing the tension member by use of tensioning equipment to apply tension to the grout and the ground. Such an anchor method is mainly used for land-side protection wall construction, stone setting works, retaining wall construction, etc.

20 The application of the anchor method offers advantages of increased effectiveness in managing downtown construction, reduction in the required duration of works, etc. Upon carrying out further construction in an adjacent region, drilling and boring machinery is required and the duration of works is lengthened due to the embedding of tension members with strength six times stronger than that of common steel reinforcements. In order to solve the above
25 problem, an anchor for removing the tension member after the completion of the drilling construction has been developed, and it is referred to as a tension member-releasing apparatus for

use in an anchor method.

Several tension member-releasing apparatuses for use in the anchor method have been proposed. For example, one tension member-releasing apparatus for use in an anchor method is disclosed in Korean Utility Model Publication No. 20-0242474. In this Utility Model, the apparatus includes a body formed with a threaded portion for fastening a cap on an outer surface of an upper end thereof and which has a wedge-receiving space; a wedge assembly mounted in the wedge-receiving space of the body, which has an external ring mounted on a groove formed on the outer surface of the wedge assembly for maintaining an assembled state thereof and which is radially expanded by an internal ring mounted on an inner groove, and in which a spoiler is inserted into a spoiler groove formed at a front portion of the inner groove; a locking member for seating the spoiler containing a resilient hook to the spoiler groove of the wedge assembly; and the cap having a protrusion which is fastened to the upper portion of the body and receives a resilient hook.

According to the method for releasing the tension member by use of the tension member-releasing apparatus described above, if the tension member installed in the ground in a tensioning state is cut, the tension member is moved toward the embedded anchor by means of repulsive force resulting from the release of the tensioning state of the tension member. At that time, the tension member and the wedge assembly mounted to the end of the tension member are moved into the wedges, and thus the wedges are expanded, thereby allowing the front end of the tension member to be released from the wedges.

The locking member assembled to the wedge assembly is also moved together with the tension member, and the resilient hook of the locking member is inserted and fixed to the protrusion of the cap. After the resilient hook of the locking member is fixed to the protrusion of the cap, all wedges of the wedge assembly are expanded to release the locking of the tension member. Therefore, the tension member may be drawn by pulling the tension member.

If the tension member is not released due to a weak repulsive force, the cut end of the

tension member is hit by a hammer so that the tension member is moved toward the anchor, thereby causing the resilient hook of the locking member to abut against the protrusion.

According to the conventional tension member-releasing apparatus disclosed in the publication, if external shock is applied to the wedge assembly with the tension assembled thereto due to carelessness, necessity or some other reason, the tension member is inserted and thus the resilient hook of the locking member mounted on the upper end of the wedge assembly is locked by the protrusion of the cap. When this occurs, it is impossible to release the tension member from the wedge assembly. Therefore, a problem results in that the wedge assembly may not be reused because all wedges of the wedge assembly are expanded.

In addition, a significant amount of force is required to hit the tension member so that the resilient hook of the locking member is abutted against the protrusion of the cap. Also, another potential problem exists in that the hammer can miss the tension member from carelessness.

Disclosure of the Invention

Therefore, an object of the present invention is to solve the problems involved in the prior art, and to provide an apparatus for releasing tension members for use in an anchor method including an anchor for firmly fastening one end of the tension member and a release for disassembling the tension member fastened to the anchor, so that upon carrying or working the tension member with an end mounted to the anchor, it may prevent the release of the tension member due to the external shock from carelessness or necessity, and the fastening or release of the tension member to the anchor may be repeated at several times.

Another object of the present invention is to provide an apparatus for releasing tension members for use in an anchor method, in which since a support plate used in a wedge unit of the anchor is formed to have the cap-shaped cross section, the end of the tension member may be held more firmly and stably.

Further another object of the present invention is to provide an apparatus for releasing

tension members for use in an anchor method, in which all or some of the wires consisting of several strands, i.e., the tension member, which is applied with the tension by the anchors positioned at both ends of the wire, are cut, and at least one cut wire is hit and inserted, in which the remaining wires which are not hit are relatively pulled out from the wedge unit, and in which
5 a diameter of the tension member is abruptly decreased at the moment that the wire leaves the end of the wedge unit, so that after releasing the fastening of the tension member from the wedge unit of the anchor, the tension member may be pulled out and removed.

In order to accomplish the above mentioned objects, there is provided an apparatus for releasing tension member, the apparatus including an anchor fastened to one end of a tension
10 member, and a release mounted to the other end of the tension member, the anchor comprising: an anchor head having opened upper and lower ends, and being formed with a cone-shape wedge-receiving space at the upper end of the anchor head; a wedge unit seated in the wedge-receiving space of the anchor head, and having three wedges assembled together to form a first hole at a center portion of the wedge unit, through which the tension member is inserted, a
15 support plate inserted into a circular groove formed at an upper portion of the first hole, and an O-shaped ring provided around three wedges so that the wedges are expanded around the support plate; a spring, positioned on an upper portion of the wedge unit, for constantly biasing the wedge unit against the wedge-receiving space of the anchor head; and a wedge cover fastened to the anchor head, with the spring being seated on the upper end of the anchor head.

20 The support plate includes a support plate of a cap-shaped cross section to stably and firmly hold the tension member inserted into the first hole of the wedge unit.

According to another aspect of the present invention, there is provided an apparatus for releasing tension member, including an anchor fastened to one end of a tension member, further comprising: a release, mounted to the other end of the tension member, for fastening and
25 releasing the tension member.

The release includes an extended pipe-type release head having a second hole for

receiving the tension member, which consists of a wire of seven strands laid together with a uniform pitch, the upper end of the release head formed with a male thread, and a release cover fastened to the release head by engaging the male thread of the release head with a female thread formed at a lower end of a third hole of the release cover, in which the third hole of the release cover is provided at an inner surface thereof with a protrusion for stopping two or more adjacent wires of the tension member.

The release is provided by assembling the release head and the release cover, but the release head and the release cover may be integrally formed.

According to still another aspect of the present invention, there is provided a method for releasing tension members for use in an anchor method, comprising the steps of: cutting at least one of wires forming a tension member, which is installed with one end of the tension member in a ground together with an anchor and the other end fastened to another anchor, with the tension member being applied with maximum tension; hitting the entire or some of the cut wires of the tension member toward the anchor installed in the ground to push the remaining wires from the wedge unit; repeating the hitting step, so that an outer diameter of the tension member is abruptly decreased and thus the tension member is released from a wedge unit, at a moment that the moved wires of the tension member leave one end of the wedge unit; and drawing the released tension member.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the present invention as claimed.

Brief Description of the Drawings

The above objects, other features and advantages of the present invention will become more apparent by describing the preferred embodiment thereof with reference to the accompanying drawings, in which:

FIG. 1 is a cross-sectional view showing a tension member-releasing apparatus according to one preferred embodiment of the present invention.

FIG. 2 is an exploded perspective view of the anchor shown in FIG. 1.

FIG. 3 is an exploded view of the release shown in FIG. 1.

5 FIG. 4a is a cross-sectional view depicting the state in which a tension member is fixed to an anchor according to the present invention.

FIG. 4b is a cross-sectional view depicting the process where a wedge unit is pushed by wires of a tension member.

10 FIGs. 5a to 5c are cross-sectional views depicting the process wherein wires of tension member are pushed from a release head according to the present invention.

FIGs. 6 and 7 are cross-sectional views depicting an anchor according to another embodiment of the present invention.

Best Mode for Carrying Out the Invention

15 Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

An apparatus for releasing tension members for use in an anchor method according to the present invention will now be described with reference to the accompanying drawings.

20 FIG. 1 is a cross-sectional view showing a tension member-releasing apparatus for use in the anchor method according to one preferred embodiment of the present invention, FIG. 2 is an exploded perspective view of the anchor shown in FIG. 1, and FIG. 3 is an exploded view of the release shown in FIG. 1.

25 As shown in the figures, the tension member-releasing apparatus for use in the anchor method includes an anchor A fastened to one end of a tension member 10, which is inserted into the ground, and a release R, which is mounted to the other end of the tension member 10 and is used for fastening and releasing the tension member 10.

The tension member 10 includes a wire of seven strands consisting of 6 strands 10b laid together around a center strand 10a with a uniform pitch.

The anchor A includes a wedge cover 50 used to resiliently support a wedge unit 30 against an anchor head 20 by means of a spring 40. The anchor head 20 has opened upper and lower ends, and a cone-shape wedge-receiving space 21 is formed at an upper portion of the anchor head 20. The wedge unit 30 is seated in the wedge-receiving space 21 of the anchor head 20. The anchor head 20 is provided on a lower portion thereof with a plastic tube 12 such that an airtight state may be maintained when the tension member 10 is inserted into the anchor head. The tube 12 functions as a waterproof member for preventing water from permeating into the inside of the anchor A, thereby providing an anticorrosive effect.

The wedge unit 30 includes three wedges 31 assembled together to form a first hole 32 at the center portion of the wedge unit through which the tension member 10 is inserted. A support plate 34 is inserted into a circular groove 33 formed at the upper portion of the first hole 32, and an O-shaped ring 35 is provided around three wedges 31 so that the wedges may be expanded around the support plate 34. An inner surface of the first hole 32 of the wedge unit 30 is formed with a helical or indented recess, thereby preventing the tension member 10 from sliding or leaving the wedge unit 30 when the tension member 10 is pulled.

The wedge unit 30 includes a compressive cover 42 to allow smooth motion of the respective wedges 31; a spring 40 for constantly biasing the compressive cover 42 and the wedge unit 30 to the wedge-receiving space 21 of the anchor head 20; and a wedge cover 50 fastened to the anchor head 20 with the spring 40 located on the upper end of the anchor head 20.

The reason why the wedge unit is tightened by the compressive cover 42 is that the upper surface of the wedge unit 30 and the lower surface of the compressive cover 42 are formed to share the same inclined angle (generally, 30 degrees) in a radial outward direction, and thus the wedge unit 30 is constantly pressed toward the center. Also, the lower surface of the compressive cover 42 may be formed to have an incline with an angle larger than that of the

upper surface of the wedge unit 30 by about 15 degrees.

The release R includes an extended pipe-type release head 60, which has a second hole 61 for receiving the tension member 10 and which consists of a wire of seven strands 10a and 10b laid together with a uniform pitch, the upper end of the release head formed with a male thread 62, and a release cover 70 fastened to the release head 60 by engaging the male thread 62 of the release head 60 with a female thread 72 formed at a lower end of a third hole 71 of the release cover, through which the tension member 10 passes. The third hole 71 of the release cover 70 is located at the inner surface of the hole with a protrusion 73 for stopping two or more adjacent wires 10b of the tension member 10. A locking bolt 64 is fastened to a front end of the release head 60 to selectively lock the tension member 10.

The release head 60 and the release cover 70 are fastened to each other by a male thread 62 and a female thread 72, but the release head 60 and the release cover 70 may be integrally formed.

The protrusion 73 may be formed to stop one wire or two or more wires according to the arrangement of the wires 10a and 10b.

A releasing process of the tension member will now be described in detail with reference to the tension member-releasing apparatus for the anchor method.

As shown in FIGs. 1 and 4a, after the anchor A is fastened to one end of the tension member 10 and an anchor member consisting of the tension member 10 and a grout-feeding hose is inserted into a ground hole drilled by a drill, grout is poured through the grout-feeding hose and then is cured. When the curing of the poured grout is completed, the anchor A is fastened to the other end of the tension member 10, and the tension member 10 is pulled by means of a tensioner so as to apply maximum tension to the tension member 10, in addition to the grout.

When the outwardly pulled portion of the tension member 10 is cut, the tension applied to the tension member 10 is released, and simultaneously the tension member 10 and the wedge unit 30 positioned at the end of the tension member are moved toward the installed anchor A against

the resilience of the spring 40 by the repulsive force that is generated by cutting the tension member 10. Since the repulsive force of the tension member 10 is completely depleted at the time that it is equal to the resilience of the spring 40, the tension member is returned to the wedge-receiving space 21 of the anchor head 20 by the biasing force of the spring. At that time,
5 the tension member 10 is maintained, as it is held by the wedge unit 30 of the anchor A.

When the cut end of the tension member 10 is inserted into the second hole 61 formed at the release head 60 of the release R, the end of the tension member 10 is positioned at the lower end of the protrusion 73 formed at the third hole 71 of the release cover 70 through the second hole 61 of the release head 60. At that time, the protrusion 73 formed on the inner surface of the
10 third hole 71 of the release cover 70 is laid on two adjacent wires 10b that form the tension member 10, as shown in FIGs. 5a and 5b.

Then, when the end of the release cover 70 is hit by a hammer, two adjacent wires 10b among the wires 10a and 10b that form the tension member 10 are pulled toward the anchor A by means of the protrusion 73 formed on the inner surface of the second hole 61 of the release cover
15 70, as shown in FIG. 5c.

The wedge unit 30 pushes the support plate 34 of the wedge unit 30 against the wedge cover 50 by a distance of the two wires 10b, as shown in FIG. 4b, and then is returned to the original position by the biasing force of the spring 40, as shown in FIG. 4a.

In other words, the wedge-receiving space 21 of the anchor head 20 is outwardly
20 expanded by an allowable range by the O-shaped ring 35 provided at the outer surface of the wedge unit 30, by the pushed distance of the wedge unit 30 when the two wires 10b forming the tension member 10 pushes the wedge unit 30. At that time, the remaining wires 10a and 10b among the tension member 10, except for the two wires 10b are pushed toward the release R hitting the tension member 10.

When the external force hitting the release R is completely exhausted, the wedge unit 30
25 is pushed into the wedge-receiving space 21 of the anchor head 20 by the biasing force of the

spring 40, such that the wedges 31 of the wedge unit 30 are radially contracted. At that time, the outer surface of the tension member 10 comes into contact with the inner surface of the wedges 31 of the wedge unit 30.

As described above, two wires 10b among the tension member 10 are inserted into the anchor A installed in the ground by repeatedly hitting the release R, and thus the remaining wires 10a and 10b among the tension member 10 that are not hit are pushed in a direction opposite to the direction of the hit. At the moment that the relatively moved wires 10a and 10b of the tension member 10 leave the end of the wedge 31 from the support plate 34 of the wedge unit 30, the outer diameter of the tension member 10 is abruptly decreased. Therefore, the tension member 10 is released from the wedge 31 of the wedge unit 30.

Specifically, even though the wedges 31 of the wedge unit 30 are contracted, some wires 10b forming the tension member 10 are not fastened because they are less than the diameter of the first hole 32 of the wedge unit 30.

If the tension member 10 is released from the wedge unit 30 of the anchor A, the tension member 10 is applied with its one weight and slight frictional resistance only. After tightening the locking bolt 64 of the release head 60, the tension member 10 is extracted and removed by pulling the release R.

The releasing method described above is carried out by cutting all of tension member 10 and drawing out the tension member 10 from the anchor A installed in the ground, but another method may be carried out by cutting only wire 10b, or wires 10a and 10b, among the tension member 10 and hitting at least one wire 10b between the cut wires 10a and 10b against a separate hand tool.

FIG. 6 depicts a support plate of a wedge unit 30 for an anchor A according to another embodiment of the present invention, which is substantially similar to the above embodiment except that a support plate 34a is formed in a cap-shaped cross section and has a flange around an external lower end thereof.

In this embodiment, if the support plate 34a is formed to have the cap-shaped cross section, the tension member 10 is upwardly pushed into the first hole 32 of the wedge unit 30. If the tension member 10 is deeply inserted upward, the end of the tension member 10 that is not held by the wedge 31 of the wedge unit 30 is radially expanded. Therefore, the flange of the support plate 34a is rested, thereby stably and firmly holding the tension member.

FIG. 7 is a view showing an anchor A according to another embodiment of the present invention, in which the support plate 34a, which has the cap-shaped cross section assembled to an upper portion of the wedge 31 of the wedge unit 30, is protruded beyond the upper end of the wedge 31. In this case, a lower end portion of a spring 40 abutted against the upper surface of the wedge 31 is formed to have a diameter smaller than that of an upper portion thereof, so that the spring encloses a circumference of the support plate 34a protruded from the upper portion of the wedge 31. The embodiment does not require the compressive cover 42 applied to the present invention, thereby reducing the number of components and thus decreasing the cost.

While the present invention has been described and illustrated herein with reference to the preferred embodiments thereof, it will be apparent to those skilled in the art that various modifications and variations can be made therein without departing from the spirit and scope of the invention. Thus, it is intended that the present invention covers all modifications and variations of this invention that come within the scope of the appended claims and their equivalents.

Industrial Applicability

In the above description, when the tension member-releasing apparatus for the anchor method according to the present invention removes the tension member installed in the ground, the process is independent from the problems of rust or strong repulsive force, which are common reasons that tension member removal fails. In addition, upon carrying or working the tension member that has end mounted to the anchor, the release of the tension member due to

external shock from carelessness, necessity, etc is prevented. Moreover, the fastening or release of the tension member to the anchor may be repeated several times.

Since the support plate used in the wedge unit of the anchor is formed to have a cap-shaped cross section, the end of the tension member may be held more firmly and stably. In the event that the spring's lower end has a diameter less than that of the upper end thereof, the compressive cover is not required, thereby reducing the number of components, and thus decreasing the cost.

Furthermore, all or some of the wires consisting of several strands, i.e., the tension member to which tension is applied by the anchors positioned at both ends of the wire, are cut, and at least one cut wire is hit and inserted. The remaining wires that are not hit are relatively pulled out from the wedge unit. The diameter of the tension member is abruptly decreased at the moment that the wire leaves the end of the wedge unit. Therefore, after releasing the fastening of the tension member from the wedge unit of the anchor, the tension member may be pulled out and removed.

15

Claims

1. An apparatus for releasing tension member, including an anchor A fastened to one end of a tension member 10, and a release mounted to the other end of the tension member 10, the anchor A comprising:

an anchor head 20 having opened upper and lower ends, and being formed with a cone-shape wedge-receiving space 21 at the upper end of the anchor head 20;

a wedge unit 30 seated in the wedge-receiving space 21 of the anchor head 20, which has three wedges 31 assembled together to form a first hole 32 at a center portion of the wedge unit, through which the tension member 10 is inserted, a support plate 34 inserted into a circular groove 33 formed at an upper portion of the first hole 32, and an O-shaped ring 35 provided around three wedges 31 so that the wedges are expanded around the support plate 34;

a spring 40, positioned on an upper portion of the wedge unit 30, for constantly biasing the wedge unit 30 against the wedge-receiving space 21 of the anchor head 20; and

a wedge cover 50 fastened to the anchor head 20, with the spring 40 being seated on the upper end of the anchor head 20.

2. The apparatus as claimed in claim 1, wherein a compressive cover 42 for allowing smooth motion of the respective wedges 31 is interposed between the spring 40 and the wedge unit 30.

3. The apparatus as claimed in claim 2, wherein the support plate 34 includes a support plate 34a of a cap-shaped cross section to stably and firmly hold the tension member 10 inserted into the first hole 32 of the wedge unit 30.

4. The apparatus as claimed in claim 3, wherein if the support plate 34a is protruded beyond

an upper end of the wedge 31 of the wedge unit 30, a lower end portion of a spring 40 abutted against an upper surface of the wedge 31 is formed to have a diameter smaller than that of an upper portion thereof.

5 5. An apparatus for releasing tension member including an anchor A fastened to one end of a tension member 10, further comprising:

 a release R mounted to the other end of the tension member 10 for fastening and releasing the tension member 10.

10 6. The apparatus as claimed in claim 5, wherein the release R includes an extended pipe-type release head 60 having a second hole 61 for receiving the tension member 10 consisting of a wire composed of seven strands laid together with a uniform pitch, the upper end of the release head formed with a male thread 62, and a release cover 70 fastened to the release head 60 by engaging the male thread 62 of the release head 60 with a female thread 72 formed at a lower end
15 of a third hole 71 of the release cover in which the third hole 71 of the release cover 70 is provided at an inner surface thereof with a protrusion 73 for stopping two or more adjacent wires 10b of the tension member 10.

20 7. The apparatus as claimed in claim 6, wherein a locking bolt 64 is fastened to a front end of the release head 60 to selectively lock the tension member 10.

8. The apparatus as claimed in claim 6, wherein the release head 60 and the release cover 70 are integrally formed.

25 9. A method for releasing tension members for use in an anchor method, comprising the steps of:

cutting at least one of wires 10a and 10b forming a tension member 10, in which one end of the tension member 10 is installed in a ground together with an anchor A and the other end is fastened to another anchor A, with the tension member 10 being applied with maximum tension;

5 hitting all or some of the cut wires 10a and 10b of the tension member 10 toward the anchor A installed in the ground to push the remaining wires 10a and 10b from the wedge unit 30;

repeating the hitting step, so that an outer diameter of the tension member 10 is abruptly decreased and thus the tension member 10 is released from a wedge unit 30, at a moment that the moved wires 10a and 10b of the tension member 10 leaves an end of the wedge unit 30; and

10 drawing the released tension member 10.

10. The method as claimed in claim 9, wherein in the cutting step, all of the wires 10a and 10b of the tension member 10 are cut.

15