



(51) International Patent Classification:
H02K 49/10 (2006.01) **H02K 7/106** (2006.01)

(21) International Application Number:
PCT/EP2009/005184

(22) International Filing Date:
16 July 2009 (16.07.2009)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US):
CAMERON INTERNATIONAL CORPORATION
[US/US]; 1333 West Loop South, Suite 1700, Houston,
TX 77027-9109 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BIESTER, Klaus**
[DE/DE]; Am Maschsee 2, 29342 Wienhausen (DE).
KUNOW, Peter [DE/DE]; Gustav-Freytag-Strasse 15a,
14193 Berlin (DE).

(74) Agent: **ROTHAEMEL, Bernd**; Grünecker, Kinkeldey,
Stockmair & Schwanhäusser, Anwaltssozietät, Leopold-
strasse 4, 80802 München (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ELECTRIC MOTOR INCLUDING A POSITION HOLDING DEVICE




FIG. 4

(57) Abstract: An electric motor, particularly for an actuating device for displacing a control device, such as a valve, a gate valve, a blow-out preventer or the like, for use in oil or gas production comprises a stator (4) and a rotor (6) assigned to a motor shaft (5), and a position holding device (7) for exerting a holding torque on the motor shaft. To improve an electric motor of this type such that said motor is of a compact structure, comprises less additional parts for a corresponding position holding device and, particularly in case of failure of an external power supply, reliably prevents a situation where the motor shaft is moved out of the attained position upon corresponding pressure application e.g. by the control device, the position holding device comprises a plurality of permanent magnets (8), the permanent magnets (8) being arranged in radial direction (9) relative to the rotor (6) and the motor shaft (5), respectively.

