

DESCRIPTION

INJECTION DEVICE

TECHNICAL FIELD

The present invention relates to an injection
5 device used for molding a resin.

BACKGROUND ART

As an injection device used for molding a resin, an injection device is known comprising a cylinder having an injection nozzle at an end thereof, a plunger
10 sliding in the axial direction in a position opposite to the injection nozzle within the cylinder and driving device for advancing and retracting the plunger, wherein the cylinder has a port for supplying a molding material between the sliding position of the plunger and the
15 injection nozzle, and the molding material supplied into the cylinder is compressed by advancement of the plunger, so that the molding material is injected into a cavity of molds connected to the injection nozzle. In such an injection device, a screw for melting the molding
20 material is provided outside the cylinder in the case of a preplasticizing type, and integrally with a leading end of the plunger within the cylinder in the case of an in-

line type. The plunger of such an injection device of the preplasticizing type may be provided with a larger diameter portion in contact with an inner circumferential wall surface of the cylinder for isolating inner and outer regions of the cylinder from each other and a smaller diameter portion in a leading end thereof.

Above injection device of a conventional injection molding machine has presented such issues as described below.

When the molds are opened for removing a product, because a molding material is forced out of a leading end of the injection nozzle, causing so-called drooling condition, in the case a pressure (back pressure) of the molding material in the side of a plunger head is too high, while weighing comes to be unstable, in the case the back pressure is too low, a suck-back operation has been conducted for further moving the plunger slightly backward from a position of the plunger after it has been pushed back by the back pressure to an extent sufficient to prevent the drooling.

In order to prevent the molding material from leaking out of the cylinder through a clearance (gap) between the cylinder and the plunger at the time of supplying the molding material into the cylinder, injecting the molding material into the mold cavity and

the like, the length of a portion of the plunger in contact with the cylinder has been made longer, and the clearance between the plunger and the cylinder has been reduced, that is, narrowed to such minimum extent to allow the plunger to slide.

In the cylinder, a check valve (ring valve) has been employed between a fluid holding part with the injection nozzle and the supply port for preventing a molten liquid of molding material held in the fluid holding part from flowing back to the supply port. The check valve is brought into tight contact with a valve seat of the plunger by the back pressure of the molten liquid of molding material, when the backward movement of the plunger is discontinued after weighing, so that back flow of the molten liquid to the supply port is prevented.

On the other hand, in an attempt of preventing back flow of the molding material from the mold cavity to an inner region of the cylinder until completion of a pressure-holding and compression process after injection of the molding material to the mold cavity, a pressure control has been conducted by applying a force to the plunger in the advancing direction of the plunger until completion of the pressure-holding and compression process after injection of the molding material to the

mold cavity, so that a force of the molding material flowing back from the mold cavity into the cylinder is counterbalanced with the force applied to the plunger.

Such injection device according to the prior art, however, has below-mentioned issues.

During the suck-back operation, because the inner region of the cylinder is reduced in pressure, the air is brought into the cylinder from outside the cylinder through a trailing end of the plunger, and the air is entrapped in a product as a void (bubble), causing a defect in the product. Although $P_2 > P_0$ at the time of weighing of the molding material, $P_2 < P_0$ after completion of the weighing where a pressure of molding material from the plunger head to a guide is P_1 , a pressure of the molding material (back pressure) in the side of a leading end of the plunger head is P_2 , and a pressure outside the cylinder is P_0 (atmospheric pressure), and entrainment of the air from outside the cylinder is caused at $P_1 < P_0$ due to such reason as insufficient closing of the check-valve.

Even if the clearance between the plunger and the cylinder is narrowed, the molding material is adhered to the wall surfaces of the plunger and the cylinder in the sliding zone of the plunger, and it is unavoidable that the molding material enters between the plunger and

the cylinder. Moreover, once the molding material enters between the plunger and the cylinder, it hardly flows between them, because the clearance is very narrow, and retention of the molding material in the clearance is caused. The molding material retained therein is reduced in quality and carbonized due to a frictional heat caused by sliding movement of the plunger. Then, the carbide is entrained in the molding material in the cylinder, and contaminates a molded product, causing a defect in the product.

As shown in Fig. 8A, in an injection device of preplasticizing type comprising a plunger 2 with a larger diameter portion 21 in contact with an inner circumferential wall surface of a cylinder 1 for isolating inner and outer regions of the cylinder from each other and a smaller diameter portion 22 in a leading end thereof, although a molten liquid of molding material fed from a port 12 for supplying the molding material in the cylinder 1 is guided toward an injection nozzle (lower side of the figure, not shown) by a stepped surface 23 in a boundary between the larger diameter portion 21 and the smaller diameter portion 22, a part of the molten liquid of molding material supplied from the molding material supply port 12 is divided into two streams flowing in the right and left directions about

the smaller diameter portion 22 of the plunger 2 as shown in Fig. 8B, which are collided against each other in a position backside in relation to the supply port 12, and cause a stagnating area 9 in that position. Then, the molding material in the stagnating area 9 has been reduced in quality and carbonized by heat, and the carbide has been removed from the wall surface of the smaller diameter portion 22, and contaminated a product, causing a defect in the product.

Since the check valve is not brought into sufficiently tight contact with the valve seat of the plunger, that is, not completely closed, even when the backward movement of the plunger is discontinued after completion of weighing, and completely closed only after injection is completed, a significant and unstable quantity of molten liquid of the molding material flows back before the valve is completely closed, as a result, a preset quantity of the molding material to be supplied and an actual quantity of molding material supplied has been unequal to each other, the actual quantity supplied has been varied, and it has been difficult to assure a fixed quantity of molding material to be supplied into the mold cavity.

In the pressure control described above, although the position of plunger in the cylinder should

be stable, as the pressure of the molding material in the mold cavity during the pressure-holding and compression process and the force applied to the plunger in the advancing direction of the plunger are balanced with each other, because the balance between them is actually varied in a subtle manner, the position of the plunger is, therefore, varied, thus it has been also difficult to consistently maintain the forces in perfectly balanced condition in order to provide a constant holding pressure. Accordingly, the molding material is forced in and out of the molding cavity during the pressure-holding and compression process, and it has been difficult to assure a fixed quantity of molding material to be supplied into the cavity.

DISCLOSURE OF INVENTION

Accordingly, an object of the present invention is to provide an injection device capable of eliminating defects in a molding due to entrainment of carbides and voids and difficulty in assuring a fixed quantity of molding material to be supplied into a mold cavity.

In accomplishing these and other aspects, according to one aspect of the present invention, there is provided an injection device comprising:

a cylinder having an injection nozzle at an end thereof;

a plunger sliding in an axial direction thereof in a position opposite to the injection nozzle within the cylinder and;

a driving device for advancing and retracting the plunger,

wherein the cylinder has a port for supplying a molding material between a sliding position of the plunger and the injection nozzle, and the molding material supplied into the cylinder is compressed by advancement of the plunger, so that the molding material is injected into a cavity of molds connected to the injection nozzle, and the plunger has a groove circumferentially extending along an outer circumferential wall surface thereof.

Insofar, the injection device may be either of a preplasticizing type or in-line type.

Where a pressure in an inner region X of the cylinder is P_x , a pressure in an outer region Z of the cylinder is P_z , and a pressure in an area Y of the plunger is P_y , the air in the outer region of the cylinder cannot be drawn into the inner region of the cylinder, in the case the inner region of the cylinder is at a positive pressure ($+P_x$), because a pressure gradient

shown by a solid line in Fig. 6, that is, a gradient of (a positive pressure $+P_y$) in the area Y of plunger is present between the inner and outer regions of the cylinder. However, the air in the outer region of the cylinder is drawn into the inner region of the cylinder, if no groove is provided in the outer circumferential wall surface of the plunger, when the inner region of the cylinder is at a negative pressure ($-P_x$), because a pressure gradient shown by a dotted line in Fig. 6, that is, a gradient of (a negative pressure $-P_y$) in the area of plunger is present between the inner and outer regions of the cylinder. In contrast, in the case a groove is provided in the outer circumferential wall surface of the plunger, as shown in an alternate long and short dash line in Fig. 6, a positive pressure ($+P_y$) can be temporarily maintained in an area of the groove, and the air is prevented from being drawn into the inner region of the cylinder.

Although one such groove may be provided, it is preferable to provide a plurality of such grooves for the purpose of increasing an effect of preventing the air from being drawn from outside the cylinder. Although the groove may have any sectional shape, in order to prevent retention of a molding material in a bottom part of the

groove, it is preferably formed with round corners in the bottom part of the groove.

The injection device of a second aspect of the present invention is characterized in that it is of a preplasticizing type, the plunger has a smaller diameter portion in a leading part and a larger diameter portion in a trailing part thereof, an outer circumferential wall surface of the larger diameter portion is in contact with an inner circumferential wall surface of the cylinder for isolating inner and outer regions of the cylinder from each other, so that a molding material is guided toward the injection nozzle by a stepped surface between the smaller diameter portion and the larger diameter portion, and, in the case one groove is provided in the plunger,

a clearance between the outer circumferential wall surface of the larger diameter portion of the plunger and the inner circumferential wall surface of the cylinder is defined by a below-described equation 1 where η is a viscosity of the molding material, P is a back pressure (kgf/cm^2) during weighing, Q is a quantity (cm^3/s) of the molding material to be supplied, R is an inner radius of the cylinder, r_1 is an outer radius of the smaller diameter portion, r_2 is an outer radius of a part of the larger diameter portion before the groove, r_3 is an outer radius of a bottom surface of the groove, r_4

is an outer radius of a part of the larger diameter portion after the groove, l_1 is an axial length of the smaller diameter portion, l_2 is an axial length of the part of the larger diameter portion before the groove, l_3 is an axial length (width) of the groove, l_4 is an axial length of the part of the larger diameter portion after the groove, and k is the ratio of a flow rate in the upward direction of the plunger from a port for supplying the molding material into the cylinder to a total quantity of the molding material supplied.

$$\begin{aligned} & \pi P / 2 \eta Q + \{ (1 - k) l_1 / [(R^4 - r_1^4) - (R^2 - r_1^2) / (l_n R - l_n r_1)] \} \\ & = k l_2 / [(R^4 - r_2^4) - (R^2 - r_2^2) / (l_n R - l_n r_2)] \\ & \quad + k l_3 / [(R^4 - r_3^4) - (R^2 - r_3^2) / (l_n R - l_n r_3)] \\ & \quad + k l_4 / [(R^4 - r_4^4) - (R^2 - r_4^2) / (l_n R - l_n r_4)] \end{aligned}$$

-----[Equation 1]

By providing the smaller diameter portion and the larger diameter portion in the plunger, and guiding the molding material toward the injection nozzle by the stepped surface in the boundary between them, back flow of a molten liquid of the molding material is reduced. For smoothly effecting the guiding operation, it is preferable that the molding material supply port is partly covered by the larger diameter portion, when the

molding material is supplied from the molding material supply port.

By defining the clearance between the outer circumferential wall surface of the larger diameter portion of the plunger and the inner circumferential wall surface of the cylinder as set forth above, the molten liquid of molding material can flow more easily in the clearance in comparison with the prior art, and the wall surfaces are washed by the molding material, stagnation of the molding material is reduced. Degradation and carbonization of the molding material can be thereby prevented.

In this regard, although the length of the larger diameter portion of the plunger should be shorter and the clearance should be increased in view of preventing stagnation of the molding material, the length of the larger diameter portion of the plunger should be longer and the clearance should be reduced in view of preventing entrainment of air from the outer region of the cylinder to the inner region of the cylinder, thus the parameters are in close relation with each other, and the inventors, as a result of studies, found out the above equation 1 for determining an optimum value of the clearance.

The equation 1 could be derived from equations shown below. That is, the following equation 2 is given where pressure losses in parts A, B, C, and D in a sliding zone of the plunger 2 within the cylinder 1 are P_A , P_B , P_C , and P_D , as shown in Fig. 4.

$$dP_A/dx = (2\eta Q_1/\pi) \{1/[(R^4 - r_1^4) - (R^2 - r_1^2)/(l_n R - l_n r_1)]\}$$

$$dP_B/dx = (2\eta Q_2/\pi) \{1/[(R^4 - r_2^4) - (R^2 - r_2^2)/(l_n R - l_n r_2)]\}$$

$$dP_C/dx = (2\eta Q_2/\pi) \{1/[(R^4 - r_3^4) - (R^2 - r_3^2)/(l_n R - l_n r_3)]\}$$

$$dP_D/dx = (2\eta Q_2/\pi) \{1/[(R^4 - r_4^4) - (R^2 - r_4^2)/(l_n R - l_n r_4)]\}$$

-----[Equation 2]

Therefore, the equation 3 is established.

$$P_A = (2\eta Q_1/\pi) \{l_1/[(R^4 - r_1^4) - (R^2 - r_1^2)/(l_n R - l_n r_1)]\}$$

$$P_B = (2\eta Q_2/\pi) \{l_2/[(R^4 - r_2^4) - (R^2 - r_2^2)/(l_n R - l_n r_2)]\}$$

$$P_C = (2\eta Q_2/\pi) \{l_3/[(R^4 - r_3^4) - (R^2 - r_3^2)/(l_n R - l_n r_3)]\}$$

14

$$P_D = (2\eta Q_2/\pi) \{l_4/[(R^4 - r_4^4) - (R^2 - r_4^2)/(l_n R - l_n r_4)]\}$$

----[Equation 3]

Here, since $Q = Q_1 + Q_2$, $P + P_A = P_B + P_C + P_D$,
 5 and $Q_1 = (1 - k)Q$, if $Q_2 = kQ$, a below-described equation
 4 is given.

$$P + (2\eta(1 - k)Ql_1/\pi\{(R^4 - r_1^4) - (R^2 - r_1^2)/(l_n R - l_n r_1)\})$$

$$\begin{aligned} &= (2\eta kQl_2/\pi\{(R^4 - r_2^4) - (R^2 - r_2^2)/(l_n R - l_n r_2)\}) \\ &+ (2\eta kQl_3/\pi\{(R^4 - r_3^4) - (R^2 - r_3^2)/(l_n R - l_n r_3)\}) \\ &+ (2\eta kQl_4/\pi\{(R^4 - r_4^4) - (R^2 - r_4^2)/(l_n R - l_n r_4)\}) \end{aligned}$$

-----[Equation 4]

In such manner, the first mentioned equation 1
 is derived.

15 An injection device according to an aspect of
 the invention is further characterized in that it is a
 preplasticizing type, and a guide element is provided in
 the smaller diameter portion of the plunger in a position
 backside in relation to the supply port for guiding two
 20 streams of a molten liquid of molding material, which
 flow circumferentially about the smaller diameter portion
 to reach the backside position, toward the injection

nozzle. In addition, the guide element preferably has a pair of inclined guide surfaces with the approximately same inclined angle to the axial direction of the plunger, or the guide element is preferably formed in
5 generally triangular shape at a protruding end of its apex, although it is not specifically limited to such form. In such case, two opposite oblique lines of the triangle can be curved for smoother flow of the molten liquid.

10 Although the protrusion of the guide element is only required to be convex in the advancing direction of plunger such that it matches the flowing direction of the molding material in order to prevent stagnation of the molding material thereabout, and it may, therefore, be in
15 the form of a partition plate, since the stagnating area of molding material is generally triangular, and a relation of $xy = c$ (where x is a base of the shape similar to a triangle of molding material stagnating area (a part of the plunger bottom surface), y is a height of
20 the shape similar to the triangle, and c depends on a viscosity of the molding material and the like) is given, it is preferably formed in said triangular shape, and most preferably such shape that meets the equation. It is further preferable that the convex portion is

progressively reduced in thickness toward the apex thereof, and has no thickness at the apex.

5 The backside position of the smaller diameter portion is preferably located in such a position that occupies an upper half of the molding material supply port in view of preventing back flow and stagnation and facilitating flow of the molding material in the head direction of the plunger, although it is not specifically limited thereto.

10 In order to assure a fixed quantity of molding material to be supplied into a mold cavity, an injection device of an aspect of the invention is still further characterized in that a check valve is employed between a fluid holding part with the injection nozzle and the
15 supply port for preventing back flow of a molten liquid of molding material held in the fluid holding part to the supply port, and the check valve is continuously forced against a valve seat provided in the plunger by means of a spring, which is located in a connecting shaft
20 extending frontward from the plunger. Insofar, the injection device may be either of a preplasticizing type or an in-line type.

 In such case, although the material of the spring is not specifically limited, for example, the
25 spring may be a metal spring or the like, and a coil

spring or the like as an example can be employed without limitation to any specific shape. As for the number of springs, at least one spring is required.

Finally, an injection device of an aspect of the invention is characterized in that the driving device is further provided with a control means having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection. Insofar, the injection device may be either of a preplasticizing type or an in-line type.

BRIEF DESCRIPTION OF DRAWINGS

These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying drawings, in which:

Fig. 1 is a schematic sectional view showing an overall arrangement of an injection device according to an embodiment of the invention, a pre-plasticizing device and molds;

Fig. 2 is a perspective view showing a plunger for use in the embodiment of the invention;

Fig. 3 is a rear view showing a shape of the plunger;

Fig. 4 is a side view showing a shape and dimensions of the plunger;

5 Figs. 5A, 5B, 5C are explanatory views for explaining arrangement of a check valve in the embodiment;

Fig. 6 is a graph for explaining entrainment of air into the cylinder and a solution thereto;

10 Fig. 7 is a sectional view showing a modification of the embodiment of the present invention with a left half of the plunger showing its outer appearance and a right half of the plunger showing its sectional view; and

15 Figs. 8A and 8B are explanatory views for explaining formation of a stagnating area in a backside position of a smaller diameter portion of the plunger.

BEST MODE FOR CARRYING OUT THE INVENTION

20 Before the description of the present invention proceeds, it is to be noted that like parts are designated by like reference numerals throughout the accompanying drawings.

By referring to the drawings, embodiments of the invention are described in detail below.

It should be appreciated, however, that the invention is not limited to the embodiments described below, and materials, shapes and other conditions of components described in respect to the embodiments are not intended to limit the scope of the invention thereto, unless any restrictive description is made, and are shown only for illustrative purpose.

Figs. 1 through 5 show an injection device according to an embodiment of the invention. The injection device according to the embodiment is for use in an injection molding machine of a screw-pre-plunger type.

Fig. 1 is a sectional view showing an overall arrangement of an injection device 100, a pre-plasticizing device 200 for supplying a plasticized molding material to the injection device 100 and molds 300 for receiving the plasticized molding material injected from the injection device 100.

The injection device 100 comprises a cylinder 1 having an injection nozzle 11 at an end thereof, a plunger 2 sliding in the axial direction of the cylinder 1 in a position opposite to the injection nozzle 11 within the cylinder 1 and a driving device 3 for advancing and retracting the plunger 2, respectively, and the cylinder 1 is also provided with a supply port 12 of

molding material between the sliding position of the plunger 2 and the injection nozzle 11.

The guide element 24 preferably has at least a pair of inclined guide surfaces 24a, 24b with the approximately same inclined angle to an axial direction of the plunger 2 in order to guide two streams of molten liquid of the molding material flowing about the smaller diameter portion and reaching the backside position toward the injection nozzle with good balance.

Furthermore, it is preferable that the guide element 24 is formed in generally isogonal trapezoid having the pair of inclined guide surfaces 24a, 24b. It is preferable that in order to more reliably prevent stagnation of the molten liquid of molding material at a lower portion of the lower end of the trapezoid, the guide element 24 is a generally isosceles triangle having a protruding end of an apex thereof directed to the injection nozzle. Moreover, it is preferable that the guide element 24 is formed in equilateral triangle so as to more effectively guide the molten liquid of molding material.

The plunger 2 has a larger diameter portion 21 and a smaller diameter portion 22 formed integrally in a leading end thereof, as shown either in Figs. 2 through 4, and is also formed in the smaller diameter portion 22 with a guide element 24 of a generally triangular shape

in a position backside in relation to the molding material supply port 12.

In an outer circumferential wall surface of the larger diameter portion 21 of the plunger 2, a groove 211 is provided for preventing entrainment of air from outside the cylinder. In order to prevent stagnation of the molding material in the concave area of groove 211, bottom corners of the groove 211 are rounded as shown in the figures.

In this case, a clearance between the outer circumferential wall surface of the larger diameter portion 21 of the plunger 2 and an inner circumferential wall surface of the cylinder 1 is designed to be at an optimum value in relation to an axial length of the larger diameter portion 21 of the plunger 2 according to the equation 1.

Fig. 7 shows a modification of the embodiment in which the molding material come into and come out from the groove 211 can be cut by a cutting member 250 to remove the unnecessary molding material from the inside of the cylinder 1 and reliably prevent the stagnation of the molding material in the concave area of groove 211.

In Fig. 7, the molding material comes into the groove 211 of the larger diameter portion 21 of the plunger 2 and then the molding material 499 in the groove

211 is flown out from the groove 211 because of the rounded bottom corners of the groove 211 and the movement of the plunger 2 and flown into a clearance between the upper part of the larger diameter portion 21 and the cylinder 1. Then, the molding material in the clearance may be carbonized by heat to become carbides. The carbides move upward in accordance with the upward and downward movements of the plunger 2 and finally, come out from the inside of the uppermost part of the cylinder.

The cylindrical cutting member 250 is arranged at the uppermost part of the cylinder 1 as shown in Fig. 7. The cutting member 250 has a body 250c with its inner circumferential surface sliding on the outer circumferential wall surface of the plunger 2, and at its lower end a cutting blade 250a for cutting the carbides 500 around the plunger 2 and having notches 250b, arranged separately at equal distances, for dividing the carbides 500 while the carbides 500 are cut. The plunger 2 upward and downward slides inside the cutting member 250 fixed to the cylinder 1, and then the cylindrical carbides 500 moved upward from the groove 211 are cut by the cutting blade 250a and divided into many chips due to the notches 250b. The carbides 500 are accommodated in a carbide accommodating space 100 provided in the cylinder 1. Compressed air is blown into the space 100 from an

air blowing-in port 101 thereof to discharge the carbides 500 together with the air through a discharge port 102. When the air is sucked through the discharge part 102, the carbides 500 can be more smoothly discharged from the space 100 therethrough. It is preferable that the axial direction of the air blowing-in port 101 is not located on the axial direction of the discharge port 102 as shown in Fig. 7 to prevent the air from being discharged generally linearly and to cause turbulent flows in the space 100, thus more effectively discharging the carbides 500 from the space 100. The cutting blade 250a can have a curved surface for guiding the cut carbides 500 so as to separate the carbides 500 from the outer circumferential wall surface of the plunger 2. The cutting blade 250a can have no notch.

The driving device 3 comprises a slide guide shaft 31 extending from a rear end of the cylinder 1, a servo motor 33 mounted on a support mount 32 at the other end of the slide guide shaft 31, a screw shaft 34 coupled at an end to the servo motor 33 for rotation, and a transmission member 35 engaged with the screw shaft 34, and advanced and retracted along the slide guide shaft 31 according to forward and reverse rotations of the screw shaft 34. The transmission member 35 is connected at an end to a trailing end of the plunger 2, and transmits its

forward and backward movements to the plunger 2 for advancing and retracting the plunger 2.

As shown in Fig. 1, a check valve 4 is employed between a fluid holding part 13 and the supply port 12 in a stage before the injection nozzle 11 within the cylinder 1 for preventing a molten liquid of molding material held in the fluid holding part 13 to flow back to the supply port 12. The check valve 4 is cylindrical, as shown in Fig. 5C, and is passed therethrough, as shown in Fig. 5A, by a connecting shaft 25, which extends from the smaller diameter portion 22 of plunger toward the injection nozzle 11 (see Fig. 1) for sliding within the cylinder 1 in the vertical direction of the figure. At a leading end of the smaller diameter portion 22 of the plunger, a valve seat 221 in conformity with a tapered valve element 41 of the check valve 4 is provided.

A spring 27 is employed in an arrowhead-shaped head 26 formed at a leading end of the connecting shaft 25, and the valve element 41 of the check valve 4 is continuously forced against the valve seat 221 in the smaller diameter portion 22 of the plunger by means of the spring 27, as shown in Fig. 5B.

As shown in Fig. 1, the driving device 3 includes an encoder 51 associated with the servo motor 33 for detecting an angle of rotation of the servo motor 33.



The encoder 51 detects the position of the plunger 2 within the cylinder from the angle of rotation detected. The driving device 3 comprises control means 5 for controlling operation of the driving device 3, and the control means 5 receives a detection signal from the encoder 51 for controlling operation of the servo motor 33 of the driving device 3.

The pre-plasticizing device 200 comprises, as shown in Fig. 1, a hopper 201 and a screw unit 202, and feeds a molding material plasticized in the screw unit 201 through the supply port 12 of cylinder 1 into the cylinder 1. After the molten liquid of molding material is fed into the cylinder 1, it is guided toward the injection nozzle 11 by a stepped surface 23 in a boundary between the larger diameter portion 21 and smaller diameter portion 22 of the plunger 2, as shown in Fig. 4, while a part of it is divided into two streams, which flow about the smaller diameter portion 22, and reach a position backside in relation to the supply port 12, as shown in Fig. 8B, then smoothly guided along the contour of the guide element 24 toward the injection nozzle 11 as shown in Fig. 3, thereby forming no stagnating area in the backside position.

As shown in Fig. 4, by allowing the larger diameter portion 21 of the plunger to close up to

approximately a half of the molding material supply port 12, when the molding material is supplied into the cylinder 1, the molding material hardly leaks out of the cylinder through the clearance between the outer circumferential wall surface of the larger diameter portion 21 of the plunger and the inner circumferential wall surface of the cylinder 1, and easily tends to be directed toward the injection nozzle 11.

The molding material within the cylinder 1 is forwarded to the fluid holding part 13 ahead of the plunger head 26 for weighing. Although the molding material forwarded to the fluid holding part 13 reacts to the forwarding action and thus causes the plunger 2 to be retracted slightly the weighing process, as soon as a preset quantity (one shot) of the molding material is reached in the fluid holding part 13, the plunger 2 is no longer retracted, and the weighing process is completed. The plunger 2 is advanced for compressing the molding material supplied into the cylinder 1. The preset quantity of the molten liquid of molding material held in the fluid holding part 13 within the cylinder 1 maintains a positive pressure by the compression, and is injected due to the positive pressure to a cavity 301 of the molds 300 that is connected to the injection nozzle 11. The molding material forced into the mold cavity 301 at a



high speed under a high pressure is maintained at the injection pressure by the plunger 2 until it comes to be solid.

5 The check valve 4 closes a passage of the molding material as shown in Fig. 5B, as the valve element 41 of the check valve 4 is pressed against the valve seat 221 in the smaller diameter portion 22 of the plunger during injection, after the injection, and during pressure-holding process. The passage is open, as shown
10 in Fig. 5A, at the initiation of weighing, during the weighing, and when the molding material is fed, because the feeding pressure of the molding material overcomes the spring force. Although if the spring 27 is absent the valve tends to be opened when it is subjected to a
15 negative pressure during suck-back operation, since the check-valve 4 is continuously forced by the spring 27 in the injection device, it is not opened and keeps closing the passage of the molding material, even if it is
20 subjected to a negative pressure. In such manner, back flow of the molding material can be prevented, and a fixed quantity of the molding material can be supplied to the mold cavity 301.

The molding material tends to flow back into the cylinder from inside the mold cavity 301 after
25 injection to the mold cavity 301 until completion of the

This Sheet Has Been Replaced



pressure-holding and compression process. Then, the control means 5 of the driving device 3 detects the position of the plunger 2 within the cylinder 1 by means of the encoder 51, and controls rotation of the servo motor 33 according to a detection signal thereof, so that the position of the plunger 2 is fixed to a proper position at the end of the injection process. The position control allows more reliable regulation of an injection capacity in comparison with the conventional pressure control.

Because the invention is constituted as described above, the following effects are obtained.

In the injection device, by providing the groove circumferentially along the outer circumferential wall surface of the plunger, as entrainment of air from outside the cylinder to inside the cylinder can be prevented, and voids can be thereby eliminated, a molded product of a good quality can be produced.

In the injection device, by providing the smaller diameter portion and the larger diameter portion in the plunger, and defining the clearance between the outer circumferential wall surface of the larger diameter portion and the inner circumferential wall of the cylinder by the specified equation, since stagnation of a molding material between the outer circumferential wall

surface of the larger diameter portion and the inner circumferential wall surface of the cylinder can be prevented, a molded product of a good quality can be produced without contamination by a carbide of the molding material.

In the injection device, by providing the guide element in the backside position of the smaller diameter portion of the plunger for directing the molding material toward the injection nozzle, because stagnation of the molding material in that position can be prevented, a molded product of a good quality can be produced without contamination by a carbide of the molding material.


In the injection device, by forming the guide element in the generally triangular shape that extends toward the injection nozzle at the protruding end of the apex thereof, the molding material can be guided more smoothly, and stagnation can be further prevented.

In the injection device, by continuously applying the force in the closing direction to the check valve by means of the spring, time required for the check valve to be closed is reduced, back flow can be effectively prevented, a fixed quantity of molding material can be supplied to the mold cavity, and a molded product of a good quality can be produced.

In the injection device, because a fixed quantity of molding material can be supplied into the mold cavity by the position control of the plunger, a molded product of a good quality can be produced.

5 The entire disclosure of Japanese Application No. 8-117637 filed on May 13, 1996 including specification, claims, drawings, and summary are incorporated herein by reference in its entirety.

10 Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and modifications are to be understood as included within the
15 scope of the present invention as defined by the appended claims unless they depart therefrom.



31

THIS SHEET HAS BEEN
REPLACED

CLAIMS

1. An injection device comprising:

a cylinder (1) having an injection nozzle (11)
at an end thereof;

5 a plunger (2) sliding in an axial direction
thereof in a position opposite to the injection nozzle
within the cylinder and;

a driving device (3) for advancing and
retracting the plunger,

10 wherein the cylinder has a port (12) for supplying a
molding material between a sliding position of the
plunger and the injection nozzle, and the molding
material supplied into the cylinder is compressed by
advancement of the plunger, so that the molding material
15 is injected into a cavity (301) of molds (300) connected
to the injection nozzle, and the plunger has a groove
(211) circumferentially extending along an outer
circumferential wall surface thereof.

2. An injection device according to Claim 1,
20 wherein the plunger has a smaller diameter portion (22)
in a leading part and a larger diameter portion (21) in a
trailing part thereof, an outer circumferential wall
surface of the larger diameter portion is in contact with
an inner circumferential wall surface of the cylinder for

This Sheet Has Been Replaced





isolating inner and outer regions of the cylinder from each other, and a stepped surface (23) in a boundary between the small diameter portion and the large diameter portion serves for guiding the molding material toward the injection nozzle, and:

in the case there is one said groove,

a clearance between the outer circumferential wall surface of the larger diameter portion of the plunger and the inner circumferential wall surface of the cylinder is defined by the following equation where η is a viscosity of the molding material, P is a back pressure (kgf/cm²) during weighing, Q is a quantity (cm³/s) of the molding material to be supplied, R is an inner radius of the cylinder, r_1 is an outer radius of the smaller diameter portion, r_2 is an outer radius of a part of the larger diameter portion before the groove, r_3 is an outer radius of a bottom surface of the groove, r_4 is an outer radius of a part of the larger diameter portion after the groove, l_1 is an axial length of the smaller diameter portion, l_2 is an axial length of the part of the larger diameter portion before the groove, l_3 is an axial length of the groove (width of the groove), l_4 is an axial length of the part of the larger diameter portion after the groove, and k is a ratio of a flow rate in an upward direction of the plunger from the supply port of the





molding material into the cylinder to a total quantity of the molding material supplied:

$$\begin{aligned} & \pi P / 2 \eta Q + \{ (1 - k) l_1 / [(R^4 - r_1^4) - (R^2 - r_1^2) / (l_n R - l_n r_1)] \} \\ 5 \quad & = k l_2 / [(R^4 - r_2^4) - (R^2 - r_2^2) / (l_n R - l_n r_2)] \\ & + k l_3 / [(R^4 - r_3^4) - (R^2 - r_3^2) / (l_n R - l_n r_3)] \\ & + k l_4 / [(R^4 - r_4^4) - (R^2 - r_4^2) / (l_n R - l_n r_4)] \end{aligned}$$

3. An injection device according to Claim 1 or 2, wherein the plunger has a smaller diameter portion (22) in a leading part and a larger diameter portion (21) in a trailing part thereof, the larger diameter portion is in contact with the cylinder for isolating inner and outer regions of the cylinder from each other, a stepped surface (23) in a boundary between the smaller diameter portion and the larger diameter portion serves for guiding the molding material toward the injection nozzle, a guide element (24) is provided in the smaller diameter portion of the plunger in a position backside in relation to the supply port so that two streams of molten liquid of the molding material flowing about the smaller diameter portion and reaching the backside position are guided toward the injection nozzle.

4. An injection device comprising:
a cylinder (1) having an injection nozzle (11)
at an end thereof;





a plunger (2) sliding in an axial direction thereof in a position opposite to the injection nozzle within the cylinder; and

5 a driving device (3) for advancing and retracting the plunger,

wherein the cylinder has a port (12) for supplying a molding material between a sliding position of the plunger and the injection nozzle, and the molding material supplied into the cylinder is compressed by
10 advancement of the plunger, so that the molding material is injected into a cavity (301) of molds (300) connected to the injection nozzle, the plunger has a smaller diameter portion (22) in a leading part and a larger diameter portion (21) in a trailing part thereof, the
15 larger diameter portion is in contact with the cylinder for isolating inner and outer regions of the cylinder from each other, a stepped surface (23) in a boundary between the smaller diameter portion and the larger diameter portion serves for guiding the molding material toward the injection nozzle, a guide element (24) is
20 provided in the smaller diameter portion of the plunger in a position backside in relation to the supply port so that two streams of molten liquid of the molding material flowing about the smaller diameter portion and reaching





THIS SHEET HAS BEEN
REPLACED

35

the backside position are guided toward the injection nozzle.

5 5. An injection device according to Claim 3 or 4, wherein the guide element has a pair of inclined guide surfaces with the approximately same inclined angle to an axial direction of the plunger.

10 6. An injection device according to Claim 5, wherein the guide element is a generally isosceles triangle having the pair of inclined guide surfaces with a protruding end of an apex of the guide element directed to the injection nozzle.

7. An injection device according to Claim 6, wherein the guide element is formed in equilateral triangle.

15 8. An injection device according to any one of Claims 1-7, further comprising a check valve (4) provided within the cylinder between a fluid holding part (13) with the injection nozzle and the supply port for preventing a molten liquid of the molding material held
20 in the fluid holding part from flowing back to the supply port, wherein a valve element (41) of the check valve is continuously forced against a valve seat (221) in the plunger by means of a spring (27) that is provided in a connecting shaft (25) extending frontward from the
25 plunger.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



36

9. An injection device comprising:

a cylinder (1) having an injection nozzle (11)
at an end thereof;

5 a plunger (2) sliding in an axial direction
thereof in a position opposite to the injection nozzle
within the cylinder; and

10 a driving device (3) for advancing and
retracting the plunger, wherein the cylinder has a port
(12) for supplying a molding material between a sliding
position of the plunger and the injection nozzle, and the
molding material supplied into the cylinder is compressed
by advancement of the plunger, so that the molding
material is injected into a cavity (301) of molds (300)
connected to the injection nozzle,

15 the device further comprising: a check valve (4) is
provided within the cylinder between a fluid holding part
(13) with the injection nozzle and the supply port for
preventing a molten liquid of the molding material held
in the fluid holding part from flowing back to the supply
20 port, wherein a valve element (41) of the check valve is
continuously forced against a valve seat (221) in the
plunger by means of a spring (27) that is provided in a
connecting shaft (25) extending frontward from the
plunger.

This Sheet Has Been Replaced





10. An injection device according to any one of Claims 1-9, wherein the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.

11. An injection device comprising:


a cylinder (1) having an injection nozzle (11) at an end thereof;

a plunger (2) sliding in an axial direction thereof in a position opposite to the injection nozzle within the cylinder; and

a driving device (3) for advancing and retracting the plunger,

wherein the cylinder has a port (12) for supplying a molding material between a sliding position of the plunger and the injection nozzle, and the molding material supplied into the cylinder is compressed by advancement of the plunger, so that the molding material is injected into a cavity (301) of molds (300) connected to the injection nozzle, the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.

This Sheet Has Been Replaced

A standard 1D barcode with vertical black bars of varying widths on a white background.

Fig. 1




Fig. 2




Fig. 3




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 6




Fig. 7




Fig. 8A





Fig. 8B



Hamburg
Patentanwalt
European Patent Attorney
Jochen Ehlers
Patentanwalt
Dipl.-Phys. Frank Meier
Rechtsanwalt
Rainer Böhm

München
Patentanwälte
European Patent Attorneys
Dipl.-Phys. Gernard Liedt
Dipl.-Wirtsch.-Ing. Rainer Fritzsche
Patentanwalt
Dipl.-Chem. Dr. Peter Schuler

Berlin
Patentanwältin
European Patent Attorney
Dipl.-Ing. Jutta Kaden

Alicante
European Trademark Attorney
Dipl.-Ing. Jürgen Klinghardt

Bremen
Patentanwälte
European Patent Attorneys
Dipl.-Ing. Günther Eisenführ
Dipl.-Ing. Dieter K. Speiser
Dr.-Ing. Werner W. Rabus
Dipl.-Ing. Jürgen Brügge
Dipl.-Ing. Jürgen Klinghardt
Dipl.-Ing. Klaus G. Göken
Patentanwälte
Dipl.-Ing. Mark Andres
Dipl.-Ing. Joachim von Oppen

Rechtsanwälte
Jirich H. Sander
Christian Spintig
Sabine Richter

Martinistrasse 24
D-28195 Bremen
Tel. 0421-36 35 0
Fax 0421-36 35 35 (G3)
Fax 0421-32 88 631 (G4)

73 064.125 @compuserve.com

Bremen, 5 June 1998

Our Ref.: M 4842 JOE/aw


Applicant: MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.
Serial Number: PCT/JP97/01557



New Claims

1. An injection device comprising:
a cylinder (1) having an injection nozzle (11) at an end thereof;
a plunger (2) sliding in an axial direction thereof in a position opposite to the injection nozzle within the cylinder; and
a driving device (3) for advancing and retracting the plunger,
wherein the cylinder has a port (12) for supplying a molding material between a sliding position of the plunger and the injection nozzle, and the molding material supplied into the cylinder is compressed by advancement of the plunger, so that the molding material is injected into a cavity (301) of molds (300) connected to the injection nozzle, and the plunger has a groove (211) circumferentially extending along an outer circumferential wall surface thereof;
wherein the plunger has a smaller diameter portion (22) in a leading part and a larger diameter portion (21) in a trailing part thereof, an outer circumferential wall surface of the larger diameter portion is in contact with an inner circumferential wall surface of the cylinder for isolating inner and outer regions of the cylinder from each other, and a stepped surface (23) in a boundary between the small diameter portion and the large diameter portion serves for guiding the molding material toward the injection nozzle, and
in the case there is one said groove,

AMENDED SHEET





a clearance between the outer circumferential wall surface of the larger diameter portion of the plunger and the inner circumferential wall surface of the cylinder is defined by the following equation where η is a viscosity of the molding material, P is a back pressure (kgf/cm^2) during weighing, Q is a quantity (cm^3/s) of the molding material to be supplied, R is an inner radius of the cylinder, r_1 is an outer radius of the smaller diameter portion, r_2 is an outer radius of a part of the larger diameter portion before the groove, r_3 is an outer radius of a bottom surface of the groove, r_4 is an outer radius of a part of the larger diameter portion after the groove, l_1 is an axial length of the smaller diameter portion, l_2 is an axial length of the part of the larger diameter portion before the groove, l_3 is an axial length of the groove (width of the groove), l_4 is an axial length of the part of the larger diameter portion after the groove, and k is a ratio of a flow rate in an upward direction of the plunger from the supply port of the molding material into the cylinder to a total quantity of the molding material supplied:

$$\begin{aligned} & \pi P / 2 \eta Q + \{ (1 - k) l_1 / [(R^4 - r_1^4) - (R^2 - r_1^2) / (l_n R - l_n r_1)] \} \\ & = k l_2 / [(R^4 - r_2^4) - (R^2 - r_2^2) / (l_n R - l_n r_2)] \\ & \quad + k l_3 / [(R^4 - r_3^4) - (R^2 - r_3^2) / (l_n R - l_n r_3)] \\ & \quad + k l_4 / [(R^4 - r_4^4) - (R^2 - r_4^2) / (l_n R - l_n r_4)] \end{aligned}$$

2. An injection device comprising:
 - a cylinder (1) having an injection nozzle (11) at an end thereof;
 - a plunger (2) sliding in an axial direction thereof in a position opposite to the injection nozzle within the cylinder; and
 - a driving device (3) for advancing and retracting the plunger;
 wherein the cylinder has a port (12) for supplying a molding material between a sliding position of the plunger and the injection nozzle, and the molding material supplied into the cylinder is compressed by advancement of the plunger, so that the molding material is injected into a cavity (301) of molds (300) connected to the injection nozzle, and the plunger has a groove (211) circumferentially extending along an outer circumferential wall surface thereof; and
 - wherein the plunger has a smaller diameter portion (22) in a leading part and a larger diameter portion (21) in a trailing part thereof, the larger diameter portion is in contact with the cylinder for isolating inner and outer regions of the cylinder from each other, a stepped surface (23) in a boundary between the smaller diameter portion and the larger diameter portion serves for guiding the molding material

REPLACEMENT SHEET

12 JUN 1998

AMENDED SHEET



toward the injection nozzle, a guide element (24) is provided in the smaller diameter portion of the plunger in a position backside in relation to the supply port so that two streams of molten liquid of the molding material flowing about the smaller diameter portion and reaching the backside position are guided toward the injection nozzle.

3. An injection device according to Claim 1 or 2,
wherein the plunger has a smaller diameter portion (22) in a leading part and a larger diameter portion (21) in a trailing part thereof, the larger diameter portion is in contact with the cylinder for isolating inner and outer regions of the cylinder from each other, a stepped surface (23) in a boundary between the smaller diameter portion and the larger diameter portion serves for guiding the molding material toward the injection nozzle, a guide element (24) is provided in the smaller diameter portion of the plunger in a position backside in relation to the supply port so that two streams of molten liquid of the molding material flowing about the smaller diameter portion and reaching the backside position are guided toward the injection nozzle.
4. An injection device according to Claim 2 or 3,
wherein the guide element has a pair of inclined guide surfaces with the approximately same inclined angle to an axial direction of the plunger.
5. An injection device according to Claim 4,
wherein the guide element is a generally isosceles triangle having the pair of inclined guide surfaces with a protruding end of an apex of the guide element directed to the injection nozzle.
6. An injection device according to Claim 5,
wherein the guide element is formed in equilateral triangle.
7. An injection device according to one of Claims 1 - 6,
further comprising a check valve (4) provided within the cylinder between a fluid holding part (13) with the injection nozzle and the supply port for preventing

AMENDED SHEET

REPLACEMENT SHEET

12 JUN 1998



- 4 -



a molten liquid of the molding material held in the fluid holding part from flowing back to the supply port, wherein a valve element (41) of the check valve is continuously forced against a valve seat (221) in the plunger by means of a spring (27) that is provided in a connecting shaft (25) extending frontward from the plunger.

8. An injection device according to Claim 1,

the device further comprising: a check valve (4) is provided within the cylinder between a fluid holding part (13) with the injection nozzle and the supply port for preventing a molten liquid of the molding material held in the fluid holding part from flowing back to the supply port, wherein a valve element (41) of the check valve is continuously forced against a valve seat (221) in the plunger by means of a spring (27) that is provided in a connecting shaft (25) extending frontward from the plunger.

9. An injection device according to Claim 1,

wherein the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.


10. An injection device according to Claim 1,

wherein the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.


11. An injection device according to Claim 8 or 9,


wherein the valve element (41) of the check valve (4) has a tapered portion in conformity with the valve seat (221).

This Sheet Has Been Replaced



REPLACEMENT SHEET





Substitute sheet - 11 May 1999


24

forward and backward movements to the plunger 2 for advancing and retracting the plunger 2.

As shown in Fig. 1, a check valve 4 is employed between a fluid holding part 13 and the supply port 12 in a stage before the injection nozzle 11 within the cylinder 1 for preventing a molten liquid of molding material held in the fluid holding part 13 to flow back to the supply port 12. The check valve 4 is cylindrical, as shown in Fig. 5C, and is passed therethrough, as shown in Fig. 5A, by a connecting shaft 25, which extends from the smaller diameter portion 22 of plunger toward the injection nozzle 11 (see Fig. 1) for sliding within the cylinder 1 in the vertical direction of the figure. At a leading end of the smaller diameter portion 22 of the plunger, a valve seat 221 in conformity with a tapered valve element 41 of the check valve 4 is provided.

A spring 27 is employed in an arrowhead-shaped head 26 formed at a leading end of the connecting shaft 25, and the ~~value~~^{valve} element 41 of the check valve 4 is continuously forced against the valve seat 221 in the smaller diameter portion 22 of the plunger by means of the spring 27, as shown in Fig. 5B.

As shown in Fig. 1, the driving device 3 includes an encoder 51 associated with the servo motor 33 for detecting an angle of rotation of the servo motor 33.




Substitute sheet - 11 May 1999

27

high speed under a high pressure is maintained at the injection pressure by the plunger 2 until it comes to be solid.

5 The check valve 4 closes a passage of the molding material as shown in Fig. 5B, as the ^{valve}~~value~~ element 41 of the check ~~value~~^{valve} 4 is pressed against the valve seat 221 in the smaller diameter portion 22 of the plunger during injection, after the injection, and during pressure-holding process. The passage is open, as shown
10 in Fig. 5A, at the initiation of weighing, during the weighing, and when the molding material is fed, because the feeding pressure of the molding material overcomes the spring force. Although if the spring 27 is absent the valve tends to be opened when it is subjected to a
15 negative pressure during suck-back operation, since the check-valve 4 is continuously forced by the spring 27 in the injection device, it is not opened and keeps closing the passage of the molding material, even if it is subjected to a negative pressure. In such manner, back
20 flow of the molding material can be prevented, and a fixed quantity of the molding material can be supplied to the mold cavity 301.

25 The molding material tends to flow back into the cylinder from inside the mold cavity 301 after injection to the mold cavity 301 until completion of the



a molten liquid of the molding material held in the fluid holding part from flowing back to the supply port, wherein a ^{valve}~~valve~~ element (41) of the check valve is continuously forced against a valve seat (221) in the plunger by means of a spring (27) that is provided in a connecting shaft (25) extending frontward from the plunger.

8. An injection device according to Claim 1,
the device further comprising: a check valve (4) is provided within the cylinder between a fluid holding part (13) with the injection nozzle and the supply port for preventing a molten liquid of the molding material held in the fluid holding part from flowing back to the supply port, wherein a ^{valve}~~valve~~ element (41) of the check valve is continuously forced against a valve seat (221) in the plunger by means of a spring (27) that is provided in a connecting shaft (25) extending frontward from the plunger.

9. An injection device according to Claim 1,
wherein the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.

10. An injection device according to Claim 1,
wherein the driving device is further provided with a control means (5) having a position detector for detecting a position of the plunger within the cylinder in order to control operation of the driving device according to a detection signal thereof for fixing the position of the plunger to a position at the end of injection.

11. An injection device according to Claim 8 or 9,
wherein the valve element (41) of the check valve (4) has a tapered portion in conformity with the valve seat (221).



9805651-8
IPDS copy



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B29C 45/54, 45/52		A1	(11) International Publication Number: WO 97/43106
			(43) International Publication Date: 20 November 1997 (20.11.97)
(21) International Application Number: PCT/JP97/01557 (22) International Filing Date: 9 May 1997 (09.05.97) (30) Priority Data: 8/117637 13 May 1996 (13.05.96) JP (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka 571 (JP). (72) Inventors; and (75) Inventors/Applicants (for US only): KADORIKU, Shinji [JP/JP]; 2-1-2-208, Sumiregaoka, Takarazuka-shi, Hyogo 665 (JP). HIGASHIDA, Takaaki [JP/JP]; 5-22-13, Toda-cho, Moriguchi-shi, Osaka 570 (JP). YUTANI, Hiroshi [JP/JP]; 30-13, Kisaichi 6-chome, Katano-shi, Osaka 576 (JP). MURATA, Tadao [JP/JP]; 2-10-5, Tsutsujigaoka-kita, Sanda-shi, Hyogo 669-13 (JP). (74) Agents: AOYAMA, Tamotsu et al.; Aoyama & Partners, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Osaka-shi, Osaka 540 (JP).			(81) Designated States: KR, SG, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: INJECTION DEVICE

(57) Abstract

In an injection device, a groove (211) is provided in an outer circumferential wall surface of a plunger (2), a clearance between the outer circumferential wall surface of the plunger (2) and an inner circumferential wall surface of a cylinder (1) is determined by a specified equation, a guide element (24) is provided in a position backside of the plunger, a check valve (4) employed in the cylinder is continuously forced against a valve seat (221) by means of a spring (27), and a driving device (3) is provided with control means (5) for fixing a position of the plunger to a position at the end of injection process.

