

ABSTRACT

An adhesive film (50) of the present invention includes a base material layer (10); an adhesive resin layer (A) provided on a first surface (10A) side of the base material layer (10); and an adhesive resin layer (B) provided on a second surface (10B) side of the base material layer (10) and in which an adhesive force is decreased by an external stimulus, in which, as measured by method 1, an integrated tacking force value ($F_{2.5}$) of the adhesive resin layer (B) is 1.0 gf/sec or more at a test speed of 2.5 mm/min and a test temperature of 130°C, and an integrated tacking force value (F_{30}) of the adhesive resin layer (B) is 7.0 gf/sec or more at a test speed of 30 mm/min and a test temperature of 130°C.

(method 1) using a tacking tester, a probe is pressed on the adhesive resin layer (B) for 60 seconds under conditions of a probe load of 100 gf and a probe pushing speed of 120 mm/min, then, at a test temperature of 130°C, tack strengths (gf) are respectively measured at test speeds of 2.5 mm/min and 30 mm/min, a measurement time is set as a horizontal axis and the tack strength (gf) is set as a vertical axis, integrated values are each calculated from a point where the tack strength starts to rise from 0 to a point where the tack strength becomes 0 again, and the calculated values are respectively set as $F_{2.5}$ and F_{30} .