

PORTABLE CHARGEABLE SPRAYING BOTTLE

BACKGROUND OF THE INVENTION

1. Technical Field

5 The present invention relates to a spray bottle which can carry and spray liquid, and more especially, to a portable chargeable spray bottle.

2. Description of Related Art

Currently, the well-known portable spray bottle comprises a nozzle assembly, an inner bottle and an enclosure. The majority of spray bottles are used only once
10 and thrown away when the liquid is used up. Though charging bottles with charging accessories appear in the market, they are complex, easy to spill and leak, and inconvenient. The current spray bottles made from plastic or glass causes environmental pollution when they are thrown away. Besides, for manufacturers and consumers, disposable goods are uneconomical, resulting in the waste of
15 productive materials. Another problem is that the large bottles are inconvenient to carry if they are used by consumers on the go.

BRIEF SUMMARY OF THE INVENTION

The technical problem to be solved by the present invention is to provide a
20 portable chargeable spray bottle which is easy to carry, features simple operation and quick charging, and bears certain negative pressure. To address the aforesaid technical problems, the present invention adopts the following technical solution:

The portable chargeable spray bottle comprises an inner bottle and a nozzle assembly installed on the upper inner part of inner bottle. The liquid charging
25 structure equipped at the bare bottom of inner bottle includes a stepped liquid charging mouth located at the bottom of the inner bottle, a protuberant piston equipped on the liquid charging mouth and a piston resetting structure. The piston

is provided with a liquid charging passage and a discharging opening is arranged on the top of the liquid charging passage. A stop block with one flared end is equipped on the top of piston. The first sealing ring capable of performing static sealing is arranged on the stop block. The piston is provided with a groove at the bottom in which the second sealing ring is equipped. A compression spring resetting the piston is fitted on the piston. As well, the spring is equipped between the first step surface of stepped liquid charging mouth and that of protuberant piston. The piston is pushed downwards by the spring and the stop block is driven to compress the first sealing ring to perform static sealing towards the inner bottle. The bottom of the piston is provided with a concave surface on which the third sealing ring used to prevent liquid from leaking during liquid charging is equipped. An exhaust structure is available in the inner bottle.

Embodiment 1: the exhaust structure includes an exhaust hole 16 equipped on the upper part of side wall of inner bottle. The exhaust hole 16 is interconnected with the outside by penetrating side wall of inner bottle.

Embodiment 2: the exhaust structure includes an exhaust hole 26 equipped on the lower inner part of inner bottle which corresponds to the groove of piston, and an air duct interconnected with exhaust hole 26 and extending to upper inner part of inner bottle. Obviously, the independent or simultaneous use can be adopted for exhaust. The dynamic sealing is formed by the second sealing ring in the groove at the bottom of piston and exhaust hole. That is, when charging, the second sealing ring moves upwards driven by the piston and separates from exhaust hole 26, so that, the air duct is directly connected with atmosphere; the second sealing ring is compressed in the exhaust hole 26 in normal status, and the air duct is blocked from atmosphere, thus forming sealing.

Embodiment 3: the exhaust structure includes an exhaust hole 36 equipped on the lower inner part of inner bottle, and an air duct interconnected with exhaust

hole 36 and extending to upper inner part of inner bottle. A silicon rubber gasket is equipped at the bottom of the exhaust hole 36. In order to exhaust the air, various pores are arranged on the silicon rubber gasket along the axis. For another realization mode of this embodiment, the silicon rubber gasket is equipped on the top of nozzle assembly installed on the upper part of inner bottle, wherein various pores are arranged on the silicon rubber gasket.

Embodiment 4: the exhaust structure includes an exhaust hole 46 equipped on the lower inner part of inner bottle, and an air duct is interconnected with exhaust hole 46 and extends to upper inner part of inner bottle. A bead is equipped on the lower part of the exhaust hole 46 and on the compression spring which is set on the lower inner part of inner bottle.

The reverse buckling or threaded connection can be adopted for the nozzle assembly installed on the upper part of inner bottle, which is beneficial to sealing and hard to loosen. It is possible to use other connection modes in other embodiments.

In consideration of aesthetic perception, the inner bottle can be equipped with a decorative enclosure. The exhaust structure described in the present invention is not limited to the abovementioned liquid charging structure. It can be applied in the charging bottle of different liquid charging structures in other embodiments.

With the abovementioned structures, the spray bottle is convenient for carrying and can be reused, thus reducing the waste of resources. The user can quickly charge the spray bottle through charging structure instead of throwing it away once the liquid in the bottle is used up. Consequently, it can save the cost and protect the environment. In addition, the exhaust structure arranged in the present invention can ensure that it can bear certain negative pressure and work normally during air transport or in high altitude localities.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 is the left view of one embodiment;

FIG. 2 is the sectional view of A-A in FIG. 1;

FIG. 3 is the front view of one embodiment;

5 FIG. 4 is the sectional view of B-B in FIG. 3;

FIG. 5 is the schematic view of Embodiment 2 of the present invention;

FIG. 6 is the partial amplified view of part 15 in FIG. 5;

FIG. 7 is schematic view of liquid charging structure sealed by a marble bead;

10 FIG. 8 is schematic view of liquid charging structure sealed by a silicon rubber gasket;

FIG. 9 is the schematic view of realization mode 1 of Embodiment 3;

FIG. 10 is the partial amplified view of part 25 in FIG. 7;

FIG. 11 is the schematic view of realization mode 2 of Embodiment 3;

FIG. 12 is the schematic view of Embodiment 4;

15 FIG. 13 is the partial amplified view of part 35 in FIG. 9;

FIG. 14 is the schematic view of a liquid charging state of an embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

20 For a better understanding of those skilled in this art, the basic structure of present invention is further detailed by the embodiments in combination with the drawings as below.

As shown in FIG. 1-6, the present invention comprises a nozzle assembly 1 and an inner bottle 2, wherein the pressing nozzle in the prior art is equipped in nozzle assembly 1, including the nozzle used in the bottle of scent, shampoo, gel
25 and medical liquid. It is unnecessary to give details about the structural principles. The nozzle assembly 1 is installed in the upper mouth of the inner bottle 2 and is connected through reverse buckling or thread. They are closely fitted, so it is easy

and fast to assembly them. Obviously, it is possible to use other connection modes in other embodiments. Moreover, to give a fantastic aesthetic perception, the inner bottle 2 can be equipped on the decorative enclosure 3.

5 A bare stepped liquid charging mouth 21 is equipped at the bottom of inner bottle 2. The liquid charging mouth 21 is fitted with a piston 5 in which a liquid charging passage 51 is installed. The opening 510 of liquid charging passage 51 is located on the top of piston 5. A stop block 52 with one flared end is equipped on the top of piston 5. The first sealing ring 53 capable of performing static sealing is arranged on the stop block 52 and seals the inner bottle 2 and liquid charging
10 mouth 21 when out of charging. The protuberant piston 5 is equipped on the stepped liquid charging mouth 21 and is provided with a compression spring 56. The compression spring 56 is equipped between the first step surface 210 of stepped liquid charging mouth 21 and stop block 52. The piston 5 is pushed downwards by the spring 56. Then the stop block 52 is driven to compress the first
15 sealing ring 53 to perform static sealing towards inner bottle 2. The piston 5 is provided with a groove in between its bottom and the stop block 52 in which the second sealing ring 54 is equipped. The bottom of piston 5 is designed as a concave surface on which the third sealing ring 57 used to prevent liquid from leaking during liquid charging is equipped. Furthermore, the liquid charging structure can
20 adopt other modes, such as the liquid charging structure sealed by bead, as shown in FIG. 7, and one sealed by silicon rubber, as shown in FIG. 8.

When the spray bottle is charged, the air inside the inner bottle 2 is compressed, resulting in the increase of pressure. As a result, if without an exhaust structure, the failure of exhaust air will cause an obstacle to charging. As well, the
25 spray bottle may be damaged or cannot be fully charged. To address the problem above, an exhaust structure is arranged in the inner bottle 2. The present invention will be further perfected in combination with the embodiments.

Embodiment 1: As shown in FIG. 4, an exhaust hole 16 is equipped on the upper part of inner bottle 2. The exhaust hole 16 penetrates the side wall of inner bottle and is interconnected with the outside. When charging, the air inside the inner bottle 2 is compressed, resulting in the increase of pressure. The air inside the inner bottle 2 is exhausted via exhaust hole 16. Since the exhaust hole 16 is interconnected with the outside and is relatively small, it is easy to be blocked by dust and unwanted objects. The liquid in the bottle may flow out through exhaust hole 16 due to air pressure in the plane or localities with high air pressure, so other embodiments will be stated as below.

Embodiment 2: as shown in FIG. 5 and 6, an exhaust hole 26 is equipped on the lower inner part of inner bottle 2 and corresponds to the groove of piston 5. An air duct 24 is interconnected with exhaust hole 26 and extends to the upper inner part of the inner bottle 2. Accordingly, the air in the inner bottle 2 can be exhausted through air duct 24 and exhaust hole 26. The dynamic sealing is formed by the second sealing ring 54 in the groove at the bottom of piston 5 and exhaust hole 26. That is, when charging, the second sealing ring 54 moves upwards driven by the piston and separates from exhaust hole 16, so that, the air duct 24 is directly connected with atmosphere; the second sealing ring 54 is compressed in the exhaust hole 26 in normal status, and the air duct 24 is blocked from atmosphere, thus forming sealing. Obviously, the simultaneous use can be carried out for Embodiment 1 and 2. That is to say, the exhaust hole 16 and 26 can coexist in the inner bottle 2.

Embodiment 3: as shown in FIG. 9 and 10, Embodiment 3 differs from Embodiment 2 in arrangement of exhaust hole. In the realization mode 1 of this embodiment, an exhaust hole 36 is equipped on the lower inner part of inner bottle and interconnected with the air duct 24 extending to upper inner part of inner bottle 2. A silicon rubber gasket 61 is equipped at the bottom of the exhaust hole 36 and is

provided with various pores along the axis. As shown in FIG. 11, in another realization mode of this embodiment, a silicon rubber gasket 68 is equipped on the top of nozzle assembly 1 installed on the upper part of inner bottle 2, wherein various pores are arranged on the silicon rubber gasket 68 along its axis. Of course, the simultaneous use can be carried out for Embodiment 1 and 3. That is to say, the exhaust hole 16 and 36 can coexist in the inner bottle 2, or both the silicon rubber gasket 68 and exhaust hole 16 are set in the inner bottle, or the three parts coexist.

Embodiment 4: as shown in FIG. 12 and 13, an exhaust hole 46 is equipped on the lower inner part of inner bottle 2, and an air duct 24 is interconnected with exhaust hole 46 and extends to upper inner part of inner bottle 2. A bead 58 is equipped at the bottom of exhaust hole 46 and on the compression spring 59, wherein the compression spring 59 is set on the lower inner part of inner bottle 2. Obviously, the simultaneous use can be carried out for Embodiment 1 and 4. That is to say, the exhaust hole 16 and 46 can coexist in the inner bottle 2.

As shown in FIG. 14, when the spray bottle is charged, the nozzle of the external large bottle is aligned with liquid charging mouth 21, thus the opening of liquid charging passage 51 of piston is aimed at the nozzle of the external large bottle. Then the spray bottle is pressed down to drive the piston 5 to move upwards and compress spring 56. Furthermore, the first sealing ring 53 on the piston 5 is separated from the sloped side wall 212 on the top of liquid charging mouth 21, and the inner bottle 2 is connected with liquid charging mouth 21, namely it is connected with liquid charging passage 51. Under certain pressure in the large bottle, the liquid in the large bottle enters liquid charging mouth 21 and then the inner bottle 2 via liquid charging passage 51.

Following the liquid in the large bottle entering inner bottle 2, the compressed air in inner bottle 2 results in the increase of pressure, so the air is required to be exhausted so as to ensure continuous charging. In Embodiment 1, the air is

drained away via exhaust hole 16.

In Embodiment 2, when charging, the second sealing ring 54 moves upwards and separates from exhaust hole 26; the air duct 24 is directly connected with atmosphere; the air in inner bottle 2 is compressed, which causes the pressure to increase; the air is drained away through air duct 24 and exhaust hole 26. Upon stopping charging, the second sealing ring 54 moves downwards to seal exhaust hole 26. Consequently, the liquid in inner bottle 2 fails to flow out, and the air duct 24 is blocked from atmosphere. After the charging is finished, the nozzle of the large bottle and piston 5 are disconnected. The piston 5 can move backwards with the help of spring 56. The first sealing ring 53 arranged on stop block 52 contacts the upper part of sloped side wall 212 on the liquid charging mouth 21, thus forming sealing and completing charging.

In the realization mode 1 of Embodiment 3, when the air inside inner bottle 2 is connected with silicon rubber gasket 61 which has no pores in it, the surface of silicon rubber gasket 61 is compressed to make it deform. Thus, the air can be exhausted from the circumference of the silicon rubber gasket 61. When pores are available in silicon rubber gasket 61, the air inside inner bottle 2 impels the pores to have a radial extension. As a result, the pores on silicon rubber gasket 61 are enlarged and the air can be drained away via exhaust hole 36. When exhaust is complete, silicon rubber gasket 61 resets to block exhaust hole 36 and seal it. In the realization mode 2 of Embodiment 3, the air inside inner bottle 2 impels the pores on silicon rubber gasket 68 to have a radial extension, so the air can be drained away via pores on silicon rubber gasket 68. Then, the sealing is realized when the pores silicon rubber gasket 68 recover.

In Embodiment 4, the bead 58 compressed by air in inner bottle 2 impels the compression spring 59 to move downwards. The air is drained away via exhaust hole 46 when bead 58 is separated from it. With exhaust completed, the compression spring 59 supports bead 58, thus it can block the opening of exhaust

hole 46 and form excellent sealing.

A variety of liquid charging structures can be used in the exhaust structure in other embodiments. As for the preferred embodiments of the present invention above, the substitutions made towards the present invention without deviating from
5 the concept of the present invention are all within the protective scope of the present invention.

What is claimed is:

1. A portable chargeable spray bottle, comprising:
 - a bottle having an upper part and a bottom part;
 - a nozzle assembly equipped on the upper part of the bottle, and
 - a liquid charging structure provided at the bottom part of the bottle, the liquid charging structure comprising:
 - a liquid charging mouth;
 - a piston provided in the liquid charging mouth, and
 - a resetting structure of the piston, wherein a liquid charging passage is arranged on the piston and is fitted with a discharging opening in fluid communication with the interior of the bottle,
 - wherein a stop block is provided on top of said piston, and wherein a first sealing ring capable of performing static sealing is arranged about the stop block, and
 - wherein the piston is provided with a groove at the bottom in which a second sealing ring is provided, and wherein the bottom of said piston is designed as a concave surface on which a third sealing ring used to prevent liquid from leaking during liquid charging is provided.