

(51) International Patent Classification:
E21B 43/04 (2006.01)(21) International Application Number:
PCT/US2013/020247(22) International Filing Date:
4 January 2013 (04.01.2013)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
13/345,500 6 January 2012 (06.01.2012) US(71) Applicant: **WEATHERFORD/LAMB, INC.** [US/US];
2000 St. James Place, Houston, TX 77056 (US).(72) Inventor (for US only): **VAN PETEGEM, Ronald**; 11568
Grand Pine Drive, Montgomery, TX 77356 (US).(72) Inventors: **BROUSSARD, John, P.**; 4106 Quiet Glade
Court, Kingwood, TX 77345 (US). **HALL, Christopher**;
16331 Cumberland Trail, Cypress, TX 77433 (US). **ZIM-
MERMAN, Patrick, J.**; 2002 Red Bay Court, Houston,
TX 77062 (US).(74) Agent: **MCDERMOTT, Sean, P.**; Wong, Cabello,
Lutsch, Rutherford & Bruculeri, LLP, 20333 Tomball
Parkway, Suite 600, Houston, TX 77070 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: GRAVEL PACK BYPASS ASSEMBLY



(57) **Abstract:** A gravel pack operation disposes slurry from an inner string into the annulus around a shoe track. A valve on the shoe track can open and close flow through a port, and seats around the port allow an outlet of the tool to seal with the port. When the valve is open and the outlet sealed with the port, the slurry in the string is pumped into the borehole around the shoe track by flowing the slurry from the outlet into the borehole through the flow port. As this occurs, gravel collects around the shoe track, and fluid returns in the borehole flow back into the shoe track through a screen disposed toward the track's toe. Once inside the shoe track, the fluid returns communicate through a bypass on the shoe track around the sealed outlet and port. At this point, the fluid returns can pass uphole in the gravel pack assembly.

