




- (51) International Patent Classification:
E21B 33/038 (2006.01)
- (21) International Application Number:
PCT/US2013/035332
- (22) International Filing Date:
4 April 2013 (04.04.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/620,346 4 April 2012 (04.04.2012) US
- (71) Applicant: NATIONAL OILWELL VARCO, L.P.
[US/US]; 7909 Parkwood Circle Drive, Houston, TX
77036 (US).
- (72) Inventors: MILLER, Travis, James; 21923 Amber Elm
Trl, Cypress, TX 77433 (US). GREBING, Kent, Allen;
6019 Live Oak Place, Spring, TX 77379 (US). POL-
LARD, Michael, Edwin; 12119 Lieder Drive, Houston,
TX 77065 (US). SPRINGETT, Frank, B.; 1303 Rose-
berry Manor, Spring, TX 77379 (US).
- (74) Agent: SALAZAR, JL, Jennie; The JL Salazar Law Firm,
PLLC, 1934 West Gray Street, Houston, TX 77019 (US).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

- (54) Title: MISALIGNMENT-TOLERANT WELLSITE CONNECTION ASSEMBLY, SYSTEM, AND METHOD



(57) Abstract: A connection assembly, system and method for connecting components of a wellsite are provided. The wellsite has a wellbore extending into a subsurface formation, the connection assembly includes a female connector having a cavity extending therein, a floating cartridge having, and a male connector. The female connector or floating cartridge is operatively connectable to a first of the components. The floating cartridge is operatively connectable to the female connector and laterally movable therein. The male connector is receivable in the cavity and is operatively connectable to the second of the components and the floating cartridge such that the male connector and the female connector are movably positionable relative to each other by the floating cartridge whereby a misalignment between the wellsite components is tolerated. The male connector may have a joint pivotally connectable to the floating cartridge.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, **Published:**
ML, MR, NE, SN, TD, TG).

— *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*