PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : H04L — A2

(11) International Publication Number: **WO 00/07322**

(43) International Publication Date: 10 February 2000 (10.02.00)

(21) International Application Number: PCT/US99/15644

(22) International Filing Date: 12 July 1999 (12.07.99)

(30) Priority Data:
09/123,486 28 July 1998 (28.07.98) US

(71) Applicant *(for all designated States except US)*: SERCONET LTD. [IL/IL]; Poleg Industrial Park, P.O. Box 8027, 42101 Netanya–South (IL).

(71) Applicant *(for TJ only)*: FRIEDMAN, Mark, M. [US/IL]; Alharizi 1, 43406 Raanana (IL).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: BINDER, Yehuda [IL/IL]; Yeshurun Street 30, 45200 Hod Hasharon (IL).

(74) Common Representative: FRIEDMAN, Mark, M.; c/o Castorina, Anthony, Suite 207, 2001 Jefferson Davis Highway, Arlington, VA 22202 (US).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
Without international search report and to be republished upon receipt of that report.

(54) Title: LOCAL AREA NETWORK OF SERIAL INTELLIGENT CELLS

(57) Abstract

A serial intelligent cell (SIC) and a connection topology for local area networks using Electrically–conducting media. A local area network can be configured from a plurality of SIC's interconnected so that all communications between two adjacent SIC's is both point–to–point and bidirectional. Each SIC can be connected to one or more other SIC's to allow redundant communication paths. Communications in different areas of a SIC network are independent of one another, so that, unlike current bus topology and star topology, there is no fundamental limit on the size or extent of a SIC network. Each SIC can optionally be connected to one or more data terminals, computers, telephones, sensors, actuators, etc., to facilitate interconnectivity among such devices. Networks according to the present invention can be configured for a variety of applications, including a local telephone system, remote computer bus extender, multiplexers, PABX/PBX functionality, security systems, and local broadcasting services. The network can use dedicated wiring, as well as existing wiring as the in–house telephone or electrical wiring.