

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 January 2001 (04.01.2001)

PCT

(10) International Publication Number
WO 01/00430 A1

- (51) International Patent Classification⁷: **B60C 19/00, G01M 1/32**
- (21) International Application Number: **PCT/DK00/00331**
- (22) International Filing Date: **21 June 2000 (21.06.2000)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
99112199.7 24 June 1999 (24.06.1999) EP
- (71) Applicant (for all designated States except US): **CARNE-HAMMAR, Lars, Bertil [SE/GB]; 52 Allestree Road, London SW6 6AE (GB).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **RONLAN, Alvin [DK/US]; 3414 Norfolk Street, Hillsboro Shores, FL 33062 (US).**
- (74) Agent: **PLOUGMANN, VINGTOFT & PARTNERS A/S; Sankt Annæ Plads 11, P.O. Box 3007, DK-1021 Copenhagen K (DK).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KR (utility model), KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**
- Published:
— *With international search report.*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **TYRE BALANCING COMPOSITIONS**

WO 01/00430 A1

(57) Abstract: The invention relates to tyre balancing compositions having improved balancing properties comprise a visco-plastic gel and solid bodies having an average smallest dimension in the range of 0.5-5 mm; preferably 1-4 mm, more preferably around 3 mm. When applied in a layer to the inside of a motor vehicle tyre, the compositions act by allowing the solid bodies move through the gel and to concentrate in areas to counteract imbalances. The solid bodies preferably have an average ratio α between their smallest and their largest dimension of $\alpha \leq 2$, more preferably $\alpha \leq 1.5$, especially around 1. The visco-plastic gel preferably has a storage modulus (G') between 1000 Pa and 25000 Pa at 22 °C, a loss modulus (G'') smaller than the storage modulus, and a critical yield stress above 3 Pa at 22 °C. The bodies may be shaped as prolate or oblate ellipsoids, cylinders, rectangular parallelepipeds, or spheres, or mixtures of such bodies; they may have an apparent specific gravity in the range of 500-3000 kg/m³, preferably 600-2000 kg/m³, in particular 700-1000 kg/m³, especially 800-900 kg/m³; they may be made from polyolefins, polystyrene, polyvinyl chloride, polyamide, rubber or glass. The weight ratio between the solid bodies and the gel is from 10:1 to 1:10, preferably from 5:1 to 1:5, in particular from 2:1 to 3:1, such as from 1:1 to 1:2. The invention further concerns a tyre balancing kit and a method for balancing automobile wheel assemblies.