~~**EXEMPLARY CLAIMS:**~~

What is claimed is:

1. A targeting method, comprising:

capturing, by a first processor, a first video of a scene about a potential targeting coordinate by a first video sensor on a first aircraft, the first aircraft comprising the first processor, and the first processor in communication with the first video sensor;

transmitting, by the first processor, ~~-~~the first video and associated potential targeting coordinate ~~by the first aircraft~~;

receiving, by a second processor, ~~-~~the first video on a first display in communication with ~~a~~ the second processor, the second processor also receiving the potential targeting coordinate;

selecting, by the second processor, ~~-~~the potential targeting coordinate to be an actual targeting coordinate for a second aircraft ~~in response to viewing~~ based on the first video on the first display, wherein the selected actual targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the captured first video; and

guiding ~~a~~, by the second processor, to launch the second aircraft toward the actual targeting coordinate, the second aircraft comprising a third processor;

capturing, by the third processor, a second video of the scene by a second video sensor on the second aircraft after being launched;

displaying, by the second processor, the second video proximate to the first video as the second aircraft approaches the actual targeting coordinate;

wherein a positive identification ~~of~~ is executed, by the second processor, based on a target ~~corresponding to the actual targeting coordinate is maintained from selection of the actual targeting coordinate.~~ being identified in both is in the first video and the second video simultaneously; and

controlling, by the second processor, the second aircraft to impact the target while maintaining the positive identification.

2. The method claim 1, further comprising:

launching the second aircraft, the second aircraft having ~~a~~ the second video sensor~~.~~; and

~~3. The method of claim 2, further comprising:~~

guiding, by the second processor, the first aircraft about the actual targeting coordinate to maintain a field of view (FOV) of the first video sensor about the actual targeting coordinate.

4.3. The method of claim ~~3~~1, further comprising:

~~capturing a~~ setting, via the second ~~video of the scene by the second video sensor; and displaying the second video proximate~~ processor, an entry point, to the ~~first video as the second aircraft approaches the~~ actual targeting coordinate, for the second aircraft based on a predetermined distance from the target and wind speed.

5.4. The method of claim ~~4~~1, wherein ~~maintaining~~ the positive identification ~~of the target~~ transfer further comprises:

comparing, by a user of the second processor, the received first video of the scene and the received second video of the scene on the first display to confirm the second aircraft is approaching the actual targeting coordinate.

~~6.~~5. The method of claim ~~4~~1, further comprising:

selecting, by the second processor, a terminal homing mode on the target by the second aircraft in response to viewing the first video and the second video on the first display.

~~7.~~6. The method of claim 5~~6~~, wherein the terminal homing mode further comprises at least one of: impacting the target by the second aircraft, impacting the target by a payload deployed by the second aircraft, and impacting the target by a marker deployed by the second aircraft.

~~8.~~7. The method of claim ~~7~~6, further comprising:

confirming a condition of the target after impact in response to viewing the first video on the first display.

~~9.~~8. The method of claim ~~8~~7, further comprising:

capturing, by the first processor, a new first video of a new scene about a new potential targeting coordinate by the first video sensor on the first aircraft;

transmitting, by the first processor, ~~-~~the new first video and associated new potential targeting coordinate by the first aircraft;

receiving, by the second processor the new first video on the first display in communication with the second processor, the second processor also receiving the new potential targeting coordinate;

selecting, by the second processor, the new potential targeting coordinate to be a new actual targeting coordinate for a third aircraft in response to viewing the new first video on the first display; and

guiding, by a second processor, ~~-~~the third aircraft toward the new actual targeting coordinate, the third aircraft comprising a fourth processor;

wherein positive identification of a new target corresponding to the new actual targeting coordinate is maintained from selection of the new actual targeting coordinate.

~~10.~~9. The method of claim ~~1~~8, wherein the selected potential targeting coordinate is a geographical coordinate corresponding to a center field of view (CFOV) of the captured new first video.

~~11. The method of claim 1, wherein the selected potential targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the captured new first video.~~

~~12.~~10. A method, comprising:

receiving, by a ground control system (GCS)~~,~~ comprising a first processor, a first video stream from a first aircraft and a potential targeting coordinate related to the first video stream , the first aircraft comprising a second processor and configured to transmit the first video stream; ~~;~~

selecting, by the GCS, the potential targeting coordinate corresponding to a target as an actual targeting coordinate, wherein the selected actual targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the received first video stream;

receiving, by the GCS, a second video stream from a second aircraft, the second aircraft comprising a third processor and configured to transmit the second video stream; and

guiding, by the GCS, the second aircraft towards the actual targeting coordinate;

wherein a positive identification ~~of the target~~ is ~~maintained~~ executed, by the second processor of the GCS ~~from selection~~ , based on the target being identified in both a field of ~~the actual targeting coordinate.~~ view (FOV) of the received first video stream and a FOV of the received second video stream simultaneously; and

controlling, by the second processor of the GCS, the second aircraft to impact the target while maintaining the positive identification.

~~13.~~11. The method of claim ~~12~~10, further comprising:

selecting, by the GCS, a terminal homing mode on the target by the second aircraft.

~~14.~~12. The method of claim ~~13~~11, wherein the terminal homing mode comprises at least one of: impacting the target by the second aircraft, impacting the target by a payload deployed by the second aircraft, and impacting the target by a marker deployed by the second aircraft.

~~15.~~13. The method of claim ~~14~~12, further comprising:

confirming, via the GCS, a condition of the target after impact via the received first video stream from the first aircraft.

~~16.~~14. The method of claim ~~15~~13, further comprising:

selecting, by the GCS, a new potential targeting coordinate corresponding to a new target as a new actual targeting coordinate;

receiving, by the GCS, a third video stream from a third aircraft, the third aircraft comprising a fourth processor and configured to transmit the third video stream; and

guiding, by the GCS, the third aircraft towards the new actual targeting coordinate;

wherein positive identification of the new target corresponding to the new actual targeting coordinate is maintained from selection of the new actual targeting coordinate.

~~17.~~15. The method of claim 10~~2~~, wherein the selected potential targeting coordinate is a geographical coordinate corresponding to a center field of view (CFOV) of the received first video stream.

~~18. The method of claim 12, wherein the selected potential targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the received first video stream.~~

~~19.~~16. A system comprising:

a first aircraft, the first aircraft comprising a first processor and configured to transmit a first video stream and a potential targeting coordinate related to the first video stream;

a second aircraft, the second aircraft comprising a second processor and configured to transmit a second video stream;

a first ground control system (GCS), the first GCS comprising a third processor, and wherein the first GCS is configured to guide the first aircraft; and

a second ground control system (GCS), the second GCS comprising a fourth processor, and wherein the second GCS is configured to:

receive the first video stream, the potential targeting coordinate related to the first video stream~~, and the second video stream~~;

select the potential targeting coordinate corresponding to a target as an actual targeting coordinate

, wherein the selected actual targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the received first video stream;

~~; and~~

guide the second aircraft towards the actual targeting coordinate;

wherein a positive identification ~~of~~ is executed based on the target ~~is maintained by~~ being identified in both the first video stream and the second ~~GCS from selection of the actual targeting coordinate.~~ video stream simultaneously; and

control the second aircraft to impact the target while maintaining positive identification.

~~20.~~17. The system of claim ~~19~~ 16 wherein the first GCS is further configured to receive the first video stream.

~~21.~~18. The system of claim ~~20~~ 17 wherein the first GCS further comprises a first digital data link (DDL) to guide the first aircraft and receive the first video stream.

~~22.~~19. The system of claim ~~21~~ 18 wherein the second GCS further comprises a second DDL to receive the first video stream, the potential targeting coordinate related to the first video stream, and the second video stream, and guide the second aircraft towards the actual targeting coordinate.

~~23.~~20. The system of claim ~~19~~ 16 wherein the selected potential targeting coordinate is a geographical coordinate corresponding to ~~at least one of:~~ a center field of view (CFOV) of the first video stream~~, and a pixel in the field of view (FOV) of the first video stream~~.

~~24.~~21. The system of claim ~~19~~ 16 wherein the second GCS further comprises a graphical user interface (GUI) in communication with the fourth processor, and wherein the GUI is configured to display the first video stream and the second video stream.

~~25.~~22. The system of claim 2~~1~~4 wherein the GUI of the second GCS is further configured to display a map having a location of the first aircraft, a location of the second aircraft, a CFOV of the first video stream of the first aircraft, and a CFOV of the second video stream of the second aircraft.

~~26.~~23. The system of claim ~~25~~ 22 wherein the second GCS is further configured to:

select a terminal homing mode on the target by the second aircraft, wherein the terminal homing mode comprises at least one of: impacting the target by the second aircraft, impacting the target by a payload deployed by the second aircraft, and impacting the target by a marker deployed by the second aircraft; and

confirm a condition of the target after impact via the received first video stream from the first aircraft.

~~27.~~24. A method, comprising:

receiving, by a ground control system (GCS)~~,~~ comprising a first processor, a first video stream from a first aircraft and a potential targeting coordinate related to the first video stream~~;~~, the first aircraft comprising a second processor and configured to transmit the first video stream;

selecting, by the GCS, the potential targeting coordinate corresponding to a target as an actual targeting coordinate, wherein the selected actual targeting coordinate is a geographical coordinate corresponding to a pixel in the field of view (FOV) of the received first video stream;

receiving, by the GCS, a second video stream from a second aircraft of a plurality of aircraft, wherein the second aircraft of the plurality of aircraft is closest to the actual

targeting coordinate~~;~~ , the second aircraft comprising a third processor and configured to transmit the second video stream;

guiding, by the GCS, the second aircraft of the plurality of aircraft towards the actual targeting coordinate;

wherein a positive identification ~~of the target~~ is ~~maintained~~ executed, by the GCS ~~from selection of~~ , based on the target being identified in both the ~~actual targeting coordinate.~~first video stream and the second video stream simultaneously; and

controlling, by the GCS, the second aircraft to impact the target while maintaining the positive identification.

~~the actual targeting coordinate.~~

~~28.~~25. The method of claim ~~27~~24, further comprising:

selecting, by the GCS, a terminal homing mode on the target by the second aircraft.

~~29.~~26. The method of claim ~~28~~25, wherein the terminal homing mode comprises at least one of: impacting the target by the second aircraft, impacting the target by a payload deployed by the second aircraft, and impacting the target by a marker deployed by the second aircraft.

~~30.~~27. The method of claim ~~29~~26, further comprising:

confirming, via the GCS, a condition of the target after impact via the received first video stream from the first aircraft.

~~31.~~28. The method of claim ~~30~~27, further comprising:

guiding, by the GCS, a third aircraft of the plurality of aircraft towards the actual targeting coordinate.

~~32.~~29. The method of claim ~~27~~24, wherein the plurality of aircraft loiter about a pre-set area until the actual targeting coordinate is selected.

~~33.~~30. The method of claim ~~32~~29, wherein each aircraft of the plurality of aircraft follows the guided second aircraft towards the actual targeting coordinate and is spaced apart by a set time.