

PATENT
97-009 SGSPECIFICATIONEDGE CONNECTOR FOR A PRINTED CIRCUIT BOARDField of the Invention

5 This invention generally relates to the art of electrical connectors and, particularly, to a high density edge connector for a printed circuit board.

Background of the Invention

10 A popular type of electrical connector which is used widely in the electronic industry is called an "edge card" connector. An edge connector receives a printed circuit board having a mating edge and a plurality of contact pads adjacent the edge. Such edge connectors have an elongate housing defining an elongate receptacle or slot for receiving the mating edge of the printed circuit board.

15 A plurality of terminals are spaced along one or both sides of the slot for engaging the contact pads adjacent the mating edge of the board. In many applications, such edge connectors are mounted on a second printed circuit board. The mating edge board or card commonly is called the

20 "daughter" board, and the board to which the connector is mounted commonly is called the "mother" board.

25 One of the problems with edge connectors of the character described above centers around the ever-increasing demands for high density electronic circuitry. The terminals of such a connector are mounted in a housing fabricated of dielectric material such as plastic or the like. Not only are the terminals becoming ever-increasingly miniaturized, but their density within the housing is becoming greater and greater. The terminals are mounted in

30 rows along the slot of the housing, with the terminals being separated by a dielectric partition or wall integral with the housing.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN REPLACED

In order to increase the density of terminals in edge connectors, it has become known to design the connector as a bi-level connector. In such bi-level connectors, terminals are provided with contact portions that contact the daughter printed circuit board at two locations or at two levels relative to the mating edge of the board. Often, the different terminals are in an alternating arrangement along the length of the card-receiving slot in the connector housing and may be in two rows along opposite sides of the slot.

The problems outlined above are further complicated when certain features, parameters or characteristics are desired to be incorporated in the array of terminals along the edge card slot. For instance, it may be desirable to provide all of the terminals with equal electrical path lengths regardless of the particular shape of the terminals. It usually is desirable for the tips of the tail portions of all of the terminals to be generally coplanar. It also may be desirable to have the tail portions of the terminals staggered in at least two rows along the length of the connector in order to increase the density of the "footprint" of circuit traces, pads or holes on or in the mother printed circuit board. Finally, it may be desirable for each of the terminals to exert an equal force on the daughter printed circuit board.

This invention is directed to improvements in such edge connectors, particularly in the structural relationship between the dielectric housing and the terminals, including improvements directed to solving the above problems.

Summary of the Invention

An object, therefore, of the invention is to provide a new and improved edge connector for a printed circuit board.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

In particular, the invention is directed to applications wherein the printed circuit board has a mating edge and a plurality of contact pads on one or both opposite sides of the board adjacent the edge.

5 In the exemplary embodiment of the invention, the edge connector includes an elongate dielectric housing having a board-receiving face. An elongated slot is disposed in the board-receiving face generally along a longitudinal axis of the housing for receiving the edge of
10 the printed circuit board. A plurality of terminal-receiving cavities are spaced along at least the one side of the slot separated by transverse walls extending generally perpendicular to the longitudinal axis of the housing. Each cavity has a preload rib extending across the cavity
15 between a pair of the transverse walls generally adjacent the board receiving face. The cavities are also disposed between longitudinal side walls of the housing. One of a plurality of first and second terminals are received in each of the terminal-receiving cavities. Each of the first
20 terminals includes a generally planar base portion having a retention section press-fit between the transverse walls of its respective cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an opposite end of the base portion. The
25 resilient spring arm has a first elongated section extending upward from the base at an acute angle thereto, a second curved contact section extending from the first section and within the slot, a third section extending from the second contact section and at an obtuse angle relative
30 to the first section, and a distal end including a preload arm positioned against one of the preload ribs and above the contact section. Each of the second terminals includes a generally planar base portion having a retention section press-fit between the transverse walls of its respective
35 cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an



opposite end of the base portion. The resilient spring arm has a first generally horizontal section extending generally perpendicularly the base, a second generally vertical section extending generally perpendicularly from the first section and offset from the plane of the base , a third elongated section extending upward from the second section at an acute angle thereto, a fourth curved contact section extending from the third section and within the slot, a fifth section extending from the fourth contact section and at an obtuse angle relative to the third section, and a distal end including a preload arm positioned against one of the preload ribs and above the contact section.

Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

This Sheet Has Been Replaced



Brief Description of the Drawings

The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a perspective view of an electrical connector for incorporating electrical terminals fabricated according to the invention, in conjunction with a fragmented depiction of an edge of a printed circuit board insertable into the connector;

FIGURE 2 is a fragmented front elevational view of the connector housing;

FIGURE 3 is a fragmented top plan view of the connector housing of Figure 2;

FIGURE 4 is a fragmented bottom plan view of the connector housing of Figure 2;

FIGURE 5 is an enlarged vertical section taken generally along line 5-5 of Figure 1;

FIGURE 6 is a view similar to that of Figure 5, but with the terminals removed;

FIGURE 7 is a vertical section through the housing similar to Figure 6, but of an adjacent pair of terminal-receiving cavities;

FIGURES 8 and 9 are side elevational and plan views, respectively, of one of the two different shapes of terminals;

FIGURES 10 and 11 are side elevational and plan views, respectively, of the second shape of terminals;

FIGURE 12 is a fragmented perspective view of an elongate strip of electrical terminals still interconnected by the main carrier strip and the mid-carrier strip;

This Sheet Has Been Replaced



FIGURE 13 is a plan view of the elongate strip of terminals after just the stamping step and prior to being formed into the configuration of Figure 12;

5 FIGURE 14 is a plan view of the stamped and formed strip of terminals as shown in Figure 12;

FIGURE 15 is a side elevational view of the elongate strip of terminals in Figure 14;

10 FIGURES 16A-16C are schematic illustrations of processes during the fabrication and subsequent use of the elongate strip of terminals;

FIGURE 17 is an enlarged vertical section similar to Figure 5 showing an alternate embodiment of the connector housing;

15 FIGURE 18 is an enlarged fragmented bottom plan view of a portion of the connector housing showing a plurality of terminal receiving cavities and one cavity modified as shown in Figure 17;

20 FIGURE 19 is an enlarged vertical section similar to Figure 5 showing still another alternate embodiment of the connector housing; and

FIGURE 20 is an enlarged vertical section taken generally along line 20-20 of Figure 4.

This Sheet Has Been Replaced



Detailed Description of the Preferred Embodiment

Referring to the drawings in greater detail, and first to Figures 1-4, an elongated electrical connector, generally designated 20, of the edge card type is shown. The connector is typical of this type of electrical connector in that it includes a unitarily molded, elongate housing 22 defining a board-mounting or terminating face 22a and a board-receiving face 22b. The board-receiving face 22b includes an elongate receptacle or card slot 24 for receiving a mating edge 26 of a printed circuit board 28. A plurality of terminals (described hereinafter) are spaced along both sides of slot 24 for engaging contact pads 30a and 30b adjacent mating edge 26 on both sides of printed circuit board 28. It can be seen that contact pads 30a and 30b are in two rows, with the row of contact pads 30b being closer to edge 26 than the row of contact pads 30a. Each of the rows 30a and 30b is generally parallel to mating edge 26. Lastly, a polarizing rib 32 spans slot 24 for insertion into a polarizing notch 34 in edge 26 of the printed circuit board to ensure the board is properly oriented endwise within the slot relative to the elongate connector.

In many applications, edge card connectors, such as connector 20, are mounted on a second printed circuit board. The mating circuit board 28 commonly is called the "daughter" board, and the board 29 (Fig. 5) to which the connector is mounted commonly is called the "mother" board. Connector 20 is of this type and includes three boardlocks 35 for insertion into appropriate mounting holes in the mother board. A plurality of standoffs 36 project downwardly from board-mounting face 22a of housing 22 a predetermined distance to space the housing from the mother board upon placement thereon.

Figures 1 and 3 best show that elongate housing 22 of connector 20 has two rows of terminal-receiving cavities or passages extending lengthwise of the housing



generally parallel to the longitudinal axis of the housing, one on each of opposite sides of card slot 24. Each row includes an alternating series of differently shaped first and second cavities 38a and 38b. In addition, the shapes within one row are offset relative to the other row by the distance between adjacent cavities. As a result, each first cavity 38a has a differently shaped second cavity 38b on both sides of it within its row and as well as an additional second cavity 38b laterally across card slot 24 in the other row of cavities.

More particularly, referring to Figures 5-7 in conjunction with Figures 1-4, housing 22 includes a series of the pairs of first and second cavities 38a and 38b with one pair of the cavities shown in each of Figures 5, 6 and 7. Figures 5 and 6 show first cavity 38a on the left-hand side of slot 24 with second cavity 38b on the right-hand side of the slot. Conversely, Figure 7 shows one of the first cavities 38a on the right-hand side of slot 24, whereas second cavity 38b is shown on the left-hand side of the slot. These depictions in the drawings illustrate that the first and second cavities 38a and 38b alternate lengthwise of the connector housing on opposite sides of the slot. All of the adjacent cavities in each row thereof are separated lengthwise along the housing by transverse walls 40.

Still referring to Figures 5-7, a reinforcing rib 42 is disposed in the lower half of the housing separating the two cavities 38a and 38b in each pair thereof. The reinforcing ribs 42 not only separate the cavities, but also span the cavities and are integrally molded between transverse walls 40 to provide support for the walls and allow the walls to be molded as thin as possible, thereby enhancing the high density nature of the connector. All of the reinforcing ribs between adjacent cavities 38a and 38b are located along a longitudinal centerline "C" of housing 22 (Fig. 3) immediately below slot 24 as can be seen by



5 comparing Figures 6 and 7. Lastly, each reinforcing rib 42 is tapered, as at 44, at its bottom end to provide a camming surface for engaging the terminals and assisting during insertion of the terminals into first and second cavities 38a and 38b, as described hereinafter. Therefore, it can be understood that reinforcing ribs 42 perform a multitude of functions.

10 Each second cavity 38b includes an enlarged recess 46 and an inner press-fit terminal retention slot 48 in each of its transverse walls 40, as well as an upper preloading wall 50, all for different purposes in cooperating with a respective terminal inserted into the cavity. Similarly, each cavity 38a includes an enlarged recess 52 and an outer press-fit terminal retention slot 54 in its transverse walls 40, as well as a preloading wall 56, again for cooperating with a respective terminal inserted into the cavity. It can be seen that preloading wall 56 of cavity 38a is shorter than preloading wall 50 of cavity 38b.

20 A plurality of retention bosses 57 are molded integrally with housing 22 in alignment with terminal-receiving cavities 38b whereby the cavities extend through the retention bosses. Actually, the retention bosses are "split" portions of housing 22 projecting downwardly from transverse walls 40 on opposite sides of terminal-receiving cavities 38b adjacent the lower portions of the retention sections of the terminals received in the cavities as described below. As best seen in Figure 5, the standoffs 36 extend downward from board-mounting face 22a of housing 22 slightly further than retention bosses 57 extend downward. As a result, the retention bosses will not contact printed circuit board 29 when the connector 20 is mounted thereon.

35 As shown in Figures 4 and 20, a recess 39 is located adjacent the opposite ends of the rows of terminal receiving cavities 38a and 38b. In addition, a pair of



recesses 39 are located on opposite sides of center boardlock 35c which is aligned with and positioned below polarizing rib 32. These recesses 39 extend laterally from the longitudinal axis of the housing at least as far as the terminal receiving cavities 38a and 38b, and preferably slightly further. In the vertical direction, they extend in a manner similar to cavities 38a and 38b although they do not extend through board-receiving face 22b of the housing. These recesses 39 provide additional flexibility to the plastic housing at the inner and outer press-fit slots 48 and 54 adjacent the ends of the housing and the center boardlock 35c in order to reduce the likelihood of cracking of the housing. In addition, they also reduce shrinkage of the plastic.

Generally, electrical connector 20 includes a series of simple cantilevered beam terminals along each side of slot 24. The terminals of such series include first and second shapes, generally designated 58a and 58b, respectively, that are inserted into cavities 38a and 38b, respectively, in the direction of arrows "A" (Fig. 5).

More particularly, referring to Figures 8 and 9 in conjunction with Figure 5, first terminal 58a insertable into a respective one of the cavities 38a includes a generally planar base portion 60 having a retention section 62 with outwardly projecting barbs 62a (Fig. 9) on opposite side edges thereof. A tail portion 64 projects from one end 60a of base portion 60 and includes a tapered tip 64a. A resilient spring arm or beam 66 extends from a second, opposite end 60b of the base portion at approximately a 24° angle thereto. The spring arm includes a first generally straight section 66a that extends up to an inwardly bowed contact section 66b, which projects into slot 24 as best seen in Figure 5. Although difficult to see in the drawings, straight section 66a is tapered so it is widest adjacent base 60 and narrowest adjacent contact section 66b. This reduces stress concentrations in the arm 66. A



relatively steep lead-in section 66c is positioned above contact section 66b with a generally vertical upper arm section 66d adjacent the end of arm 66. A generally arcuate transition section 66e extends between lead-in section 66c and upper arm section 66d in order to permit the lead-in section to have its desired angle relative to vertical to provide a low insertion force yet position upper arm section 66d generally vertically to engage preloading wall 56. As best seen in Figure 5, the lead-in section 66c extends from slot 24 slightly into cavity 38c to ensure that the edge 26 of card 28 initially engages lead-in section 66c. Finally, the tip 66f of arm 66 is coined or chamfered to prevent stubbing while inserting the terminal 58a into cavity 38a during the assembly process.

Finally, Figure 9 shows a pair of protrusions 68 at opposite side edges adjacent second end 60b of base portion 60 which are the result of severing the terminal from a mid-carrier strip 82 (described hereinafter). In essence, these protrusions comprise cutoffs of the carrier strip. When each terminal 58a is inserted into its respective cavity 38a, cutoffs 68 are aligned with enlarged recesses 52. The recesses are sufficiently large and deep enough to prevent any interference with the cutoffs and to allow free movement during insertion of the terminal into the housing in the area of the cutoffs.

Referring to Figures 10 and 11 in conjunction with Figure 5, each of the second terminals 58b includes a generally planar base portion 70 having a retention section 72 which includes barbs 72a at opposite side edges thereof. A tail portion 74 projects from one end 70a of base portion 70 and includes a tapered tip 74a. A resilient spring arm or beam extends from a second, opposite end 70b of the base portion 70. The spring arm 76 includes a generally horizontal first section 76a extending from the base at approximately a 90° angle thereto and leads to a generally



vertical second section 76b with an arcuate lower transition section 76c therebetween. A generally straight third section 76d extends from vertical section 76b at approximately a 38° angle thereto and ends in an inwardly bowed contact section 76e. Although difficult to see, such third section is tapered to reduce stress concentrations within the beam. A relatively steep lead-in section 76f extends away from contact section 76e where it intersects with an arcuate upper transition section 76g. As best seen in Figure 5, lead-in section 76f extends from slot 24 slightly into cavity 38b to ensure that the edge 26 of card 28 initially engages lead in-section 76f. A generally vertical upper arm 76h for engaging preload wall 50 extends upwardly from upper transition section 76g and ends in curved or arcuate tip 76i. The curved tip minimizes the likelihood of stubbing of the terminal while inserting the terminal 58b into cavity 38b during the assembly process.

Somewhat similar to first terminal 58a, each second terminal 58b also includes mid-carrier cutoffs 78 which become located between enlarged recesses 46 of the respective cavity. The recesses 46 are sufficiently large and deep to allow for free movement of horizontal section 76a and vertical section 76b relative to the housing both during insertion of the terminal into the housing as well as operatively when fully inserted therein and a daughter printed circuit board 28 is inserted into slot 24.

In comparing Figures 6 and 7, it can be seen that housing 22 has side walls 22c and 22d bounding the outsides of cavities 38a and 38b. Since the cavities 38a and 38b alternate along the length of housing 22, the thickness of side walls 22c and 22d also alternate along the length of the housing. The thicker portion of the side walls 22c and 22d is designated 80a and associated with cavity 38a while the thinner portion is designated 80b and associated with cavity 38b. The thickened portion 80a of the side wall provides additional support for transverse walls 40 of



cavity 38a as the retention section of terminal 58a is press-fit into slots 54 in the transverse walls. In fact, it can be seen in Figures 6 and 7 that press-fit slots 54 are located immediately adjacent the thickened portions 80a of the side walls. As such, it can be seen in Figure 5 that base 60 of first terminal 58a is next to and supported by the thicker portion 80a of the side wall on one side. This assists in preventing movement of any portion of the terminal except spring arm 66.

Figures 17 and 18 show an alternate embodiment wherein a modified first cavity 38a' extends slightly further into sidewall 22c as compared to an unmodified first cavity 38a. This provides additional flexibility at the end of transverse wall 40 adjacent side wall 22c'. The extension 59' of cavity 38a' can best be seen in Figure 18 wherein a second cavity 38b is shown between a modified first cavity 38a' and an unmodified first cavity 38a. The width of the extension 59' between transverse walls 40 is less than the width of the main portion of cavity 38a'. In the alternative, as shown in Figure 19, the extension 59'' could be widened so that the width between the transverse walls 40 is uniform throughout cavity 38a'', including extension 59''. In either case, since the width of the extension 59'' is still less than the distance across cutoffs 68, terminal 58a is still supported along base 60 to prevent outward deflection thereof.

It can be seen in Figure 5 that the tips 64a of tail portions 64 of terminals 58a and the tips 74a of tail portions 74 of terminals 38b all substantially lie in a common plane generally parallel to the mother board 29. In use, all of the tails will be inserted into holes in the mother board and, generally, the circuit traces on the mother board are generally coplanar. It is desirable to have the electrical paths through both shapes of terminals 58a and 58b be of equal lengths, while still having the terminals engage the contact pads 30a and 30b (Fig. 1)



along edge 26 of printed circuit board 28 at two different levels, as described above. It can be seen that contact sections 66b of terminals 38a engage contact pads 30a at a different level than contact sections 76e of terminals 58b. This permits an increase in density of the terminals without substantially increasing the insertion forces. Although the contact sections 76e of terminals 58b are closer vertically to mother board 29 than the contact sections 66b of terminals 58b, the electrical paths through the terminals between the contact sections and the tips of the tails are substantially equal. In addition, the specific shapes of the spring arms of terminals 58a and 58b provide for substantially similar normal forces on contact pads 30a and 30b since the spring arms have substantially similar spring rates and are deflected equal amounts.

During assembly, the terminals 58a and 58b are inserted into their respective cavities 38a and 38b from the bottom or terminating face 22a of the housing. As the terminals enter their respective cavities, their respective contact section 66b and 76e initially contact the tapered lower portion 44 of center reinforcing rib 42 that separates the two cavities 38a and 38b. The contact sections 66b and 76e slide along the center rib 42 until they reach slot 24. A tool (not shown) generally shaped like edge card 28 is positioned within slot 24 in order to further deflect the contact arms 66 and 76 of the two terminals 58a and 58b. By engaging this tool, the generally vertical upper arms 66d and 76h of the two terminals are properly positioned so that they will slide behind their respective preloading walls 56 and 50.

As the terminals are inserted into their respective cavities, their respective cutoffs 68 and 78 enter recesses 52 and 46. Since the distance between the recesses 52 in the transverse walls 40 on opposite sides of cavity 38a is greater than the width across cutoffs 68, the cutoffs 68 do not bind or engage the recesses during



insertion. Likewise, the distance between transverse walls 40 at recesses 46 is larger than the distance across cutoffs 78 so that the cutoffs 78 also do not bind or engage the walls of the recesses during insertion of the second terminals 58b. As the first terminal 58a is inserted into its final position, retention section 62, including barbs 62a, are press-fit into outer retention slot 54 (Fig. 6). During such insertion, the barbs 62a skive or dig into the side walls of the slot 54 to retain the terminal within the housing. Likewise, during insertion of second terminal 58b, the retention section 72, including barbs 72a, are press-fit into inner retention slot 48. During such insertion, the barbs 72a also skive or dig into the side walls of slot 48 to retain the terminal 58b within the housing.

Figure 12 shows the different shapes of terminals 58a and 58b after fabrication and as integral components of a stamped and formed elongate strip of electrical terminals, generally designated 81. First and second terminals 58a and 58b, respectively, alternate lengthwise of elongate strip 81. The series of alternating terminals are joined by a mid-carrier strip 82 and a second carrier strip 84.

Still referring to Figure 12, mid-carrier strip 82 joins first and second terminals 58a and 58b, respectively, at the base portions 60 of the first terminals 58a and the vertical sections 76b of the spring arm 76 of the second terminals 58b. This mid-carrier strip 82 facilitates forming of the lower portion of second terminals 58b, as described in greater detail below.

Second carrier strip 84 is used in a conventional manner to index the strip of terminals through appropriate processing machines. To that end, carrier strip 84 includes a plurality of indexing holes 86 as is known in the art. It should be noted that carrier strip 84 interconnects only alternating ones of the tail portions of the



terminals, namely, tail portions 64 of each of first terminals 58a.

Figure 13 shows the stamping step in the method of fabricating elongate strip 81 (Fig. 12) of electrical terminals 58a and 58b prior to forming such terminals. In particular, Figure 13 shows a flat blank "B" which has been stamped of sheet metal material. The flat outline of terminals 58a and 58b can be seen in Figure 13, before the terminals are formed, and with the terminals alternating along the elongate strip and joined by mid-carrier strip 82 and second carrier strip 84. This view clearly shows how the second carrier strip is joined to the tips 64a of tail portions 64 of only the first shape of terminals 58a. This allows the portions of terminals 58b below the mid-carrier strip 82 to move freely during the forming operation relative to the second carrier strip 84.

Figure 14 shows the elongate strip 81 of Figure 13 after it has been fully formed. In essence, Figures 14 and 15 correspond to the perspective view of Figure 12. In particular, blank "B" (Fig. 13) is shaped by appropriate forming processes to define the configurations of spring contact portion 66 of terminals 58a and spring contact portion 76 of terminals 58b as well as base 70 and tail 74 of terminals 58b. Figure 15 clearly shows how the forming of terminals 58b is effective to bring the tips 74a of tail portions 74 into substantially the same plane as the tips 64a of tail portions 64 of terminals 58b. In essence, the vertical distance that tail portions 74 of terminals 58b extend from mid-carrier strip 82 has been shortened because the portions of terminals 58b below the mid-carrier strip are formed relative to second carrier strip 84. Figures 12 and 15 clearly show how this forming step is effective to move retention sections 72 and tail portions 74 of terminals 58b out of the plane of retention sections 62 and tail portions 64 of terminals 58a.



Prior to inserting the terminals into their respective cavities 38a and 38b, mid-carrier strip 82 is severed. This severing step creates cutoffs 68 and 78. Rather than having to perform a relatively expensive "deburring" process to remove cutoffs 68 and 78, the recesses 46 and 52 of the housing 22 are dimensioned so that recesses 46 and 52 freely accept the protruding cutoffs whereby the cutoffs do not interfere with either insertion of the terminals into their respective cavities or movement of spring contact portion 76 of terminals 58b once they are fully inserted. Eventually, either prior to or after insertion of the terminals into their respective cavities, main carrier strip 84 is severed, as at 90 in Figure 14, to remove the carrier strip from terminals 58a.

As stated above, retention bosses 57 are molded integrally with housing 22 in alignment with terminal-receiving passages 38b, and the retention bosses actually are "split" portions of housing 22 on opposite sides of terminal-receiving cavities 38b adjacent lower portions of retention sections 72 of terminals 58b. In other words, in order to minimize the vertical amount of housing above board-mounting face 22a utilized to retain terminals 58b (which maximizes the vertical height usable for the contact beam 76 of the terminal 58b), retention bosses 57 extend downward below board-mounting face 22a in order to provide additional material to retain the terminals within the housing. At least portions of the retention sections of terminals 58b may be located in the passages through "split" retention bosses 57. In essence, this enables the retention sections of terminals 58b to project downwardly below bottom board-mounting face 22a of the housing and still be surrounded by sufficient plastic material of the housing to effect a retention function for the terminals between the retention sections and the housing. As a result, a longer portion of terminals 58b may be used for the spring contact portions 76. This concept is more fully



disclosed in U.S. Patent No. 5,378,175, issued January 3, 1995 and assigned to the assignee of the present invention. Of course, it should be understood that, in spite of the different shapes of terminals 58a and 58b, the electrical path lengths from the contact portions to the tails of the terminals are substantially the same.

Lastly, Figures 16A-16B show how elongate strip 81 of terminals 58a and 58b (shown in Figures 12, 14 and 15) comprise an article of manufacture for subsequent operations and/or use. In particular, Figure 16A shows strip 81 leaving a die 92 after the final step of stamping and forming the strip into the configuration of Figure 12. The strip is wound onto a reel 94 in the direction of arrow "B" for subsequent processing steps. Figure 16B shows strip 80 being wound off of reel 94 in the direction of arrow "C" to a plating station 96 whereat certain portions, such as the contact sections of the terminals, are plated with highly conductive material, such as gold. The plated strip then is fed in the direction of arrow "D" onto a second reel 98. This plating operation normally takes place at a different location than the stamping and forming operations as represented by die 92 in Figure 16A. In fact, the plating operation may take place in different buildings from the stamping and forming operations. Reel 98, with plated strip 81 wound thereon, then may be shipped to a further location as indicated by Figure 16C where the strip is unwound from reel 98 in the direction of arrow "E" for further use. For instance, the strip may be unwound at its final destination for inserting terminals 58a and 58b into connector housing 22 of connector 20, as described above.

THIS SHEET HAS BEEN
REPLACED

This Sheet Has Been Replaced



It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

5

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

CLAIMS

1. A push-pull edge card electrical connector for receiving an edge of a printed circuit board having conductive contact pads on at least one side of the board adjacent the edge, comprising:

an elongated dielectric housing including
a board-receiving face,

an elongated slot disposed in the board-receiving face generally along a longitudinal axis of the housing for receiving said edge of the printed circuit board, and

a plurality of terminal-receiving cavities spaced along at least said one side of the slot separated by transverse walls extending generally perpendicular to the longitudinal axis of the housing, each cavity having a preload rib extending across said cavity between a pair of said transverse walls generally adjacent said board receiving face and immediately adjacent said slot, said cavities being disposed between longitudinal side walls of the housing; and

a plurality of first and second terminals, each terminal being received in one of said terminal-receiving cavities,

each of said first terminals including a generally planar base portion having a retention section press-fit between the transverse walls of its respective cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an opposite end of the base portion, the resilient spring arm having a first elongated section extending upward from said base at an acute angle thereto, a second curved contact section extending from said first section and within said slot, a third section extending from said second contact section and at an obtuse angle relative to said first section, a distal end including a preload arm positioned against one of said preload ribs and above said contact section; and





each of said second terminals including a generally planar base portion having a retention section press-fit between the transverse walls of its respective cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an opposite end of the base portion, the resilient spring arm having a first generally horizontal section extending generally perpendicularly from said base, a second generally vertical section extending generally perpendicularly from said first section and offset from the plane of said base, a third elongated section extending upward from said second section at an acute angle thereto, a fourth curved contact section extending from said third section and within said slot, a fifth section extending from said fourth contact section and at an obtuse angle relative to said third section, and a distal end including a preload arm positioned against one of said preload ribs and above said contact section.

2. The push-pull electrical connector of claim 1 wherein said distal end of the spring arm of each said second terminal is generally S-shaped.

3. The push-pull electrical connector of claim 1 wherein said first section of said first terminals and said third section of said second terminals are tapered.

4. The push-pull electrical connector of claim 1 wherein said third section of said second terminals extends into the slot and through the plane of said base.

5. The push-pull electrical connector of claim 1 wherein said distal end of said second terminals includes a sixth curved transition section extending from said fifth section to said preload arm.





6. An edge card electrical connector for receiving an edge of a printed circuit board having contact pads on opposite sides of the board adjacent the edge and having a predetermined thickness, comprising:

5 an elongated dielectric housing including
 a board-receiving face,

 an elongated slot disposed in the board-receiving face generally along a longitudinal axis of the housing for receiving said edge of the printed circuit board, and

10 a plurality of pairs of transversely spaced apart first and second terminal-receiving cavities for receiving respective ones of a pair of first and second terminals engageable with the contact pads on opposite sides of the printed circuit board and defining first and second rows of
15 alternating first and second cavities lengthwise of the housing, the first cavity of each pair being located on an opposite side of the slot from said second cavity, the first and second cavities within each row being separated by transverse walls extending generally perpendicular to
20 the longitudinal axis of the housing, each cavity having a preload rib extending across said cavity between a pair of said transverse walls generally adjacent said board receivingface, said cavities being disposed between longitudinal side walls of the housing;

25 a plurality of first and second terminals, one of said first terminals being received in each of said first terminal-receiving cavities, and one of said second terminals being received in each of said second terminal-receiving cavities, each of said first terminals facing one of
30 said second terminals,

 each of said first terminals including a generally planar base portion having a retention section press-fit between the transverse walls of its respective cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an opposite end
35 of the base portion, the resilient spring arm having a





first elongated section extending upward from said base at an acute angle thereto, a second curved contact section extending from said first section and within said slot, a third section extending from said second contact section and at an obtuse angle relative to said first section, a distal end including a preload arm positioned against one of said preload ribs and above said contact section, each of said contact sections being movable between a first position prior to insertion of said printed circuit board and a second, deflected position in which said printed circuit board is fully inserted into said slot; and

each of said second terminals including a generally planar base portion having a retention section press-fit between the transverse walls of its respective cavity, a tail portion projecting from one end of the base portion and a resilient spring arm extending from an opposite end of the base portion, the resilient spring arm having a first generally horizontal section extending generally perpendicularly from said base, a second generally vertical section extending generally perpendicularly from said first section and offset from the plane of said base, a third elongated section extending upward from said second section at an acute angle thereto, a fourth curved contact section extending from said third section and within said slot, a fifth section extending from said fourth contact section and at an obtuse angle relative to said third section, and a distal end including a preload arm positioned against one of said preload ribs and above said contact section;

each of said curved contact sections of said terminals being movable between a first position prior to insertion of said printed circuit board and a second, deflected position in which said printed circuit board is fully inserted into said slot, at least a portion of the curved contact sections of said first and second terminals being positioned within the slot when positioned at said first position, whereby upon inserting a printed circuit





board into said slot, said contact pads of said printed circuit board slidably engage said curved contact sections of said terminals.

5 7. The edge card electrical connector of claim 6 wherein said distal end of the spring arm of each said second terminal is generally S-shaped.

8. The edge card electrical connector of claim 6 wherein said first section of said first terminals and said third section of said second terminals are tapered.

10 9. The edge card electrical connector of claim 6 wherein said third section of said second terminals extends into the slot and through the plane of said base.

15 10. The edge card electrical connector of claim 6 wherein said distal end of said second terminals includes a sixth curved transition section extending from said fifth section to said preload arm.

