

Description

This invention relates to stamped and formed terminals for mounting on a circuit board.

It is common manufacturing practice in the electrical industry to mount terminals on circuit boards by means of mounting legs which are dimensioned to be received in circular holes in the circuit board as described in U.S. 3,845,455. The mounting legs are usually, but not always, soldered to conductors on the circuit board after insertion. In the manufacture of circuit boards having terminals thereon, the terminals may be inserted by machinery or manually at one work station and are usually handled and transported at a later time to other work stations for subsequent operations such as soldering of the terminals to the circuit board conductors. It is important, therefore, that the mounting legs be capable of holding the terminals on the circuit board prior to soldering with sufficient security to prevent their being removed prior to the soldering operation and during all handling subsequent to insertion.

The mounting legs for terminals, in accordance with known practice, may be dimensioned to have an interference fit in the circuit board hole or they may be designed to provide a resilient force on the walls of the circuit board hole after they are inserted. Known terminals having mounting legs of these general types are acceptable if the dimensions of the mounting legs and the diameters of the circuit board holes are such that the terminals are retained in the holes. However, if the circuit board holes are oversized relative to the dimensions of the mounting legs on the terminals, frequent problems are encountered in that the terminals tend to fall from the mounting holes. Manufacturers of electrical equipment are frequently troubled by such problems for the reason that they usually obtain their circuit boards from a remote source and they have limited control over the manufacture of the circuit boards. A manufacturer of electrical equipment must, therefore, frequently solve problems involving oversized circuit board holes and resulting in securely placed terminals on a circuit board by the use of added manpower and reworking and inspection of the circuit boards immediately prior to soldering.

It would be desirable to improve presently available mounting legs for terminals in a way which would permit the use of the mounting legs in circuit board holes of varying diameters beyond the variations in hole diameters which are acceptable for presently available mounting means on terminals and thereby avoid problems as discussed above, which are presently being encountered.

We have disclosed in US-A-4261629 a stamped and formed sheet metal terminal intended for mounting in a circular hole in a circuit board, the terminal having first and second mounting legs which are received in the hole to

retain the terminal, each of the legs having a retaining portion extending from the terminal partially along its length, the retaining portion having a width sufficient to establish an interference fit in a small diameter circuit board hole.

The present invention is directed to the achievement of improved mounting legs for terminals which can be used in circuit board holes having a range of hole diameters. According to the present invention, a stamped and formed sheet metal terminal intended for mounting in a circular hole in a circuit board has first and second mounting legs which are received in the circuit board hole to retain the terminal on the circuit board. Each of the mounting legs has a retaining portion which extends from the terminal partially along its length, the retaining portion having a width which is sufficient to establish an interference fit into a small diameter circuit board hole. The legs are characterized in that each leg has a reduced width portion between the retaining portions and the free ends of the legs.

Each of the legs also has camming means on the reduced width portions and each of the legs has cam actuator means which are cooperable with the wall of the circuit board hole to cause the camming means to in turn cause movement of the legs away from each other during movement of the legs into the circuit board hole whereby, the legs can easily be inserted into the circuit board hole by reason of the reduced width portions, and during movement of the legs into said circuit board hole, the legs will be moved apart by the camming means and the retaining portions will establish an interference fit in the circuit board hole and retain the terminal on said circuit board.

An embodiment of the invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 is a perspective view of a terminal in accordance with the invention, the terminal being shown as exploded from a circuit board and in alignment with a hole in the circuit board.

Figure 2 is a view similar to Figure 1 showing the terminal mounted on a circuit board.

Figures 3—9 are a series of views illustrating the movement of mounting legs of the terminal into a circuit board hole of a minimum diameter.

Figure 3 shows the legs in alignment with the circuit board hole prior to insertion.

Figure 4 is a cross-sectional view taken along the lines 4—4 of Figure 3.

Figure 5 is a view similar to Figure 3 showing the legs partially inserted into the circuit board hole, this view being taken along the lines 5—5 of Figure 6.

Figure 6 is a view taken along the lines 6—6 of Figure 5.

Figure 7 is a view showing the legs in their fully inserted positions.

Figure 8 is a view taken along the lines 8—8 of Figure 7.

Figure 9 is a view taken along the lines 9—9 of Figure 8.

Figure 10 is a view similar to Figure 8 showing the manner in which the legs are retained in a relatively large diameter circuit board hole.

Figure 11 is a graphical representation of the retention force of the mounting legs of a terminal in accordance with the invention, as compared with one known retaining means for terminals.

Figure 1 shows a stamped and formed sheet metal terminal 2 having mounting means on its lower end for mounting the terminal on the circuit board such that the terminal can be soldered to conductors 6 on the underside of the circuit board 8. The terminal 2, except for its mounting legs, is in accordance with U.S. 4,261,629.

The terminal 2 comprises opposed inner platelike members 10, 10' and outer platelike members 12, 12' which are connected to the inner platelike members by reverse bends or bights 16, 16'. The inner platelike members 10, 10' are connected to each other by an integral bight 14 and the outer platelike members 12, 12' are inwardly turned at their lower ends as shown at 20, 20'. The mounting means comprises first and second mounting legs 22, 22' which extend downwardly from the inwardly turned portions 20, 20'. When the terminal is to be mounted on the circuit board 8, the legs 22, 22' are moved relatively towards each other and are then inserted into the circuit board hole 9. After soldering of the lower ends of the legs to the conductors 6, a wire 4 can be moved into the slots 18, 18' of the platelike members 10, 12, and 10' and 12' so that the edges of these slots will penetrate the insulation of the wire and contact the conducting core of the wire.

The legs 22, 22' are similar but are not identical to each other and the same reference numerals differentiated by prime marks are therefore used to identify corresponding structural features of the two legs.

Each leg has a retaining portion 24, 24' which is adjacent to the portions 20, 20', a cam actuator portion 26, 26' which adjoins the retaining portions 24, 24' and camming and guiding portions 28, 28' which extend to the free ends 30, 30' of the legs. The legs have opposed surfaces 36, 36' and first and second side edges on each side of the opposed surfaces. The side edges of the first leg 22 are indicated at 32 and 34 and the first and second side edges of the second leg 22' being indicated at 32' and 34'.

The legs are of the same width as measured between the side edges in the retaining portions 24, this width being substantially equal to, and slightly less than, the diameter of the smallest hole for which the device is intended. For example, the retaining portions 24, 24' should have a width of about 1.01 ± 0.05 mm when the smallest hole 9 for which the device is intended, has a diameter of about 1.07 mm. If

the retaining portions have a width of 1.02 mm, the device can be mounted in circuit board holes in the range of about 1.07 mm to 1.27 mm.

The cam actuator sections 26, 26' and the camming and guiding portions 28, 28' of the legs are of a reduced width relative to the retaining portions 24, 24'. As shown best in Figure 1, the first side edge 32 of the first leg 22 is inclined, as shown at 38, inwardly beginning at the lower end of the retaining portion and the first side edge 32 of the first leg 22 is inwardly displaced as shown at 40 in the camming and guiding portion relative to the first side edge 32' of the leg 22'. The second side edge 34' of the second leg 22' slopes inwardly as shown at 38' and in the camming and guiding portion, this second side edge of leg 22' is inwardly displaced as shown at 40' relative to the second side edge 34 of the first leg 22. The width of the legs in the camming and guiding sections 28, 28' should be such that the legs will move freely into the smallest diameter hole for which the device is intended. For example, this width may be 0.76 mm when the terminal is intended for circuit board holes having diameters in the range of 1.07 to 1.27 mm. The opposed surfaces of the legs have camming bosses 46, 46' thereon, located in the camming and guiding portions 28, 28'. These camming bosses have camming surfaces 47, 47' which are approximately parabolic, as shown in Figure 4, and are opposed to each other when the legs are in their normal positions so that when the legs are moved towards each other these surfaces will engage each other. These bosses are formed by indenting the outwardly facing surfaces of the legs 22, 22', as shown in Figure 1 at 50.

Adjacent to the free end 30 of the leg 22, the second side edge 34 is sharply inclined inwardly as shown at 42 to provide a lead-in surface for the terminal when it is inserted into the hole 9. The lower portion of the first side edge 32' of the second leg 22' is similarly inclined inwardly as shown at 42'. The free ends of the legs 30, 30' can also be swaged, as shown at 44, to further facilitate movement of the free ends into the circuit board hole.

The legs 22, 22' are normally opposed to each other as shown in Figures 3 and 4, and their camming and guiding portions 28, 28' overlap so that the total width of both legs is the same as the width of an individual leg 22, 22' in the retaining portions 24, 24'. The legs are, however, capable of limited flexing laterally in their own planes, for reasons which will be explained below and as illustrated in Figure 5.

When the terminal 2 is to be inserted into a circuit board 8, the outer platelike members 12, 12' are flexed inwardly towards the inner platelike members 10, 10' until the surfaces 47, 47' of the cams 46, 46' are against each other as shown in Figure 4. The operation of flexing the terminal in this manner and inserting it into the circuit board hole can be carried out either

manually or by an insertion machine.

After the legs have been brought against each other, they are aligned with the circuit board hole 9 and moved downwardly from the position of Figure 3 to the position of Figure 5. During this downward motion, the inclined lower portions 42, 42' of the second side edge 34 of the first leg and the first side edge 32' of the second leg 22' will engage the edge 11 of the circuit board hole and the legs will be flexed slightly so that their camming and guiding portions 28, 28' coincide, as shown in Figure 5. This flexure of the legs causes their camming and guiding portions to move in opposite directions parallel to their own planes so that the camming surfaces 47, 47' move across each other until the cams 46, 46' are side-by-side, see Figure 6.

Upon further movement of the legs into the circuit board hole, the inclined portions 38, 38' of the first and second legs engage the edge 11 of the circuit board hole thereby causing the legs to be moved back towards their aligned positions. When this movement is completed, the cams 46, 46' will again be brought into opposed aligned positions and the legs will thereby be cammed apart, see Figure 8. As the result, the retaining portions 24, 24' penetrate the circuit board and establish a secure interference fit of these retaining portions in the circuit board hole. The cams 46, 46' serve as a locking means after complete insertion of the terminal and maintain this interference fit in the circuit board hole.

Figures 3—8 illustrate the movement of the legs into a circuit board hole 9 at the lower tolerance limit of the range of circuit board holes for which the legs are intended. Under these circumstances it will be seen from Figure 8, that the corners 52, 52' of the legs penetrate the material of the circuit board relatively deeply. The condition shown in Figure 8 has been observed and this condition will come about if the circuit board is of relatively soft material, for example, if the circuit board is of a paper filled phenolic resin. If the circuit board is of a relatively hard material which is resistant to penetration by the corners 52, 52', the legs may not be fully returned to their aligned positions and may be flexed along their axes to some extent. In this latter event, however, a tight interference fit of the legs in the circuit board hole is nonetheless obtained.

Figure 10 is similar to Figure 8 except that it shows the condition which exists when the legs are inserted into a hole at the upper tolerance limit of the range of hole diameters. The corners 52, 52' do not penetrate the material of the circuit board to the same extent, however, they are wedged tightly in the hole and are maintained in their wedged condition by the cams 46, 46'.

Figure 11 illustrates the advantage obtained in the practice of the invention, as compared with prior art methods of mounting terminals in

circuit boards. The dotted line curve in Figure 11 relates the pushout force, the force in kilograms required to push a terminal out of a circuit board hole after insertion, to the diameter, in millimeters, of the circuit board hole. These data for the dotted line curve were obtained from tests in which the terminal had two legs designed to provide a simple interference fit as shown in U.S. Patent 4,261,629. It can be seen from this dotted line curve that the pushout force drops abruptly within a very narrow band of hole diameters to an unacceptably low level when the hole diameter reaches 1.27 mm. The solid line curve relates the push out force to the hole diameter for a terminal having mounting legs in accordance with the invention. The solid line curve shows that the pushout force drops only very slightly when the hole diameter changes from 1.07 mm to 1.27 mm and satisfactory results are obtained even if the hole is a diameter greater than 1.27 mm.

Claims

1. A stamped and formed sheet metal terminal (2) intended for mounting in a circular hole (9) in a circuit board (8), the terminal (2) having first and second mounting legs (22, 22') which are received in the circuit board hole (9) to retain the terminal on the circuit board (8), each of the mounting legs (22, 22') having a retaining portion (24, 24') which extends from the terminal (2) partially along its length, the retaining portion having a width which is sufficient to establish an interference fit in a small diameter circuit board hole (9), the legs (22, 22') being characterized in that:

each of the legs (22, 22') has a reduced width portion (28, 28') between said retaining portions (24, 24') and the free ends (30, 30') of the legs,

each of the legs has camming means (46, 46') on the reduced width portions (28, 28') and each of the legs has cam actuator means (38, 38') which are cooperable with the wall of the circuit board hole (9) to cause the camming means (46, 46') to cause movement of the legs (22, 22') away from each other during movement of the legs into the circuit board hole (9) whereby,

the legs (22, 22') can easily be inserted into the circuit board hole (9) by reason of said reduced width portions (28, 28'), and during movement of the legs into said circuit board hole, the legs (22, 22') will be moved apart by the camming means and the retaining portions (24, 24') will establish an interference fit in the circuit board hole (9) and retain the terminal on said circuit board (8).

2. A terminal as set forth in claim 1 characterized by the legs (22, 22') having opposed major surfaces (36, 36') and each leg having first (32) and second (32') side edges on each side of said major surfaces.

3. A terminal as set forth in claim 2 charac-

manually or by an insertion machine.

After the legs have been brought against each other, they are aligned with the circuit board hole 9 and moved downwardly from the position of Figure 3 to the position of Figure 5. During this downward motion, the inclined lower portions 42, 42' of the second side edge 34 of the first leg and the first side edge 32' of the second leg 22' will engage the edge 11 of the circuit board hole and the legs will be flexed slightly so that their camming and guiding portions 28, 28' coincide, as shown in Figure 5. This flexure of the legs causes their camming and guiding portions to move in opposite directions parallel to their own planes so that the camming surfaces 47, 47' move across each other until the cams 46, 46' are side-by-side, see Figure 6.

Upon further movement of the legs into the circuit board hole, the inclined portions 38, 38' of the first and second legs engage the edge 11 of the circuit board hole thereby causing the legs to be moved back towards their aligned positions. When this movement is completed, the cams 46, 46' will again be brought into opposed aligned positions and the legs will thereby be cammed apart, see Figure 8. As the result, the retaining portions 24, 24' penetrate the circuit board and establish a secure interference fit of these retaining portions in the circuit board hole. The cams 46, 46' serve as a locking means after complete insertion of the terminal and maintain this interference fit in the circuit board hole.

Figures 3—8 illustrate the movement of the legs into a circuit board hole 9 at the lower tolerance limit of the range of circuit board holes for which the legs are intended. Under these circumstances it will be seen from Figure 8, that the corners 52, 52' of the legs penetrate the material of the circuit board relatively deeply. The condition shown in Figure 8 has been observed and this condition will come about if the circuit board is of relatively soft material, for example, if the circuit board is of a paper filled phenolic resin. If the circuit board is of a relatively hard material which is resistant to penetration by the corners 52, 52', the legs may not be fully returned to their aligned positions and may be flexed along their axes to some extent. In this latter event, however, a tight interference fit of the legs in the circuit board hole is nonetheless obtained.

Figure 10 is similar to Figure 8 except that it shows the condition which exists when the legs are inserted into a hole at the upper tolerance limit of the range of hole diameters. The corners 52, 52' do not penetrate the material of the circuit board to the same extent, however, they are wedged tightly in the hole and are maintained in their wedged condition by the cams 46, 46'.

Figure 11 illustrates the advantage obtained in the practice of the invention, as compared with prior art methods of mounting terminals in

circuit boards. The dotted line curve in Figure 11 relates the pushout force, the force in kilograms required to push a terminal out of a circuit board hole after insertion, to the diameter, in millimeters, of the circuit board hole. These data for the dotted line curve were obtained from tests in which the terminal had two legs designed to provide a simple interference fit as shown in U.S. Patent 4,261,629. It can be seen from this dotted line curve that the pushout force drops abruptly within a very narrow band of hole diameters to an unacceptably low level when the hole diameter reaches 1.27 mm. The solid line curve relates the push out force to the hole diameter for a terminal having mounting legs in accordance with the invention. The solid line curve shows that the pushout force drops only very slightly when the hole diameter changes from 1.07 mm to 1.27 mm and satisfactory results are obtained even if the hole is a diameter greater than 1.27 mm.

Claims

1. A stamped and formed sheet metal terminal (2) intended for mounting in a circular hole (9) in a circuit board (8), the terminal (2) having first and second mounting legs (22, 22') which are received in the circuit board hole (9) to retain the terminal on the circuit board (8), each of the mounting legs (22, 22') having a retaining portion (24, 24') which extends from the terminal (2) partially along its length, the retaining portion having a width which is sufficient to establish an interference fit in a small diameter circuit board hole (9), the legs (22, 22') being characterized in that:

each of the legs (22, 22') has a reduced width portion (28, 28') between said retaining portions (24, 24') and the free ends (30, 30') of the legs,

each of the legs has camming means (46, 46') on the reduced width portions (28, 28') and each of the legs has cam actuator means (38, 38') which are cooperable with the wall of the circuit board hole (9) to cause the camming means (46, 46') to cause movement of the legs (22, 22') away from each other during movement of the legs into the circuit board hole (9) whereby,

the legs (22, 22') can easily be inserted into the circuit board hole (9) by reason of said reduced width portions (28, 28'), and during movement of the legs into said circuit board hole, the legs (22, 22') will be moved apart by the camming means and the retaining portions (24, 24') will establish an interference fit in the circuit board hole (9) and retain the terminal on said circuit board (8).

2. A terminal as set forth in claim 1 characterized by the legs (22, 22') having opposed major surfaces (36, 36') and each leg having first (32) and second (32') side edges on each side of said major surfaces.

3. A terminal as set forth in claim 2 charac-



terized by the legs (22, 22') being substantially flat, said retaining portions (24, 24') of said legs having a width which is substantially equal to, but slightly less than, the diameter of the smallest circuit board (9) hole for which said terminal is intended.

4. A terminal as set forth in claim 3 characterized by the camming means (46, 46') comprising camming bosses on said opposed surfaces (36, 36') proximate to said free ends (30, 30').

5. A terminal as set forth in claim 3 characterized by the camming means (46, 46') comprising normally opposed camming bosses on said opposed surfaces proximate to the free ends (30, 30') and the cam actuator means (38, 38') is between the retaining portions (24, 24') and the camming bosses (46, 46').

6. A terminal as set forth in claim 5 characterized by the cam actuator means (38, 38') being the side edges of the legs.

7. A terminal as set forth in claim 6 characterized by the first and second legs (22, 22') being normally spaced apart, the legs being movable relatively towards each other for insertion into the circuit board hole (9).

8. A terminal as set forth in claim 7 characterized by portions of the first side edge (32) of the first leg (22) adjacent to said free end (30) of the first leg and portions of the second side edge (34') of the second leg (22') adjacent to the free end (30') being tapered towards the free ends (30, 30') of the legs thereby to provide guiding portions on the free ends of the legs.

9. A terminal as set forth in claim 8 characterized by the terminal device being an elongated strip of sheet metal having intermediate portions (10, 12, 10', 12') thereof formed to provide a contact portion, the legs constituting the ends of the strip.

Patentansprüche

1. Anschlußkontakt (2) aus gestanztem und geformtem Metallblech zur Anbringung in einem kreisförmigen Loch (9) in einer Schaltungsplatte (8), wobei der Anschlußkontakt (2) erste und zweite Montagebeine (22, 22') aufweist, die in dem Loch (9) der Schaltungsplatte aufgenommen sind, um den Anschlußkontakt auf der Schaltungsplatte (8) zu halten, wobei jedes der Montagebeine (22, 22') einen Halteabschnitt (24, 24') aufweist, der sich von dem Anschlußkontakt (2) teilweise entlang seiner Länge wegerstreckt und der Halteabschnitt eine Breite aufweist, die ausreicht, um einen Festsitz in einem Loch (9) kleinen Durchmessers einer Schaltungsplatte zu bewirken, und wobei die Beine (22, 22') dadurch gekennzeichnet sind, daß jedes der Beine (22, 22') einen Abschnitt (28, 28') vermindelter Breite zwischen den Halteabschnitten (24, 24') und den freien Enden (30, 30') der Beine aufweist, daß jedes der Beine Nockeneinrichtungen (46, 46') auf

den Abschnitten (28, 28') vermindelter Breite umfaßt, und daß jedes der Beine eine Nockenbetätigungseinrichtung (38, 38') aufweist, welche mit der Wand des Lochs (9) der Schaltungsplatte zusammenwirken können, um zu bewirken, daß die Nockeneinrichtungen (46, 46') eine Bewegung der Beine (22, 22') voneinander weg während der Bewegung der Beine in das Loch (9) der Schaltungsplatte hinein herbeiführen, wodurch die Beine (22, 22') leicht in das Loch (9) der Schaltungsplatte eingeführt werden können, und zwar aufgrund der Abschnitte (28, 28') vermindelter Breite, und wodurch während der Bewegung der Beine in das Loch der Schaltungsplatte hinein die Beine (22, 22') durch die Nockeneinrichtungen auseinanderbewegt werden und die Halteabschnitte (24, 24') einen Festsitz in dem Loch (9) der Schaltungsplatte errichten und den Anschlußkontakt auf der Schaltungsplatte (8) halten.

2. Anschlußkontakt nach Anspruch 1, dadurch gekennzeichnet, daß die Beine (22, 22') gegenüberliegende Hauptflächen (36, 36') aufweisen, und daß jedes Bein erste (32) und zweite (32') Seitenkanten an jeder Seite der Hauptflächen aufweist.

3. Anschlußkontakt nach Anspruch 2, dadurch gekennzeichnet, daß die Beine (22, 22') im wesentlichen flach sind, und daß die Halteabschnitte (24, 24') der Beine eine Breite haben, die im wesentlichen gleich, jedoch etwas kleiner ist als der Durchmesser des kleinsten Loches (9) der Schaltungsplatte, für welches der Anschlußkontakt bestimmt ist.


4. Anschlußkontakt nach Anspruch 3, dadurch gekennzeichnet, daß die Nockeneinrichtungen (46, 46') Nockenvorsprünge auf den gegenüberliegenden Flächen (36, 36') in der Nähe der freien Enden (30, 30') umfassen.

5. Anschlußkontakt nach Anspruch 3, dadurch gekennzeichnet, daß die Nockeneinrichtungen (46, 46') normalerweise gegenüberstehende Nockenvorsprünge an den gegenüberstehenden Flächen in der Nähe der freien Enden (30, 30') umfassen, und daß die Nockenbetätigungseinrichtung (38, 38') zwischen den Halteabschnitten (24, 24') und den Nockenvorsprüngen (46, 46') angeordnet ist.

6. Anschlußkontakt nach Anspruch 5, dadurch gekennzeichnet, daß die Nockenbetätigungseinrichtung (38, 38') die Seitenkanten der Beine sind.

7. Anschlußkontakt nach Anspruch 6, dadurch gekennzeichnet, daß die ersten und zweiten Beine (22, 22') normalerweise im Abstand zueinander angeordnet sind, und daß die Beine zum Einsetzen in das Loch (9) der Schaltungsplatte relativ aufeinander zu bewegbar sind.

8. Anschlußkontakt nach Anspruch 7, dadurch gekennzeichnet, daß Abschnitte der ersten Seitenkante (32) des ersten Beines (22) in der Nähe des freien Endes (30) des ersten Beins und das Abschnitte der zweiten Seitenkante (34') des zweiten Beins (22') angrenzend an das freie Ende (30') zu den freien Enden (30, 30')



der Beine hin verjüngt sind, so daß Führungsabschnitte an den freien Enden der Beine werden.

9. Anschlußkontakt nach Anspruch 8, dadurch gekennzeichnet, daß die Anschlußvorrichtung ein länglicher Streifen aus Metallblech ist, der mittlere Abschnitte (10, 12, 10', 12') aufweist, die derart geformt sind, daß ein Kontaktabschnitt gebildet wird, wobei die Beine die Enden des Streifens darstellen.

Revendications

1. Borne (2) un tôle emboutie et formée destinée à être montée dans un trou circulaire (9) d'une plaque (8) à circuit, la borne (2) comportant des premier et second pieds de montage (22, 22') qui sont reçus dans le trou (9) de la plaque à circuit afin de retenir la borne sur la plaquette (8) à circuit, chacun des pieds de montage (22, 22') comportant une partie de retenue (24, 24') qui s'étend à partir de la borne (2) sur une partie de sa longueur, la partie de retenue ayant une largeur qui est suffisante pour établir un ajustement serré dans un trou (9) de plaquette à circuit de faible diamètre, les pieds (22, 22') étant caractérisés en ce que:

chacun des pieds (22, 22') comporte une partie (28, 28') de largeur réduite entre lesdites parties de retenue (24, 24') et les extrémités libres (30, 30') des pieds,

chacun des pieds comporte des moyens de came (46, 46') situés sur les parties (28, 28') de largeur réduite et chacun des pieds comporte des moyens d'actionnement de came (38, 38') qui peuvent coopérer avec la paroi du trou (9) de la plaquette à circuit afin d'agir sur les moyens de came (46, 46') pour provoquer un mouvement d'écartement des pieds (22, 22') l'un de l'autre pendant un mouvement de pénétration des pieds dans le trou (9) de la plaquette à circuit, de façon que les pieds (22, 22') puissent être aisément insérés dans le trou (9) de la plaquette à circuit grâce auxdites parties (28, 28') de largeur réduite et, pendant le mouvement de pénétration des pieds dans ledit trou de la plaquette à circuit, que les pieds (22, 22') soient écartés l'un de l'autre par les moyens de came et que les parties de retenue (24, 24') établissent un ajustement serré dans le trou (9) de la plaquette à circuit et retiennent la borne sur ladite plaque (8) à circuit.

2. Borne selon la revendication 1, caractérisée en ce que les pieds (22, 22') présentent des surfaces principales opposées (36, 36') et chaque pied comporte des premier (32) et second (32') bords latéraux situés de chaque côté desdites surfaces principales.

3. Borne selon la revendication 2, caractérisée en ce que les pieds (22, 22') sont sensiblement plats, lesdites parties retenues (24, 24') desdits pieds ayant une largeur qui est sensiblement égale, mais légèrement inférieure au diamètre du plus petit trou de la plaquette (9) à circuit pour lequel ladite borne est prévue.

4. Borne selon la revendication 3, caractérisée en ce que les moyens de came (46, 46') comprennent des bossages de came situés sur lesdites surfaces opposées (36, 36'), à proximité desdites extrémités libres (30, 30').

5. Borne selon la revendication 3, caractérisée en ce que les moyens de came (46, 46') comprennent des bossages de came normalement opposés situés sur lesdites surfaces opposées, à proximité des extrémités libres (30, 30'), et les moyens d'actionnement de came (38, 38') sont situés entre les parties de retenue (24, 24') et les bossages de came (46, 46').

6. Borne selon la revendication 5, caractérisée en ce que les moyens d'actionnement de came (38, 38') sont les bords latéraux des pieds.

7. Borne selon la revendication 6, caractérisée en ce que les premier et second pieds (22, 22') sont normalement écartés, les pieds pouvant être rapprochés l'un de l'autre pour une insertion dans le trou (9) de la plaquette à circuit.

8. Borne selon la revendication 7, caractérisée en ce que des parties du premier bord latéral (32) du premier pied (22), adjacentes à ladite extrémité libre (30) du premier pied, et des parties du second bord latéral (34') du second pied (22'), adjacentes à l'extrémité libre (30'), sont effilées vers les extrémités libres (30, 30') des pieds afin de former des parties de guidage sur les extrémités libres des pieds.

9. Borne selon la revendication 8, caractérisée en ce que le dispositif à borne est une bande allongée de tôle comportant des parties intermédiaires (10, 12, 10', 12') qui sont formées de façon à constituer une partie de contact, les pieds constituant les extrémités de la bande.

