CLAIMS:

1. A lighting device having uninterruptible illumination and an external power supply function, in which the lighting device is combined with an energy storing/discharging device thereby providing an uninterruptible illumination function and supplying uninterruptable AC or DC power to the exterior during a power blackout; electric power supplied by at least one of a public power source (PS100) and the energy storing/discharging device is outputted to a controller assembly (1000) for controlling output of the AC or DC power, wherein the controller assembly (1000) inputs power from an AC, or DC, or AC converted to DC, or DC converted to AC power source (PS100) for outputting power to the electric control unit (ECU100), so as to control power for one or more of the following: (a) to charge the energy storing/discharging device (ESD100), (b) to supply power from at least one of the public power source (PS100) and the energy storing/discharging device to the electric-driven lighting device (L100), and (c) to output AC or DC power from at least one of the public power source (PS100) and the energy storing/discharging device to the exterior through a power output control circuit device (OPC100) and an external power supply interface device (C100), the lighting device comprising:

an operation device (OP100) constituted by at least one of manually-operated electromechanical switches, buttons, press keys, a touch-controlled or voice-controlled interface, an operation switch, a user identification device, and a command identification device, for actuating functions of the light device and supplying command signals to and controlling an electric control unit (ECU100);

the energy storing/discharging device (ESD100) constituted by a rechargeable energy storing device including a secondary battery capable of charging and discharging or a super capacitor or a capacitor, controlled by the electric control unit (ECU100) for controlling the electric power from the power source (PS100) used for charging the energy storing/discharging device (ESD100) through the electric control unit (ECU100), and controlled by the electric control unit (ECU100) for carrying out either or both of the following: (i) controlling output of electric power from the energy storing/discharging device (ESD100) for supplying power to the electric-driven lighting device (L100), and (ii) supplying power to the exterior through the power output control circuit device

(OPC100) and the external power supply interface device (C100);

the electric control unit (ECU100) constituted by electromechanical components or solid electric circuit components or chips and corresponding software, for receiving the input power from the power source (PS100) and controlled by the operation device (OP100), to carry out one or more than one operational functions: (1) controlling the ON/OFF timing of the power supplied by the power source (PS100) for driving the electric-driven lighting device (L100); or (2) controlling the timing of charging the energy storing/discharging device (ESD100) or terminating the charging when saturated; or (3) through the energy storing/discharging device (ESD100), outputting electric power upon receipt by the electric control unit of a detection signal from the operation device (OP100) for controlling supply or termination of power to the power-driven lighting device (L100); or (4) controlled by the power output control circuit device (OPC100) to supply the AC public power with the voltage being regulated to the exterior through the external energy supply interface device (C100); or (5) through the setting of the electric control unit (ECU100) or controlled by the power output control circuit device (OPC100), converting the DC power of the energy storing/discharging (ESD100) into AC output power; or (6) directly outputting, or outputting through control of the power output control circuit device (OPC100), the DC power of the energy storing/discharging device (ESD100);

electric-driven lighting device (L100) including an electric-driven lamp, for illumination or for indication signal lighting, wherein when the power source (PS100) is terminated, the electric power of the energy storing/discharging device (ESD100) replaces the electric power of the power source (PS100) being supplied to the electric-driven lamp, the electric-driven lamp continuing operation according to the set operating state of the operation device (OP100) and the electric control unit (ECU100), and subsequently being controlled by the operation device (OP100) and operated by the set function through the electric control unit (ECU100); wherein when the power source (PS100) recovers to supply electric power, the electric power of the power source (PS100) replaces the electric power of the energy storing/discharging device (ESD100), the electric-driven lighting device (L100) is operated according to the set operating state of the operation device

(OP100) and the electric control unit (ECU100), and is subsequently controlled by the operation device (OP100) and operated by the set function through the electric control unit (ECU100);

the external power supply interface device (C100) constituted by a plug or socket structure and a voltage and current controlling and protective device, through which the DC or AC power is input from the electric control unit (ECU100) and output to the power output control circuit device (OPC100) for output to the exterior such that when the power source (PS100) is terminated, power is supplied to the external power supply interface device (C100) from the energy storing/discharging device, and such that when the power source (PS100) recovers, power is supplied to the external power supply interface device (C100) from the power source (PS100); and

power output control circuit device (OPC100) constituted by one or more of electromechanical components or electric circuit components, a fuse or break protection device, an electric power measuring device, a monitoring device for outputted voltage and current, and a wired or wireless detecting and monitoring device for the operation state at load end;

wherein the lighting device is further installed with a charging grid surface and at least one of the following peripheral devices for charging management: a charging indication lamp, a charging grid, a charging grid protection cover (101), and a cover lock (103), wherein the charging grid protection cover (101) includes being sealed or formed with a ventilation heat dissipating hole (102).

2. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is a street lamp device (201) which is uninterruptable during an electric blackout and includes one of an illumination lamp or signal lamp, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

3. A lighting device having uninterruptible illumination and external power supply

function as claimed in claim 1, wherein the electric-driven lighting device (L100) is a public lighting device (401) which is uninterruptable during an electric blackout and includes illumination lighting or a high-altitude warning lamp, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

4. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, the electric-driven lighting device (L100) is a moveable lighting device (601) which is uninterruptable during an electric blackout and includes a moveable indoor or outdoor illumination function, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

5. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, the electric-driven lighting device (L100) is a blackout illumination device (701) which is uninterruptable during an electric blackout and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

6. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is an uninterruptable wall-hanging lighting (801) which is uninterruptable during an electric blackout and installed on a wall, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

7. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is an interface with external power supply function installed with a cover locked radially-arranged power supply case (901).

8. A lighting device having uninterruptible illumination and external power supply

function as claimed in claim 1, wherein the electric-driven lighting device (L100) is an interface with an external power supply function installed with a cover locked transversally-arranged power supply case (1001).

CLAIMS

1. A lighting device having uninterruptible illumination and an external power supply function, in which the lighting device is combined with an energy storing/discharging device thereby providing an uninterruptible illumination function and supplying uninterruptable AC or DC power to the exterior during a power blackout; electric power supplied by at least one of a public power source (PS100) and the energy storing/discharging device is outputted to a controller assembly (1000) for controlling output of the AC or DC power, wherein the controller assembly (1000) inputs power from an AC, or DC, or AC converted to DC, or DC converted to AC power source (PS100) for outputting power to the electric control unit (ECU100), so as to control power for one or more of the following: (a) to charge the energy storing/discharging device (ESD100), (b) to supply power from at least one of the public power source (PS100) and the energy storing/discharging device to the electric-driven lighting device (L100), and (c) to output AC or DC power from at least one of the public power source (PS100) and the energy storing/discharging device to the exterior through a power output control circuit device (OPC100) and an external power supply interface device (C100), the lighting device comprising:

an operation device (OP100) constituted by at least one of manually-operated electromechanical switches, buttons, press keys, a touch-controlled or voice-controlled interface, an operation switch, a user identification device, and a command identification device, for actuating functions of the light device and supplying command signals to and controlling an electric control unit (ECU100);

the energy storing/discharging device (ESD100) constituted by a rechargeable energy storing device including a secondary battery capable of charging and discharging or a super capacitor or a capacitor, controlled by the electric control unit (ECU100) for controlling the electric power from the power source (PS100) used for charging the energy storing/discharging device (ESD100) through the electric control unit (ECU100), and controlled by the electric control unit (ECU100) for carrying out either or both of the following: (i) controlling output of electric power from the energy storing/discharging device (ESD100) for supplying power to the electric-driven lighting device (L100), and (ii) supplying power to the exterior through the power output control circuit device (OPC100) and the external power supply interface device (C100);

the electric control unit (ECU100): constituted by electromechanical components or

solid electric circuit components or chips and corresponding software, for receiving the input power from the power source (PS100) and controlled by the operation device (OP100), to carry out one or more than one operational functions: (1) controlling the ON/OFF timing of the power supplied by the power source (PS100) for driving the electric-driven lighting device (L100); or (2) controlling the timing of charging the energy storing/discharging device (ESD100) or terminating the charging when saturated; or (3) through the energy storing/discharging device (ESD100),outputting electric power upon receipt by the electric control unit of a detection signal from the operation device (OP100) for controlling supply or termination of power to the power-driven lighting device (L100); or (4) controlled by the power output control circuit device (OPC100) to supply the AC public power with the voltage being regulated to the exterior through the external energy supply interface device (C100); or (5) through the setting of the electric control unit (ECU100) or controlled by the power output control circuit device (OPC100), converting the DC power of the energy storing/discharging (ESD100) into AC output power; or (6) directly outputting, or outputting through control of the power output control circuit device (OPC100), the DC power of the energy storing/discharging device (ESD100);

electric-driven lighting device (L100) including an electric-driven lamp, for illumination or for indication signal lighting, wherein when the power source (PS100) is terminated, the electric power of the energy storing/discharging device (ESD100) replaces the electric power of the power source (PS100) being supplied to the electric-driven lamp, the electric-driven lamp continuing operation according to the set operating state of the operation device (OP100) and the electric control unit (ECU100), and subsequently being controlled by the operation device (OP100) and operated by the set function through the electric control unit (ECU100); wherein when the power source (PS100) recovers to supply electric power, the electric power of the power source (PS100) replaces the electric power of the energy storing/discharging device (ESD100), the electric-driven lighting device (L100) is operated according to the set operating state of the operation device (OP100) and the electric control unit (ECU100), and is subsequently controlled by the operation device (OP100) and operated by the set function through the electric control unit (ECU100);

the external power supply interface device (C100) constituted by a plug or socket

structure and a voltage and current controlling and protective device, through which the DC or AC power is input from the electric control unit (ECU100) and output to the power output control circuit device (OPC100) for output to the exterior such that when the power source (PS100) is terminated, power is supplied to the external power supply interface device (C100) from the energy storing/discharging device, and such that when the power source (PS100) recovers, power is supplied to the external power supply interface device (C100) from the power source (PS100); and

power output control circuit device (OPC100): constituted by one or more of electromechanical components or electric circuit components, a fuse or break protection device, an electric power measuring device, a monitoring device for outputted voltage and current, and a wired or wireless detecting and monitoring device for the operation state at load end;

wherein the lighting device is further installed with a charging grid surface and at least one of the following peripheral devices for charging management: a charging indication lamp, a charging grid, a charging grid protection cover (101), and a cover lock (103), wherein the charging grid protection cover (101) includes being sealed or formed with a ventilation heat dissipating hole (102).

2. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is a street lamp device (201) which is uninterruptable during an electric blackout and includes one of an illumination lamp or signal lamp, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

3. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is a public lighting device (401) which is uninterruptable during an electric blackout and includes illumination lighting or a high-altitude warning lamp, and meanwhile also outputs AC power, DC power, or AC and DC power during the power blackout.

4. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is an interface with external power supply function installed with a cover locked radially-arranged power supply case (901).

5. A lighting device having uninterruptible illumination and external power supply function as claimed in claim 1, wherein the electric-driven lighting device (L100) is an interface with an external power supply function installed with a cover locked transversally-arranged power supply case (1001).