

COMPUTER DEVICE AND METHOD FOR READING/WRITING DATA BY COMPUTER DEVICE

TECHNICAL FIELD

5 [0001] The present invention relates to the field of information technologies, and in particular, to a computer device and a method for reading/writing data by a computer device.

BACKGROUND

10 [0002] With development of data centers and approaching of the era of big data, a data center architecture has developed into a virtualization-technology-centered architecture from a tightly coupled siloed server architecture. To adapt to the current era of big data, an existing data center is faced with a series of challenges in future big data processing, and the challenges include P bits/second real-time data processing, dynamic resource allocation and adjustment on demand, energy efficiency improvement of a large-scale system, or the like. In this case, a high-throughput computer data center with features such as resource pooling, hardware decoupling, and silicon photonic interconnection comes into being.

15 [0003] In an architecture of a high-throughput computer data center, resource pooling of memory resources, input/output resources, or the like is implemented. A high-throughput computing node is connected to a memory resource pool or an input/output resource pool by using a network, to dynamically allocate and adjust resources and improve system energy efficiency. Due to resource pooling, hardware decoupling makes an interconnect technology, for example, silicon photonic interconnection, become a most crucial technology. A current data center level interconnect technology relies mainly on an Ethernet interconnect technology. However, due to a complex and bloated protocol stack and an extremely high interconnect delay of the Ethernet itself, the interconnect technology becomes less capable of meeting a requirement of a data center on quick and high-capacity data exchange, while a

20

simplified resource pooling-centered interconnect and access protocol (PRAP, Pooled Resource Access Protocol) protocol that can provide high bandwidth and a low delay can meet a requirement of a high-throughput computer data center on low delay.

[0004] In a current method for decoupling a built high-throughput computer, a cloud controller (Cloud Controller) is used as a key module for interconnection, the PRAP interconnect protocol is used to connect a computing pool, a remote storage (memory) resource pool, an input/output (I/O) resource pool, and the like, and a double data rate (DDR, Double Data Rate) interface is used to connect to a central processing unit CPU. However, when data in the remote memory resource pool or input/output resource pool needs to be read, due to a network delay, the cloud controller cannot return required data at the DDR within a specified time. Therefore, when a CPU of a high-throughput computer accesses the remote memory resource pool or input/output resource pool by using a network, an interrupt of the CPU is caused, leading to a high access delay and a problem that overall performance of a system is affected because the CPU cannot perform another operation during the interrupt.

SUMMARY

[0005] Embodiments of the present invention provide a computer device and a method for reading/writing data by a computer device, so as to resolve a prior-art problem that system performance is affected because a high delay is caused when a CPU of a computer device reads/writes remote data.

[0006] To achieve the foregoing objective, a first aspect of the embodiments of the present invention provides a computer device, including a central processing unit CPU and a cloud controller, where the cloud controller includes a transmission queue module, a response queue module, a double data rate DDR interface, and a network interface, the DDR interface is configured to connect the CPU to the cloud controller, and the network interface is configured to connect the cloud controller to a network device;

the CPU is configured to: after generating a request for performing a read/write operation on the network device, convert the read/write operation request into a control command, and write the control command into the transmission queue module, where the

control command is used to instruct the cloud controller to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation; and

the cloud controller is configured to: when the control command in the transmission queue module is triggered, perform the read operation or the write operation on the network device according to the operation information in the control command, receive a response message sent by the network device, and write the response message sent by the network device into the response queue module.

[0007] With reference to the first aspect, in a first possible implementation of the first aspect of the embodiments of the present invention, the read/write operation request is a read operation request;

the transmission queue module includes a command transmission queue module and a data transmission queue module;

the response queue module includes a response command queue module and a data receiving queue module;

the CPU is specifically configured to: convert the read operation request into a read control command, and write the read control command into the command transmission queue module, where the read control command carries read operation information and is used to instruct the cloud controller to perform a read operation on the network device according to the read operation information; and

the cloud controller is specifically configured to: when the read control command in the command transmission queue module is triggered, perform the read operation on the network device according to the read operation information in the read control command, receive a read response message sent by the network device, write the read response message sent by the network device into the response command queue module, and write, into the data receiving queue module, data that is to be read by means of the read operation and that is returned by the network device.

[0008] With reference to the first possible implementation of the first aspect of the embodiments of the present invention, in a second possible implementation of the first aspect of the embodiments of the present invention, the read operation information includes an

address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or

the read operation information includes a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

[0009] With reference to the first possible implementation and the second possible implementation of the first aspect of the embodiments of the present invention, in a third possible implementation of the first aspect of the embodiments of the present invention,

the CPU is further configured to: after writing the read control command into the command transmission queue module, query, in a polling manner, whether the read response message sent by the network device exists in the response command queue module, and when the CPU determines that the read response message sent by the network device exists in the response command queue module and the read response message is a read success response message, read, from the data receiving queue module, the data to be read by means of the read operation.

[0010] With reference to the first possible implementation and the second possible implementation of the first aspect of the embodiments of the present invention, in a fourth possible implementation of the first aspect of the embodiments of the present invention,

the cloud controller is further configured to: determine whether the read response message sent by the network device exists in the response command queue module, and notify the CPU by means of an interrupt when the read response message sent by the network device exists in the response command queue module; and

the CPU is further configured to: receive an interrupt message sent by the cloud controller, obtain the read response message from the response command queue module according to the interrupt message, and when the obtained read response message indicates a read success, read, from the data receiving queue module, the data to be read by means of the read operation.

[0011] With reference to the first aspect of the embodiments of the present invention, in a fifth possible implementation of the first aspect of the embodiments of the present invention,

the read/write operation request is a write operation request;

the transmission queue module includes a command transmission queue module and a data transmission queue module;

the response queue module includes a response command queue module and a data receiving queue module;

5 the CPU is specifically configured to: convert the write operation request into a write control command, write the write control command into the command transmission queue module, and write, into the data transmission queue module, data to be written by means of the write operation, where the write control command carries write operation information and is used to instruct the cloud controller to write, into the network device
10 according to the write operation information, the data to be written by means of the write operation; and

 the cloud controller is specifically configured to: when the write control command in the command transmission queue module is triggered, extract, from the data transmission queue module according to the write operation information in the write control command, the
15 data to be written by means of the write operation, and write, into the network device, the data to be written by means of the write operation; and when receiving a write response message sent by the network device, write the write response message sent by the network device into the response command queue module.

[0012] With reference to the fifth possible implementation of the first aspect of the
20 embodiments of the present invention, in a sixth possible implementation of the first aspect of the embodiments of the present invention,

 the write operation information includes an address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation; or

25 the write operation information includes a node address and an offset address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation.

[0013] With reference to the fifth possible implementation and the sixth possible implementation of the first aspect of the embodiments of the present invention, in a seventh possible implementation of the first aspect of the embodiments of the present invention,

the CPU is further configured to: after writing the write control command into the command transmission queue module, query, in a polling manner, whether the write response message sent by the network device exists in the response command queue module, and when the CPU determines that the write response message sent by the network device exists in the response command queue storage module, obtain the write response message.

[0014] With reference to the fifth possible implementation and the sixth possible implementation of the first aspect of the embodiments of the present invention, in an eighth possible implementation of the first aspect of the embodiments of the present invention,

the cloud controller is further configured to: determine whether the write response message sent by the network device exists in the response command queue module, and notify the CPU by means of an interrupt when the write response message sent by the network device exists in the response command queue module; and

the CPU is further configured to: receive an interrupt message sent by the cloud controller, and obtain the write response message from the response command queue module according to the interrupt message.

[0015] According to a second aspect, an embodiment of the present invention further provides a method for reading/writing data by a computer device, where the computer device includes a central processing unit CPU, a cloud controller, and a network interface, the CPU is connected to the cloud controller by using a double data rate DDR interface, and the network interface is configured to connect the cloud controller to a network device; and the method includes:

converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller, where the control command is used to instruct the cloud controller to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation; and

performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command when the control command in the transmission queue module is triggered, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device.

[0016] With reference to the second aspect, in a first possible implementation of the second aspect of the embodiments of the present invention,

the read/write operation request is a read operation request;

correspondingly, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller includes:

converting, by the CPU, the read operation request into a read control command, and writing the read control command into a command transmission queue module of the transmission queue module, where the read control command carries read operation information and is used to instruct the cloud controller to perform a read operation on the network device according to the read operation information; and

the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device includes:

performing, by the cloud controller, the read operation on the network device according to the read operation information in the read control command when the read control command in the command transmission queue module is triggered, receiving a read response message sent by the network device, writing the read response message sent by the network device into the response command queue module of the response queue module, and writing, into the data receiving queue module of the response queue module, data that is to be read by means of the read operation and that is returned by the network device.

[0017] With reference to the first possible implementation of the second aspect of the embodiments of the present invention, in a second possible implementation of the second aspect of the embodiments of the present invention,

the read operation information includes an address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or

5 the read operation information includes a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

[0018] With reference to the first possible implementation and the second possible implementation of the second aspect of the embodiments of the present invention, in a third possible implementation of the second aspect of the embodiments of the present invention,

10 after writing the read control command into the command transmission queue module, querying, by the CPU in a polling manner, whether the read response message sent by the network device exists in the response command queue module, and when the CPU determines that the read response message sent by the network device exists in the response command queue module and the read response message is a read success response message,
15 reading, from the data receiving queue module, the data to be read by means of the read operation.

[0019] With reference to the first possible implementation and the second possible implementation of the second aspect of the embodiments of the present invention, in a fourth possible implementation of the second aspect of the embodiments of the present invention,

20 determining, by the cloud controller, whether the read response message sent by the network device exists in the response command queue module, and notifying the CPU by means of an interrupt when the read response message sent by the network device exists in the response command queue module; and

receiving, by the CPU, an interrupt message sent by the cloud controller, obtaining
25 the read response message from the response command queue module according to the interrupt message, and when the obtained read response message indicates a read success, reading, from the data receiving queue module, the data to be read by means of the read operation.

[0020] With reference to the second aspect of the embodiments of the present invention, in a fifth possible implementation of the second aspect of the embodiments of the present invention,

the read/write operation request is a write operation request;

5 correspondingly, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller includes:

converting, by the CPU, the write operation request into a write control command, writing the write control command into the command transmission queue module of the transmission queue module, and writing, into the data transmission queue module of the 10 transmission queue module, data to be written by means of the write operation, where the write control command carries write operation information and is used to instruct the cloud controller to write, into the network device according to the write operation information, the data to be written by means of the write operation; and

15 the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device includes:

when the write control command in the command transmission queue module is 20 triggered, extracting, by the cloud controller from the data transmission queue module according to the write operation information in the write control command, the data to be written by means of the write operation, and writing, into the network device, the data to be written by means of the write operation; and when receiving a write response message sent by the network device, writing the write response message sent by the network device into the 25 response command queue module of the response queue module.

[0021] With reference to the fifth possible implementation of the second aspect of the embodiments of the present invention, in a sixth possible implementation of the second aspect of the embodiments of the present invention,

the write operation information includes an address of the network device, a 30 length of the data to be written by means of the write operation, and an address, in the data

transmission queue, of the data to be written by means of the write operation; or

the write operation information includes a node address and an offset address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation.

[0022] With reference to the fifth possible implementation and the sixth possible implementation of the second aspect of the embodiments of the present invention, in a seventh possible implementation of the second aspect of the embodiments of the present invention, the method further includes:

after writing the write control command into the command transmission queue module, querying, by the CPU in a polling manner, whether the write response message sent by the network device exists in the response command queue module, and when the CPU determines that the write response message sent by the network device exists in the response command queue storage module, obtaining the write response message.

[0023] With reference to the fifth possible implementation and the sixth possible implementation of the second aspect of the embodiments of the present invention, in an eighth possible implementation of the second aspect of the embodiments of the present invention, the method further includes:

determining, by the cloud controller, whether the write response message sent by the network device exists in the response command queue module, and notifying the CPU by means of an interrupt when the write response message sent by the network device exists in the response command queue module; and

receiving, by the CPU, an interrupt message sent by the cloud controller, and obtaining the write response message from the response command queue module according to the interrupt message.

[0024] According to the computer device and the method for reading/writing data by a computer device that are provided in the embodiments of the present invention, a CPU of the computer device is connected to the cloud controller by using a DDR interface, and an interrupt is avoided because the DDR interface has a high data transmission rate. In addition, the CPU converts a read/write operation request into a control command and writes the

control command into a transmission queue module of the cloud controller. Because the cloud controller performs the read operation or the write operation on the network device according to operation information in the control command, after writing the control command into the transmission queue module, the CPU does not need to wait for an operation performed by the cloud controller and can continue to perform other service processing, for example, continue to write another control command. This avoids a waste of CPU resources, and improves CPU utilization and overall performance of a system.

BRIEF DESCRIPTION OF DRAWINGS

[0025] The following clearly and completely describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are merely some but not all of the embodiments of the present invention. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present invention without creative efforts shall fall within the protection scope of the present invention.

[0026] FIG. 1 is a schematic architecture diagram of a specific implementation of a high-throughput computer data center in the prior art;

[0027] FIG. 2 is a schematic structural diagram of a computer device according to an embodiment of the present invention;

[0028] FIG. 3 is a schematic structural diagram of a specific implementation of a computer device according to an embodiment of the present invention;

[0029] FIG. 4 is a schematic structural diagram of reading/writing remote data by a computer device according to an embodiment of the present invention; and

[0030] FIG. 5 is a schematic flowchart of a method for reading/writing data by a computer device according to an embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

[0031] The following clearly and completely describes the technical solutions in the embodiments of the present invention with reference to the accompanying drawings in the embodiments of the present invention. Apparently, the described embodiments are a part rather than all of the embodiments of the present invention. All other embodiments obtained by a person of ordinary skill in the art based on the embodiments of the present invention without creative efforts shall fall within the protection scope of the present invention.

[0032] FIG. 1 is a schematic architecture diagram of a specific implementation of a high-throughput computer data center in the prior art. A computer device includes a central processing unit, a memory, and a cloud controller. The cloud controller is connected to a remote resource pool by using a network. The remote resource pool includes storage resources, input/output resources, or the like. The storage resources, for example, a dynamic random access memory (DRAM, Dynamic Random Access Memory) and a non-volatile memory (NVM, NonVolatile Memory), form a storage resource pool. The input/output resources, for example, a network adapter and a Peripheral Component Interconnect Express PCIe interface, form an input/output resource pool. It should be noted that FIG. 1 shows merely an example of a structural diagram of a high-throughput computer data center. During specific implementation, another hardware resource (for example, a bus), another resource pool (for example, a computing resource pool), or the like may be further included. In addition, in a computer device, multiple central processing units and multiple memories may form a computing resource pool or the like. Moreover, a quantity of resources in the resource pool shown in FIG. 1 is used as an example. During specific implementation, at least two resources may be included, for example, a memory resource pool may include at least two memories.

[0033] In the example shown in FIG. 1, in addition to a local memory (for example, a dynamic random access memory DRAM using a DDR interface), a CPU in the computer device also has a remote storage space allocated by a system. Each physical storage space is mapped to a global address space. A mapping relationship of the address space is stored in a driver of a cloud controller corresponding to each CPU. For example, a CPU 1 has a 10 GB

local memory and a 100 G remote storage resource (that is, storage spaces in the storage resource pool that are connected by using a network and can be accessed) in total. Assuming that the CPU 1 can access a remote storage resource pool including a storage space A and a storage space B, and the storage space A and the storage space B each are a storage resource
5 with a capacity of 50 G, the CPU 1 can access a 110 GB storage space in total: a storage space of 0 to 10 GB in the local memory and a storage space of 10 GB to 110 GB in the remote storage resource pool.

[0034] When the CPU 1 accesses the local memory, data can be accessed within a specified time because network transmission is not required. However, when data is not in the
10 local memory, but in the remote storage resource pool, for example, in the storage space A or the storage space B, a cloud controller 1 can read the data only by accessing the remote storage resource pool by using a network. Because network transmission is required, the cloud controller 1 cannot return the required data to the CPU 1 at a DDR within a specified time. Therefore, after receiving a data read request delivered by the CPU 1, the cloud
15 controller 1 packs the request, sends the request to the storage resource pool by using the network, to obtain data, and returns an ECC error or a PAGE error to the CPU 1. When receiving error information sent by the cloud controller 1, the CPU 1 interrupts current memory access and suspends a corresponding access thread. After receiving the data sent from the storage resource pool, the cloud controller 1 generates an interrupt signal to notify
20 the CPU 1. The CPU 1 can obtain, according to the received interrupt signal and only by resending a memory reading request, the data that needs to be read. Because the data has been written into a storage space of the cloud controller 1 at this time, the CPU 1 can obtain the data at the DDR within a specified time. Therefore, when data that needs to be accessed by the CPU 1 is not inside the cloud controller, the CPU 1 needs to perform one interrupt
25 operation and two read operations. As a result, a high access delay is caused, and overall performance of a system is affected because the CPU 1 cannot perform another operation during the interruption.

[0035] To resolve problems of an excessively high access delay and low system performance that are caused by a network delay when a CPU in the foregoing
30 high-throughput computer data center accesses data that is not in a local resource, an

embodiment of the present invention provides a computer device 10. As shown in FIG. 2, the computer device 10 includes a central processing unit CPU 100 and a cloud controller 200. The cloud controller includes a transmission queue module 201, a response queue module 202, a double data rate DDR interface 203, and a network interface 204. The DDR interface 203 is configured to connect the CPU 100 to the cloud controller 200, and the network interface 204 is configured to connect the cloud controller 200 to a network device.

[0036] The CPU 100 is configured to: after generating a request for performing a read/write operation on the network device, convert the read/write operation request into a control command, and write the control command into the transmission queue module 201. The control command is used to instruct the cloud controller 200 to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation.

[0037] The cloud controller 200 is configured to: when the control command in the transmission queue module 201 is triggered, perform the read operation or the write operation on the network device according to the operation information in the control command, receive a response message sent by the network device, and write the response message sent by the network device into the response queue module 202.

[0038] In this embodiment of the present invention, the network device connected to the computer device 10 by using the network interface 204 is a device connected to the computer device 10 by using a network. When the CPU 100 needs to access data in the network device, the cloud controller 200 needs to send a data read/write message to the network device by using the network, and receives a response message or data returned by the network device by using the network. The CPU 100 is connected to the cloud controller 200 by using the DDR interface 203, and an interrupt is avoided because the DDR interface 203 has a high data transmission rate. In addition, the CPU 100 converts a read/write operation request into a control command and writes the control command into the transmission queue module 201 of the cloud controller 200. Because the cloud controller 200 performs the read operation or the write operation on the network device according to operation information in the control command, after writing the control command into the transmission queue module 201, the CPU 100 does not need to wait for an operation performed by the cloud controller 200, and

can continue to perform other service processing, for example, continue to write another control command. This avoids a waste of CPU 100 resources, and improves CPU 100 utilization and overall performance of the computer device.

[0039] During specific implementation, the transmission queue module 201 and the response queue module 202 of the cloud controller 200 may be implemented by hardware such as a register or a memory, and are connected to the DDR interface and the like by using a hardware interface. For example, the transmission queue module 201 stores, by using hardware such as a register, a control command written by the CPU 100, and the response queue module 202 stores a response message by using hardware such as a register. In addition, the transmission queue module 201 and the response queue module 202 store related commands or messages in an ordered arrangement manner such as in a queue form, so that the cloud controller 200 can read commands or write response messages in a queue form. In this embodiment of the present invention, that the control command in the transmission queue module 201 is triggered may be that when the control command is written into the transmission queue module 201, the cloud controller 200 is triggered to extract the control command from the transmission queue module 201 and execute the control command. Specifically, a control unit or a control module of the cloud controller 200 may extract the control command from the transmission queue module 201 and execute the control command. The control unit or the control module of the cloud controller 200 is also a hardware control component, and is connected to the transmission queue module 201, the response queue module 202, or the network interface 204 by using an interface.

[0040] When the read/write operation request is a read operation request, as shown in FIG. 3,

the transmission queue module 201 includes a command transmission queue module 2011 and a data transmission queue module 2012;

the response queue module 202 includes a response command queue module 2021 and a data receiving queue module 2022;

the CPU 100 is specifically configured to: convert the read operation request into a read control command, and write the read control command into the command transmission queue module 2011, where the read control command carries read operation information and

is used to instruct the cloud controller 200 to perform a read operation on the network device according to the read operation information; and

the cloud controller 200 is specifically configured to: when the read control command in the command transmission queue module 2011 is triggered, perform the read operation on the network device according to the read operation information in the read control command, receive a read response message sent by the network device, write the read response message sent by the network device into the response command queue module 2021, and write, into the data receiving queue module 2022, data that is to be read by means of the read operation and that is returned by the network device.

[0041] Specifically, the converting the read operation request into a read control command, and writing the read control command into the command transmission queue module 2011 is implemented by a driver that runs in the CPU 100.

[0042] That the read control command in the command transmission queue module 2011 is triggered may be that when the read control command is written into the command transmission queue module 2011, the cloud controller is triggered to extract the read control command from the command transmission queue module 2011. During specific implementation, a control unit or a control module of the cloud controller may extract the read control command from the command transmission queue module 2011 when the read control command is written into the command transmission queue module 2011, and execute the read control command.

[0043] The read operation information may include an address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or

the read operation information includes a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

[0044] Optionally, the performing, by the cloud controller 200, the read operation on the network device according to the read operation information in the read control command may include: creating a communications packet by using the address, in the network device, of the data to be read by means of the read operation and the length of the data to be read by means

of the read operation, and sending the communications packet to the network device by using a network; or creating, by the cloud controller 200, a communications packet by using the node address and the offset address, in the network device, of the data to be read by means of the read operation and the length of the data to be read by means of the read operation, and sending the communications packet to the network device by using a network. Specifically, the communications packet may be a PRAP data packet.

[0045] After converting the read operation request into the read control command and writing the read control command into the command transmission queue module 2011, the CPU 100 may perform another operation, for example, continue to write another read control command or write control command. The cloud controller 200 may extract the read control instruction from the command transmission queue module 2011 when the read control command is written into the command transmission queue module 2011, execute the read control command, write a result of executing the read control command into the response command queue module 2021, and when obtaining data that is read, write the read data into the data receiving queue module 2022. In this way, a read operation request is converted into two processes of writing a read control command by the CPU 100 and executing the read control command by the cloud controller 200. The CPU 100 can execute another task with no need to wait for a result of performing a read operation by the cloud controller 200, and only needs to obtain a read operation result when a read operation response command is written into the response command queue module 2021. This avoids an interrupt caused because the CPU 100 waits for a read operation result for an excessively long time, and improves resource utilization of the CPU 100 and overall performance of a system.

[0046] In this embodiment of the present invention, the CPU 100 may obtain the read operation result by querying in a polling manner or by being notified by means of an interrupt. For example, after writing the read control command into the command transmission queue module, the CPU 100 queries, in a polling manner, whether the read response message sent by the network device exists in the response command queue module 2021, that is, repeatedly queries, according to a preset time interval, whether the read response message sent by the network device exists in the response command queue module 2021. When determining that the read response message sent by the network device exists in the response command queue

module 2021, the CPU 100 obtains the response message in the response command queue module 2021. When the read response message is a read success response message, the CPU 100 reads, from the data receiving queue module 2022, the data to be read by means of the read operation.

5 **[0047]** The obtaining the read operation result by being notified by means of an interrupt includes: determining, by the cloud controller 200, whether the read response message sent by the network device exists in the response command queue module 2021, and notifying the CPU 100 by means of an interrupt when the read response message sent by the network device exists in the response command queue module 2021. Specifically, the response
10 command queue module 2021 may notify the CPU 100 by means of an interrupt when the read response message is written into the response command queue module 2021.

[0048] The CPU 100 receives an interrupt message sent by the cloud controller 200, obtains the read response message from the response command queue module 2021 according to the interrupt message, and when the obtained read response message indicates a
15 read success, reads, from the data receiving queue module 2022, the data to be read by means of the read operation.

[0049] During specific implementation, the CPU 100 may write a polling-based query manner or an interrupt-based notification manner into a register of the cloud controller 200. The cloud controller 200 obtains, from the register, information written by the CPU 100. If
20 the polling-based query manner is written into the register, the CPU 100 proactively queries, in a polling manner, the response command queue module 2021; if the interrupt-based notification manner is written into the register, the cloud controller 200 notifies the CPU 100 by means of an interrupt when the read response message is written into the response command queue module 2021.

25 **[0050]** When the read/write operation request is a write operation request, as shown in FIG. 3,

the transmission queue module 201 includes a command transmission queue module 2011 and a data transmission queue module 2012;

the response queue module 202 includes a response command queue module 2021
30 and a data receiving queue module 2022;

the CPU 100 is specifically configured to: convert the write operation request into a write control command, write the write control command into the command transmission queue module 2011, and write, into the data transmission queue module 2012, data to be written by means of the write operation, where the write control command carries write operation information and is used to instruct the cloud controller 200 to write, into the network device according to the write operation information, the data to be written by means of the write operation; and

the cloud controller 200 is specifically configured to: when the write control command in the command transmission queue module 2011 is triggered, extract, from the data transmission queue module 2012 according to the write operation information in the write control command, the data to be written by means of the write operation, and write, into the network device, the data to be written by means of the write operation; and when receiving a write response message sent by the network device, write the write response message sent by the network device into the response command queue module 2021.

[0051] Specifically, the converting the write operation request into a write control command and writing the write control command into the command transmission queue module 2011 is implemented by a driver that runs in the CPU 100.

[0052] That the write control command in the command transmission queue module 2011 is triggered may be that when the write control command is written into the command transmission queue module 2011, the cloud controller is triggered to extract the write control command from the command transmission queue module 2011. During specific implementation, a control unit or a control module of the cloud controller may extract the write control command from the command transmission queue module 2011 when the write control command is written into the command transmission queue module 2011, and execute the read control command.

[0053] In a specific implementation, the write operation information includes an address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation; or

the write operation information includes a node address and an offset address of

the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation.

[0054] Optionally, the extracting, by the cloud controller 200 from the data transmission queue module 2012 according to the write operation information in the write control command, the data to be written by means of the write operation, and writing, into the network device, the data to be written by means of the write operation may include: creating a communications packet by using the data to be written by means of the write operation, the address of the network device, and the length of the data to be written by means of the write operation, and sending the communications packet to the network device by using a network; or creating, by the cloud controller 200, a communications packet by using the data to be written by means of the write operation, the node address and the offset address of the network device, and the length of the data to be written by means of the write operation, and sending the communications packet to the network device by using a network. Specifically, the communications packet may be a PRAP data packet.

[0055] After converting the write operation request into the write control command and writing the write control command into the command transmission queue module 2011, the CPU 100 may perform another operation, for example, continue to write another read control command or write control command. The cloud controller 200 may extract the write control instruction from the command transmission queue module 2011 when the write control command is written into the command transmission queue module 2011, execute the write control command, and write a result of executing the write control command into the response command queue module 2021. In this way, a write operation request is converted into two processes of writing a write control command into the command transmission queue module 2021 of the cloud controller and executing the write control command by the cloud controller 200. The CPU 100 can execute another task with no need to wait for a result of performing a write operation by the cloud controller 200, and only needs to obtain a write operation result when a write operation response command is written into the response command queue module 2021. This avoids an interrupt caused because the CPU 100 waits

for a write operation result for an excessively long time, and improves resource utilization of the CPU 100 and overall performance of the computer device.

[0056] In this embodiment of the present invention, the CPU 100 may further obtain the read operation result by querying in a polling manner or by being notified by means of an interrupt. For example, after writing the write control command into the command transmission queue module, the CPU 100 queries, in a polling manner, whether the write response message sent by the network device exists in the response command queue module 2021, that is, repeatedly queries, according to a preset time interval, whether the write response message sent by the network device exists in the response command queue module 2021. When determining that the write response message sent by the network device exists in the response command queue storage module 2021, the CPU 100 obtains the write response message.

[0057] The obtaining the write operation result by being notified by means of an interrupt includes: determining, by the cloud controller 200, whether the write response message sent by the network device exists in the response command queue module 2021, and notifying the CPU 100 by means of an interrupt when the write response message sent by the network device exists in the response command queue module 2021. Specifically, the cloud controller 200 may notify the CPU 100 by means of an interrupt when the read response message is written into the response command queue module 2021. The CPU 100 is further configured to: receive an interrupt message sent by the cloud controller 200, and obtain the write response message from the response command queue module 2021 according to the interrupt message.

[0058] In the foregoing embodiment, the command transmission queue module 2011, the data transmission queue module 2012, the response command queue module 2021, and the data receiving queue module 2022 may be implemented by hardware such as a register or a memory, and are connected to the DDR interface or the like by using a hardware interface. In addition, the command transmission queue module 2011 and the response command queue module 2021 store related commands or messages in an ordered arrangement manner such as in a queue form, and the data transmission queue module 2012 and the data receiving queue module 2022 store related data in an ordered arrangement manner such as in a queue form, so

that the cloud controller 200 can perform reading or writing in a queue form. Specifically, a control unit or a control module of the cloud controller 200 may extract a control command from the command transmission queue module 2011 or the response command queue module 2021, execute the control command, and read data from the data transmission queue module 2012 or write data into the data receiving queue module 2022. The control unit or the control module of the cloud controller 200 is also a hardware control component, and is connected to the command transmission queue module 2011, the data transmission queue module 2012, the response command queue module 2021, the data receiving queue module 2022, and the network interface 204 by using interfaces.

[0059] In an optional implementation, the computer device 10 further includes a memory, and the CPU 100 obtains to-be-read data from the data receiving queue module 2022 and writes the to-be-read data into the memory. For example, the to-be-read data may be written into the memory in a direct memory access (DMA, Direct Memory Access) manner. The writing, by the CPU 100 into the data transmission queue module 2012, the data to be written by means of the write operation is writing, into the data transmission queue module 2012 by configuring a DMA controller of a memory controller (MC, Memory Controller), the data in the memory that is to be written by means of the write operation.

[0060] In this embodiment of the present invention, the network device is a device connected to the computer device by using a network, and includes a device that provides a storage resource or a device that provides an input/output resource. Optionally, the device that provides a storage resource includes a device that provides a memory resource.

[0061] The computer device 10 in the foregoing embodiment may be applied to a high-throughput computer data center, and is used as a high-throughput computer for data processing. When the computer device 10 is used as a high-throughput computer for data processing, the computer device 10 may include at least two CPUs and at least two memories. The at least two CPUs form a CPU resource pool and separately process data in the high-throughput computer data center.

[0062] It should be noted that the DDR interface in the foregoing embodiment is a quick interface for reading/writing data between a CPU and a memory currently. To quickly read/write data, the DDR is used between the CPU 100 and the cloud controller 200, so as to

meet a requirement of quickly obtaining data by the CPU. However, in this embodiment of the present invention, no limitation is imposed on a specific form of an interface used between a CPU and a cloud controller. Another interface that can be used for quickly reading/writing data and that can meet a requirement of quickly reading/writing data by a CPU, for example, an interface whose reading/writing rate is equal to or similar to a reading/writing rate between a CPU and a memory, can be used as an interface between the CPU and the cloud controller.

[0063] The following uses a specific example to describe a schematic structural diagram of a manner of reading/writing remote data by a computer device according to an embodiment of the present invention. As shown in FIG. 4, in addition to a local memory (for example, a DRAM using a DDR interface), a CPU 1 in a CPU resource pool also has remote storage spaces (a storage space A and a storage space B) allocated by a system. Each physical storage space is mapped to a global address space. A mapping relationship of the address space is stored in a driver of a cloud controller corresponding to each CPU. In this embodiment, descriptions are provided by using an example in which the remote storage spaces include only the storage space A and the storage space B. During specific implementation, two or more storage spaces may be included. For example, the CPU 1 has a 10 GB local memory and a 100 G remote storage in total, the CPU 1 can access a remote storage resource pool including the storage space A and the storage space B, and the storage space A and the storage space B each are a storage space with a capacity of 50 G. In this case, the CPU 1 can access a 110 GB storage space in total: a storage space of 0 to 10 GB in the local memory and a storage space of 10 GB to 110 GB in the remote storage resource pool.

[0064] When the CPU 1 accesses the local memory, if an address space of 0 GB to 10 GB is accessed, the address space is mapped to the local memory, and the local memory is accessed by using the DDR interface.

[0065] When the CPU 1 accesses an address space of 10 GB to 110 GB, for example, 1 MB data needs to be written into the address space of 10 GB to 110 GB, the following steps are included:

[0066] Step 1. A driver of the CPU 1 first writes, into a data transmission queue module of a cloud controller 1, the 1 MB data that needs to be written. It is assumed that the data is stored in an address of 5 KB in the data transmission queue module.

[0067] Step 2. The driver of the CPU 1 obtains an address, in the storage resource pool, into which the 1 MB data to be written. Assuming that the address is the 100th GB address, the address is mapped to an address of 40 G in the storage space B. Because an address range mapped to the storage space A is 10 G to 60 G, an address range mapped to the storage space B is 60 G to 110 G.

[0068] Step 3. The driver of the CPU 1 writes, into a command transmission queue module of the cloud controller 1, information about the remote node storage space B, an offset address of 40 G of the storage space B, an address of 5 KB in a data transmission queue, information of a data length of 1 MB, an identifier ID (for example, 0x01) of a current command, and other information. The driver of the CPU 1 may write the command into the command transmission queue module of the cloud controller 1 by writing the command into a particular register.

[0069] Step 4. The cloud controller 1 obtains a new command (that is, the command of writing 1 MB data) from the command transmission queue module after finding that the command transmission queue module is not empty, parses the command to obtain the address of the remote storage space B, the offset address of the storage space B, the command identifier ID, and the data length, and other information, obtains corresponding data from the data transmission queue module according to the address, in the data transmission queue module, of the 1 MB data in the command transmission queue module to create a communications packet, and sends the communications packet to the storage space B by using a network. In this case, if the CPU 1 needs to further perform another write operation, the driver of the CPU 1 may repeatedly perform the foregoing steps, and continue to write corresponding data and a corresponding command into the cloud controller 1.

[0070] Step 5. After the 1 MB data is written into the storage space B, return a packet (carrying the corresponding command identifier ID: 0x01) indicating that data writing is complete. After the cloud controller 1 of the CPU 1 receives the returned packet, the cloud controller 1 of the CPU 1 writes information that a write command is complete into the

response command queue module. The driver of the CPU 1 obtains, by querying the response command queue module, a write complete operation in which an identifier is 0x01, or the response command queue module notifies, by means of an interrupt, the CPU 1 that the write complete operation in which an identifier is 0x01 has been received, and the CPU 1 learns
5 that the write operation of writing 1 MB data in the 100th G address is complete.

[0071] When the CPU 1 accesses an address space of 10 GB to 110 GB, for example, 1 MB data needs to be read from the address space of 10 GB to 110 GB, the following steps are included:

[0072] Step 1. The driver of the CPU 1 obtains an address of to-be-read data in the
10 storage resource pool. Assuming that the address is an address of 100 GB, the address is mapped to an address of 40 G on a node B.

[0073] Step 2. The driver of the CPU 1 writes, into the command transmission queue module of the cloud controller 1, address information of the storage space B, an offset address of 40 G of the to-be-read data in the storage space B, information of a data length of
15 1 MB, an identifier ID (for example, 0x02) of a current command, and other information. The driver of the CPU 1 may write, by writing a command of reading the 1 MB data into a particular register, the command of reading the 1 MB data into the command transmission queue module of the cloud controller 1.

[0074] Step 3. After finding that a command transmission queue is not empty, the cloud
20 controller 1 obtains, from the command transmission queue module, the command of reading the 1 MB data, parses the command to obtain the address information of the remote storage space B, the offset address of the 1 MB data in the storage space B, the command identifier ID, the data length, and other information to create a communications packet, and sends the communications packet to the storage space B by using a network. If the CPU 1 needs to
25 further perform another read or write operation, the CPU 1 may repeatedly perform the foregoing steps, but different command identifiers need to be used to represent different commands.

[0075] Step 4. After reading the corresponding data from the remote storage space B, the cloud controller 1 stores the returned data in the data receiving queue module, and writes, into

the response command queue module, a command identifier ID 0x02, address information (10 KB) in a data receiving queue, a data length of 1 MB, and other information.

[0076] Step 5. The driver of the CPU 1 may query, in a polling manner, a status of the response command queue module, or the response command queue module notifies the CPU 1 by means of an interrupt, and the driver of the CPU 1 learns, by reading the response command queue module, a response message of the reading the 1 MB data. When the response message indicates a read success, the 1 MB data is read from the data receiving queue module according to information, in the data receiving queue module, about the read data and is written into the local memory, or is read by means of DMA by configuring a DMA controller of the CPU.

[0077] The specific implementation is described by using a network device for storing a resource as an example. The computer device provided in this embodiment of the present invention may read data from a device that provides an input/output resource or write data into a device that provides an input/output resource. In this case, the network device is the device that provides the input/output resource.

[0078] An embodiment of the present invention further provides a method for reading/writing data by a computer device. The computer device includes a central processing unit CPU, a cloud controller, and a network interface. The CPU is connected to the cloud controller by using a double data rate DDR interface, and the network interface is configured to connect the cloud controller to a network device. Referring to FIG. 5, FIG. 5 is a schematic flowchart of a method for reading/writing data by a computer device according to an embodiment of the present invention. The method includes the following steps:

[0079] Step 500. The CPU converts a request for performing a read/write operation on the network device into a control command, and writes the control command into a transmission queue module of the cloud controller, where the control command is used to instruct the cloud controller to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation.

[0080] Step 502. The cloud controller performs the read operation or the write operation on the network device according to the operation information in the control command when

the control command in the transmission queue module is triggered, and writes a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device.

[0081] According to the foregoing method embodiment, the CPU is connected to the cloud controller by using the DDR interface, and an interrupt is avoided because the DDR interface has a high data transmission rate. In addition, the CPU converts a read/write operation request into a control command and writes the control command into the transmission queue module of the cloud controller. Because the cloud controller performs the read operation or the write operation on the network device according to operation information in the control command, after writing the control command into the transmission queue module, the CPU does not need to wait for an operation performed by the cloud controller and can continue to perform other service processing, for example, continue to write another control command. This avoids a waste of CPU resources, and improves CPU utilization.

[0082] During specific implementation, if the read/write operation request is a read operation request, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller includes:

converting, by the CPU, the read operation request into a read control command, and writing the read control command into a command transmission queue module of the transmission queue module, where the read control command carries read operation information and is used to instruct the cloud controller to perform a read operation on the network device according to the read operation information; and

the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device includes:

performing, by the cloud controller, the read operation on the network device according to the read operation information in the read control command when the read control command in the command transmission queue module is triggered, receiving a read

response message sent by the network device, writing the read response message sent by the network device into the response command queue module of the response queue module, and writing, into the data receiving queue module of the response queue module, data that is to be read by means of the read operation and that is returned by the network device.

5 **[0083]** The read operation information may include an address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or the read operation information includes a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

10 **[0084]** After converting the read operation request into the read control command and writing the read control command into the command transmission queue module, the CPU may perform another operation, for example, continue to write another read control command or write control command. The cloud controller may extract the read control instruction from the command transmission queue module when the read control command is written into the
15 command transmission queue module, execute the read control command, write a result of executing the read control command into the response command queue module, and write read data into the data receiving queue module when obtaining the read data. In this way, a read operation request is converted into two processes of writing a read control command by a CPU 100 and executing the read control command by the cloud controller. The CPU can
20 execute another task with no need to wait for a result of performing a read operation by the cloud controller, and only needs to obtain a read operation result when a read operation response command is written into the response command queue module. This avoids an interrupt caused because the CPU waits for a read operation result for an excessively long time, and improves resource utilization of the CPU.

25 **[0085]** Further, in this embodiment of the present invention, the CPU may obtain the read operation result by querying in a polling manner or by being notified by means of an interrupt.

[0086] When obtaining the read operation result by querying in a polling manner, the CPU queries, in a polling manner, after writing the read control command into the command
30 transmission queue module, whether the read response message sent by the network device

exists in the response command queue module, that is, repeatedly queries, according to a preset time interval, whether the read response message sent by the network device exists in the response command queue module. When determining that the read response message sent by the network device exists in the response command queue module and the read response message is a read success response message, the CPU reads, from the data receiving queue module, data to be read by means of the read operation.

[0087] When obtaining the read operation result by being notified by means of an interrupt, the cloud controller determines whether the read response message sent by the network device exists in the response command queue module, and notifies the CPU by means of an interrupt when the read response message sent by the network device exists in the response command queue module. The CPU receives an interrupt message sent by the cloud controller, obtains the read response message from the response command queue module according to the interrupt message, and when the obtained read response message indicates a read success, reads, from the data receiving queue module, the data to be read by means of the read operation.

[0088] When the read/write operation request is a write operation request, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller includes:

converting, by the CPU, the write operation request into a write control command, writing the write control command into the command transmission queue module of the transmission queue module, and writing, into the data transmission queue module of the transmission queue module, data to be written by means of the write operation, where the write control command carries write operation information and is used to instruct the cloud controller to write, into the network device according to the write operation information, the data to be written by means of the write operation; and

the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device includes:

when the write control command in the command transmission queue module is triggered, extracting, by the cloud controller from the data transmission queue module according to the write operation information in the write control command, the data to be written by means of the write operation, and writing, into the network device, the data to be written by means of the write operation; and when receiving a write response message sent by the network device, writing the write response message sent by the network device into the response command queue module of the response queue module.

[0089] The write operation information may include an address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation; or the write operation information includes a node address and an offset address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation.

[0090] After converting the write operation request into the write control command and writing the write control command into the command transmission queue module, the CPU may perform another operation, for example, continue to write another read control command or write control command. The cloud controller may extract the write control instruction from the command transmission queue module when the write control command is written into the command transmission queue module, execute the write control command, and write a result of executing the write control command into the response command queue module. In this way, a write operation request is converted into two processes of writing a write control command into the command transmission queue module of the cloud controller and executing the write control command by the cloud controller. The CPU can execute another task with no need to wait for a result of performing a write operation by the cloud controller, and only needs to obtain a write operation result when a write operation response command is written into the response command queue module. This avoids an interrupt caused because the CPU waits for a write operation result for an excessively long time, and improves resource utilization of the CPU.

[0091] Further, in this embodiment of the present invention, the CPU may obtain the write operation result by querying in a polling manner or by being notified by means of an interrupt.

[0092] When obtaining the write operation result by querying in a polling manner, the CPU queries, in a polling manner, after writing the write control command into the command transmission queue module, whether the write response message sent by the network device exists in the response command queue module, and the CPU obtains the write response message when determining that the write response message sent by the network device exists in the response command queue storage module.

[0093] When obtaining the write operation result by being notified by means of an interrupt, the cloud controller determines whether the write response message sent by the network device exists in the response command queue module, and notifies the CPU by means of an interrupt when the write response message sent by the network device exists in the response command queue module. The CPU receives an interrupt message sent by the cloud controller, and obtains the write response message from the response command queue module according to the interrupt message.

[0094] The implementation of the foregoing method embodiment may also be implemented with reference to the implementations of the computer device 10, and no details are repeated.

[0095] A person of ordinary skill in the art may be aware that, in combination with the examples described in the embodiments disclosed in this specification, units and algorithm steps may be implemented by electronic hardware, computer software, or a combination thereof. To clearly describe the interchangeability between the hardware and the software, the foregoing has generally described compositions and steps of each example according to functions. Whether the functions are performed by hardware or software depends on particular applications and design constraint conditions of the technical solutions. A person skilled in the art may use different methods to implement the described functions for each particular application, but it should not be considered that the implementation goes beyond the scope of the present invention.

[0096] It may be clearly understood by a person skilled in the art that, for the purpose of convenient and brief description, for a detailed working process of the foregoing system, apparatus, and unit, reference may be made to a corresponding process in the foregoing method embodiments, and details are not described herein again.

5 **[0097]** In the several embodiments provided in this application, it should be understood that the disclosed system, apparatus, and method may be implemented in other manners. For example, the described apparatus embodiment is merely an example. For example, the unit division is merely logical function division and may be other division in actual implementation. For example, a plurality of units or components may be combined or
10 integrated into another system, or some features may be ignored or not performed. In addition, the displayed or discussed mutual couplings or direct couplings or communication connections may be implemented through some interfaces, indirect couplings or communication connections between the apparatuses or units, or electrical connections, mechanical connections, or connections in other forms.

15 **[0098]** The units described as separate parts may or may not be physically separate, and parts displayed as units may or may not be physical units, may be located in one position, or may be distributed on a plurality of network units. A part or all of the units may be selected according to actual needs to achieve the objectives of the solutions of the embodiments of the present invention.

20 **[0099]** In addition, functional units in the embodiments of the present invention may be integrated into one processing unit, or each of the units may exist alone physically, or two or more units are integrated into one unit. The integrated unit may be implemented in a form of hardware, or may be implemented in a form of a software functional unit.

[0100] When the integrated unit is implemented in the form of a software functional unit
25 and sold or used as an independent product, the integrated unit may be stored in a computer-readable storage medium. Based on such an understanding, the technical solutions of the present invention essentially, or the part contributing to the prior art, or all or a part of the technical solutions may be implemented in the form of a software product. The software product is stored in a storage medium and includes several instructions for instructing a
30 computer device (which may be a personal computer, a server, or a network device) to

perform all or a part of the steps of the methods described in the embodiments of the present invention. The foregoing storage medium includes: any medium that can store program code, such as a USB flash drive, a removable hard disk, a read-only memory (ROM, Read-Only Memory), a random access memory (RAM, Random Access Memory), a magnetic disk, or an optical disc.

[0101] The foregoing descriptions are merely specific embodiments of the present invention, but are not intended to limit the protection scope of the present invention. Any modification or replacement readily figured out by a person skilled in the art within the technical scope disclosed in the present invention shall fall within the protection scope of the present invention. Therefore, the protection scope of the present invention shall be subject to the protection scope of the claims.

CLAIMS

What is claimed is:

1. A computer device, comprising a central processing unit CPU and a cloud controller, wherein the cloud controller comprises a transmission queue module, a response queue
5 module, a double data rate DDR interface, and a network interface, the DDR interface is configured to connect the CPU to the cloud controller, and the network interface is configured to connect the cloud controller to a network device;

the CPU is configured to: after generating a request for performing a read/write
operation on the network device, convert the read/write operation request into a control
10 command, and write the control command into the transmission queue module, wherein the control command is used to instruct the cloud controller to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation; and

the cloud controller is configured to: when the control command in the transmission
15 queue module is triggered, perform the read operation or the write operation on the network device according to the operation information in the control command, receive a response message sent by the network device, and write the response message sent by the network device into the response queue module.

2. The computer device according to claim 1, wherein
20 the read/write operation request is a read operation request;

the transmission queue module comprises a command transmission queue module and a data transmission queue module;

the response queue module comprises a response command queue module and a data receiving queue module;

25 the CPU is specifically configured to: convert the read operation request into a read control command, and write the read control command into the command transmission queue module, wherein the read control command carries read operation information and is used to instruct the cloud controller to perform a read operation on the network device according to

the read operation information; and

the cloud controller is specifically configured to: when the read control command in the command transmission queue module is triggered, perform the read operation on the network device according to the read operation information in the read control command, receive a read response message sent by the network device, write the read response message sent by the network device into the response command queue module, and write, into the data receiving queue module, data that is to be read by means of the read operation and that is returned by the network device.

3. The computer device according to claim 2, wherein

the read operation information comprises an address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or

the read operation information comprises a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

4. The computer device according to claim 2 or 3, wherein

the CPU is further configured to: after writing the read control command into the command transmission queue module, query, in a polling manner, whether the read response message sent by the network device exists in the response command queue module, and when the CPU determines that the read response message sent by the network device exists in the response command queue module and the read response message is a read success response message, read, from the data receiving queue module, the data to be read by means of the read operation.

5. The computer device according to claim 2 or 3, wherein

the cloud controller is further configured to: determine whether the read response message sent by the network device exists in the response command queue module, and notify the CPU by means of an interrupt when the read response message sent by the network device exists in the response command queue module; and

the CPU is further configured to: receive an interrupt message sent by the cloud controller, obtain the read response message from the response command queue module

according to the interrupt message, and when the obtained read response message indicates a read success, read, from the data receiving queue module, the data to be read by means of the read operation.

6. The computer device according to claim 1, wherein

5 the read/write operation request is a write operation request;

the transmission queue module comprises a command transmission queue module and a data transmission queue module;

the response queue module comprises a response command queue module and a data receiving queue module;

10 the CPU is specifically configured to: convert the write operation request into a write control command, write the write control command into the command transmission queue module, and write, into the data transmission queue module, data to be written by means of the write operation, wherein the write control command carries write operation information and is used to instruct the cloud controller to write, into the network device according to the
15 write operation information, the data to be written by means of the write operation; and

the cloud controller is specifically configured to: when the write control command in the command transmission queue module is triggered, extract, from the data transmission queue module according to the write operation information in the write control command, the data to be written by means of the write operation, and write, into the network device, the data to
20 be written by means of the write operation; and when receiving a write response message sent by the network device, write the write response message sent by the network device into the response command queue module.

7. The computer device according to claim 6, wherein

25 the write operation information comprises an address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation; or

the write operation information comprises a node address and an offset address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write
30 operation.

8. The computer device according to claim 6 or 7, wherein

the CPU is further configured to: after writing the write control command into the command transmission queue module, query, in a polling manner, whether the write response message sent by the network device exists in the response command queue module, and when
5 the CPU determines that the write response message sent by the network device exists in the response command queue storage module, obtain the write response message.

9. The computer device according to claim 6 or 7, wherein

the cloud controller is further configured to: determine whether the write response message sent by the network device exists in the response command queue module, and
10 notify the CPU by means of an interrupt when the write response message sent by the network device exists in the response command queue module; and

the CPU is further configured to: receive an interrupt message sent by the cloud controller, and obtain the write response message from the response command queue module according to the interrupt message.

15 10. A method for reading/writing data by a computer device, wherein the computer device comprises a central processing unit CPU, a cloud controller, and a network interface, the CPU is connected to the cloud controller by using a double data rate DDR interface, and the network interface is configured to connect the cloud controller to a network device; and the method comprises:

20 converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller, wherein the control command is used to instruct the cloud controller to perform a read operation or a write operation on the network device, and the control command carries operation information of the read operation or the write operation;

25 and

performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command when the control command in the transmission queue module is triggered, and writing a response message sent by the network device into a response queue module of the cloud controller
30 when receiving the response message sent by the network device.

11. The method according to claim 10, wherein

the read/write operation request is a read operation request;

correspondingly, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller comprises:

converting, by the CPU, the read operation request into a read control command, and writing the read control command into a command transmission queue module of the transmission queue module, wherein the read control command carries read operation information and is used to instruct the cloud controller to perform a read operation on the network device according to the read operation information; and

the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud controller when receiving the response message sent by the network device comprises:

performing, by the cloud controller, the read operation on the network device according to the read operation information in the read control command when the read control command in the command transmission queue module is triggered, receiving a read response message sent by the network device, writing the read response message sent by the network device into the response command queue module of the response queue module, and writing, into the data receiving queue module of the response queue module, data that is to be read by means of the read operation and that is returned by the network device.

12. The method according to claim 11, wherein

the read operation information comprises an address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation; or

the read operation information comprises a node address and an offset address, in the network device, of the data to be read by means of the read operation and a length of the data to be read by means of the read operation.

13. The method according to claim 11 or 12, wherein the method further comprises:

after writing the read control command into the command transmission queue module,

querying, by the CPU in a polling manner, whether the read response message sent by the network device exists in the response command queue module, and when the CPU determines that the read response message sent by the network device exists in the response command queue module and the read response message is a read success response message, reading, from the data receiving queue module, the data to be read by means of the read operation.

14. The method according to claim 11 or 12, wherein the method further comprises:

determining, by the cloud controller, whether the read response message sent by the network device exists in the response command queue module, and notifying the CPU by means of an interrupt when the read response message sent by the network device exists in the response command queue module; and

receiving, by the CPU, an interrupt message sent by the cloud controller, obtaining the read response message from the response command queue module according to the interrupt message, and when the obtained read response message indicates a read success, reading, from the data receiving queue module, the data to be read by means of the read operation.

15. The method according to claim 10, wherein

the read/write operation request is a write operation request;

correspondingly, the converting, by the CPU, a request for performing a read/write operation on the network device into a control command, and writing the control command into a transmission queue module of the cloud controller comprises:

converting, by the CPU, the write operation request into a write control command, writing the write control command into the command transmission queue module of the transmission queue module, and writing, into the data transmission queue module of the transmission queue module, data to be written by means of the write operation, wherein the write control command carries write operation information and is used to instruct the cloud controller to write, into the network device according to the write operation information, the data to be written by means of the write operation; and

the performing, by the cloud controller, the read operation or the write operation on the network device according to the operation information in the control command, and writing a response message sent by the network device into a response queue module of the cloud

controller when receiving the response message sent by the network device comprises:

when the write control command in the command transmission queue module is triggered, extracting, by the cloud controller from the data transmission queue module according to the write operation information in the write control command, the data to be written by means of the write operation, and writing, into the network device, the data to be written by means of the write operation; and when receiving a write response message sent by the network device, writing the write response message sent by the network device into the response command queue module of the response queue module.

16. The method according to claim 15, wherein

the write operation information comprises an address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation; or

the write operation information comprises a node address and an offset address of the network device, a length of the data to be written by means of the write operation, and an address, in the data transmission queue, of the data to be written by means of the write operation.

17. The method according to claim 15 or 16, wherein the method further comprises:

after writing the write control command into the command transmission queue module, querying, by the CPU in a polling manner, whether the write response message sent by the network device exists in the response command queue module, and when the CPU determines that the write response message sent by the network device exists in the response command queue storage module, obtaining the write response message.

18. The method according to claim 15 or 16, wherein the method further comprises:

determining, by the cloud controller, whether the write response message sent by the network device exists in the response command queue module, and notifying the CPU by means of an interrupt when the write response message sent by the network device exists in the response command queue module; and

receiving, by the CPU, an interrupt message sent by the cloud controller, and obtaining the write response message from the response command queue module according to the interrupt message.