

Radio frequency identification flat sheet material

The invention relates to the field of radio frequency identification, in particular, to materials containing the radio frequency labels in its layers and intended for printing and stamping by commonly available printing methods.

The following terms and abbreviations will be used hereinafter.

Radio frequency identification (abbr. RFID) is a method of transmitting wireless information in which the data stored in so-called transponders or RFID tags by means of radio signals are read or written. Generally, the RFID tags are passive, in other words, they do not include batteries.

Chip – an integrated (micro)circuit is a microelectronic device with the complexes of input resistances and/or building networks made of the semiconductor plate. The chip processes signals when receiving and transmitting information by means of the radio frequency communication with a reader, it contains a protected memory, user memory, a unique identification number, it may contain a processor for cryptography processing, programmable space to run microprograms, etc.

The antenna is a conductor configuration, which geometrically and technically is made in accordance with the type of chip used. The antenna can be closed (HF range) and open type (UHF range). The antenna comes in different shapes: the circle, oval, square, rectangle, and other free geometric shapes. The antenna's shape is designed in accordance with the specification of the chip used. The antenna is made of materials containing conductive substances, such as aluminum, copper, silver, tin, gold, graphite, and other materials. The antenna is to be applied on the substrate made of thin-film, synthetic materials, and paper by etching, silk screen printing (screen printing), thermal transfer, stamping, inkjet, offset, as well as flexographic and digital printing with special inks.

The RFID inlay is a part of the RFID product that consists of the substrate and contains at least one chip and one antenna. The location of the antennas and chips can be either synchronous relative to the sides of the sheet material with the radiofrequency tag or asynchronous, depending on the intended design and configuration of the future RFID product. The additional components can be located on the inlay, for example, capacitors, resistors, sensors, microcontrollers, etc.

The RFID tag is a combination of the chip and antenna.

The RFID product is a final product, containing an RFID tag, for example, a card, tag, label, sticker, packaging, bracelet, or other forms of the product that can be obtained by cutting it from the sheet of RFID material that includes an RFID inlay.

The RFID reader is a device designed to exchange data with RFID products, for example, information reading and writing.

The polymer composite is a composite material whose matrix is formed of polymers or elastomers.

5 Bulking paper, so-called raw paper, that has not been processed by a calendaring press, for example, with a puffiness factor of more than 1.30, is traditionally used in order to obtain a sufficiently flat surface of the material with the RFID tag. In such paper, the chip is pressed using external pressure to ensure an acceptable material surface flatness.

10 This method exposes the chip to significant pressure, which affects the occurrence of crystal deformations and the possible failure of the chip. It's also possible that hidden defects appear, whose occurrence cannot be identified in the production process. The thickness of the bulking paper should be enough to create a chip pocket. Bulking paper is usually more expensive, as it is a rare material on the printing market. Bulking paper is limited in choice and printing method. The chip can become detached from this structure as time goes by, especially if
15 storage climatic conditions change. This method limits the range of surface materials used.

20 The closest analog of the claimed invention is a sheet material with radio frequency identification, it is known from patent JP 5916028. The material has a paper-like structure in which the RFID tag is placed between the first paper layer and the second paper layer. The material is equipped with a slot that corresponds to the RFID chip. What's more, the height of the protective material upper surface is greater than the height of the RFID chip's upper surface.

25 However, the invention's background has disadvantages. The additional layer is required for manufacturing material in which holes that match the arrangement of the chips on the RFID inlay are arranged beforehand, the geometric size of the hole should be close to the size of the chip, and the thickness of this layer should correspond to the height of the chip. High-precision rotor equipment is required for combining when the alignment of the chip geometric dimensions - the change of equipment rigging. The presence of this layer increases the cost of production, complicates the production process, and reduces flexibility when changing the RFID inlay layout.

30 The technical problem the claimed invention aims to solve is to create a sheet material incorporating radio frequency identification with a surface that is sufficiently flat on both sides of the sheet for simple typographical printing, and the method of manufacturing of such a material is simple and cost-effective. It is not necessary to change the manufacturing process when changing the RFID inlay layout.

The technical result of the invention is to obtain the flexible flat sheet material in which the chips and other electronic components do not affect the level of the sheet material surface flatness.

5 The claimed material manufacturing does not impose special requirements and does not require the additional adaptation of its layers. The outer surface of the material is flat and smooth, regardless of the chip height or the electronic components used or their configuration on the inlay. The surface does not change over time.

10 The use of the claimed invention allows to simplify and accelerate the production of sheet materials suitable for printing on both sides and containing the RFID and other electronic components in its composition.

15 The inventive material provides the printing in various printing methods: offset printing, silk screen printing, inkjet, or digital printing. The material's flexibility and elasticity allow it to pass freely along the path of the printing presses, like conventional paper. The material does not change its plane-parallelism after heating up in printing equipment and during storage. The paint lays without any flaws at the location of the chips and electronic components.

This result is achieved due to the fact that the material contains a polymer film, which is finally formed in its geometry, taking into account all protruding elements, for example, the chip on the surface of the inlay, on both its sides. The polymer film is fixed on one or both sides of the RFID inlay.

20 This polymer film is formed when producing the sheet material from the polymer composite in one technological operation. The polymer composite is applied in a liquid state that makes it possible to cover the protruding RFID elements of the inlay, flowing around them. The polymer film can be formed on both sides of the inlay, including if additional electronic components are available on the rear side of the inlay. The polymer composite also has adhesive
25 properties that make it possible to reliably glue together two adjacent materials.

This polymer film is an excellent dielectric and it can freely contact the RFID chip and antenna, electronic components, and conductive tracks, which also makes it possible to ensure the use of the product in a humid environment. The polymer film has the property of the elastomer, it has extensive operating temperature ranges, from -60 to +120°C, without losing its
30 technical characteristics, which allows it to be used in the digital printing machines that expose the material to heat. Due to this, the materials are not changed due to the impact of thermal or mechanical influences, if necessary, for example, the material can be bent, but it always returns to its original shape afterward.

The polyurethane-based polymer film does not change its properties over time, it does not change its color, and it is protected against UV rays. The color of the formed polymer film can be transparent or any other by adding coloring agents.

5 The chip and other electronic products inside the material are reliably protected from mechanical stress as they are completely positioned inside the formed polymer film, which significantly increases the product life and mechanical stability during operation.

10 The claimed technical result is achieved due to the fact that the flat sheet material with radio frequency identification contains the sequentially arranged first layer of flexible material, the first intermediate layer, the substrate layer with an antenna and a chip, the second intermediate layer, the second layer of the flexible material, what's more, the first intermediate layer is made of polymer composite.

The invention is explained using Fig. 1-3, which shows:

Fig. 1 is a general view of sheet material with twenty-four radio frequency tags;

Fig. 2 – sheet material sectional view.

15 Positions 1-9 are showing in Fig. 1-2:

1 – sheet material;

2 – the first layer of the flexible material;

3 – the first intermediate layer of the polymer composite;

4 – chip;

20 5 – the layer substrate with the antenna and chip;

6 – the second intermediate layer;

7 – the second layer of the flexible material;

8 – antenna;

9 – beveled corner.

25 Flat sheet material 1 with the radio-frequency identification contains the sequentially arranged first layer 2 of flexible material, the first intermediate layer of polymer composite 3, the substrate layer 5 with antenna 8 and chip 4, the second intermediate layer 6, the second layer of flexible material 7.

The device has a sandwich structure (Fig. 1).

30 The first 2 and the second 7 layers of flexible material are printing layers.

The first 2 and the second 7 layers of flexible material can be made of offset, craft, or recycled paper; cardboard; synthetic paper, can be made of PET (Polyethylene Terephthalate), PVC (Polyvinyl Chloride), PP (Polypropylene), PE (Polyethylene), natural or synthetic fabric, artificial leather based on PVC (Polyvinyl chloride) or PU (Polyurethane), or a layer of another
35 suitable material. The flexible material can be either white or painted in any color, it should have

markings, patterns or inscriptions, textured surface or additional coating, including the primer that retains surface paint better, and it should contain metalized layers, magnet layers, metal chips, and other materials.

The flat sheet material with radio frequency identification can have the first 2 and second 5 7 layers of various flexible material, the front and back sides made of one or different grades and colors of paper, or contain the paper on one side and synthetic material on the other side, fabric, or have a siliconized layer on one side and other combinations, including those containing the metallized layers, magnetic layers, and other materials.

The polymer composite from the group of polyurethanes (polyester-polyols) is used as a 10 polymer composite.

The first 3 and second 6 intermediate layers can be made of the same material or have different properties. For example, the second intermediate layer 6 may possess residual adhesive properties, in which case it is possible to get the label in combination with the second layer of flexible material 7 coated with silicone.

15 The substrate 5 may be made, for example, of PET, special paper, or another suitable flexible material.

Antenna 8 can be made by etching or sputtering of aluminum, alloys based on copper, silver, gold, graphite, or any other conductive material suitable for chip 4's operation.

20 Antenna 16, in particular, has a rectangular shape (Fig. 2). More than one antenna with a chip, depending on the purpose, can be integrated into the sheet. Twenty-four RFID tags, which respectively contain twenty-four antennas on the substrate, are shown in Fig. 2.

The sheet material can be made in the form of standard sizes rectangular sheet: A4 size 210 mm by 297 mm, SRA3 size 320 mm by 460 mm, SRA3+ size 325 mm by 480 mm, SRA2+ size 520 mm by 720 mm, in the form of a roll with a width from 210 mm up to 850 mm, and 25 other sizes.

The sheet material can be made in the form of a rectangular sheet, in which one of the corners is geometrically different from three others, for example, it has a 45° bevel, the radius, and an internal recess.

30 The beveled corner is a positional angle for the sheet material, it ensures the correct location of the sheet at various stages of manufacturing the finished product by printing plants: stamping and die-cutting. The positional angle, in contrast to the graphically plotted angle, is more convenient, since it makes it possible to check the correct location of the sheet in the middle of the stack.

35 LEDs, sensors, transducers, thin-film batteries, and other electronic components can also be placed inside the sheet.

The positional elements can be located inside the sheet, whereby the induction sensors find the location of the RFID tags to position the sheet during printing, cutting, or other necessary operations in punching and other printing machines.

The resulting sheet thickness varies from 0.15 mm to 5.0 mm.

5 The machine-readable unique sheet number can be applied on each sheet, for example, the barcode, QR code, and other graphic elements. The tags located on the RFID sheet are linked by this number. The unique numbers of the RFID tags, located inside the sheet material are known in advance for printing plant, when the print file generating by the printing plant, that allows to print this information in one go, thereby avoiding the additional manipulations for
10 reading data from RFID tags and its subsequent additional application of graphics on the RFID product.

After printing, the sheet material with radio frequency identification can be further processed, for example, partial foil stamping, varnishing, application of laminating films based on BOPP (biaxially oriented polypropylene film), PVC, PET.

15 The sheet material is made as follows.

The first intermediate layer 3 of the polymer composite is applied in liquid form with a viscosity of 500 to 20,000 mPA*s (millipascals per second), and a thickness of 0.01 mm to 3 mm between the first layer 2 of flexible material and substrate layer 5 with antenna 8 and chip 4. Then, the second intermediate layer 6 of the polymer composite is applied in liquid form with a
20 thickness of 0.01 mm to 3 mm and a viscosity of 500 to 20,000 mPA*s (millipascals per second), or glue between the second layer 7 of flexible material and the layer of substrate 5 with antenna 8 and chip 4, if necessary.

The material passes through the system of presses, which allows you to fix the thickness of the material at the outlet and detect the recesses in the liquid polymer composite from the
25 protruding components. The deposited polymer composite goes through the polymerization stage and becomes a polymer film in this state.

The thickness of the polymer composite deposition is selected empirically, depending on the materials used, the properties of spreading over the surface, the height of the electronic components, and other factors.

30 The viscosity depends on the technical properties of the polymer composite used and the application temperature. It is selected empirically and usually ranges from 500 to 20,000 mPA*s (millipascals per second). The polymer composite material can be three-component, two-component, and one-component type.

The high-strength polymer film is formed after polymerizing the polymer composite,
35 which is no longer subjected to geometric changes, even during heating, thereby the pressure of

the chip and electronic components on the substrate does not appear on the first 2 and second 7 layers of the flexible material, since the formed polymer film starts to compensate its height. The material is flat and flexible, which provides a flat surface suitable for printing on both sides.

5 The stated sheet material can be used to produce classic products with RFID tags and other electronic components in the form of labels, tags, postcards, stickers, boxes, RFID cards, NFC business cards, and other similar products.

The feature of the invented material is its flat surface and elasticity for typographical printing.

10 The second feature is that the formed polymer film in the composition of the sheet material does not pass oxygen, which makes it possible to use the resulting material in manufacturing the packages with radio frequency identification for food products.

CLAIMS

1. A flat sheet material with radio frequency identification *contains* a sequentially arranged first layer of flexible material, a first intermediate layer, a substrate layer with an antenna and a chip, a second intermediate layer, a second layer of flexible material, and the first intermediate layer made of polyurethanes polymer composite.
2. The material according to claim 1 *is characterized by the fact that* the second intermediate layer is made of the polymer composite.
3. The material according to claim 1 *is characterized by the fact that* the second intermediate layer is glue layer.
4. The material according to claim 1 *is characterized by the fact that* first layer of flexible material or second layer of flexible material is selected as paper.
5. The material according to claim 1 *is characterized by the fact that* first layer of flexible material or second layer of flexible material is selected as non-woven fabric.
6. The material according to claim 1 *is characterized by the fact that* first layer of flexible material or second layer of flexible material is selected as polymeric film.
7. The material according to claim 1 *is characterized by the fact that* first layer of flexible material or second layer of flexible material is selected as cloth.
8. The material according to claim 1 *is characterized by the fact that* it is made in the form of a rectangular sheet with a 45° beveled angle.
9. The material according to claim 1 *is characterized by the fact that* it is made in the form of a sheet sized 210 mm by 297 mm.
10. The material according to claim 1 *is characterized by the fact that* it is made in the form of a sheet sized 320 mm by 460 mm.
11. The material according to claim 1 *is characterized by the fact that* it is made in the form of a sheet sized 325 mm by 480 mm.
12. The material according to claim 1 *is characterized by the fact that* it is made in the form of a sheet sized 520 mm by 720 mm.
13. The material according to claim 1 *is characterized by the fact that* it includes a layer of polymeric film over the flexible material layer.
14. The material according to claim 1 *is characterized by the fact that* it is made in the form of roll with a width of 210 mm to 750 mm.

15. The material according to claim 1 *is characterized by the fact that* it includes additional electronic components.

16. The material according to claim 13 *is characterized by the fact that* polymeric film is made as nontransparent or colored.