

[DESCRIPTION]

[Title of Invention] MICROBUBBLE GENERATING DEVICE

[Technical Field]

[0001]

The present invention relates to a fine bubble generating device for micronizing introduced gas to generate fine bubbles such as microbubbles or nanobubbles.

[Background Art]

[0002]

The technology shown in Figure **12** has been known as such a fine bubble generating device (see, for example, Patent Literature 1). In this fine bubble generating device **100** consisting of a container body **102** with a conical space **101** that is closed on one end with a wall and open on the other end, a gas introducing bore **103** formed on the wall on the one end, and a pressurized liquid introducing inlet **104** formed on a part of an inner wall circumferential surface of the conical space **101** in a tangential direction thereof, the wall on the one end is comprised of a conical or truncated conical shaped part which protrudes out toward the other end, such that the longitudinal cross-sectional shape of the space on the one end has an M shape, and a swirling gas-liquid mixture solution including fine bubbles is drawn out from a swirling gas-liquid drawing outlet **105** of the cylindrical space **101** on the other end.

[0003]

With the fine bubble generating device **100**, a swirl flow is formed from the inlet (pressurized liquid introducing inlet) **104** toward the outlet (swirling gas-liquid drawing outlet) **105** by providing the conical space **101** in a device container. The swirl flow rate and the flow rate towards the outlet simultaneously increase at locations closer to the swirling gas-liquid drawing outlet **105** in accordance with the tapered shape of the conical space **101**. By the generation of differences in swirl rates, a strand-like gas whirling tube section **106** is

continuously and stably severed, resulting in generation of a large quantity of fine bubbles.

[Citation List]

[Patent Literature]

[0004]

[PTL 1] Japanese Patent No. 4725707

[Summary of Invention]

[Technical Problem]

[0005]

However, the conventional fine bubble generating device **100** disclosed in Patent Literature 1, while capable of generating a large quantity of fine bubbles, had a problem that a generation peak period thereof does not continue when pump water pressure was low. The reason therefor is discussed in detail below while referring to Figure **13**.

[0006]

First, bubbles are disintegrated and fragmented by the shear force of a swirl flow inside the container body **101**, and then the fragmented fine bubbles are strongly discharged from the swirling gas-liquid drawing outlet **105** so that a generation peak period **P** shown in Figure **13** starts. At this time, a low liquid pressure section **107** with a very low liquid pressure centered around the gas whirling tube section **106** is formed in the vicinity of the swirling gas-liquid drawing outlet **105** in the container body **102**. The low liquid pressure section **107**, due to the balance with liquid pressure outside the container body **102**, exerts an effect such that liquid from outside the container body **102** flows in toward the swirling gas-liquid drawing outlet **105**. As a result, the shear force of the swirl flow is weakened. Eventually, generation of fine bubbles is no longer sustained, and fine bubble generation becomes stable at a low level to settle at a static state **S** as shown in Figure **13**. That is, a peak period of fine bubble generation starts momentarily, but the state is not sustained.

[0007]

The present invention was conceived under the aforementioned circumstances. The primary objective of the present invention is to provide a fine bubble generating device, which has a simple configuration and is capable of stably and sustainably discharging a larger quantity of fine bubbles from a discharging section.

[Solution to Problem and Advantageous Effects of Invention]

[0008]

According to the fine bubble generating device with respect to the first aspect of the present invention, in a fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and the fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, the fine bubble generating section can be configured such that the fine bubble generating section comprises a container body, a first liquid fluid introducing section provided on the container body for introducing the liquid fluid pumped out from the pumping section into the container body, a discharging section provided on the container body for discharging the liquid fluid introduced from the first liquid fluid introducing section, a liquid fluid swirling section provided in the container body for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section, and a discharged flow volume adjusting section for adjusting a discharged flow volume of a liquid fluid from the discharging section to repeatedly generate a first state, in which an increase in discharged flow volume of a liquid fluid from the discharging section leads to a decrease in a liquid pressure

around a swirl axis of a swirl generated by the liquid fluid swirling section, resulting in a liquid pressure in the vicinity of the discharging section in the container body being lower than a liquid pressure outside the container body to exert an effect of closing the discharging section, and a second state in which a decrease in the discharged flow volume of a liquid fluid from the discharging section results in a liquid pressure in the vicinity of the discharging section in the container body being higher than a liquid pressure outside the container body to exert an effect of opening the discharging section.

[0009]

By the aforementioned configuration, as shown in Figure 1, a fine bubble increasing period **I** starts where a liquid fluid introduced into the container body becomes a swirl flow by the liquid fluid swirling section in the container body and the swirl rate thereof increases so that a vortex shear force increases and thereby fine bubbles are further fragmented, and a fine bubble generation peak period **P** starts where bubbles are strongly discharged from the discharging section due to a liquid pressure in the vicinity of the discharging section in the container body being higher than a liquid pressure outside the container body.

[0010]

When the discharged flow volume of a liquid fluid from the discharging section starts to increase, the inside of the container body enters a first state in which a liquid pressure around a swirl axis of a swirl generated by the liquid fluid swirling section decreases, resulting in a liquid pressure in the vicinity of the discharging section in the container body being much lower than a liquid pressure outside of the container body to exert an effect of closing the discharging section. For this reason, the fine bubble generation peak period **P** is not sustained and starts to transition to a fine bubble decreasing period **D** with decreasing fine bubble generation. As a result,

the discharged flow volume of liquid fluid from the discharging section decreases.

[0011]

However, when the discharged flow volume of liquid fluid from the discharging section starts to decrease, a second state starts in which a liquid pressure in the vicinity of the discharging section in the container body becomes higher than a liquid pressure outside the container body to exert an effect of opening the discharging section. In other words, after the fine bubble increasing period **I** has started, the fine bubble generation peak period **P** starts again in which the liquid fluid in the container body is strongly discharged from the discharging section.

[0012]

That is, since the first state and the second state are repeatedly generated so that the fine bubble generation peak period **P** repeatedly arises, the average number of generated fine bubbles **A** increases and thereby the fine bubbles can be stably and sustainably discharged from the discharging section.

[0013]

According to the fine bubble generating device with respect to the second aspect of the present invention, the discharged flow volume adjusting section can be configured such that the discharged flow volume adjusting section comprises an axis provided approximately perpendicular to the discharging section and supported by the container body, a baffle board that has an insertion bore through which the axis is inserted, the axis being inserted through the baffle board so that the baffle board is movable in the axial direction of the axis, and a stopper section provided to prevent the baffle board from being released from the axis at a position where a suction force of a low liquid pressure generated in the container body reaches, wherein, when a liquid pressure in the vicinity of the discharging section in the container body is higher than a liquid pressure outside

the container body, the baffle board is subjected to an effect to move away from the discharging section by discharge of the liquid flow from the discharging section to open the discharging section, and, when the liquid pressure in the vicinity of the discharging section in the container body is lower than the liquid pressure outside the container body, the baffle board is subjected to an effect to move closer to the discharging section by suction from the discharging section to close the discharging section.

[0014]

By the aforementioned configuration, a first state starts, in which the discharging section is opened so that a low liquid pressure inside the container body is induced, and the baffle board is pulled by a suction force generated by the low liquid pressure and thereby the discharging section is closed. While the transition to the fine bubble decreasing period **D** starts and the number of the fine bubbles from the discharging section starts to decrease, a physical stimulation by the baffle board can be applied to the fine bubbles from the discharging section and thereby the fine bubbles from the discharging section in a decreasing trend are fragmented. A large quantity of fine bubbles can be generated again thereby. In other words, the average number of generated fine bubbles **A** is further increased and thereby the fine bubbles can be stably and sustainably discharged from the discharging section. For instance, Figure 1 shows a case where physical stimulation by the baffle board is absent, and Figure 2 shows a case where physical stimulation by a baffle board is applied. As shown in Figure 2, the discharged flow volume of fine bubbles in the first state increases.

[0015]

By the aforementioned configuration, the baffle board vibrates or swings to stir the liquid inside a tank, such that fine bubbles in the tank can be uniformly distributed.

[0016]

Furthermore, according to the fine bubble generating device with respect to the third aspect of the present invention, the axis has an end with a large outer diameter and an end with a small outer diameter and is formed to have an outer diameter that gradually increases from the small outer diameter end to the large outer diameter end, and the stopper section can be configured such that the movement of the baffle board is restricted at a position where the outer diameter of the axis is approximately identical to the inner diameter of the insertion bore of the baffle board.

[0017]

Furthermore, according to the fine bubble generating device according with respect to the fourth aspect of the present invention, the stopper section comprises a washer through which the axis is inserted, and the stopper section can be configured such that the washer restricts the movement of the baffle board from the discharging section to a direction of discharging a liquid fluid, and acts as a buffering material. By the aforementioned configuration, a washer can suppress variation in movement due to a difference in the material or shape of a baffle board to assist in more stable movement of the baffle board.

[0018]

Furthermore, according to the fine bubble generating device with respect to the fifth aspect of the present invention, the container body can be configured such that an internal space thereof having an annular shape from a cross-sectional view gradually decreases toward the discharging section. By the aforementioned configuration, an incline is formed on the inner wall of the container body. Thus, the swirl rate of a swirl flow generated in the container body by a liquid fluid swirling section is increased and thereby a vortex shear force is increased so that the bubbles are disintegrated and further fragmented.

[0019]

Furthermore, according to the fine bubble generating device with respect to the sixth aspect of the present invention, the gas introducing section can be configured to be provided upstream of the pumping section. By the aforementioned configuration, for example, a separate device for introducing gas such as a compressor is no longer required, resulting in simplification of facility and cost reduction.

[0020]

Furthermore, according to the fine bubble generating device with respect to the seventh aspect of the present invention, the gas introducing section can be configured such that the gas introducing section is provided so that one end of a tube is directed toward the discharging section and, when a liquid pressure in the vicinity of the discharging section in the container body is lower than a liquid pressure outside the container body, gas is introduced into the container body through the tube by suction from the discharging section. By the aforementioned configuration, for example, a separate device for introducing gas such as a compressor is no longer required, resulting in simplification of facility and cost reduction, and gas would not be excessively introduced into the pumping section, resulting in no risk that the pumping section idly spins and thereby breaks.

[0021]

Furthermore, according to the fine bubble generating device with respect to the eighth aspect of the present invention, the gas introducing section can be configured such that the tube and the axis which is tubular are connected. By the aforementioned configuration, the axis can also serve the role of a tube. Furthermore, the tube is secured to the axis thereby to be stabilized.

[0022]

Furthermore, according to the fine bubble generating device with respect to the ninth aspect of the present invention, the inner wall of the container body has an annular cross-section in the direction of the discharging section, and the first liquid fluid introducing section can be configured so that the liquid fluid is introduced along the tangential direction of the annular shape from a cross-sectional view and thereby the liquid fluid is swirled in a spiral toward the discharging section. By the aforementioned configuration, the first liquid fluid introducing section and the liquid fluid swirling section serve the roles of each other. For instance, a liquid fluid can be swirled in a spiral without separately providing a screw. Thus, the configuration is further simplified and more economical in terms of production or running cost.

[0023]

Furthermore, according to the fine bubble generating device with respect to the tenth aspect of the present invention, the container body can be configured such that the container body comprises a reverse swirl flow generating wall for separating the container body into a double-layer structure of a main swirl chamber and a preliminary swirl chamber and a second liquid fluid introducing section provided on the reverse swirl flow generating wall for introducing the liquid fluid from the preliminary swirl chamber to the main swirl chamber so that a second swirl flow in the opposite direction from a first swirl flow introduced from the first liquid fluid introducing section generates. By the aforementioned configuration, bubbles are disintegrated and fragmented by a vortex shear force generated when the first swirl flow is changed to a second swirl flow in the direction opposite to the first swirl flow by the second liquid fluid introducing section.

[0024]

Furthermore, according to the fine bubble generating device with respect to the eleventh aspect of the present invention, in a fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and the fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, a fine bubble generating section is configured such that the fine bubble generating section comprises a container body, a first liquid fluid introducing section for introducing a liquid fluid pumped out from the pumping section into the container body, a discharging section for discharging the liquid fluid, and a liquid fluid swirling section for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section, wherein the container body comprises a reverse swirl flow generating wall for separating the container body into a double-layer structure of a main swirl chamber and a preliminary swirl chamber and a second liquid fluid introducing section provided on the reverse swirl flow generating wall for introducing the liquid fluid from the preliminary swirl chamber to the main swirl chamber so that a second swirl flow in the opposite direction from a first swirl flow introduced from the first liquid fluid introducing section generates. By the aforementioned configuration, bubbles are disintegrated and fragmented by a vortex shear force generated when the first swirl flow is changed to the second swirl flow in the direction opposite to the first swirl flow by the second liquid fluid introducing section.

[0025]

Furthermore, according to the fine bubble generating device with respect to the twelfth aspect of the present

invention, in a fine bubble generating section of a fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and the fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, the fine bubble generating section can be configured such that the fine bubble generating section comprises a container body, a first liquid fluid introducing section provided on the container body for introducing a liquid fluid pumped out from the pumping section into the container body, a discharging section provided on the container body for discharging a liquid fluid introduced from the first liquid fluid introducing section, a liquid fluid swirling section provided in the container body for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section, and a discharged flow volume adjusting section for adjusting a discharged flow volume of a liquid fluid from the discharging section to repeatedly generate a first state, in which an increase in discharged flow volume of a liquid fluid from the discharging section leads to a decrease in a liquid pressure around a swirl axis of a swirl generated by the liquid fluid swirling section, resulting in a liquid pressure in the vicinity of the discharging section in the container body being lower than a liquid pressure outside the container body to exert an effect of closing the discharging section, and a second state in which a decrease in the discharged flow volume of a liquid fluid from the discharging section results in the liquid pressure in the vicinity of the discharging section in the container body being higher than the liquid pressure outside

the container body to exert an effect of opening the discharging section.

[Brief Description of Drawings]

[0026]

[Figure 1] Figure 1 is a schematic diagram for explaining the principle of stably and sustainably generating fine bubbles in the present invention and showing the number of generated fine bubbles when a physical stimulation by a baffle board is not taken into consideration.

[Figure 2] Figure 2 is a schematic diagram for explaining the principle of stably and sustainably generating fine bubbles in the present invention and showing the number of generated fine bubbles when a physical stimulation by a baffle board is taken into consideration.

[Figure 3] Figure 3 is a schematic diagram showing the configuration of the fine bubble generating device according to the first Example of the present invention.

[Figure 4] Figure 4 is a cross-sectional view in the longitudinal direction of the fine bubble generating section according to the present invention.

[Figure 5] Figure 5 is a diagram provided to explain the shape of the inner wall of the container body of the present invention. Figure 5A shows an example of a stepped tapered shape, and Figure 5B shows an example of a tapered shape.

[Figure 6] Figure 6 is a schematic diagram of the fine bubble generating device according to the second Example of the present invention.

[Figure 7] Figure 7 is a schematic diagram of the fine bubble generating device according to the third Example of the present invention.

[Figure 8] Figure 8 is an expanded diagram of the fine bubble generating section of the fine bubble generating device according to the third Example of the present invention. Figure 8A is a cross-sectional view in the longitudinal direction, and

Figure **8B** is a cross-sectional view that is transverse with respect to the direction toward the discharging section.

[Figure **9**] Figure **9** is a diagram provided to explain the structure of the inner wall of the container body of the present invention. Figure **9A** is a cross-sectional view in the longitudinal direction, and Figure **9B** is a cross-sectional view in the transverse direction.

[Figure **10**] Figure **10** is a flow chart showing the operation of the fine bubble generating device according to the first Example of the present invention.

[Figure **11**] Figure **11** is a flow chart showing the operation of the discharged flow volume adjusting section according to the first Example of the present invention.

[Figure **12**] Figure **12** is a schematic diagram of a conventional example of a device for rotating a suction fin to generate a liquid flow thereby to draw in gas into the liquid flow and repeating shearing and stirring of a gas-liquid mixture fluid to generate fine bubbles.

[Figure **13**] Figure **13** is a schematic diagram of a conventional example for explaining the principle of generating fine bubbles.

[Description of Embodiments]

[0027]

The embodiments of the present invention are explained hereinafter based on the drawings. However, the embodiments set forth below are examples for materialization of the technical idea of the present invention. The present invention is not limited thereto. Further, the present specification is not intended to specify the components set forth in the Claims to the components in the embodiments. In particular, the dimension, material, shape, relative arrangement, and the like of constituents described in the embodiments are merely examples used for explanation and are not intended to limit the scope of the present invention thereto, unless specifically noted

otherwise. The size, positional relationship, or the like of a component in each diagram may be exaggerated to clarify the explanation. Furthermore, the same names and symbols in the following explanation indicate the same or similar-quality components. Detailed explanation thereof is omitted when appropriate. Furthermore, each element constituting the present invention can be materialized as an embodiment in which multiple elements are configured by a single member so that the single member is used for multiple elements, or in which, conversely, function of a single member is shared by multiple members.

(First Embodiment)

(Configuration of fine bubble generating device)

[0028]

Figure 3 shows a schematic diagram illustrating the entire configuration of fine bubble generating device 1 according to one embodiment of the present invention. As shown in Figure 3, the fine bubble generating device 1 comprises, as main parts, a liquid introducing section 2 for introducing a liquid L1 in a tank T, a gas introducing section 3a for introducing gas, a pumping section 4 for pumping a liquid fluid L2 sent via the liquid introducing section 2 and gas sent via the gas introducing section 3a, and a fine bubble generating section 5 for generating fine bubbles B in the liquid fluid L2 pumped out from the pumping section 4 and discharging the fine bubbles B into the liquid L1.

[0029]

For convenience, a liquid pumped out by the pumping section 4 is defined as the liquid fluid L2 and any other liquids existing in the tank T are defined as the liquid L1. Water is generally used as the liquid L1, but the liquid L1 is not limited thereto. Liquid may be solvents such as toluene, acetone, and alcohol, fuels such as petroleum and gasoline, food and beverages such as edible oils and fats, butter, ice cream, and

beer, medicines such as nutritional drinks, health products for bathing or the like, environmental water such as lake water and contaminated water in purification tanks, and the like.

[0030]

The liquid introducing section **2** is, for example, a tube. The liquid introducing section **2** is provided upstream of the pumping section **4**. The liquid introducing section **2** serves the role of a suction inlet when the pumping section **4** suctioning the liquid **L1** and is used as a flow channel.

[0031]

The gas introducing section **3a** is, for example, a tube. In the first Example, the gas introducing section **3a** is provided upstream of the pumping section **4**. The gas introducing section **3a** serves the role of a suction inlet and a flow channel when the pumping section **4** suctioning gas, such as ambient air. In addition, one end of the tube is directed toward the fine bubble generating section **5** in the second Example discussed below.

[0032]

The pumping section **4** comprises, for example, a pump **41** for pumping gas, liquid, or the like by pressurizing drive and a tube **42** with one end connected to the pump **41** and the other end connected to the fine bubble generating section **5** as main parts. In the pumping section **4**, the pump **41** simultaneously suctions the liquid **L1** and gas via the liquid introducing section **2** and the gas introducing section **3a**, respectively, mixes the liquid fluid **L2** and gas via the tube **42** to pump them to the fine bubble generating section **5**.

(Configuration of fine bubble generating section)

[0033]

As shown in Figure **4**, the fine bubble generating section **5** comprises, as main parts, a container body **51** for housing the liquid fluid **L2**, a first liquid fluid introducing section **52** for introducing the liquid fluid **L2** pumped out from the pumping section **4** into the container body **51**, a discharging section **53**

for discharging the liquid fluid **L2** in the container body **51** into the liquid **L1**, a liquid fluid swirling section **54** for making the liquid fluid **L2** swirl in a spiral toward the discharging section **53**, and a discharged flow volume adjusting section **55** for adjusting the discharged volume of the liquid fluid **L2** from the fine bubble generating section **5**.

[0034]

The container body **51** is provided with an inner wall gradually tapering toward the discharging section **53** in an annular shape from cross-sectional view, so that the swirl rate of a swirl flow generated by the liquid fluid swirling section **54** in the container body **51** is increased and thereby the vortex shear force increases to disintegrate and further fragment bubbles. For example, the stepped tapered shape shown in Figure **5A** is preferred. Thus, multiple steps of inclines with different angles are provided, such that the swirl rate is rapidly increased for each step. Thereby, the vortex shear force is increased, so that the fine bubbles **B** are disintegrated and further fragmented. In addition, the inner wall of the container body **51** may have a tapered shape without steps, as shown in Figure **5B**.

[0035]

In the container body **51**, the outer shape is formed, for example, in a cylindrical shape or a shape conforming to the shape of the inner wall. In the case of a cylindrical shape, as the outer shape is simply formed cylindrically regardless of the shape of the inner wall, manufacturing can be readily performed. In the case of a shape conforming to the shape of the inner wall, as the outer shape is fitted to the shape of the inner wall, the container body **51** does not have excessive thickness, so that material cost can be kept low.

[0036]

The first liquid fluid introducing section **52** is provided at the end on the upstream side of the container body **51**, and

serves the role of an introducing inlet for introducing the liquid fluid **L2** pumped out from the pumping section **4** into the container body **51**. The liquid fluid **L2** introduced from the first liquid fluid introducing section **52** flows toward the discharging section **53** positioned downstream.

[0037]

The discharging section **53** is provided at the end on the downstream side of the container body **51** and discharges the liquid fluid **L2** out of the container body **51**, the liquid fluid **L2** being introduced from the first liquid fluid introducing section **52** and being swirling in a spiral.

[0038]

For example, the discharging section **53**, as shown in Figure **4**, is formed into a shape of the neck of a bottle, therefore, the pressure of the liquid fluid **L2** swirling in a spiral is first increased due to a rapid decrease of inner diameter at the thinnest area in the shape of the neck of a bottle, and then the pressure is rapidly decreased due to a gradual increase of the inner diameter toward the outside of the container body **51**. By such variation in pressure, the fine bubbles **B** contained in the liquid fluid **L2** are further pulverized to become finer bubbles. Moreover, as long as the discharging section **53** can discharge the liquid fluid **L2** swirling in a spiral toward the outside of the container body **51** to generate finer bubbles, the shape thereof is not limited.

[0039]

The liquid fluid swirling section **54** is, for example, a screw **541** provided with multiple blades, the screw **541** being rotatably provided on the first liquid fluid introducing section **52** side in the container body **51**. The screw **541** is rotated by the liquid fluid **L2** transported from the pumping section **4**. The liquid fluid **L2** becomes a swirl flow by the rotation of the screw **541**. In this manner, the liquid fluid swirling section **54** sends out the liquid fluid **L2** introduced from the first liquid

fluid introducing section **52** toward the discharging section **53** while making the liquid fluid **L2** swirl in a spiral.

[0040]

As shown in Figure **3**, the discharged flow volume adjusting section **55** comprises, as main parts, an axis **551** provided approximately perpendicular to the discharging section **53** and supported by the container body **51**, a baffle board **552** having an insertion bore **5521** (not shown) through which the axis **551** is inserted, and a stopper section **553** provided to prevent the baffle board **552** from being released from the axis **551**.

[0041]

The axis **551** is, for example, a tube and is supported, for example, by a stainless steel board **555** as shown in Figure **3** so that the axis **551** can be inserted through and support the baffle board **552**. The stainless steel board **555** is connected to the container body **51** via a bolt **556**. Further, one end of the axis **551** is directed toward the discharging section **53** side, and the gas introducing section **3b** is connected to the other end in the second Example discussed below. Moreover, in the first Example, the axis **551** only need to serve the role of an axis. The axis does not need to be a tube. Further, as long as the stainless steel board **555** and the bolt **556** can support the axis **551**, the material and the shape thereof are not limited.

[0042]

The baffle board **552** is, for example, a disk made of stainless steel having the insertion bore **5521** approximately in the center. The axis **551** is inserted through the insertion bore **5521** so that the baffle board **552** is movable between the discharging section **53** and the stopper section **553** in the axial direction of the axis **551**, and the baffle board **552** acts to open and close the discharging section **53** to adjust the discharged flow volume of the liquid fluid **L2** from the discharged section **53**. Moreover, as long as the baffle board **552** acts to open and close the discharging section **53** to allow adjustment of the

discharged flow volume, the material or shape thereof is not limited.

[0043]

The stopper section **553** serves the role of a stopper. For example, the axis **551** has an end with a large outer diameter and an end with a small outer diameter and is formed to have an outer diameter that gradually increases from the small outer diameter end to the large outer diameter end, and further the movement of the baffle board **552** is restricted at a position where the diameter of the insertion bore **5521** of the baffle board **552** is identical to the diameter of the axis **551**.

[0044]

For example, the stopper section **553** has a washer **554** through which the axis **551** is inserted. The washer **554** is disposed, for example, more toward the stainless steel board **555** than the baffle board **552** and serves the role of a stopper for preventing the release of the baffle board **552** from the axis **551** and the role of assisting a more stable movement of the baffle board **552**. The stopper section **553** is not limited to the aforementioned member. The role of a stopper may also be provided by the stainless steel board **555** in the stopper section **553**.

(Operation of fine bubble generating device)

[0045]

Next, the operation of the fine bubble generating device **1** according to the first Example of the present invention is explained while referring to the schematic diagram related to the number of generated fine bubbles in Figure **3**, the cross-sectional view in the longitudinal direction of a fine bubble generating section in Figure **4**, the diagram showing the shape of an inner wall of a container body in Figure **5**, and the flow chart in Figure **10**.

[0046]

The flow of the entire operation of the fine bubble generating device **1** according to the first Example is explained while referring to the flow chart in Figure **10**.

[0047]

In step **ST1**, the pump **41** suctions the liquid **L1** in the tank **T** via the liquid introducing section **2** into the pumping section **4** and external gas via the gas introducing section **3a** into the pumping section.

[0048]

In step **ST2**, the pump **41** forms the liquid fluid **L2** by mixing the liquid **L1** and the gas suctioned in by step **ST1**, and pumps out the liquid fluid **L2** to the container body **51** via the tube **42** and the first liquid fluid introducing section **52**.

[0049]

In step **ST3**, the screw **541** directs the liquid fluid **L2** pumped out by step **ST2** toward the discharging section **53** to generate a strong flow swirling in a spiral along the inner wall of the container body **51** and increases the shear force to fragment bubbles.

[0050]

In step **ST4**, the stepped tapered shape of the container body **51** shown in Figures **3** and **5A** rapidly increases the swirl rate of a swirl flow of the liquid fluid **L2** generated by step **ST3** at each stepped portion to increase the shear force, which disintegrates and fragments bubbles contained in the liquid fluid **L2** to generate the fine bubbles **B**.

[0051]

In step **ST5**, the discharging section **53** with a shape of the neck of a bottle shown in Figure **4** strongly discharges the liquid fluid **L2** and the fine bubbles **B** out of the container body, the swirl rate of the liquid fluid **L2** having been increased in step **ST4**.

[0052]

In step **ST6**, the baffle board **552** supported by the axis **551** moves so as to open or close the discharging section **53** thereby to adjust the discharged volume of the liquid fluid **L2** that is discharged from the discharging section **53**.

(Operation of discharged flow volume adjusting section)

[0053]

In this regard, the operation of step **ST6** is explained hereinafter in detail while referring to Figures **1** and **2** and the flow chart in Figure **11**.

[0054]

In step **ST61**, the liquid fluid **L2** introduced into the container body **51** becomes a swirl flow by the liquid fluid swirling section **54** in the container body **51** and the swirl rate thereof increases. Whereby, the fine bubble increasing period **I** starts in which the vortex shear force increases and bubbles are further fragmented.

[0055]

In step **ST62**, when the fine bubble increasing period **I** starts in step **ST61** as shown in Figure **1**, in the liquid fluid **L2** introduced into the container body **51**, a liquid pressure in the vicinity of the discharging section **53** in the container body **51** becomes higher than the liquid pressure outside the container body **51**. Thus, the generation peak period **P** of the fine bubble **B** starts in which the liquid fluid **L2** is strongly discharged from the discharging section **53**.

[0056]

As shown in Figure **1**, in step **ST63**, when the discharged flow volume of the liquid fluid **L2** from the discharging section **53** starts to increase, a liquid pressure around a swirl axis of a swirl generated by the liquid fluid swirling section **54** decreases inside the container body **51**, and thereby a liquid pressure in the vicinity of the discharging section **53** in the container body **51** becomes much lower than a liquid pressure outside the container body **51**. Whereby, the baffle board **552**

enters a first state in which the baffle board **552** is subjected to an effect to close the discharging section **53**. For this reason, the generation peak period **P** of the fine bubble **B** does not continue and starts to transition to the fine bubble decreasing period **D** in which generation of the fine bubbles **B** decreases. As a result, the discharged flow volume of the liquid fluid **L2** from the discharging section **53** decreases.

[0057]

When the transition to the fine bubble decreasing period **D** starts, a physical stimulation by the baffle board **552** can be applied to the liquid fluid **L2** from the discharging section **53** and thereby the discharged flow volume of the liquid fluid **L2** from the discharging section **53** decreases and the fine bubbles **B** in a decreasing trend are further fragmented. Thus, a large quantity of fine bubbles **B** can be generated again, as illustrated by the first waveform in Figure 2. Further, when adjusting such as pumping section **4**, discharged flow volume adjusting section **55**, and the shape of the container body **51** to shorten the interval between first state and the second state, the number of generated fine bubbles **B** would exhibit the second waveform in Figure 2 and the generation peak period **P** appears more frequently.

[0058]

In step **ST64**, when the discharged flow volume of the liquid fluid **L2** from the discharging section **53** starts to decrease, a liquid pressure in the vicinity of the discharging section **53** in the container body **51** becomes higher than a liquid pressure outside the container body **51**. In the result, the baffle board **552** enters a second state in which the baffle board **552** is subjected to an effect to open the discharging section **53**. In other words, after the fine bubble increasing period **I** has started, the generation peak period **P** of the fine bubble **B** starts again in which the liquid fluid **L2** in the container body **51** is strongly discharged from the discharging section **53**.

[0059]

That is, as the first state and the second state are iteratively occur and thereby the generation peak period **P** of the fine bubble **B** repeatedly arises, the average number of generated fine bubbles **A** can be increased and the fine bubbles **B** can be stably and sustainably discharged from the discharging section **53**.

[0060]

As shown in the third waveform of Figure 2, the pressures from both sides via the baffle board **552** generated in the first state and the second state may be equalized so that the baffle board **552** may vibrate and swing at a predetermined position to more stably generate the fine bubbles **B**.

(Second Example)

[0061]

In the first Example, the gas introducing section **3a** is provided upstream of the pumping section **4** and the pumping section **4** functions as a drive source for suctioning gas such as ambient air. Thereby, a separate device for introducing gas such as a compressor is no longer required, resulting in the effect of simplifying a facility and reducing cost, but the same effect can be attained as follows.

[0062]

Figure 6 is a schematic diagram of the fine bubble generating device **1** according to the second Example of the present invention. In the second Example, the gas introducing section **3b** is connected to the tube shaped axis **551** instead of upstream of the pumping section **4**. Thereby, gas is suctioned into the container body **51** via the gas introducing section **3b** by the suction force from the discharging section **53** generated when the liquid pressure in the vicinity of the discharging section **53** in the container body **51** becomes lower than the liquid pressure outside the container body **51** as the discharged flow volume of the liquid fluid **L2** from the discharging section **53**

increases. The gas suctioned via the gas introducing section **3b** is mixed with the liquid fluid **L2** to become a swirl flow in the container body **51** and is discharged as the liquid fluid **L2** comprising the fine bubbles **B** from the discharging section **53** when the liquid pressure in the vicinity of the discharging section **53** in the container body **51** becomes higher than the liquid pressure outside the container body **51** with a decrease in the discharged flow volume of the liquid fluid **L2** from the discharging section **53** to exert an effect to open the discharging section **53**. As a result, a separate device for introducing gas such as a compressor is no longer required, resulting in simplification of a facility and cost reduction. In addition, gas would not be excessively introduced into the pumping section **4**, so that there is no risk of the pumping section **4** idly spinning and breaking.

(Third Example)

[0063]

In the first Example and the second Example, the liquid fluid swirling section **54** is provided, so that the screw **541** provided on the first liquid fluid introducing section **52** side in the container body **51** is rotated by the liquid pressure of the liquid fluid **L2** sent out from the pumping section **4** to send out the liquid fluid **L2** introduced from the first liquid fluid introducing section **52** toward the discharging section **53** while making the liquid fluid **L2** swirl in a spiral. Meanwhile, the same effect can be attained as follows.

[0064]

Figure **7** is a schematic diagram of the fine bubble generating device **1** according to the third Example of the present invention. Figure **8A** is a cross-sectional view in the longitudinal direction of the fine bubble generating section **5**, and Figure **8B** is a cross-sectional view that is transverse to the direction towards the discharging section. In the third Example, without providing the liquid fluid swirling section

54, the first liquid fluid introducing section **52** is provided on a part of the circumferential surface of the container body **51** so that the liquid fluid **L2** is introduced along the tangential direction of the annular shape from the cross-sectional view to allow the liquid fluid **L2** to swirl in a spiral toward the discharging section **53**. Thereby, the first liquid fluid introducing section **52** also serves the role of the liquid fluid swirling section **54**. For instance, the liquid fluid **L2** can be swirled in a spiral without separately providing the screw **541**. Thus, the configuration is further simplified and economical in terms of production cost or running cost.

(Fourth Example)

[0065]

In the first to third Examples, the fine bubble generating section **5** is comprised of the container body **51**, the first liquid fluid introducing section **52**, the discharging section **53**, the liquid fluid swirling section **54**, and the discharged flow volume adjusting section **55**. Meanwhile, a similar effect can also be attained as follows.

[0066]

Figure **9A** is a cross-sectional view in the longitudinal direction of the fine bubble generating section **5**, and Figure **9B** is a cross-sectional view in the transverse direction. In the fourth Example, without providing the discharged flow volume adjusting section **55**, as shown in Figure **9A**, the container body **51a** is modified to a container body **61** of a double-layer structure. The container body **61** comprises a preliminary swirl chamber **611** and a main swirl chamber **612** and a reverse swirl flow generating wall **613** as the main parts.

[0067]

The preliminary swirl chamber **611** is a space formed on the outside of the reverse swirl flow generating wall **613** discussed below. A first swirl flow **S1** is introduced from the first liquid fluid introducing section **52**. The first swirl flow

S1 is swirled by the screw **541** and swirls in the same direction as the screw **541**.

[0068]

The main swirl chamber **612** is a space formed inside the reverse swirl flow generating wall **613** discussed below. A second swirl flow **S2** is introduced from a second liquid fluid introducing section **62** discussed below. The second swirl flow **S2** swirls in the opposite direction from the first swirl flow **S1** due to a collision board **6131** discussed below.

[0069]

The second liquid fluid introducing section **62** comprises the reverse swirl flow generating wall **613** and the collision board **6131** as the main constituents. As shown in Figure **9B**, the second swirl flow **S2** is generated by the first swirl flow **S1** colliding with the collision board **6131**.

[0070]

Thereby, bubbles are disintegrated and fragmented by a vortex shear force generated when a first swirl flow is changed into a second swirl flow in the opposite direction from the first swirl flow.

[0071]

In view of the above, the present invention is capable of stably and sustainably discharging a large quantity of fine bubbles from a discharging section with a simple configuration.

[0072]

In addition, it is understood that the present invention is not limited to only the aforementioned embodiments and various modifications can be made thereto within the scope that does not depart from the substance of the present invention.

[Reference Signs List]

[0073]

1 ... fine bubble generating device, **2** ... liquid introducing section, **3a**, **3b** ... gas introducing section, **4** ... pumping section, **41** ... pump, **42** ... tube, **5** ... fine bubble generating section, **51**

... container body, **52** ... first liquid fluid introducing section, **53** ... discharging section, **54** ... liquid fluid swirling section, **541** ... screw, **55** ... discharged flow volume adjusting section, **551** ... axis, **552** ... baffle board, **5521** ... insertion bore, **553** ... stopper, **554** ... washer, **555** ... stainless steel board, **556** ... bolt, **61** ... container body, **611** ... preliminary swirl chamber, **612** ... main swirl chamber, **613** ... reverse swirl flow generating wall, **6131** ... collision board, **62** ... second liquid fluid introducing section, **S1** ... first swirl flow, **S2** ... second swirl flow, **T** ... tank, **L1** ... liquid, **L2** ... liquid fluid, **A** ... average number of generated fine bubbles, **B** ... fine bubbles, **D** ... fine bubble decreasing period, **I** ... fine bubble increasing period, **P** ... generation peak period

[Claims]

[Claim 1]

A fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and a fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, the fine bubble generating section comprising:

- a container body;

- a first liquid fluid introducing section provided on the container body for introducing the liquid fluid pumped out from the pumping section into the container body;

- a discharging section provided on the container body for discharging the liquid fluid introduced from the first liquid fluid introducing section;

- a liquid fluid swirling section provided in the container body for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section; and

- a discharged flow volume adjusting section consisting of an axis provided approximately perpendicular to the discharging section and supported by the container body, a baffle board that has an insertion bore through which the axis is inserted, the axis being inserted through the baffle board so that the baffle board is movable in the axial direction of the axis, and a stopper section provided so as to prevent the baffle board from being released from the axis at a position where a suction force of a low liquid pressure generated in the container body reaches;

wherein, when a liquid pressure in the vicinity of the discharging section in the container body is higher than a

liquid pressure outside the container body, the baffle board is subjected to an effect to move away from the discharging section by discharging of the liquid flow from the discharging section to open the discharging section, and, when the liquid pressure in the vicinity of the discharging section in the container body is lower than the liquid pressure outside the container body, the baffle board is subjected to an effect to move closer to the discharging section by suction from the discharging section to close the discharging section.

[Claim 2]

The fine bubble generating device of claim 1, wherein the axis has an end with a large outer diameter and an end with a small outer diameter and is formed to have an outer diameter that gradually increases from the small outer diameter end to the large outer diameter end, and

the stopper section is configured to restrict the movement of the baffle board at a position where an outer diameter of the axis is approximately identical to an inner diameter of the insertion bore of the baffle board.

[Claim 3]

The fine bubble generating device of claim 2, wherein the stopper section comprises a washer through which the axis is inserted, and

the washer restricts the movement of the baffle board from the discharging section to a direction of discharging the liquid fluid and acts as a buffering material.

[Claim 4]

The fine bubble generating device of any one of claims 1 to 3, wherein

the container body has a shape in which an inner wall having an annular shape from the cross sectional view gradually decreases toward the discharging section.

[Claim 5]

The fine bubble generating device of any one of claims 1 to 4, wherein

the gas introducing section is provided upstream of the pumping section.

[Claim 6]

The fine bubble generating device of any one of claims 1 to 4, wherein

the gas introducing section is provided, so that one end of a tube is directed toward the discharging section and gas is introduced into the container body through the tube by suction from the discharging section when a liquid pressure in the vicinity of the discharging section in the container body is lower than a liquid pressure outside the container body.

[Claim 7]

The fine bubble generating device of claim 6, wherein in the gas introducing section, the tube and the axis which is tubular are connected.

[Claim 8]

The fine bubble generating device of any one of claims 1 to 7, wherein

an inner wall of the container body has an annular cross-section in a direction of the discharging section,

the first liquid fluid introducing section is provided so that the liquid fluid is introduced along a tangential direction of the annular shape from a cross-sectional view and thereby the liquid fluid is swirled in a spiral toward the discharging section, and

the first liquid fluid introducing section and the liquid fluid swirling section serve the role of each other.

[Claim 9]

The fine bubble generating device of any one of claims 1 to 8, wherein

the container body comprises

a reverse swirl flow generating wall for separating the container body into a double structure of a main swirl chamber and a preliminary swirl chamber and

a second liquid fluid introducing section provided on the reverse swirl flow generating wall for introducing the liquid fluid from the preliminary swirl chamber to the main swirl chamber so that a second swirl flow in the opposite direction from a first swirl flow introduced from the first liquid fluid introducing section generates.

[Claim 10]

A fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and a fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, the fine bubble generating section comprising:

a container body;

a first liquid fluid introducing section for introducing a liquid fluid pumped out from the pumping section into the container body;

a discharging section for discharging the liquid fluid;
and

a liquid fluid swirling section for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section;

wherein the container body comprises

a reverse swirl flow generating wall for separating the container body into a double structure of a main swirl chamber and a preliminary swirl chamber and

a second liquid fluid introducing section provided on the reverse swirl flow generating wall for introducing the

liquid fluid from the preliminary swirl chamber to the main swirl chamber so that a second swirl flow in the opposite direction from a first swirl flow introduced from the first liquid fluid introducing section generates on the other side of the reverse swirl flow generating wall.

[Claim 11]

A fine bubble generating section of a fine bubble generating device comprising a pumping section for pumping a liquid fluid from a liquid, a gas introducing section for introducing gas into the liquid fluid, and the fine bubble generating section used in the liquid for generating fine bubbles in the liquid fluid from the gas introduced from the gas introducing section and the liquid fluid pumped out from the pumping section and discharging the liquid fluid and the fine bubbles to the liquid, the fine bubble generating section comprising:

- a container body;

- a first liquid fluid introducing section provided on the container body for introducing a liquid fluid pumped out from the pumping section into the container body;

- a discharging section provided on the container body for discharging a liquid fluid introduced from the first liquid fluid introducing section;

- a liquid fluid swirling section provided in the container body for making the liquid fluid introduced from the first liquid fluid introducing section swirl in a spiral toward the discharging section; and

- a discharged flow volume adjusting section consisting of an axis provided approximately perpendicular to the discharging section and supported by the container body, a baffle board that has an insertion bore through which the axis is inserted, the axis being inserted through the insertion bore of the baffle board so that the baffle board is movable in the axial direction of the axis, and a stopper section provided to prevent the baffle

board from being released from the axis at a position which a suction force of a low liquid pressure generated in the container body reaches to;

wherein, when a liquid pressure in the vicinity of the discharging section in the container body is higher than a liquid pressure outside the container body, the baffle board is subjected to an effect to move away from the discharging section by discharging of the liquid flow from the discharging section to open the discharging section, and, when the liquid pressure in the vicinity of the discharging section in the container body is lower than the liquid pressure outside the container body, the baffle board is subjected to an effect to move closer to the discharging section by suction from the discharging section to close the discharging section.