

ERROR DETECTION AND CORRECTION METHOD AND APPARATUS FOR COMPUTER MEMORY

ABSTRACT OF THE DISCLOSURE

An S8ED system is implemented in a memory system to detect single errors involving one or more bits in a byte of subject data, stored in and retrieved from the memory system.

5 Relationships between the subject data and parity data, which are used to detect errors in the subject data, are defined by a novel check matrix. The novel check matrix includes a number of constituent matrices, each of which includes eight (8) vectors. Each vector of a constituent matrix (i) has a number of elements which is equal to the number of parity bits used to detect errors in the subject data; (ii) is a concatenation of a building block vector, one or more instances
10 of one of two base generating vectors, and one or more instances of the other of the two base generating vectors; and (iii) is distinct from all other vectors of the same constituent matrix. The building block vector is derived from a signature vector and the two base generating vectors. The signature vector is a vector having a specific value for all constituent matrices of the check matrix. The number of elements of the signature vector is one-fourth the number of parity bits used to
15 detect errors in the subject data. The base generating vectors are vectors which have the same number of elements as the signature vector and have an even weight if the signature vector has an odd weight or have an odd weight if the signature vector has an even weight. Each base generating vector is distinct from all other base generating vectors used to construct a single check matrix. Each unique pair of base generating vectors is used to construct a respective
20 constituent matrix. The check matrix includes a respective and unique one of the constituent matrices corresponding to each byte of the subject data and an identity matrix which has a number of columns and rows equal to the number of bits of parity data used to detect errors in the subject data. Each vector of the check matrix represents check data resulting from a single erroneous bit in either the subject data or the initial parity data and accordingly defines relationships between
25 the subject data and the parity data. These relationships are implemented in error correction code generators to derive parity data from subject data to detect errors in the subject data.

