

VACUUM PUMP

The invention relates to an insert for a pump, to a vacuum pump including such an insert, and to a method of assembling a pump insert.

5

Vacuum pumps typically comprise a body and a rotor supported for rotation relative to the body to draw gas from a tool connected to the inlet of the pump. The rotor is supported by a bearing arrangement comprising two bearings located at or intermediate respective ends of the rotor. Usually, the upper
10 bearing is in the form of a magnetic bearing, and the lower bearing is in the form of a rolling bearing.

As illustrated in Figure 1, a typical rolling bearing 10 comprises an inner race 12 extending about the rotor 14, an outer race 16, and a plurality of rolling
15 elements 18, supported by a cage 20, for allowing relative rotation of the inner race 12 and the outer race 16. The rolling bearing 10 is lubricated to establish a load-carrying film separating the bearing components in rolling and sliding contact in order to minimize friction and wear, and shield elements 22 are provided to resist seepage of lubricant from the rolling bearing 10. A radial
20 damping ring 24 is positioned radially between a radial end surface of the outer race 16 and the body 26 of the pump for damping radial movement of the outer race 16. An axial damping ring 28 is provided between an axial end surface of the outer race 16 and the body 26 for damping axial movement of the outer race 16. The rolling bearing 10 is secured to the rotor 14 by a
25 threaded nut 30 which is screwed on to the end of the rotor 14 so that the upper (as illustrated) axial end surface 32 of the inner race 12 engages an abutment surface 34 of the rotor 14.

The upper magnetic bearing (not shown) typically comprises a stack of
30 magnetic bearing rotor rings mounted on the rotor 14, and a stack of magnetic bearing stator rings, concentric with and located inside the rotor rings, mounted on an axially adjustable mounting which is accessed through the

- 2 -

inlet of the pump. The axial position of the mounting is adjusted so that the stacks of rings are axially offset. Due to the forces of repulsion between the rings, the rotor 14 is biased in the axial direction so that an axial preload is applied to the rotor 14.

5

The rolling bearing 10 and the damping rings 24, 28 are usually replaced when the pump is serviced. As there is a tolerance stack-up between the upper (as illustrated) axial end surface of the inner race 12 of the bearing and the upper axial end surface 36 of the axial damping ring 28, this can result in
10 the rotor 14 being in a different axial position following the replacement of these components. A change in this position of the rotor 14 will change the axial preload applied to the rotor 14 by the magnetic bearing; if this preload is too high the rolling bearing 10 may be subject to excessive wear, whilst if this preload is too low components of the rotor 14 may clash with components of
15 the pump body 26 during use of the pump. Consequently, once the rolling bearing 10 has been replaced, the pump has to be disconnected from the tool so that the mounting for the magnetic bearing stator rings can be adjusted to ensure that the axial preload is at the required value. This can considerably increase the time required to service the pump.

20

The present invention provides a vacuum pump comprising a body and a rotor supported for rotation relative to the body by an insert inserted around the rotor, the insert comprising a metallic, annular resilient support comprising inner and outer annular portions connected by a plurality of flexible members,
25 the resilient support extending about a rolling bearing having an inner race, an axially preloaded outer race fixed to the inner annular portion of the resilient support, and a plurality of rolling elements located between the races.

During assembly, the rolling bearing can be accurately positioned within the
30 support so that there is a very low tolerance stack-up when the insert is fitted to the rotor. Consequently, a set of inserts can be assembled with the rolling bearing being located in the same position relative to the support throughout

- 3 -

the set of inserts. As a result, the position of the rotor will not change when the rolling bearing is replaced during servicing of the pump, and so there is no change in the axial preload of the rotor, and so no requirement to disconnect the pump from a tool during servicing. By axially preloading the outer race of the bearing, any internal clearance in the bearing is removed, thereby
5 eliminating radial and axial play, and increasing system rigidity.

The invention extends to the insert per se, and therefore also provides an insert for insertion around a rotor of a pump, the insert comprising a metallic,
10 annular resilient support comprising inner and outer annular portions connected by a plurality of flexible members, the resilient support extending about a rolling bearing having an inner race, an axially preloaded outer race fixed to the inner annular portion of the resilient support, and a plurality of rolling elements located between the races.

15 An axial end surface of the inner race is preferably axially displaced relative to an axial end surface of the resilient support. The end surface of the inner race is preferably axially displaced relative to the end surface of the resilient support by a distance in the range from 1 to 3 mm, and in the preferred
20 embodiment is axially displaced by 1.8 mm.

The outer surface of the outer race is preferably attached to an inner surface of the inner annular portion of the support.

25 Each of the flexible members is preferably an elongate, arcuate member substantially concentric with the inner and outer annular portions. In the preferred embodiment, these members are circumferentially aligned. The flexible members of the resilient support can thus provide integral leaf springs of the resilient support, and hence determine the radial stiffness of the
30 resilient support. The radial flexibility of the resilient support may be readily designed, for example using finite element analysis, to have predetermined flexure characteristics adapted to the vibrational characteristics of the drive

shaft. Low radial stiffness in the range from 50 to 500 N/mm may be achieved to meet the required rotor dynamics of the pump; lowering the radial stiffness reduces the second mode natural frequency of the pump, which in turn reduces the transmissibility of vibration at full pump speed and hence the level
5 of pump vibration for a specific shaft out-of-balance. In view of this, acceptable levels of transmission imbalance vibration may be achieved without the need to perform high speed balancing, providing a significant cost reduction per pump.

10 The resilient support is preferably formed from metallic material such as tempered steel, aluminium, titanium, phosphor bronze, beryllium copper, an alloy of aluminium or an alloy of titanium. In this case, the radial and axial stiffnesses of the resilient support do not change with temperature or with time, that is, through creep.

15

The support is preferably adhered to the outer race using an adhesive.

The present invention also provides a method of assembling a pump insert, the method comprising the steps of locating an annular resilient support about
20 a rolling bearing having an inner race, an outer race and a plurality of rolling elements located between the races, positioning the bearing at a desired location within the support relative to an axial end surface of the support, and at this location, fixing the support to the outer race of the bearing whilst applying a preload to the outer race of the bearing.

25

As discussed above, at the desired location an axial end surface of the inner race is preferably axially displaced relative to the axial end surface of the resilient support. A spacer may be used to position the bearing at the desired location so that the end surface of the inner race is axially displaced relative to
30 the end surface of the resilient support by a desired amount. For example, the spacer may have a support engaging portion for engaging the end surface of the support, and a bearing engaging portion which protrudes into the bore

of the support by the desired amount when the end surface of the support is engaged by the support engaging portion of the spacer. The bearing can be readily positioned within the support so that the end surface of the inner race engages the bearing engaging portion of the spacer, thus enabling the
5 bearing to be accurately positioned at the desired location within the support. A resilient member, for example a spring, can be provided between the spacer and the outer race for applying the axial load to the bearing when it is positioned at the desired location.

10 The present invention further provides a method of assembling a vacuum pump comprising a body and a rotor supported for rotation relative to the body, the method comprising the steps of sliding an insert as aforementioned over the rotor until an axial end surface of the support engages the body and an axial end surface of the inner race of the bearing engages the rotor, and
15 securing the insert to the rotor.

Preferred features of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

20 Figure 1 illustrates a cross-sectional view of a known rolling bearing supporting the rotor of a pump;

Figure 2 illustrates a cross-sectional view of a pump insert including a rolling bearing;

25

Figure 3 illustrates a perspective view of the resilient support of the insert of Figure 2;

Figure 4 illustrates a method of assembling the insert of Figure 2; and

30

Figure 5 illustrates a cross-sectional view of the insert of Figure 2 supporting the rotor of a pump.

Figure 2 illustrates a cross-sectional view of the pump insert 50, which forms part of a bearing arrangement of a pump. The insert 50 comprises a known rolling bearing 10 as described above with reference to Figure 1, and which
5 comprises an inner race 12, an outer race 16, and a plurality of rolling elements 18, supported by a cage 20, for allowing relative rotation of the inner race 12 and the outer race 16. The rolling bearing 10 is lubricated to establish a load-carrying film separating the bearing components in rolling and sliding contact in order to minimize friction and wear, and shield elements 22 are
10 provided to resist seepage of lubricant from the rolling bearing 10.

The rolling bearing 10 is located within an annular resilient support 52, which is illustrated in more detail in Figure 3. The resilient support 52 comprises a metallic member having integral inner and outer annular portions 54, 56
15 connected together by a plurality of integral flexible members 58 formed by machining slots 60 in the support 52. Each flexible member 58 is connected by a first resilient hinge 62 to the inner portion 54, and by a second resilient hinge 64 to the outer portion 56. Each flexible member 58 is in the form of an elongate, arcuate member substantially concentric with the inner and outer
20 annular portions 54, 56, and, as illustrated in Figure 3, the flexible members 58 are preferably circumferentially aligned. The flexible members 58 of the resilient support 52 thus provide integral leaf springs of the resilient support 52.

25 Returning to Figure 2, the outer radial surface 38 of the outer race 16 of the bearing 10 is fixed to the inner, axially extending cylindrical surface 66 of inner portion 54 of the support 52, preferably using an adhesive. The bearing 10 is preferably positioned within the support 52 at a location at which the axial end surface 32 of the inner race 12 of the bearing 10 is axially displaced from the
30 axial end surface 68 by a desired amount y , which is preferably in the range from 1 to 3 mm, and which in a preferred embodiment is 1.8 mm.

- 7 -

Figure 4 illustrates a method of assembling the insert 50. A spacer 80 is used to position the bearing 10 at the desired location within the support 52. The spacer 80 has a support engaging portion 82 for engaging the axial end surface 68 of the support 52, and a bearing engaging portion 84 for engaging the axial end surface 32 of the inner race 12 of the bearing 10. The support engaging portion 82 has an annular, planar surface 86 which is located on the axial end surface 68 of the support 52 so that the bearing engaging portion 84 of the spacer 80 protrudes into the bore 70 of the support 52 by the desired amount y . The bearing 10 is inserted into the bore 70 of the support 52, and is pushed towards the spacer 80 until the axial end surface 32 of the inner race 12 engages the axial end surface 88 of the bearing engaging portion 84 of the spacer 80. The bearing 10 is then fixed to the support 52, preferably using an adhesive to adhere the outer radial surface 38 of the outer race 16 of the bearing 10 to the inner cylindrical surface 66 of inner portion 54 of the support 52.

As also illustrated in Figure 4, a resilient member 90, preferably a tension spring, is located between the spacer 80 and the bearing 10. The resilient member 90 preferably has one end connected to the annular surface 86 of the spacer 80 to retain the resilient member in position. As the bearing 10 is moved towards the spacer 80, the resilient member 90 is compressed between the spacer 80 and the outer race 16 of the bearing 10 to exert an axial load on the outer race 16. When the bearing 10 is positioned at the desired location, this resilient member 90 applies a known axial load to the outer race 16, so that in the assembled insert 50 the outer race 16 is axially preloaded.

A set of inserts 50 can thus be assembled, sequentially, using the spacer 80 so that, within the set, each rolling bearing 10 is located at the same position relative to its support 52, and each rolling bearing 10 has the same axial preload.

Figure 5 illustrates the insert 50 in situ about the rotor 14 of a vacuum pump. During assembly of the pump, and with the rotor 14 restrained to inhibit its rotation, the insert 50 is located over the end 15 of the rotor 14, and is slid along the rotor 14 until the axial end surface 68 of the support 52 engages the pump body 26 and the axial end surface 32 of the inner race 12 of the bearing 10 engages the abutment surface 34 of the rotor 14. The oil nut 30 is then screwed on to the end of the rotor 14 to secure the inner race 12 of the bearing 10 to the rotor 14. If the pump also has a magnetic bearing forming part of its bearing arrangement for supporting the rotor, the mounting for the magnetic stator rings of the magnetic bearing is adjusted to exert a desired axial preload on the rotor 14.

During servicing of the pump when it is in situ for evacuating a tool, the rotor 14 is again restrained to prevent its rotation, the oil nut is unscrewed from the rotor 14 and the insert 50 is removed from the pump. A fresh insert 50 is then inserted on to the rotor 14 and slid in position, and the oil nut 30 is screwed back on to the rotor to retain the insert 50 in position. As there is a very low tolerance stack-up between the axial end surface 68 of the support 52 and the axial end surface 32 of the inner race 12 of the bearing 10, the axial position of the rotor 14 will hardly change, if at all, as a result of changing the insert 50. Consequently, there is no need to disconnect the pump from the tool to adjust the axial preload on the rotor 14.

CLAIMS

1. A method of assembling a pump insert (50), the method comprising the steps of:
 - locating an annular resilient support (52) about a rolling bearing (10) having an inner race (12), an outer race (16) and a plurality of rolling elements (18) located between the races; characterised by the steps of
 - positioning the bearing (10) at a desired location within the support (52) relative to an axial end surface of the support (52); and
 - at this location, fixing the support (52) to the outer race (16) of the bearing (10) whilst applying a preload to the outer race of the bearing.
2. A method according to Claim 1, wherein, at the desired location, an axial end surface of the inner race (12) is axially displaced relative to the axial end surface of the resilient support (52).
3. A method according to Claim 2, wherein a spacer (80) is used to position the bearing (10) at the desired location so that the end surface of the inner race (12) is axially displaced relative to the end surface of the resilient support (52) by a desired amount.
4. A method according to Claim 3, wherein the spacer (80) has a support engaging portion for engaging the end surface of the support (52), and a bearing engaging portion which protrudes into the bore of the support by the desired amount when the end surface of the support is engaged by the support (52) engaging portion of the spacer (80), and wherein the bearing (10) is positioned within the support (52) so that the end surface of the inner race (12) engages the bearing engaging portion of the spacer.
5. A method according to Claim 4, wherein a resilient member (90) is provided between the spacer (80) and the outer race (16) for applying the axial load to the bearing (10) when it is positioned at the desired location.

6. A method according to any preceding claim, wherein the support (52) is adhered to the outer race (16) using an adhesive.
7. A method according to any preceding claim, wherein the resilient support (52) comprises inner and outer annular portions connected by a plurality of flexible members, and wherein the outer surface of the outer race (16) is fixed to an inner surface of the inner annular portion of the support (52).
8. An insert (50) for insertion around a rotor of a pump, the insert comprising a metallic, annular resilient support (52) comprising inner and outer annular portions connected by a plurality of flexible members (58), the resilient support (52) extending about a rolling bearing (10) having an inner race (12), an axially preloaded outer race (16), and a plurality of rolling elements (18) located between the races characterised in that the outer race is fixed to the inner annular portion of the resilient support.
9. An insert according to Claim 8, wherein an axial end surface of the inner race (12) is axially displaced relative to an axial end surface of the resilient support (52).
10. An insert according to Claim 8 or Claim 9, wherein the end surface of the inner race (12) is axially displaced relative to the end surface of the resilient support (52) by a distance in the range from 1 to 3 mm.
11. An insert according to any of Claims 8 to 10, wherein the outer surface of the outer race (16) is attached to an inner surface of the inner annular portion of the resilient support (52).
12. An insert according to any of Claims 8 to 11, wherein each of the flexible members (58) is an elongate, arcuate member substantially concentric with the inner and outer annular portions.

13. An insert according to Claim 12, wherein the flexible members (58) are circumferentially aligned.
14. An insert according to any of Claims 8 to 13, wherein the flexible members (58) provide a plurality of integral leaf springs of the resilient support.
15. An insert according to any of Claims 8 to 14, wherein the metallic material comprises one of tempered steel, aluminium, titanium, phosphor bronze, beryllium copper, an alloy of aluminium and an alloy of titanium.
16. A vacuum pump comprising a body and a rotor supported for rotation relative to the body by a bearing arrangement comprising an insert (50) according to any of Claims 8 to 15.