



- (51) **International Patent Classification:**
A61F 2/04 (2013.01)
- (21) **International Application Number:**
PCT/US2014/025994
- (22) **International Filing Date:**
13 March 2014 (13.03.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
61/791,517 15 March 2013 (15.03.2013) US
- (71) **Applicant:** PNEUMRX, INC. [US/US]; 530 Logue Avenue, Mountain View, California 94043 (US).
- (72) **Inventors:** VASQUEZ, Jaime; 2563 Bishop Avenue, Fremont, California 94536 (US). MATHIS, Mark L.; 44619 Parkmeadow Drive, Fremont, California 94539 (US). MACHOLD, Timothy; 65 Bernal Avenue, Moss Beach, California 94038 (US). STEIN, Andrew; 530 Logue Avenue, Mountain, California 94043 (US).
- (74) **Agents:** CHANG, Shin-Tsen (Dennis) et al.; Kilpatrick Townsend & Stockton LLP, Eighth Floor, Two Embarcadero Center, San Francisco, California 94111 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) **Title:** TORQUE ALLEVIATING INTRA-AIRWAY LUNG VOLUME REDUCTION COMPRESSIVE IMPLANT STRUCTURES




FIG. 26A

(57) **Abstract:** A device for enhancing the breathing efficiency of a patient is provided. The implantable device may include a deployed configuration with one or more helical sections with proximal end in a stand-off proximal end configuration. The stand-off proximal end configuration may reduce migration of the deployed device and may preserve implant tissue compression. Alternative configurations may include two or more helical sections with a transition section disposed between the two or more helical sections. A device may include a right-handed helical section and a left-handed helical section and the transition section comprises a switchback transition section. The switchback section may provide greater control of the device during deployment by limiting recoiling forces of a device comprising a spring material. The deployed device may compress the lung to increase a gas filling resistance of the compressed portion of the lung, and/or increase tension and elastic recoil in other portions of the lung.

