

Description

This invention relates generally to a lock for a downhole apparatus and more particularly, but not by way of limitation, to a hydraulic lock for holding down an upper packer mounted on a packer mandrel connected to a lower packer disposed in an open well bore.

In fracturing a formation intersected by a well bore, it is known to have two seals, referred to as packers, set in the well at the upper and lower boundaries of the formation to be fractured. A pressurized fracturing fluid is then injected between the set packers through a tubing or pipe string on which the packers are carried into the hole. Such procedure can be used either when the well bore is lined with a casing or when the well bore is unlined (referred to herein as an open well bore, or the like). It is important that once the packers are set, they remain set (until specifically released) so that the fracturing fluid will be properly contained to achieve the desired fracturing, and so that hazardous conditions are not thereby created. It is also important for the packers to remain set when a measuring tool, such as a precision caliper tool subassembly, is carried between them. Any movement of the packers that is communicated to a tool such as a caliper can produce false readings and also seriously damage the tool if it has its measurement arms extended.

When the well bore is lined with a casing or the like, known types of mechanical and hydraulic slips can be used to engage the casing so that upward movement of the top packer, such as in response to the pressure of the fracturing fluid exceeding the hydrostatic pressure existing above the top packer, is prevented. Preventing such upward movement can also sometimes be accomplished to some degree by "slacking off" the tubing or pipe string so that the weight of the string exerts a downward acting force on the packers.

When packers are to be set in open well bores, however, the aforementioned mechanical and hydraulic slips have not been helpful in anchoring the top packer against upward movement. Likewise, the use of "slacked-off" tubing has been inadequate in general because in deep wells where the slacked-off pipe weight would be sufficient to prevent upward movement, the weight has been known to create a force exceeding the loading characteristic of the packer, thereby damaging it. In shallower wells, the upward applied force exerted by the fracturing fluid can easily overcome the lesser pipe weight, thereby causing the top packer to become unseated.

The foregoing problem particularly pertains to upward movement of the top packer because the lower packer has the greater fracturing fluid pres-

sure acting downwardly on it, and its downward movement is limited by an anchor pipe resting on the bottom of the hole or engaging the side wall of the bore. The interconnecting construction of conventional dual packers known to the art is such that this downward limitation is also applicable to the top packer so that it is only the upward movement of the upper packer which is of primary concern.

Although one can circumvent this problem by always casing or lining the well bore and by then using the known types of casing engaging locks, it is desirable to solve the problem in a manner whereby open hole packers can be securely set and locked in open well bores because this saves the time and expense of always having to case or line the well bore while still accomplishing reliable fracturing.

The foregoing exemplifies the particular need for a lock by which a top or upper packer can be locked relative to a bottom or lower packer to prevent upward movement of the upper packer in response to the fracturing fluid pressure exerted between the two packers when the packers are used in an open well bore. The satisfaction of this need, however, would also provide an improved lock useful in other types of downhole apparatus which require locking against relative movement between different parts of the apparatus.

The present invention reduces or mitigates the above-noted shortcomings of the prior art by providing an improved lock for a downhole apparatus. The present invention has particular utility in a double packer used in an open well bore. That is, with the present invention, the upper packer of the double or dual packer assembly can be controllably locked and unlocked against upward movement which would otherwise occur in response to a pressure, applied through the tubing between the two packers, exceeding the hydrostatic pressure and the weight of the pipe or tubing acting downwardly on the upper packer. However, the present invention has broader applications with respect to, in general, a downhole apparatus having an inner tubular member and an outer tubular member in which the inner tubular member is slidably disposed.

US-A-4258787 describes a lock for a downhole apparatus having an inner tubular member and an outer tubular member in which the inner tubular member is slidably disposed, the lock comprising a latch member mounted on the inner tubular members, actuating pressure communicating means disposed in the inner tubular member for communicating an actuating pressure to the latch member so that the latch member moves towards the outer tubular member in response to the actuating pressure.

According to the present invention, there is

provided a lock for a downhole apparatus having an inner tubular member and an outer tubular member in which the inner tubular member is slidably disposed, said lock comprising: a latch member mounted on one of the inner and outer tubular members; actuating pressure communicating means, disposed in the one of the inner and outer tubular members on which said latch member is mounted, for communicating an actuating pressure to said latch member so that said latch member moves towards the other of the inner and outer tubular members in response to the actuating pressure; characterised in that said lock further comprises latch member engagement means, mounted on the other of the inner and outer tubular members, for interlocking with said latch member when said latch member is moved in response to the actuating pressure; and hydrostatic pressure communicating means, disposed in the other of the inner and outer tubular members, for communicating a hydrostatic pressure to said latch member so that a force exerted by the hydrostatic pressure is applied to said latch member in opposition to a force exerted on said latch member by the actuating pressure.

In a preferred embodiment, a lock of the invention further comprises biasing means, connected to the one of the inner and outer tubular members on which the latch member is mounted, for biasing the latch member away from the other of the inner and outer tubular members. This preferred embodiment lock also comprises hydrostatic pressure communicating means, disposed in the other of the inner and outer tubular members, for communicating a hydrostatic pressure to the latch member so that a force exerted by the hydrostatic pressure is applied to the latch member in opposition to a force exerted on the latch member by the actuating pressure.

In one embodiment of the present invention, the lock is particularly for a packer assembly wherein said inner tubular member comprises a packer mandrel and said outer tubular member comprises a packer carrier sleeve, said lock comprising locking mandrel means for connecting with the packer mandrel inside the packer carrier sleeve, said locking mandrel means having a longitudinal channel and a transverse cavity defined therein; said latch member means is slidably disposed in said transverse cavity, for engaging the packer carrier sleeve when said latch member means is moved to an engagement position between said locking mandrel means and the packer carrier sleeve; and wherein the actuating pressure communicating means are disposed in said locking mandrel means for communicating an actuating pressure from said longitudinal channel to said transverse cavity to move said latch member

means to said engagement position.

In another embodiment, the lock is particularly for holding down an upper packer mounted on a packer mandrel connected to a lower packer, wherein said inner tubular member comprises said packer mandrel, and said outer tubular member comprises a locking sleeve, said lock comprising said locking sleeve connected to the upper packer, said locking sleeve having an inner surface along which is defined said latch member engagement means comprising a locking sleeve engagement surface; a locking mandrel connected to the packer mandrel, said locking mandrel having an outer surface, facing said inner surface of said locking sleeve, and an inner surface, defining an axial channel through said locking mandrel, said outer surface having a radial cavity defined therethrough extending within said locking mandrel towards said axial channel; and wherein said latch member is slidably disposed in said cavity, said latch member having a latch member engagement surface facing said inner surface of said locking sleeve; and wherein said actuating pressure communicating means are disposed in said locking mandrel for communicating a hydraulic pressure from said axial channel into said cavity and against said latch member, whereby said latch member is thereby movable, so that at least a portion of said latch member engagement surface interlocks with at least a portion of said locking sleeve engagement surface when said portions are radially aligned and said hydraulic pressure is applied.

In order that the present invention may be more fully understood, an embodiment thereof will now be described, by way of example only, with reference to the accompanying drawings, wherein:

FIG. 1 is a schematic illustration of a double or dual packer/working tool assembly with which a lock of the present invention can be used.

FIGS. 2A-2F form a partial sectional view of an upper packer section which can be used in the example, illustrated in FIG. 1 and which includes a preferred embodiment of the lock of the present invention.

FIG. 3 is a sectional end view of a locking mandrel of the lock of the preferred embodiment as taken along line 3-3 shown in FIG. 2B, but without the other structures shown in FIG. 2B.

FIG. 4 is a plan view of a portion of a latch member of the lock of the preferred embodiment.

The preferred embodiment of the present invention will be described with reference to a dual packer assembly 2 disposed in an open well bore 4. This particular construction is schematically illustrated in FIG. 1 (although not so illustrated because of the schematic nature of FIG. 1, the bore 4 has an irregular side wall, not a smooth side wall, as

known to the art). It is contemplated, however, that the present invention has a more general utility, such as in any downhole apparatus having an inner tubular member and an outer tubular member in which the inner tubular member is slidably disposed but to which the inner tubular member is to be controllably lockable. Thus, the present invention provides a lock to selectably retain these tubular members against relative movement in at least one direction.

The dual packer assembly 2 schematically illustrated in FIG. 1 includes a bottom or lower packer section 6 of conventional design (such as the lower end of a Halliburton Services No. 2 NR packer assembly). Spaced above the lower packer section 6 is a top or upper packer section 8 which includes at least part of a conventional upper packer assembly (such as the top portion of a Halliburton Services No. 2 NR packer assembly), but which also incorporates the novel and improved lock of the present invention.

Shown mounted within a slotted sleeve 9 extending between the packer sections 6, 8 is a caliper tool 10 which is not part of the present invention. The caliper tool 10, however, exemplifies a device whose proper operation requires that the top packer section 8 not be displaced when the fracturing pressure, applied to the volume of the well bore 4 which is between the packer sections and in which the caliper tool 10 is disposed, exerts a force that exceeds any downwardly acting weight of the pipe on which the packer assembly 2 and the tool 10 are lowered into the well and the force of any hydrostatic head acting downwardly on the upper packer section 8. This illustrates the need for the lock of the present invention by which the upper packer section 8 can be effectively locked to the lower packer section 6, which is anchored by an anchor pipe 12 into the bottom or the side of the hole 4, to prevent upward movement of the packer of the section 8. The preferred embodiment of this lock is illustrated within the downhole apparatus shown in FIGS. 2A-2F.

The downhole apparatus illustrated in FIGS. 2A-2F in conjunction with the lock of the present invention is an example of the upper packer section 8. This apparatus broadly includes an inner tubular member 14 and an outer tubular member 16, both of which include a plurality of components. The inner member 14 is slidable relative to the outer member 16, but these two members can be locked together by a lock 18 of the present invention.

The inner tubular member 14 of the upper packer section 8 is characterized in the preferred embodiment as a mandrel assembly including a packer mandrel 20 (FIGS. 2C-2F) and a locking mandrel 22 (FIGS. 2A-2C). The packer mandrel 20

is a cylindrical tube of conventional design having a lower externally threaded end for engaging a lower adapter 24 of a conventional type used for connecting (through the caliper tool 10 in the FIG. 1 configuration) to the lower packer section 6 anchored on the bottom or in the side wall of the well bore 4 by the anchor pipe 12. The packer mandrel 20 has an internally threaded throat at its other end for threadedly coupling with an externally threaded end of the locking mandrel 22, which locking mandrel 22 forms part of the lock 18 and will be more particularly described hereinbelow.

The outer tubular member 16 is characterized in the preferred embodiment as an upper packer carrying assembly having a packer 26 (FIGS. 2D-2E) connected (such as by a bolting fastening means including the nut and bolt combination 28 shown in FIG. 2D) to a packer carrier sleeve. The packer carrier sleeve includes a packer retaining collar 30, to which the packer 26 is fastened, and a connecting sleeve 32, to which the retaining collar 30 is connected by a quick change coupling 34 (FIGS. 2B-2D). The packer carrier sleeve of the outer tubular member 16 also includes a locking sleeve 36 (FIGS. 2A-2C) which is threadedly connected to the connecting sleeve 32 and which forms another part of the lock 18 to be more particularly described hereinbelow.

The packer 26 of the preferred embodiment is made of a composition (e.g., an elastomer) of a type as known to the art. It has an annular shape defining a hollow interior in which the packer mandrel 20 is slidably received. Providing lower support to the packer 26 are a packer support 38 (shown in FIG. 2E as being splined with the packer mandrel 20), a rubber packer shoe 40, a packer shoe support 42 and a coupling collar 44 threadedly interconnecting the shoe support 42 with the lower adapter 24 (FIGS. 2E-2F). These elements are of conventional designs known to the art and thus will not be further described.

The packer retaining collar 30, the connecting sleeve 32, and the quick change coupling 34 are also of conventional designs and will not be particularly described because these designs are known to the art. It will be noted, however, that the coupling between the packer retaining collar 30 and the connecting sleeve 32 includes a known type of seal 46 retained in between the packer retaining collar 30 and the connecting sleeve 32 and adjacent the packer mandrel 20 as shown in FIG. 2D. Additionally, the connecting sleeve 32 is shown as having a splined interconnecting relationship with the packer mandrel 20 as identified by the reference numeral 48 in FIG. 2C.

The outer tubular member 16 connects at its upper end to an upper adapter 50 (FIG. 2A) having a conventional design for connecting to the tubing

or pipe string (not shown) on which the dual packer assembly 2, and the caliper tool 10 in the FIG. 1 example, are run into the open well bore 4. The upper adapter 50 carries a seal 52 for providing a sliding fluid seal between the upper adapter 50 and the locking mandrel 22.

The lock 18 includes not only the aforementioned locking mandrel 22 and the locking sleeve 36, but also a latching mechanism 54. Each of these elements will be more particularly described with primary reference to FIGS. 2A-2C, 3 and 4.

The locking mandrel 22 is a means for connecting part of the lock 18 with the packer mandrel 20 inside the portion of the upper packer section 8 defining the outer tubular member 16. The locking mandrel 22 is an elongated member having a cylindrical inner surface 56 defining a longitudinal channel 58 extending throughout the length of the locking mandrel 22. The channel 58 of the preferred embodiment is disposed axially through the mandrel 22.

The mandrel 22 also has a cylindrical protuberant portion 60 extending radially outwardly from the main body of the mandrel 22. Milled or otherwise defined in the protuberant portion 60 are four cavities 62, 64, 66, 68 (FIGS. 2B and 3) which extend through the outer surface of the protuberant portion 60 and into the protuberant portion 60 transversely to the length of the mandrel 22. In the preferred embodiment these cavities extend radially with respective parallel side walls or surfaces extending perpendicularly from a respective bottom wall or surface. Associated with each of the four cavities are two slots extending longitudinally from opposite ends of the respective cavity. The two slots associated with the cavity 62 are identified in FIG. 2B by the reference numerals 70, 72. For the cavities 64, 66, 68, slots 74, 76, 78, respectively, corresponding to the slot 72 for the cavity 62, are shown in FIG. 3. The cavities 62, 64, 66, 68 are disposed in two pairs of diametrically opposed cavities whereby one pair includes the cavities 62, 66 and the other pair includes the cavities 64, 68. These cavities and slots open towards or face the locking sleeve 36.

The mandrel 22 also includes a cylindrical outer surface 80 defining a lower sealing surface engaged by a seal 82 (FIG. 2C) retained in a recess 84 of the locking sleeve 36. The diameter of the surface 80 is less than the outermost diameter of the protuberant portion 60 so that a radially extending annular shoulder 86 is defined therebetween.

The mandrel 22 has another cylindrical outer surface 88. The outer surface 88 extends longitudinally from the end of the protuberant portion 60 opposite the end thereof from which the surface 80 extends. The surface 88 has the same diameter as the surface 80; therefore, there is also a radially

extending annular shoulder defined between the surface 88 and the outermost portion of the protuberant portion 60, which annular shoulder is identified in FIG. 2B by the reference numeral 90. The outer surface 88 defines an upper sealing surface engaged by the seal 52 carried by the upper adapter 50. The seal 52 and the seal 82 have the same size so that a hydraulically balanced seal is created between the locking mandrel 22 and the locking sleeve 36 on opposite sides of the protuberant portion 60.

The protuberant portion 60 can travel longitudinally or axially within a volume 91 defined between facing surfaces of the locking mandrel 22 and an inner surface 92 of the locking sleeve 36. This volume is also between the longitudinally spaced, circumferential seals 52, 82. This volume is defined in part by the inner surface 92 of the locking sleeve 36 being offset radially outwardly from an inner surface 94 of the locking sleeve 36. This offset is established across a radial annular shoulder 95 which faces the shoulder 86 of the locking mandrel 22. The locking sleeve 36 has a cylindrical outer surface 96 and a threaded outer cylindrical surface 98 radially inwardly offset from the surface 96 for engaging an internal thread of the connecting sleeve 32.

Defined along the inner surface 92 is a locking sleeve engagement surface 100 comprising in the preferred embodiment grooves or serrations or teeth defining engagement means for interlocking with cooperating elements of a latch member forming part of the latching mechanism 54. The locking sleeve engagement surface 100 is not coextensive with the length of the surface 92 so that the latching mechanism 54 is longitudinally movable between a longitudinally located unlatched or disengagement position, located in the preferred embodiment relatively closer to the shoulder 95 than to the opposite end of the volume adjacent a radial annular surface 101 of the upper adapter 50, and a longitudinally located latchable or engagement position, wherein at least part of the latching mechanism overlies at least a portion of the locking sleeve engagement surface 100.

The latching mechanism 54 of the preferred embodiment includes latch member means, slidably disposed in at least one of the cavities 62, 64, 66, 68, for engaging the packer carrying sleeve assembly (specifically, the locking sleeve engagement surface 100 in the preferred embodiment) when the latch member means is moved to the aforementioned longitudinal engagement position and then to a radially located latched or engagement position. The latching mechanism 54 also includes actuating pressure communicating means, disposed in the tubular member on which the latch member means is mounted, for communicating an

actuating pressure to the latch member means so that the latch member means moves towards the other tubular member, and into the radial engagement position, in response to the actuating pressure. The latching mechanism 54 also includes biasing means, connected to the tubular member on which the latch member means is mounted, for exerting a biasing force against the latch member means in opposition to a force exerted on the latch member means by the actuating pressure so that the latch member means is biased away from the other tubular member and thus towards a radial disengagement position which is out of engagement with the locking sleeve engagement surface 100 even though the locking member means even partially overlies the engagement surface 100 and is thus at a longitudinal latchable or engageable position. Thus, this biasing force tends to move the latch member means deeper into its respective cavity. The latching mechanism 54 still further includes hydrostatic pressure communicating means, disposed in the tubular member on which the latch member means is not mounted, for communicating a hydrostatic pressure to the latch member means so that a force exerted by the hydrostatic pressure is applied to the latch member means in opposition to a force exerted on the latch member means by the actuating pressure.

The latch member means of the preferred embodiment includes four latch members, each disposed in a respective one of the cavities 62, 64, 66, 68. Because each of these latch members is identical, only a latch member 102 principally shown in FIG. 2B will be described. The latch member 102 includes a gripping member or means 104 for defining a latch member engagement surface 92 of the locking sleeve 36. The gripping means 104 of the preferred embodiment is constructed of an oblong carrier block 108 and a plurality of gripping teeth 110 defined in the preferred embodiment by carbide inserts retained in the carrier block 108 at oblique angles thereto to give a tilted configuration to the carbide inserts which facilitates their ability to bite or grip into the locking sleeve engagement surface 100 of the locking sleeve 36. The teeth 110 are received along a rectangular planar surface 111 of the carrier block 108, and they define a plurality of protuberances extending from the surface of the carrier block 108. Milled or otherwise defined in opposite ones of the curved ends of the oblong block 108 are respective recesses 112, 114. The recess 112 has a curved lower surface 116. Parallel planar surfaces 118, 120 extend from opposite edges of the surface 116. The recess 114 has a curved lower surface 122 and parallel planar surfaces 124, 126 extending from opposite edges of the surface 122.

The latch member 102 also includes seal means 128, detachably connected to the carrier block 108, for providing a sliding seal between the latch member 102 and the inner side walls of the cavity 62 in which the latch member 102 is disposed. The seal means 128 includes a seal support member 130 having an oblong configuration similar to that of the carrier block 108 and similar to the shape of the cavity 62. A peripheral groove 132 is defined around the perimeter of the seal support member 130. The groove 132 receives a seal assembly 134 comprising an O-ring or other suitable fluid member and also comprising a seal back-up ring which reduces the friction of the movable seal and which reinforces the primary seal ring against high pressure differentials that may exist across the sealing structure.

The seal support member 130 is connected to the carrier block 108 by a suitable connector means whereby the two are releasably connected to enable the carrier block 108 to be released from the seal support member 130, such as when the latch member engagement surface defined by the gripping teeth 110 is worn out and is to be replaced with another such gripping means. In the preferred embodiment this connector means includes a dovetail tenon 136, protruding from a central portion of the seal support member 130, and a mortise 138, defined centrally along and transversely across a surface of the carrier block 108 for slidably receiving the dovetail tenon 136.

These components of the latch member 102 define a slidable body which is movable within the cavity 62. Corresponding components define a plurality of other latch members respectively disposed in the cavities 64, 66, 68 for simultaneous slidable movement with the latch member 102. These movements occur in response to an actuating pressure provided through the tubing or pipe string from the surface and into the channel 58 of the locking mandrel 22 for communication into the cavities 62, 64, 66, 68 through respective ones of the plurality of actuating pressure communicating means contained in the preferred embodiment of the present invention. Because each of these communicating means is identical in the preferred embodiment, only the one associated with the cavity 62 will be particularly described hereinbelow.

In the preferred embodiment the actuating pressure communication means communicates a hydraulic pressure from the axial channel 58 into the cavities 62, 64, 66, 68 of the locking mandrel 22. This pressure exerts a force against the latch member 102 and the other similar latch members. This force, when sufficiently strong, moves the latch members radially outwardly so that at least portions of the engagement surfaces thereof interlock with at least a portion of the locking sleeve

engagement surface 100 of the locking sleeve 36 when these portions are radially aligned. This radial alignment is achieved after the packers have been set as will be more particularly described hereinbelow.

To provide this communication to the cavity 62, the preferred embodiment actuating pressure communicating means associated with the cavity 62 includes two holes 140, 142 defined by respective transverse walls of the locking mandrel 22. These walls extend between the channel 58 and the transverse cavity 62. In the preferred embodiment these walls are specifically radially extending walls. The actuating pressure communicated through these holes can be derived from the fracturing fluid pumped down through the central channel extending through the entire upper packer section 8 for introduction into the open well bore volume encompassed between the spaced packers of the lower and upper packer sections 6, 8.

The biasing means of the preferred embodiment latch mechanism 54 includes two spring members for each of the latch members. Because the spring members are identical, only the two associated with the latch member 102 shown in FIG. 2B will be described. These spring members are identified by the reference numerals 144, 146. The spring member 144 has a support portion 148 and an engagement portion 150 extending at an obtuse angle from the support portion 148. The spring member 144 is made of a resilient material so that the engagement portion 150 can bend relative to the support portion 148, but with a resulting biasing force being created tending to return the engagement portion 150 to its rest position shown in FIG. 2B. This action provides a biasing force which acts in opposition to the direction of the hydraulic actuating pressure applied through the holes 140, 142 and thereby tends to move the latch member 102 deeper into the cavity 62. This acts as a return force when the actuating pressure is removed.

The support portion 148 is received in the slot 70, and the engagement portion 150 extends as a spring finger into the recess 112 of the latch member 102. The spring member 144 is secured in the slot 70 by suitable connecting means which achieves the aforementioned construction wherein the end of the spring member 144 defined by the engagement portion 150 overhangs the cavity 62 and engages the carrier block 108 within its recess 112 to exert a radially inwardly directed force on the block 108 and thus on the overall latch member 102. This connecting means comprises in the preferred embodiment a spring backup or support member 152 placed adjacent the support portion 148 of the spring member 144, and the connecting means also includes a screw or bolt 154 extending

through holes defined in the support portion 148 and the spring support member 152 and into a radially extending threaded bore extending from the slot 70 into the protuberant portion 60 of the locking mandrel 22.

The spring member 146 is constructed and situated similarly to the spring member 144, except that it has a support portion 156 which is secured in the slot 72 by a spring support member 158 and a screw or bolt 160. This allows an engagement portion 162 of the spring member 146 to extend into the recess 114 of the latch member 102. Therefore, the spring member 146 extends in an opposite direction towards the spring member 144 and in a manner so that the engagement portion 162 overhangs the cavity 62 and engages the carrier block 108 to exert a radially inwardly directed force on the block 108.

The biasing means also includes a retaining ring 164 freely disposed between the screws or bolts 154, 160 and partially overlying the spring members 144, 146 and the carrier block 108. The ring 164 acts as a safety backup to prevent the spring members 144, 146 from becoming too outwardly extended.

The hydrostatic pressure communicating means of the latching mechanism 54 includes four radial passages defined through the locking sleeve 36 so that a pressure existing externally of the locking sleeve 36 is communicated internally thereof to exert a radially inwardly directed force on the latch member 102 and, in particular, on the carrier block 108 thereof. These four passages are equally spaced around the circumference of the locking sleeve 36 so that only one, identified as a hole 166, is shown in FIG. 2B. In the preferred embodiment each of these holes has a one-half inch diameter; however, any suitable size hole can be used. The hole 166, and its three counterparts, extend radially through the locking sleeve 36 along the shoulder 95 defined between the offset inner surfaces 92, 94. This provides communication passages for allowing the hydrostatic pressure existing outside the upper packer section 8 and above the packer 26 to be communicated into the volume 91 within the locking sleeve 36 between the seals 52, 82. These holes also allow the hydraulic chamber or volume 91 to fill with fluid as the dual packer assembly 2 is run in the hole, thereby balancing the internal and external pressures across the latch members during this time.

To use the present invention, the packer assembly 2 is attached to a tubing or pipe string (not shown) and run into the well bore 4 in a manner as known to the art. When the dual packer assembly 2 is at the appropriate location, the packer 26 and the packer of the lower packer section 6 are set, also in a manner as known to the art. In running this

structure into the well bore 4, the inner and outer tubular members of the upper packer section 8 are situated as shown in FIGS. 2A-2F; however, when the packers are set, relative movement between the inner and outer tubular members occurs so that the latch member 102, and the other three latch members disposed in the cavities 64, 66, 68, have at least portions of their latch member engagement surfaces radially aligned with at least a portion of the locking sleeve engagement surface 100. At this time, but prior to a sufficient actuating pressure being applied down through the tubing or pipe string and into the channel 58 of the locking mandrel 22, the spring members of the biasing means are holding the respective latch members in their radial unlatched positions, which are relatively radially inward positions, such as is illustrated by the position of the latch member 102 in FIG. 2B. These latch members are also held in these unlatched radial positions by the hydrostatic pressure existing in the annulus between the locking sleeve 36 and the surface of the well bore 4. This hydrostatic pressure is exerted on the latch members by being communicated thereto through the radial passages of the hydrostatic pressure communicating means (e.g., the hole 166). Locating the lock 18 above the top packer 26 isolates and limits the outside or external force acting radially inwardly on the latch members to the hydrostatic pressure.

When the hydraulic lock of the preferred embodiment of the present invention is to be actuated, whereby the latch members are moved into their engagement positions with the gripping teeth of the latch members interlocking with the locking sleeve engagement surface 100, a fluid is flowed down the tubing or pipe string into the channel 58 and pressurized until a sufficiently strong radially outwardly directed force is exerted through the actuating pressure communicating means (e.g., the holes 140, 142) on each of the latch members. A sufficient force is one which exceeds the forces exerted by the spring members and the hydrostatic pressure. The application of this radially outwardly directed force simultaneously moves each of the latch members radially outwardly to lock the inner tubular member 14 to the outer tubular member 16. This in effect locks the packer 26 to the lower packer section 6 because the inner tubular member 14 is connected to the lower packer section 6 through the lower adapter 24. As long as the tubing pressure exceeds the hydrostatic pressure and the biasing force of the spring members, the latch members lock into the outer housing of the upper packer section 8, thereby preventing upward movement of the top packer 26. Once the fracturing or other actuating pressure is removed, the latch members are returned to their original radially disengaged positions by the hydrostatic pressure and

the retracting spring members of the biasing means.

Thus, the present invention is well adapted to carry out the objects and attain the ends and advantages mentioned above as well as those inherent therein. While a preferred embodiment of the invention has been described for the purpose of this disclosure, numerous changes in the construction and arrangement of parts can be made by those skilled in the art, which changes are encompassed within the spirit of this invention as defined by the appended claims.

Claims

1. A lock (18) for a downhole apparatus having an inner tubular member (14) and an outer tubular member (16) in which the inner tubular member is slidably disposed, said lock comprising: a latch member (102) mounted on one of the inner and outer tubular members; actuating pressure communicating means (140,142), disposed in the one of the inner and outer tubular members on which said latch member is mounted, for communicating an actuating pressure to said latch member so that said latch member moves towards the other of the inner and outer tubular members in response to the actuating pressure; characterised in that said lock further comprises latch member engagement means (100), mounted on the other of the inner and outer tubular members, for interlocking with said latch member when said latch member is moved in response to the actuating pressure; and hydrostatic pressure communicating means (166), disposed in the other of the inner and outer tubular members, for communicating a hydrostatic pressure to said latch member so that a force exerted by the hydrostatic pressure is applied to said latch member in opposition to a force exerted on said latch member by the actuating pressure.
2. A lock according to claim 1, further comprising biasing means (144,146), connected to the one of the inner and outer tubular members on which said latch member is mounted, for biasing said latch member away from the other of the inner and outer tubular members.
3. A lock according to claim 1 or 2, wherein said latch member includes: a slidable body (104) disposed in a cavity (62) defined in the one of the inner and outer tubular members on which said latch member is mounted; and a plurality of gripping teeth (110) protruding from said slidable body.

structure into the well bore 4, the inner and outer tubular members of the upper packer section 8 are situated as shown in FIGS. 2A-2F; however, when the packers are set, relative movement between the inner and outer tubular members occurs so that the latch member 102, and the other three latch members disposed in the cavities 64, 66, 68, have at least portions of their latch member engagement surfaces radially aligned with at least a portion of the locking sleeve engagement surface 100. At this time, but prior to a sufficient actuating pressure being applied down through the tubing or pipe string and into the channel 58 of the locking mandrel 22, the spring members of the biasing means are holding the respective latch members in their radial unlatched positions, which are relatively radially inward positions, such as is illustrated by the position of the latch member 102 in FIG. 2B. These latch members are also held in these unlatched radial positions by the hydrostatic pressure existing in the annulus between the locking sleeve 36 and the surface of the well bore 4. This hydrostatic pressure is exerted on the latch members by being communicated thereto through the radial passages of the hydrostatic pressure communicating means (e.g., the hole 166). Locating the lock 18 above the top packer 26 isolates and limits the outside or external force acting radially inwardly on the latch members to the hydrostatic pressure.

When the hydraulic lock of the preferred embodiment of the present invention is to be actuated, whereby the latch members are moved into their engagement positions with the gripping teeth of the latch members interlocking with the locking sleeve engagement surface 100, a fluid is flowed down the tubing or pipe string into the channel 58 and pressurized until a sufficiently strong radially outwardly directed force is exerted through the actuating pressure communicating means (e.g., the holes 140, 142) on each of the latch members. A sufficient force is one which exceeds the forces exerted by the spring members and the hydrostatic pressure. The application of this radially outwardly directed force simultaneously moves each of the latch members radially outwardly to lock the inner tubular member 14 to the outer tubular member 16. This in effect locks the packer 26 to the lower packer section 6 because the inner tubular member 14 is connected to the lower packer section 6 through the lower adapter 24. As long as the tubing pressure exceeds the hydrostatic pressure and the biasing force of the spring members, the latch members lock into the outer housing of the upper packer section 8, thereby preventing upward movement of the top packer 26. Once the fracturing or other actuating pressure is removed, the latch members are returned to their original radially disengaged positions by the hydrostatic pressure and

the retracting spring members of the biasing means.

Thus, the present invention is well adapted to carry out the objects and attain the ends and advantages mentioned above as well as those inherent therein. While a preferred embodiment of the invention has been described for the purpose of this disclosure, numerous changes in the construction and arrangement of parts can be made by those skilled in the art, which changes are encompassed within the spirit of this invention as defined by the appended claims.

Claims

1. A lock (18) for a downhole apparatus having an inner tubular member (14) and an outer tubular member (16) in which the inner tubular member is slidably disposed, said lock comprising: a latch member (102) mounted on one of the inner and outer tubular members; actuating pressure communicating means (140,142), disposed in the one of the inner and outer tubular members on which said latch member is mounted, for communicating an actuating pressure to said latch member so that said latch member moves towards the other of the inner and outer tubular members in response to the actuating pressure; characterised in that said lock further comprises latch member engagement means (100), mounted on the other of the inner and outer tubular members, for interlocking with said latch member when said latch member is moved in response to the actuating pressure; and hydrostatic pressure communicating means (166), disposed in the other of the inner and outer tubular members, for communicating a hydrostatic pressure to said latch member so that a force exerted by the hydrostatic pressure is applied to said latch member in opposition to a force exerted on said latch member by the actuating pressure.
2. A lock according to claim 1, further comprising biasing means (144,146), connected to the one of the inner and outer tubular members on which said latch member is mounted, for biasing said latch member away from the other of the inner and outer tubular members.
3. A lock according to claim 1 or 2, wherein said latch member includes: a slidable body (104) disposed in a cavity (62) defined in the one of the inner and outer tubular members on which said latch member is mounted; and a plurality of gripping teeth (110) protruding from said slidable body.



4. A lock according to claim 3, wherein said slidable body includes carrier means (108) for carrying said gripping teeth; and seal means (128), detachably connected to said carrier means, for providing a sliding seal between said latch member and the cavity of the one of the inner and outer tubular members on which said latch member is mounted.
5. A lock according to claim 1 or 2, wherein said latch member includes a block (108) slidably disposed in a radial cavity (62) of the one of the inner and outer tubular members so that said block is constrained to radial travel in response to the actuating pressure.
6. A lock (18) according to claim 1, for a packer assembly, wherein said inner tubular member comprises a packer mandrel (20) and said outer tubular member (16) comprises a packer carrier sleeve, said lock comprising locking mandrel means (22) for connecting with the packer mandrel inside the packer carrier sleeve, said locking mandrel means having a longitudinal channel (58) and a transverse cavity (62) defined therein; said latch member means (102) is slidably disposed in said transverse cavity, for engaging the packer carrier sleeve when said latch member means is moved to an engagement position between said locking mandrel means and the packer carrier sleeve; and wherein the actuating pressure communicating means (140,142) are disposed in said locking mandrel means for communicating an actuating pressure from said longitudinal channel to said transverse cavity to move said latch member means to said engagement position.
7. A lock according to claim 6, wherein said latch member means includes: a seal support member (130); a seal (134) disposed around the perimeter of said seal support member in slidable sealing engagement with said transverse cavity; and a gripper member (108), connected to said seal support member having a plurality of protuberances (110) extending therefrom.
8. A lock according to claim 10, further comprising at least one spring member (144,146) connected to said locking mandrel means in engagement with said gripper member.
9. A lock according to claim 6,7 or 8, wherein said actuating pressure communicating means includes a hole (140,142) defined by a transverse wall of said locking mandrel means ex-

tending between said longitudinal channel (58) and said transverse cavity (62) so that the actuating pressure communicated therethrough exerts a force on said seal support member.

10. A lock according to claim 6,7,8 or 9, wherein: said locking mandrel means includes a plurality of other transverse cavities (64,66,68) disposed circumferentially around said locking mandrel means in pairs of diametrically opposed cavities; and said lock further comprises: a plurality of other latch member means, each slidably disposed in a respective one of said other transverse cavities, for engaging the packer carrier sleeve when each is moved to a respective engagement position between said locking mandrel means and the packer carrier sleeve; and a plurality of other actuating pressure communicating means, disposed in said locking mandrel means, for simultaneously communicating the actuating pressure from said longitudinal channel to all said other transverse cavities to move said other latch member means to their respective engagement positions.
11. A lock according to claim 1, for holding down an upper packer (8) mounted on a packer mandrel (20) connected to a lower packer (6), wherein said inner tubular member (14) comprises said packer mandrel (20), and said outer tubular member (16) comprises a locking sleeve (36), said lock comprising said locking sleeve (36) connected to the upper packer, said locking sleeve having an inner surface (92) along which is defined said latch member engagement means comprising locking sleeve engagement surface (100); a locking mandrel (22) connected to the packer mandrel, said locking mandrel having an outer surface, facing said inner surface of said locking sleeve, and an inner surface (56), defining an axial channel (58) through said locking mandrel, said outer surface having a radial cavity (62) defined therethrough extending within said locking mandrel towards said axial channel; and wherein said latch member (102) is slidably disposed in said cavity, said latch member having a latch member engagement surface (106) facing said inner surface of said locking sleeve; and wherein said actuating pressure communicating means (140,142) are disposed in said locking mandrel for communicating a hydraulic pressure from said axial channel into said cavity and against said latch member, whereby said latch member is thereby movable, so that at least a portion of said latch member engagement surface interlocks with at



least a portion of said locking sleeve engagement surface when said portions are radially aligned and said hydraulic pressure is applied.

12. A lock according to claim 11, further comprising: two longitudinally spaced seals (52,82) disposed between said locking sleeve and said locking mandrel;; and hydrostatic pressure communicating means (166), disposed in said locking sleeve, for communicating a hydrostatic pressure from outside said locking sleeve into a volume (91) between said locking sleeve and said locking mandrel and between said two seals, said volume having said latch member received therein.

Patentansprüche

1. Verriegelung (18) für eine Bohrlochvorrichtung mit einem inneren rohrförmigen Glied (14) und einem äußeren rohrförmigen Glied (16), in dem das innere rohrförmige Glied gleitbar angeordnet ist, enthaltend: ein Riegelglied (102), das an einem der inneren und äußeren rohrförmigen Glieder angebracht ist; Übertragungsmittel (140, 142) für einen Betätigungsdruck in dem einen der inneren und äußeren Glieder, an dem das Riegelglied angebracht ist, zur Übertragung des Betätigungsdrucks auf das Riegelglied, so daß sich das Riegelglied unter Ansprechen auf den Betätigungsdruck zu dem anderen der inneren und äußeren rohrförmigen Glieder verstellt,

dadurch gekennzeichnet, daß die Verriegelung weiter an dem anderen der inneren und äußeren rohrförmigen Glieder angebrachte Riegelgliedeingriffsmittel (100) zur Verriegelung mit dem Riegelglied enthält, wenn das Riegelglied unter Ansprechen auf den Betätigungsdruck verstellt ist; und in dem anderen der inneren und äußeren rohrförmigen Glieder angeordnete Übertragungsmittel (166) für hydrostatischen Druck zur Übertragung von hydrostatischem Druck auf das Riegelglied, so daß eine durch den hydrostatischen Druck ausgeübte Kraft entgegen einer durch den Betätigungsdruck auf das Riegelglied ausgeübten Kraft an das Riegelglied angelegt wird.

2. Verriegelung nach Anspruch 1, ferner gekennzeichnet durch Vorspannmittel (144, 146), die mit dem einen der inneren und äußeren rohrförmigen Glieder, an dem das Riegelglied angebracht ist, verbunden sind und das Riegelglied von dem anderen der inneren und äußeren rohrförmigen Glieder weg vorspannen.

3. Verriegelung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß das Riegelglied enthält: einen Gleitkörper (104), der in einem Hohlraum (62) angeordnet ist, der in dem einen der inneren und äußeren rohrförmigen Glieder, an dem das Riegelglied angebracht ist, bestimmt ist, und eine Vielzahl von Greifzähnen (110), die von dem Gleitkörper vorstehen.

4. Verriegelung nach Anspruch 3, dadurch gekennzeichnet, daß der Gleitkörper Trägermittel (108) zum Tragen der Greifzähne enthält; und Dichtmittel (128), die mit den Trägermitteln lösbar verbunden sind und eine Gleitdichtung zwischen dem Riegelglied und dem Hohlraum des einen der inneren und äußeren rohrförmigen Glieder bilden, an dem das Riegelglied angebracht ist.

5. Verriegelung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß das Riegelglied einen Block (108) enthält, der gleitbar in einem radialen Hohlraum (62) des einen der inneren und äußeren rohrförmigen Glieder angeordnet ist, so daß der Block beim Ansprechen auf den Betätigungsdruck auf Radialverstellung beschränkt ist.

6. Verriegelung (18) nach Anspruch 1 für eine Packeranordnung, dadurch gekennzeichnet, daß das innere rohrförmige Glied einen Packerdorn (20) und das äußere rohrförmige Glied (16) eine Packerträgerhülse und die Verriegelung Riegeldornmittel (22) zur Verbindung mit dem Packerdorn innerhalb der Packerträgerhülse aufweisen und die Riegeldornmittel einen Längskanal (58) enthalten und in diesen ein quer verlaufender Hohlraum (62) bestimmt ist; daß die Riegelgliedmittel (102) gleitbar in dem quer verlaufenden Hohlraum zum Eingriff mit der Packerträgerhülse angeordnet sind, wenn die Riegelgliedmittel in eine Eingriffsstellung zwischen den Riegeldornmitteln und der Packerträgerhülse verstellt sind; und daß die Übertragungsmittel (140, 142) für den Betätigungsdruck in den Riegeldornmitteln angeordnet sind, um den Betätigungsdruck aus dem Längskanal auf den quer verlaufenden Hohlraum zu übertragen und die Riegelgliedmittel in die Eingriffsstellung zu verstellen.

7. Verriegelung nach Anspruch 6, dadurch gekennzeichnet, daß die Riegelgliedmittel enthalten: ein Dichtungstragglied (130); eine entlang dem Umfangsrand des Dichtungstraggliedes angeordnete Dichtung (134) in gleitbar abdichtender Anlage an dem quer verlaufenden Hohlraum; und ein Greifglied (108), das mit dem



Dichtungstragglied verbunden ist und eine Vielzahl von davon ausgehenden Vorsprüngen (110) enthält.

8. Verriegelung nach Anspruch 10, ferner gekennzeichnet durch wenigstens ein Federglied (144, 146), das mit den Riegeldornmitteln in Anlage an dem Greifglied verbunden ist.

9. Verriegelung nach Anspruch 6, 7 oder 8, dadurch gekennzeichnet, daß die Übertragungsmittel für den Betätigungsdruck ein Loch (140, 142) enthalten, das durch eine quer verlaufende Wandung der Riegeldornmittel bestimmt ist und sich zwischen dem Längskanal (58) und dem quer verlaufenden Hohlraum (62) erstreckt, so daß der dadurch übertragene Betätigungsdruck eine Kraft auf das Dichtungstragglied ausübt.

10. Verriegelung nach Anspruch 6, 7, 8 oder 9, dadurch gekennzeichnet, daß die Riegeldornmittel eine Vielzahl weiterer quer verlaufender Hohlräume (64, 66, 68) enthalten, die in Paaren von diametral gegenüberliegenden Hohlräumen umfangsmäßig um die Riegeldornmittel herum angeordnet sind; und daß die Verriegelung ferner aufweist: eine Vielzahl von weiteren Riegelgliedmitteln, die jeweils gleitbar in einem der weiteren quer verlaufenden Hohlräume zum Eingriff mit der Packerträgerhülse angeordnet sind, wenn sie in ihre jeweilige Eingriffsstellung zwischen den Riegeldornmitteln und der Packerträgerhülse verstellt sind; und eine Vielzahl von weiteren Übertragungsmitteln für den Betätigungsdruck, die in den Riegeldornmitteln angeordnet sind, um den Betätigungsdruck aus dem Längskanal gleichzeitig auf alle weiteren quer verlaufenden Hohlräume zu übertragen und die weiteren Riegelgliedmittel in ihre jeweiligen Eingriffsstellungen zu verstellen.

11. Verriegelung nach Anspruch 1 zur Niederhaltung eines oberen Packers (8), der an einem mit einem unteren Packer (6) verbundenen Packerdorn (20) angebracht ist, dadurch gekennzeichnet, daß das innere rohrförmige Glied (14) den Packerdorn (20) und das äußere rohrförmige Glied (16) eine Riegelhülse (36) aufweist, daß die Verriegelung eine mit dem oberen Packer verbundene Riegelhülse (36) mit einer Innenfläche (92) aufweist, entlang derer die Riegelgliedeingriffsmittel bestimmt sind, die eine Riegelhülseingriffsfläche (100) aufweisen; einen mit dem Packerdorn verbundenen Riegeldorn (22) mit einer der Innenfläche der Riegelhülse zugekehrten Außenfläche, ei-

ner Innenfläche (56), die einen Axialkanal (58) durch den Riegeldorn begrenzt, und einen in der Außenfläche bestimmten, radialen Hohlraum (62), der innerhalb des Riegeldorns zu dem Axialkanal verläuft; und daß das Riegelglied (102) gleitbar in dem Hohlraum angeordnet ist und eine Riegelgliedeingriffsfläche (106) enthält, die der Innenfläche der Riegelhülse zugekehrt ist; und daß die Übertragungsmittel (140, 142) für den Betätigungsdruck in dem Riegeldorn zur Übertragung eines hydraulischen Drucks aus dem Axialkanal in den Hohlraum und gegen das Riegelglied angeordnet sind, wodurch das Riegelglied bewegbar ist, so daß wenigstens ein Teil der Riegelgliedeingriffsfläche mit wenigstens einem Teil der Riegelhülseingriffsfläche verriegelt ist, wenn diese Teile radial zueinander ausgerichtet sind und der hydraulische Druck angelegt ist.

12. Verriegelung nach Anspruch 11, ferner gekennzeichnet durch zwei Dichtungen (52, 82), die im Längsabstand zwischen der Riegelhülse und dem Riegeldorn angeordnet sind; und in der Riegelhülse angeordnete Übertragungsmittel (166) für hydrostatischen Druck zur Übertragung von hydrostatischem Druck von der Außenseite der Riegelhülse in ein Volumen (91) zwischen der Riegelhülse und dem Riegeldorn und zwischen den beiden Dichtungen, in dem das Riegelglied aufgenommen ist.

Revendications

1. Verrou (18) pour appareil de fonds de puits ayant un organe (14) tubulaire intérieur et un organe (16) tubulaire extérieur dans lequel l'organe tubulaire intérieur est disposé de manière coulissante, ledit verrou comprenant : un organe (102) formant loquet monté sur un des organes tubulaires intérieur et extérieur ; des moyens de communication (140, 142) d'une pression d'actionnement, disposés dans celui des organes tubulaires intérieur et extérieur sur lequel l'organe formant loquet est monté, pour communiquer une pression d'actionnement à l'organe formant loquet, de sorte que l'organe formant loquet se déplace vers l'autre des organes tubulaires intérieur et extérieur en réponse à la pression d'actionnement ; caractérisé en ce que ledit verrou comporte en outre des moyens (100) de prise avec l'organe formant loquet, montés sur l'autre des organes tubulaires intérieur et extérieur, pour venir en prise avec ledit organe formant loquet lorsque l'organe formant loquet est déplacé en réponse à la pression d'actionnement ; et des moyens de communication (166) d'une pression hy-



drostatique, disposés dans l'autre des organes tubulaires intérieur et extérieur, pour communiquer une pression hydrostatique à l'organe formant loquet de sorte qu'une force exercée par la pression hydrostatique est appliquée à l'organe formant loquet en opposition à la force exercée sur l'organe formant loquet par la pression d'actionnement.

2. Verrou selon la revendication 1, comportant en outre des moyens de sollicitation (144, 146), reliés à celui des organes tubulaires intérieur et extérieur sur lequel l'organe formant loquet est monté, pour solliciter l'organe formant loquet vers l'écartement par rapport à l'autre des organes tubulaires intérieur et extérieur.

3. Verrou selon la revendication 1 ou 2, dans lequel l'organe formant loquet comporte : un corps (104) pouvant coulisser disposé dans une cavité (62) définie dans celui des organes tubulaires intérieur et extérieur sur lequel l'organe formant loquet est monté ; et plusieurs dents (110) de serrage faisant saillie à partir dudit corps pouvant coulisser.

4. Verrou selon la revendication 3, dans lequel le corps pouvant coulisser comporte des moyens (108) porteurs pour porter les dents de serrage, et des moyens d'étanchéité (128) reliés de manière détachable aux moyens porteurs, pour fournir un joint couissant entre ledit organe formant loquet et la cavité de celui des organes tubulaires intérieur et extérieur sur lequel l'organe formant loquet est monté.

5. Verrou selon la revendication 1 ou 2, dans lequel ledit organe formant loquet comporte un bloc (108) disposé de manière à pouvoir coulisser dans une cavité (62) radiale du premier des organes tubulaires intérieur et extérieur de telle sorte que le bloc est contraint de se déplacer radialement en réponse à la pression d'actionnement.

6. Verrou (18) selon la revendication 1, pour ensemble de packer, dans lequel ledit organe tubulaire intérieur comporte un mandrin (20) de packer et ledit organe tubulaire extérieur (16) comporte un manchon porteur de packer, ledit verrou comprenant des moyens (22) formant mandrin de verrouillage destinés à être reliés au mandrin de packer à l'intérieur du manchon porteur de packer, les moyens formant mandrin de verrouillage ayant un canal longitudinal (58) et une cavité transversale (62) qui y sont définis ; l'organe (102) formant loquet étant disposé de manière à pouvoir coulisser dans

ladite cavité transversale, pour venir en contact avec le manchon porteur de packer lorsque l'organe formant loquet est déplacé jusqu'à une position de prise entre les moyens formant mandrin de verrouillage et le manchon porteur de packer ; et dans lequel les moyens (140, 142) de communication d'une pression d'actionnement sont disposés dans lesdits moyens formant mandrin de verrouillage pour communiquer une pression d'actionnement depuis ledit canal longitudinal jusqu'à ladite cavité transversale pour déplacer l'organe formant loquet jusqu'à ladite position de prise.

7. Verrou selon la revendication 6, dans lequel l'organe formant loquet comporte : un organe (130) support de joint ; un joint (134) disposé autour de la périphérie dudit organe support de joint, en contact étanche avec la cavité transversale et pouvant coulisser, et un organe (108) de saisie, relié à l'organe support de joint, ayant plusieurs protubérances (110) s'étendant à partir de celui-ci.

8. Verrou selon la revendication 7, comprenant en outre au moins un organe formant ressort (144, 146) relié aux moyens formant mandrin de verrouillage, en contact avec ledit organe de saisie.

9. Verrou selon la revendication 6, 7 ou 8, dans lequel lesdits moyens de communication d'une pression d'actionnement comportent un trou (140, 142) défini par une paroi transversale desdits moyens formant mandrin de verrouillage s'étendant entre ledit canal (58) longitudinal et ladite cavité (62) transversale de telle sorte que la pression d'actionnement communiquée à travers celui-ci exerce une force sur l'organe support de joint.

10. Verrou selon la revendication 6, 7, 8 ou 9, dans lequel : les moyens formant mandrin de verrouillage comportent plusieurs autres cavités (64, 66, 68) transversales disposées circonférentiellement autour des moyens formant mandrin de verrouillage en formant des paires de cavités diamétralement opposées ; et le verrou comporte en outre : plusieurs autres organes formant loquet, chacun étant disposé de manière à pouvoir coulisser dans une cavité respective desdites autres cavités transversales, pour venir en contact avec le manchon porteur de packer lorsque chacun est déplacé jusqu'à une position respective de prise entre lesdits moyens formant mandrin de verrouillage et le manchon porteur de packer ; et plusieurs autres moyens de communication d'une



pression d'actionnement, disposés dans lesdits moyens formant mandrin de verrouillage, pour simultanément communiquer la pression d'actionnement à partir dudit canal longitudinal jusqu'à toutes les autres cavités transversales pour déplacer lesdits autres organes formant loquet jusqu'à leurs positions respectives de prise.

5

de verrouillage, pour communiquer une pression hydrostatique à partir de l'extérieur dudit manchon de verrouillage jusqu'à un volume (91) situé entre ledit manchon de verrouillage et ledit mandrin de verrouillage et entre lesdits deux joints, ledit volume recevant ledit organe formant loquet.

11. Verrou selon la revendication 1, pour maintenir vers le bas un packer supérieur (8) monté sur un mandrin (20) de packer relié à un packer inférieur (6), dans lequel ledit organe (14) tubulaire intérieur comporte ledit mandrin (20) de packer, et ledit organe (16) tubulaire extérieur comporte un manchon (36) de verrouillage, ledit verrou comportant ledit manchon (36) de verrouillage relié au packer supérieur, ledit manchon de verrouillage ayant une surface intérieure (92) le long de laquelle sont définis lesdits moyens de prise d'organe formant loquet comprenant une surface (100) de prise du manchon de verrouillage ; un mandrin (22) de verrouillage relié au mandrin de packer, ledit mandrin de verrouillage ayant une surface extérieure située en vis-à-vis de ladite surface intérieure du manchon de verrouillage, et une surface intérieure (56) définissant un canal (58) axial traversant le mandrin de verrouillage, ladite surface extérieure ayant une cavité (62) radial la traversant et s'étendant dans ledit mandrin de verrouillage vers le canal axial ; et dans lequel ledit organe (102) formant loquet est disposé de manière coulissante dans la cavité, ledit organe formant loquet ayant une surface (106) de prise d'organe formant loquet située vis-à-vis de ladite surface intérieure du manchon de verrouillage ; et dans lequel lesdits moyens (140, 142) de communication d'une pression d'actionnement sont disposés dans ledit mandrin de verrouillage pour communiquer une pression hydraulique à partir du canal axial jusqu'à ladite cavité et contre ledit organe formant loquet, de sorte que l'organe formant loquet est ainsi rendu mobile, de telle sorte qu'au moins une partie de ladite surface de prise de l'organe formant loquet vient en prise avec au moins une partie de la surface de prise du manchon de verrouillage lorsque lesdites parties sont alignées radialement et que ladite pression hydraulique est appliquée.

10

15

20

25

30

35

40

45

50

12. Verrou selon la revendication 11, comportant en outre : deux joints (52, 82) espacés longitudinalement disposés entre le manchon de verrouillage et le mandrin de verrouillage ; et des moyens (166) de communication d'une pression hydrostatique, disposés dans le manchon

55

