

Description

The present invention relates to beverage mixes, more particularly to beverage mixes in which beverage base agglomerates are coated with a thin layer of a fat-based confectionery coating.

GB-A-1273298 discloses a method of improving the quality and storage stability of dehydrated comestible products such as freeze-dried coffee.

There is a desire for beverage mixes, which are to be mixed with hot milk or water for consumption, which contain real chocolate.

Beverage mixes are known in which a small amount of chocolate powder is mixed with a beverage powder such as cocoa, but these products suffer from the disadvantages that the presence of chocolate is not self-evident before dissolution or if larger pieces of chocolate are used, the melting and distribution of chocolate throughout the drink is not as rapid as may be desired.

We have devised a method of preparing beverage mixes which comprises spraying a fat based confectionery coating onto beverage mix agglomerates as a thin layer. When the fat-based confectionery material is chocolate, not only is the presence of real chocolate self-evident before dissolution but the melting and distribution of the chocolate throughout the drink is extremely rapid.

Accordingly, the present invention provides a beverage mix in which beverage base agglomerates are coated with a layer of a fat-based confectionery material in an amount of from 2.5 to 50% by weight based on the total weight of the beverage mix.

The beverage base may be for example, cocoa, hot cocoa mix, coffee or a mixture of skim milk powder and sugar. The agglomerates may advantageously be made by any suitable method e.g. free-fall, spray drying, spray cooling or in a fluidised bed. One convenient method involves atomising water in a fluidised bed at a temperature of, for instance, 30°C to 50°C. The agglomerates made are generally of irregular shape and have a low density.

The agglomerates of the beverage base conveniently have a particle size of from 2mm to 0.42mm (10 to 40 mesh, U.S. Standard), i.e. the average diameter of the particles is from 0.4 mm to 2.0 mm, and preferably from 0.6 mm to 1.0 mm.

The fat-based confectionery coating may be any kind of confectionery material with fat as the continuous phase, for example, milk or dark chocolate or compound coatings containing non-cocoa butter vegetable fats or various substitutes such as direct cocoa butter replacements, stearines, coconut oil, palm oil, butter or any mixture thereof.

The fat-based confectionery material should be in a fluidised state e.g. molten for application onto the agglomerates of a beverage base to form a coating and it is conveniently adjusted for viscosity and hard-

ening properties, i.e. it has an appropriate viscosity at a certain specified temperature so that it is pumpable and will harden at a suitable stage after application to the agglomerates. The application of the fat-based confectionery material to the agglomerates of a beverage base is advantageously achieved by spraying. Conveniently, the fat-based confectionery material in the molten state is broken down into particles of a size sufficiently small for coating, for example by atomising, and sprayed on to the agglomerates of the beverage base, conveniently in a fluidised bed, at a temperature of, for instance, from 20° to 60°C. Alternatively, the fat-based confectionery material may be dispensed in drops onto the agglomerates and coated in conventional coating equipment.

The amount of fat-based confectionery coating may be, preferably, from 5 to 25% by weight based on the total weight of the beverage mix. Generally longer application times give a higher uptake.

Advantageously, the agglomeration of the beverage base and the application of the fat-based confectionery material are carried out in the same piece of equipment.

If desired, various flavours may be added either to the beverage base or to the coating material. Water soluble flavours may be added to the beverage base and oil soluble flavours may be added to the fat-based coating. Examples of flavours that may be added include mint, cherry, malt, orange and cinnamon.

The beverage mix prepared by the process of the present invention may be prepared for consumption by mixing with a hot liquid. Although the temperature of the hot liquid may be from 40°C to 100°C it is preferable that the temperature is at least 75°C. Any consumable liquid that can be safely heated to at least 75°C can be used as the liquid medium, for example, coffee or tea, but milk or water are most appropriate. A convenient method of preparing the beverage mix for consumption is by adding an appropriate quantity of the beverage mix to cold liquid and then putting in a microwave oven at full power for about 1.5 minutes.

The present invention also provides a process for preparing a beverage mix which comprises applying from 2.5 to 50% by weight based on the total weight of beverage mix of a fat-based confectionery material onto agglomerates of a beverage base.

The beverage mix according to this invention provides a unique means of showing that a beverage product contains real chocolate and in which the chocolate is melted and distributed rapidly throughout the drink.

The following Examples further illustrate the present invention:

Example 1

Hot Cocoa Mix agglomerates (approximately 0.84mm (20 mesh) particle size) were made by atom-

ising with water in a fluidised bed at 40°C. Then, adjusted milk chocolate at 50°C was poured into a 30 cm³ (30cc) plastic syringe. The coating was applied over a period of 2 minutes onto the tumbling particles of agglomerates by generating a spray of molten chocolate using compressed air in an atomising nozzle. The mix was heated to 60°C during addition of the chocolate and then cooled while still fluidised to harden the chocolate onto the Hot Cocoa Mix agglomerate surfaces. The amount of milk chocolate coating was on average 7% by weight based on the total weight of the mix.

Two teaspoonfuls of this beverage mix were added to 120 g (grams) of hot milk in which the agglomerates rapidly dispersed to give a tasty drink.

Example 2

A similar procedure to that described in Example 1 was followed except that the spraying of the molten chocolate took place over a longer period of 7 minutes so that the amount of milk chocolate coating was on average 20% by weight based on the total weight of the mix.

Example 3

A similar procedure to that described in Example 1 was followed except that instead of cocoa mix, a mixture of skim milk powder and sugar containing 66% skim milk powder was agglomerated and, instead of milk chocolate, dark chocolate was coated onto the agglomerates to give a product consisting of 22% dark chocolate, 31% skim milk powder and 47% sugar.

Claims

1. A beverage mix in which beverage base agglomerates are coated with a layer of a fat-based confectionery coating in an amount of from 2.5 to 50% by weight based on the total weight of the beverage mix.
2. A beverage mix according to claim 1 wherein the agglomerated beverage base is cocoa, hot cocoa mix, coffee or a mixture of skim milk powder and sugar.
3. A beverage mix according to claim 1 wherein the agglomerates of the beverage base have a particle size of from 2mm to 0.42 mm.
4. A beverage mix according to claim 1 wherein the fat-based confectionery material is milk or dark chocolate.
5. A beverage mix according to claim 1 wherein the fat-based confectionery material contains non-cocoa butter vegetable fat.
6. A beverage mix according to claim 1 wherein the application of the fat-based confectionery material to the agglomerates of the beverage base is achieved by spraying.
7. A beverage mix according to claim 1 wherein the fat-based confectionery material is atomized and sprayed on to the agglomerates of the beverage base at a temperature from 20° to 60°C.
8. A beverage mix according to claim 1 wherein the amount of fat-based confectionery material applied to the agglomerates of the beverage base is from 5 to 25% by weight based on the total weight of the beverage mix.
9. A process for preparing a beverage mix according to anyone claim 1-8 which comprises applying from 2.5 to 50% by weight based on the total weight of the beverage mix of a fat-based confectionery material onto agglomerates of a beverage base.

Patentansprüche

1. Getränkemischung, in welcher Agglomerate aus einer Getränkebasis mit einer Schicht eines Süßwarenüberzuges auf Fettbasis in einer Menge von 2,5 bis 50 Gew.-%, bezogen auf das Gesamtgewicht der Getränkemischung, überzogen sind.
2. Getränkemischung nach Anspruch 1, wobei die agglomerierte Getränkebasis Kakao, ein Heißkakaogemisch, Kaffee oder ein Gemisch aus Magermilchpulver und Zucker ist.
3. Getränkemischung nach Anspruch 1, wobei die Agglomerate aus der Getränkebasis eine Teilchengröße von 2 mm bis 0,42 mm haben.
4. Getränkemischung nach Anspruch 1, wobei das Süßwarenmateriale auf Fettbasis Milkschokolade oder dunkle Schokolade ist.
5. Getränkemischung nach Anspruch 1, wobei das Süßwarenmateriale auf Fettbasis ein nicht aus Kakaobutter bestehendes, pflanzliches Fett enthält.
6. Getränkemischung nach Anspruch 1, wobei die Aufbringung des Süßwarenmateriale auf Fettbasis auf die Agglomerate aus der Getränkebasis durch Aufsprühen erfolgt.

ising with water in a fluidised bed at 40°C. Then, adjusted milk chocolate at 50°C was poured into a 30 cm³ (30cc) plastic syringe. The coating was applied over a period of 2 minutes onto the tumbling particles of agglomerates by generating a spray of molten chocolate using compressed air in an atomising nozzle. The mix was heated to 60°C during addition of the chocolate and then cooled while still fluidised to harden the chocolate onto the Hot Cocoa Mix agglomerate surfaces. The amount of milk chocolate coating was on average 7% by weight based on the total weight of the mix.

Two teaspoonfuls of this beverage mix were added to 120 g (grams) of hot milk in which the agglomerates rapidly dispersed to give a tasty drink.

Example 2

A similar procedure to that described in Example 1 was followed except that the spraying of the molten chocolate took place over a longer period of 7 minutes so that the amount of milk chocolate coating was on average 20% by weight based on the total weight of the mix.

Example 3

A similar procedure to that described in Example 1 was followed except that instead of cocoa mix, a mixture of skim milk powder and sugar containing 66% skim milk powder was agglomerated and, instead of milk chocolate, dark chocolate was coated onto the agglomerates to give a product consisting of 22% dark chocolate, 31% skim milk powder and 47% sugar.

Claims

1. A beverage mix in which beverage base agglomerates are coated with a layer of a fat-based confectionery coating in an amount of from 2.5 to 50% by weight based on the total weight of the beverage mix.
2. A beverage mix according to claim 1 wherein the agglomerated beverage base is cocoa, hot cocoa mix, coffee or a mixture of skim milk powder and sugar.
3. A beverage mix according to claim 1 wherein the agglomerates of the beverage base have a particle size of from 2mm to 0.42 mm.
4. A beverage mix according to claim 1 wherein the fat-based confectionery material is milk or dark chocolate.
5. A beverage mix according to claim 1 wherein the fat-based confectionery material contains non-cocoa butter vegetable fat.
6. A beverage mix according to claim 1 wherein the application of the fat-based confectionery material to the agglomerates of the beverage base is achieved by spraying.
7. A beverage mix according to claim 1 wherein the fat-based confectionery material is atomized and sprayed on to the agglomerates of the beverage base at a temperature from 20° to 60°C.
8. A beverage mix according to claim 1 wherein the amount of fat-based confectionery material applied to the agglomerates of the beverage base is from 5 to 25% by weight based on the total weight of the beverage mix.
9. A process for preparing a beverage mix according to anyone claim 1-8 which comprises applying from 2.5 to 50% by weight based on the total weight of the beverage mix of a fat-based confectionery material onto agglomerates of a beverage base.

Patentansprüche

1. Getränkemischung, in welcher Agglomerate aus einer Getränkebasis mit einer Schicht eines Süßwarenüberzuges auf Fettbasis in einer Menge von 2,5 bis 50 Gew.-%, bezogen auf das Gesamtgewicht der Getränkemischung, überzogen sind.
2. Getränkemischung nach Anspruch 1, wobei die agglomerierte Getränkebasis Kakao, ein Heißkakaogemisch, Kaffee oder ein Gemisch aus Magermilchpulver und Zucker ist.
3. Getränkemischung nach Anspruch 1, wobei die Agglomerate aus der Getränkebasis eine Teilchengröße von 2 mm bis 0,42 mm haben.
4. Getränkemischung nach Anspruch 1, wobei das Süßwarenmateriel auf Fettbasis Milkschokolade oder dunkle Schokolade ist.
5. Getränkemischung nach Anspruch 1, wobei das Süßwarenmateriel auf Fettbasis ein nicht aus Kakaobutter bestehendes, pflanzliches Fett enthält.
6. Getränkemischung nach Anspruch 1, wobei die Aufbringung des Süßwarenmateriels auf Fettbasis auf die Agglomerate aus der Getränkebasis durch Aufsprühen erfolgt.



- | | | |
|--|--|--|
| <p>7. Getränkemischung nach Anspruch 1, wobei des Süßwarenmateriale auf Fettbasis zerstäubt und auf die Agglomerate aus der Getränkebasis bei einer Temperatur von 20° bis 60°C aufgesprüht wird.</p> <p>8. Getränkemischung nach Anspruch 1, wobei die Menge des auf die Agglomerate aus der Getränkebasis aufgetragenen Süßwarenmateriale auf Fettbasis 5 bis 25 Gew.%, bezogen auf das Gesamtgewicht der Getränkemischung, beträgt.</p> <p>9. Verfahren zur Herstellung einer Getränkemischung nach einem der Ansprüche 1 bis 8, welches das Aufbringen eines Süßwarenmateriale auf Fettbasis, in einer Menge von 2,5 bis 50 Gew.%, bezogen auf das Gesamtgewicht der Getränkemischung, auf die Agglomerate aus einer Getränkebasis umfaßt.</p> | <p>5</p> <p>10</p> <p>15</p> <p>20</p> | <p>1, dans laquelle la matière de confiserie à base de matières grasses est atomisée et pulvérisée sur les agglomérats de la base pour boisson à une température comprise entre 20° et 60°C.</p> <p>8. Préparation pour boisson selon la revendication 1, dans laquelle la quantité de matière de confiserie à base de matières grasses appliquée aux agglomérats de la base pour boisson est comprise entre 5 et 25 % en poids sur la base du poids total de la préparation pour boisson.</p> <p>9. Procédé pour élaborer une préparation pour boisson selon l'une quelconque des revendications 1 à 8, qui consiste à appliquer de 2,5 à 50 % en poids, sur la base du poids total de la préparation pour boisson, d'une matière de confiserie à base de matières grasses sur les agglomérats d'une base pour boisson.</p> |
|--|--|--|

Revendications

- | | |
|--|--|
| <p>1. Préparation pour boisson dans laquelle des agglomérats de base pour boisson sont enrobés d'une couche d'un enrobage de confiserie à base de matières grasses en quantité comprise entre 2,5 et 50 % en poids sur la base du poids total de la préparation pour boisson.</p> <p>2. Préparation pour boisson selon la revendication 1, dans laquelle la base agglomérée pour boisson est formée de cacao, d'une préparation de cacao chaud, de café ou d'un mélange de lait écrémé en poudre et de sucre.</p> <p>3. Préparation pour boisson selon la revendication 1, dans laquelle les agglomérats de la base pour boisson ont une dimension de particules comprise entre 2 mm et 0,42 mm.</p> <p>4. Préparation pour boisson selon la revendication 1, dans laquelle la matière de confiserie à base de matières grasses est du lait ou du chocolat noir.</p> <p>5. Préparation pour boisson selon la revendication 1, dans laquelle la matière de confiserie à base de matières grasses contient une matière grasse végétale autre que du beurre de cacao.</p> <p>6. Préparation pour boisson selon la revendication 1, dans laquelle l'application de la matière de confiserie à base de matières grasses sur les agglomérats de la base pour boisson est réalisée par pulvérisation.</p> <p>7. Préparation pour boisson selon la revendication</p> | <p>25</p> <p>30</p> <p>35</p> <p>40</p> <p>45</p> <p>50</p> <p>55</p> <p>4</p> |
|--|--|

