



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: A47K 3/22, E06B 3/80	A1	(11) International Publication Number: WO 96/32873
		(43) International Publication Date: 24 October 1996 (24.10.96)
(21) International Application Number: PCT/US96/05405		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 18 April 1996 (18.04.96)		
(30) Priority Data: 08/424,858 19 April 1995 (19.04.95) US		
(71) Applicant: STERLING PLUMBING GROUP, INC. [US/US]: 2900 Golf Road, Rolling Meadows, IL 60008-4013 (US).		
(72) Inventors: PAREDES, Raul, M.; 321 Roslyn, Barrington, IL 60010 (US). POGGIO, Frank, T.; Apartment 206, 5550 Astor Lane, Rolling Meadows, IL 60008 (US). SAUTER, Bruce, M.; 1636 St. Andrews Circle, Elgin, IL 60123 (US). BUCCICONE, Dana, F.; 1749 Hartford Lane, Crystal Lake, IL 60014 (US).		Published With international search report.
(74) Agent: BRUESS, Steven, C.; Merchant, Gould, Smith, Edell, Welter & Schmidt, P.A., 3100 Norwest Center, 90 South Seventh Street, Minneapolis, MN 55402 (US).		

(54) Title: BREAKTHROUGH SHOWER DOOR

(57) Abstract

A lightweight, low cost shower door assembly for enclosing a tub or shower enclosure having sides and a base. It includes an upper member (3) adapted to be positioned against opposing sides of the enclosure and a lower support member (11) adapted to be positioned against the base of the enclosure. A door in the assembly includes a flexible rod (18) connecting first and second frame members (7A, 7B). The first frame member (7A) is connected to the upper and lower support member (3, 11) and positioned for movement about a vertical axis. The flexible rod (18) is bowed to apply an upward force on the second frame member (7B) in order to maintain it in releasable connection with the upper support member (3). In use, a section of replaceable fabric (9) or vinyl extends across the frame members (7A, 7B) in order to provide a water barrier for the door.

