

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 March 2007 (29.03.2007)

PCT

(10) International Publication Number
WO 2007/033406 A1

(51) International Patent Classification:

F2IV 23/04 (2006.01) *F2IV 21/12* (2006.01)
F2IL 4/04 (2006.01) *F2IV 21/14* (2006.01)
F2IL 4/08 (2006.01) *F21W 131/40* (2006.01)
F2IS 9/02 (2006.01)

(21) International Application Number:

PCT/AU2006/001345

(22) International Filing Date:

13 September 2006 (13.09.2006)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2005905295 26 September 2005 (26.09.2005) AU

(71) Applicant (for all designated States except US): **NEOZ PTY LTD** [AU/AU]; 5-7 Manning Street, Rozelle, New South Wales 2039 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ELLIS, Peter, John**

[AU/AU]; 5-7 Manning Street, Rozelle, New South Wales 2039 (AU). **CHAN, Chi, Kin** [AU/AU]; 5-7 Manning Street, Rozelle, New South Wales 2039 (AU).


(74) Agent: **F B RICE & CO**; Level 23, 44 Market Street, Sydney, NSW 2000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: LAMP SYSTEM PARTICULARLY FOR CORDLESS LAMPS



(57) Abstract: A rechargeable lamp system (10) comprises a lamp unit (12) and a docking station (14) on which the lamp unit (12) may be placed for charging of a rechargeable battery (22) within the lamp unit. The base (18) of the lamp unit and the docking station are configured so that the lamp unit may be rotated on the docking station. Rotation of the lamp on the docking station is arranged to operate a reed switch (104) in the base (18) of the lamp unit for turning a light bulb (56) ON or OFF. The reed switch (104) is switched ON and OFF by one or more magnets (100) provided in the docking station (14). The docking station (14) defines an upstanding ring (130) in the centre of which are located positive (132) and negative (134) contacts. The base (18) of the lamp unit defines an aperture (136) which locates over the circular ring (130) so that the lamp unit may rotate on the docking station. A telescopic stem extends upwards from the base (18). The light bulb (56) is fitted at the top of the stem (50). A battery pack (22) defines a central aperture and in use, fits over and around the stem so that the battery pack is located above the base surrounding the stem and below the light emitting device.



FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*