

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)


PCT

(10) International Publication Number
WO 2005/003470 A1

- (51) International Patent Classification⁷: **E03B 1/04**, F16K 11/065
- (21) International Application Number: PCT/AU2004/000888
- (22) International Filing Date: 6 July 2004 (06.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2003903518 8 July 2003 (08.07.2003) AU
- (71) Applicants and
(72) Inventors: **TRUONG, David** [AU/AU]; 230 - 232 Parramatta Road, Stanmore, NSW 2048 (AU). **TRUONG, Ke, Hung** [AU/AU]; 230 - 232 Parramatta Road, Stanmore, NSW 2048 (AU).
- (74) Agent: **WALSH & ASSOCIATES**; Locked Bag 2011, Glebe Post Office, Glebe, NSW 2037 (AU).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: FILTRATION ASSEMBLY FOR MIXING FAUCET



(57) Abstract: An assembly (1) enabling filtration of mixed hot and cold water; the assembly including A faucet (2) capable of receiving hot and cold water and discharging mixed hot and cold water through an outlet (7a) in the faucet, control means (6) for operating the faucet; a filter assembly (11) adapted for insertion in a water supply line in which water to be filtered flows; at least a first conduit (4,5) having a supply of water and in communication with a mixing chamber (9) disposed in the faucet; a first outlet line (10) from said mixing chamber (9) communicating with the filter assembly; an outlet line from said filter assembly (11) communicating with said mixing faucet (2); wherein mixed water exiting from the mixing chamber (9) is filtered by the filter assembly (11) upstream of said faucet and prior to discharge of mixed water from the outlet of the faucet.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*