

This Sheet Has Been Replaced

TITLEMULTIPLE ELECTROMAGNETIC TILES
FOR BOUNDARY LAYER CONTROLBACKGROUND OF THE INVENTIONField of the Invention

The present invention relates to multiple electromagnetic tiles for magnetically controlling the flow of a fluid along a wall and, more particularly, to magnetic control of the boundary layer on aerodynamic bodies (such as wings, rotors and flaps) and hydrodynamic bodies (such as submarine sails, bow-planes, stern appendages and propellers).

Description of the Prior Art

A viscous fluid, and a body completely immersed in the fluid, form a boundary layer at the body's surface when the fluid and the body move relative to each other. That is, the layer of fluid in contact with the body is essentially at rest, while in an area removed from the body, the fluid is moving at its free-stream velocity. The region between the body and that area is known as a boundary layer.



The boundary layer is laminar at low Reynolds' numbers. ($Re = UL/\nu$, where U is a characteristic velocity, such as the free-stream velocity, L is a characteristic dimension of the body, such as the length of a wing chord or boat hull, and ν is the kinematic viscosity of the fluid.) When the Reynolds' number increases, the boundary layer becomes unstable and turbulent. In some cases, it can "separate" from the body.

Figs. 1(a) and 1(b) illustrate flow over an airfoil. It will be appreciated that the same principles apply whether the fluid is a liquid or a gas and regardless of the shape of the body.

When the airfoil 10 is operating at a small angle of attack α , as shown in Fig. 1(a), the fluid stream 12, with a free-stream velocity U_∞ , flows smoothly over the upper surface 14 of the airfoil. The downward deflection of the fluid stream by the airfoil causes an equal and opposite upward lift force to act on the airfoil.

As the angle of attack α increases, as shown in Fig. 1(b), the boundary layer may become turbulent, as indicated by the irregular flow 17. (For purposes of illustration, the boundary layer is depicted in Fig. 1 as much thicker than it is in actuality.) At very high angles of attack the boundary layer may separate from the airfoil, which then stalls. In addition to the loss of lift caused by boundary layer separation, eddies and turbulence 18 develop in the boundary layer.

Instability leading to boundary layer turbulence at a body's surface has several implications.

First, boundary layer turbulence increases viscous drag, which may create the need for additional



propulsive force to be applied to the airfoil or other body, which in turn requires more fuel to be expended to maintain the speed of the airplane, submarine, propeller blade, etc., to which the airfoil is attached. Moreover, if the flow separates completely, additional pressure drag is created.

In addition, a turbulent boundary layer exhibits large velocity and pressure fluctuations, which induce noise. Noise can be a significant problem in many environments, one example being submarine control surfaces and propeller screw blades. Pressure fluctuations associated with boundary layer separation can cause vibration, which in turn causes fatigue, which can be a serious problem particularly in metal aircraft parts.

Various approaches have been taken to stabilize boundary layer flow and delay boundary layer separation. One of these approaches includes optimizing the geometry of the airfoil to achieve a maximum possible angle of attack. However, an optimum airfoil shape still only allows the airfoil to operate at limited angles of attack.

Approaches for controlling the boundary layer along a surface of an object have also included providing suction or injection of air through fine slits in the airfoil surface to supply or withdraw energy from the boundary layer. However, in addition to the burden of providing fine slits over the surface of the object, such approaches require extensive tubing networks to supply the force necessary for suction or injection. Accordingly, this approach adds considerably to the overall weight and complexity of the object, which is generally inconsistent with the design objectives of most applications.



The prior art has not yet achieved the capability to provide all of these types of boundary layer control in a very efficient, practical and easily implemented fashion.

SUMMARY OF THE INVENTION

It is an object of the present invention to control the flow over a body for at least the following purposes:

1. Control of shear stress in the fluid in the boundary layer to reduce shear stress in the fluid at the wall and reduce viscous drag on the body.
2. Control of boundary layer separation to decrease or increase the resulting form (pressure) drag on the body, which also can be used to create forces and moments on the body and thereby provide directional control.
3. Control of the characteristics of the acoustic field in the fluid surrounding the body.
4. Control of heat transfer between the body and the fluid.
5. Control of turbulent fluid mixing in the boundary layer.
6. Control of the characteristics of the pressure field in the fluid surrounding the body and the resulting coupled forces.

In accordance with an aspect of the present invention, an apparatus for controlling a boundary layer in a flow of a fluid having a predetermined electrical conductivity and moving relative to a surface comprises conductivity altering means for providing an electrical conductivity gradient in a near-wall region of the flow proximate to the surface, a plurality of selectively actuatable control region tiles distributed over the surface, each tile being bounded by magnetic field generating means for generating in the near-wall region



of the flow a magnetic field $\bar{B}(x,y,z,t)$ having flux lines with a predetermined orientation with respect to the direction of relative movement of the fluid and the surface and electric current generating means for generating in the fluid in the near-wall region of the flow an electric current density $\bar{J}(x,y,z,t)$ traversing the magnetic flux lines, wherein actuation of a particular tile generates a magnetic field $\bar{B}$ and electric current density $\bar{J}$ that create in the near-wall region of the flow a force $\bar{L}(x,y,z,t) = \bar{J} \times \bar{B}$ having a component normal to the surface, and control means for selectively actuating the tiles to create the force $\bar{L}$ in the flow along selected tiles.

BRIEF DESCRIPTION OF THE DRAWINGS

The various aspects of the present invention can be best understood by reference to the detailed description of preferred embodiments set forth below taken with the drawings, in which:

Figs. 1(a) and 1(b) depict fluid flow around an airfoil.

Figs. 2(a) to 2(c) depict boundary layer flow conditions that illustrate principles utilized in the present invention.

Fig. 3(a) is a planform view of a magnetic boundary layer control device with a single control region that illustrates the principles of the present invention and Fig. 3(b) is a cross-section along line B-B of Fig. 3(a).

Fig. 4 depicts a section of the fluid flow shown in Figs. 3(a) and 3(b).

- 6 -

Fig. 5 is a qualitative plot relating to the conductivity of the fluid flow shown in Figs. 3(a) and 3(b).

Fig. 6 shows a one-dimensional array of control region tiles that illustrates one embodiment of the present invention.

Fig. 7 shows a two-dimensional array of control region tiles.

Fig. 8 shows a test setup used to demonstrate the efficacy of an embodiment of the invention using a one-dimensional array of control region tiles like that shown in Fig. 6.

Figs. 9(a) to 9(c) show the test set-up shown in Fig. 8 and flow therein as visualized using a fluorescent dye.


DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Figs. 2 to 5 illustrate principles underlying the present invention.

Figs. 2(a) to 2(c) illustrate generally accepted principles regarding flow conditions in a boundary layer.

Fig. 2 plots the velocity in a fluid at a wall ($y = 0$) of a flat plate and in the region of the boundary layer. At $y = 0$, the velocity u is generally considered to be zero. The velocity increases as y increases, and approaches the free-stream velocity U_{∞} . The velocity u in the mean-flow direction can thus be expressed as $u(y)$.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

- 7 -

The average wall shear stress τ_w in the mean-flow direction is expressed by the following relation:

This Sheet Has Been Replaced.



$$\tau_w = \mu \left. \frac{du}{dy} \right|_{\text{wall}} \quad (1)$$

where μ is the viscosity of the fluid.

In turn, the wall shear stress is related to viscous drag as follows:

$$D_{\text{viscous}} = \int_{\text{wall}} \tau_w dA \quad (2)$$

where dA is an elemental area of the wall.

Equations (1) and (2) show that τ_w and D_{viscous} increase as du/dy at the wall increases.

Fig. 2(a) illustrates $u(y)$ for a laminar boundary layer, shown as a solid line, and $u(y)$ for a turbulent boundary layer, shown in a dotted line, for the same external conditions. It will be appreciated that du/dy at the wall is lower for a laminar boundary than for a turbulent boundary layer at the same location on the wall. Accordingly, viscous drag can be reduced if the flow in the boundary layer can be maintained laminar.

However, instability in the flow in the boundary layer can cause the flow to become turbulent. An illustration of this phenomena is shown in Figs. 2(b) and 2(c).

Fig. 2(b) illustrates the velocity profile in an unstable boundary layer. The velocity of the fluid immediately adjacent the wall begins to slow down and can even approach zero. This is often an unstable

THIS SHEET HAS BEEN REPLACED



condition, which leads to the replacement of the low velocity fluid near the wall by the higher energy (higher velocity) fluid in the free-stream. The boundary layer thus established is generally turbulent, as illustrated in Fig. 2(c). Accordingly, du/dy at the wall is higher than it would have been if the transition to turbulent flow had not occurred.

Turbulence in the boundary layer has implications beyond the resulting increase in viscous drag. For one thing, the turbulent flow in the boundary layer creates noise because velocity fluctuations inherent in turbulent flow produce pressure fluctuations that tend to propagate into the free-stream flow.

The present invention can stabilize the flow in the boundary layer and thus reduce viscous drag and noise. The present invention can also serve the purposes listed above, in ways described in more detail in the course of the following discussion.

Fig. 3(a) is a planform view of a device illustrating the present invention. A wall or flat plate 100, simulating a wing or a control surface, is provided with a magnet having a North pole 101 and a South pole 102 for generating a magnetic field $\vec{B}$ with flux lines 103. The flux lines 103 enter and exit the surface 104 of the wall, thus being oriented parallel to the wall surface 104 and normal to the free-stream fluid flow direction x . (The coordinate system used herein is shown in Figs. 3(a) and 3(b).)

The magnetic poles 101 and 102 shown in Fig. 3(a) are provided by a horseshoe magnet (not shown) beneath the plate 100 (that is, on the side opposite the surface 104), and the plate is a non-ferrous material that allows free passage of magnetic flux.



However, the magnetic poles can be provided by any suitable structure. For example, the poles of one or more magnets can be placed flush with the surface 104 so as to form a part of the surface itself, and can even protrude from the surface.

A voltage source 105 attached across electrodes 106 and 107 generates an electric current density $\bar{J}$, represented by arrows 109, between the two electrodes. Of course, if the plate 100 is electrically conductive, the electrodes 106 and 107 are insulated from the plate.

To control the boundary layer using the present invention it is highly desirable that the fluid in the boundary layer have a certain degree of electrical conductivity σ different from the conductivity of the rest of the fluid. In the device shown in Figs. 3(a) and 3(b), an electrolyte 130 is added to the boundary layer by bleeding an electrolyte from a reservoir 108 through a slit 108a into the medium to increase the conductivity of a thin layer of the liquid adjacent to the wall.

A direction of the current flow through the conductive fluid is in the direction from an anode electrode 106 to a cathode electrode 107 such that the current density can be expressed as a vector $\bar{J}$ parallel to the mean flow direction x of the fluid medium. As depicted in Fig. 3(b), a Lorentz force $\bar{L}$, represented by arrows 131, resulting from the interposition of the electric current and magnetic field, is expressed as $\bar{J} \times \bar{B}$, the vector- or cross-product of $\bar{J}$ and $\bar{B}$ acting in a control region in a direction normal to and toward the wall 100.




The Lorentz force $\bar{L} = \bar{J} \times \bar{B}$ stabilizes the boundary layer by counteracting regions of positive and negative vorticity ω , in accordance with the mechanism illustrated in Fig. 4.

Fig. 4 is a view looking downstream in the flow along the plate 100 in Figs. 3(a) and 3(b). (That is, a cross-section of the flow in the spanwise (z) direction.) As a result of the introduction of the electrolyte 130, the fluid has a higher conductivity σ_1 in the near-wall region than the conductivity σ_2 in regions outside the near-wall region. As those skilled in this art know, the "near-wall" region is that part of the flow in the boundary layer responsible for most of the turbulence production. In the near-wall region, viscous forces predominate over momentum forces.

The double line 140 denotes where the gradient of the conductivity σ in the y-direction is at a maximum in the near-wall region. Optimally, the conditions under which the electrolyte 130 is introduced into the fluid flow are controlled so that the conductivity gradient is at a maximum at a predetermined distance from the wall, in accordance with principles discussed below. In Fig. 5, the right side qualitatively illustrates the conductivity variation in the y direction ($y=0$ at the surface of plate 100) and the left side plots the conductivity gradient for the conductivity illustrated on the right-hand side. The double line 140 is drawn in Fig. 4 at the distance from the wall where the conductivity gradient is at a maximum, as shown in Fig. 5.

This distance is typically between 10 and 30 wall units (y^+), that is, $10 < y^+ < 30$, although it can vary depending on the properties of a particular fluid flow. A "wall unit" is a dimensionless number, usually



expressed as y^+ , used by those skilled in the art to express distance when phenomena being measured relate to the flow conditions along a surface. In particular, the vertical distance from the wall of a flat plate may be expressed as:

$$y^+ = y \frac{u_\tau}{\nu} \quad (3)$$

where ν is the kinematic viscosity of the fluid and

$$u_\tau = \sqrt{\tau_w / \rho}, \quad \tau_w \text{ being wall shear stress (see Equation 1)}$$

and ρ being the density of the fluid.

Referring back to Fig. 4, turbulence in a boundary layer is generally associated with regions of positive and negative vorticity $+\omega$ and $-\omega$. As illustrated in Fig. 4 by the raised portion 141 of the double line, this vorticity is believed to be one of the mechanisms at work in the lift-up of near-wall low-momentum fluid and its replacement by higher momentum fluid from regions further from the wall, that is, the phenomenon explained previously in connection with Figs. 2(a) to 2(c).

While the exact mechanism by which the present invention prevents this lift-up of a near-wall fluid is not completely understood, due to the as yet incomplete understanding of the feedback mechanisms that stimulate the creation of near-wall streamwise vorticity ($+\omega$ and $-\omega$), Fig. 4 illustrates one of the mechanisms believed to be at work. Since the boundary between the low- and high-conductivity fluid is displaced, as seen by the raised portion 141 of the double line in Fig. 4, the Lorentz force L_y superimposed on the flow exhibits a



gradient in the areas where that boundary is dislocated.

At the dislocation 141a on the left-hand side, L_y is decreasing in the z -direction, to create streamwise vorticity ω_z in the positive direction that counteracts the vorticity $-\omega$ that caused the dislocation 141a in the boundary layer. At the right-hand dislocation 141b, L_y is increasing in the z -direction, thus creating streamwise vorticity ω_z in a negative direction that counteracts the $+\omega$ at that location. The bolder vector for L_y in Fig. 4 indicates a stronger force. Thus, since L_y (which is negative because it is directed in the minus y -direction) becomes larger in the z -direction for the left-hand dislocation 141a, and smaller in the z -direction for the right-hand dislocation 141b, it creates vorticities in the opposite directions from $-\omega$ and $+\omega$, respectively.

The gradient of L_y in the z -direction creates the counteracting vorticities because the near-wall region conductivity σ_1 is higher than the more remote conductivity σ_2 , and the higher conductivity fluid carries more current. Accordingly, L_y where there is more such fluid, such as where the boundary layer has been lifted up, is larger than in the adjacent areas.

Fig. 4 illustrates how the present invention is believed to counteract flow disturbances in the spanwise (z) direction. It is believed that the invention counteracts disturbances in the streamwise (x) direction in the same manner. That is, a schematic cross-section of the flow taken in the streamwise (x) direction instead of the spanwise (z) direction would look much the same as Fig. 4.



It is preferable that the conductivity gradient be a maximum at the edge of the near-wall region. However, that is not necessary. It is believed to be sufficient simply to have a conductivity gradient in the y -direction in the near-wall region in order to generate the L_y gradients that create vorticity. That is, if δ is the height of the near-wall region, then there should be a conductivity gradient in the y -direction between $y = 0$ and $y = \delta$, with the maximum gradient preferably being at $y = \delta$.

It will be appreciated that by reversing the polarity of either the magnetic field or the electric current density, the force $\bar{J} \times \bar{B}$ can be provided in a direction normal to but directed away from the wall 100, which will result in the flow medium being pushed in a direction away from the wall surface 104. This effect can be used to disturb and destabilize the boundary layer by creating the dislocating vortices $-\omega$ and $+\omega$.

In the embodiment illustrated in Fig. 3, the current density and the magnetic field are normal to each other. This of course provides a maximum force $\bar{J} \times \bar{B}$ for given magnetic flux density B and current density J . However, it will also be appreciated that the electric current density and the magnetic field need not be perpendicular to each other as shown in these figures. Any arrangement which provides a current and magnetic field traversing each other will result in a force $\bar{J} \times \bar{B}$.

Arrangements besides that depicted in Fig. 3 are also possible in accordance with the present invention. For example, the electrodes could be arranged so that the current flows across the mean fluid flow direction while the magnetic flux lines are along the flow direction. Or the amount of current density and

This Sheet Has Been Replaced



- 14 -

strength of the magnetic field can be varied with time to change that force.

In one of its most general aspects, the present invention provides for varying the magnetic field and current density over the entire control region and with time to provide boundary layer control effects precisely tailored to any particular flow condition. That is, the magnetic field can be expressed as a function $\bar{B}(x,y,z,t)$ and the current density can be expressed as a function $\bar{J}(x,y,z,t)$, so that the resulting force $\bar{L} = \bar{J} \times \bar{B}$ is a function $\bar{L}(x,y,z,t)$. Accordingly, to provide the desired control of the flow around an object it is possible to provide $\bar{B}(x,y,z,t)$ and $\bar{J}(x,y,z,t)$ that will provide the desired flow effects.

Although it may be possible under some circumstances to provide functions $\bar{B}(x,y,z,t)$ and $\bar{J}(x,y,z,t)$ that will produce the proper L_y variations (see Fig. 4), a considerably more expedient manner of producing those variations is by providing a layer of different, preferably higher, conductivity fluid in the near-wall region. Accordingly, another of the general aspects of the present invention involves the provision of such a layer. In such a case, $\bar{B}$ and $\bar{J}$ need not be varied to produce the L_y variations necessary for boundary layer control, although for given desired flow effects $\bar{B}$ and $\bar{J}$ may still be varied spatially and temporally.

The present invention has numerous significant implications. It can reduce viscous drag by stabilizing the boundary layer and preventing transition to turbulent flow. In addition, it can inhibit velocity fluctuations in the near-wall region over a wide area of a flow surface and thereby damp and dissipate velocity fluctuations in the free-stream

THIS SHEET HAS BEEN REPLACED

This Sheet Has Been Replaced



- 15 -

flow. This can significantly affect the acoustic field in the fluid surrounding the body. And by stabilizing the boundary layer and preventing transition to turbulent flow, the present invention can reduce heat transfer between the fluid and the body, which is of great potential significance in reducing the temperatures to which space vehicles are subjected upon re-entry into the Earth's atmosphere.

On the other hand, providing $\bar{J} \times \bar{B}$ directed away from the body can destabilize the flow in the boundary layer and induce transition to turbulent flow. In that manner, heat transfer between the fluid and the body can be enhanced, which is important in applications such as heat exchanger design. Moreover, turbulent boundary layer flow enhances fluid mixing, which can have important ramifications in combustion and chemical processing applications (where two fluids may flow along opposite surfaces of a body to be mixed at the body's trailing edge). And a turbulent boundary layer is ordinarily less prone to separation than a laminar boundary layer, so that inducing turbulent boundary layer flow can delay separation.

Controlling boundary layer separation is, of course, important because of both the form (pressure) drag and the unstable pressure fluctuations associated with such a flow condition. Separation greatly increases the drag on the body due to the altered distribution of pressure when the flow separates. Accordingly, preventing separation reduces such drag. Separation can also create a fluctuating pressure field in the fluid that subjects the body to coupled forces which can cause fatigue. Delaying separation (by inducing turbulent boundary layer flow) or inhibiting separation (by providing a strong $\bar{J} \times \bar{B}$ force toward the body),

THIS SHEET HAS BEEN REPLACED

- 16 -

can reduce these pressure fluctuations and the resulting fatigue.

By the same token, preventing or inducing separation under controlled conditions can be used to create forces and moments on the body and provide directional control.

The present invention uses those principles to provide efficient boundary layer control over a wide area.

Results of experiments using a single control region indicate that it becomes less capable of providing the desired boundary layer control as the distance between the electrodes, D_e , and the distance between the magnetic poles, D_B , become larger. The reason lies in the fact that the present invention seeks to control the fluid in the near-wall region of the flow. Accordingly, a certain magnitude magnetic field and electric current density is desired in that region. As D_B and D_e increase, the magnitudes of the magnetic field and current density at the near-wall region actually decrease for a given strength magnet and electric current. Thus, one way to increase the size of the control region while maintaining the same degree of flow control is simply to increase the strength of the magnet or current or both. That approach results in an inefficient use of the magnetic field and current density being generated, since only a small percentage of each is in the near-wall region contributing to flow control.

However, the present invention enables flow control over a large area while efficiently using the magnetic field and electric current density.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

- 17 -

The optimum distances D_e and D_B for maintaining a certain percentage of the magnetic flow and current in the near-wall region can be calculated using Maxwell's equations. If that percentage is chosen as, say, 50%, then Maxwell's equations can be used to show that

This Sheet Has Been Replaced



$$\frac{D_e}{\delta} \sim \frac{D_B}{\delta} \sim 10. \quad (4)$$

Since δ is a small distance, the value of D_e and D_B required to maintain 50% of the magnetic field and electric current within the near-wall region are also very small.

That consideration illustrates the principle underlying the present invention, namely the provision of a plurality of separately actuatable control region tiles. With such an arrangement, flow control over a large area can be provided with less magnetic flux and electric current than would be required to provide flow control for that area using a single control region.

Fig. 6 schematically illustrates the present invention as applied to a one-dimensional array of individual control region tiles.

A wall or flat plate 200, simulating a wing or control surface as in Figs. 3(a) and 3(b), is provided with a series of magnets having North poles 201a, 201b, ..., 201g, and South poles 202a, 202b, ... 202g. These magnets generate a magnetic field $\vec{B}$ with flux lines 203. A plurality of electrodes 206a, 206b, 206c and 206d are spaced from each other to provide three control tiles 260a, 260b, and 260c, disposed in Fig. 6 in a one-dimensional array in the direction of fluid flow. To provide a layer of higher conductivity fluid in the near-wall region, a slot 208a bleeds an

THIS SHEET HAS BEEN
REPLACED



electrolyte 230 into the fluid, in a fashion similar to that illustrated in Figs 3(a) and 3(b).

Each electrode 206 is connected to wiring 207 that leads to a control circuit 250. The control circuit is made from known components and is capable of selectively applying a potential across each electrode pair through wiring 207. That is, the control circuit 250 can apply a potential across any pair of electrodes 206a-206b, 206b-206c or 206c-206d in any polarity.

Fig. 6 shows the case where electrodes 206a and 206b are at the same potential, electrodes 206b and 206c are at potentials that make 206b an anode electrode relative to electrode 206c, and electrodes 206c and 206d are at the same potential. In that case, there is an electric current $\bar{J}$ between the electrodes 206b and 206c. This electric current is represented by the vector $\bar{J}$ and arrows 209. Accordingly, a force $\bar{L} = \bar{J} \times \bar{B}$ is generated in the actuated tile 260b.

When any one of the tiles 260a, 260b or 260c is actuated, the flow along that tile is quickly stabilized. However, when the tile is deactuated, it may take a relatively long time for the flow to destabilize. Accordingly, it is possible to actuate the tiles sequentially so that each is actuated for a relatively short length of time, while still maintaining stable flow over all of the tiles.

The present invention also contemplates a three-dimensional array 300 of n tiles as shown in Fig. 7. Each tile has associated with it a pair of electrodes and a pair of magnetic poles provided by electromagnets. For example, the first row of tiles 360_{11} to 360_{1n} has associated with it electromagnets 301_1 and 302_1 ; the second row of tiles 360_{21} to 360_{2n} has



associated with it electromagnets 301₁ and 302₁; etc. By the same token, the first column of tiles 360₁₁ to 360_{n1} has associated with it electrodes 306₁₁ and 306₁₂; the second column of tiles 360₁₂ to 360_{n2} has associated with it electrodes 306₁₂ and 306₂₂; etc.

By suitably addressing the electromagnets and electrodes associated with the tiles, it is possible to provide a high degree of flow control over a large area. Of course, the electrodes and electromagnets must be addressed in a fashion that ensures that no two tiles in close proximity are simultaneously actuated. Otherwise, the magnetic fields and electric currents would not be provided in the proper direction for flow control. For example, the adjacent electrodes in two adjoining tiles could not be made simultaneously to have different polarities, since current would then flow between such electrodes rather than along the tile surface.

A microcomputer COM can be programmed to provide an appropriate addressing sequence depending on flow conditions such as free stream velocity, fluid density, angle of attack (if the array 300 is on a lifting body such as an aircraft wing or submarine control surface), etc.

The present invention enables flow control over a large area, and may reduce the strength of the magnetic field and the electric current required for the same area if only one control region were provided for such area. Under certain flow conditions, the flow over a tile may destabilize very quickly after that tile is deactuated. However, even in those circumstances, the flow stabilization achieved by simultaneously actuating plural, spaced-apart tiles can substantially reduce the

- 20 -

shear stress in the fluid at the wall over the entire area covered by the array of tiles.

Example

A test rig was set up to perform a feasibility study using the device shown in Fig. 3. The rig was tested in a flow channel in the test setup depicted in Fig. 8. The rig, shown in Fig. 8, consisted of a plate 609 about four meters long, having the components shown in Fig. 3 mounted thereon. The boundary layer control device 608 consisted of seven permanent magnets 601a to 601f. The poles of each magnet were about 18 cm. apart, that is, the control region was 18 cm. wide in the spanwise direction. Stainless steel (Type 304) electrodes 606a, 606b, 606c and 606d were provided approximately 8 cm. apart. They were approximately 1 cm. wide and 8 cm. long.

Anode and cathode voltage were established for each test run. The electrode 606a was maintained at the anode voltage and the 606d was maintained at the cathode voltage. The electrodes 606b and 606c were alternately switched between the anode and cathode voltages by a control unit (not shown in Fig. 8). The three control region tiles were sequentially actuated for 100 msec. each (with a duty cycle of 1/3). B_z for each tile was about 160 gauss and J_z for each tile was about 10 ma/cm².

Various electrolytic substances were injected into the flow medium from a slot 604. The electrolytic substance consisted of a dilute solution of NaOH containing a fluorescing disodium fluorescein dye to obtain flow visualization in a manner discussed below.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



The test tank shown in Fig. 8 consisted of a tank approximately 1.5 meters wide, 0.5 meters high and six meters long. The test fluid 605 was set to flow at 15 cm/sec. A laser was arranged to provide a thin sheet of laser energy 610 along the boundary layer at $y^+ = 20$ for activating the fluorescing dye in a thin layer along the surface of the plate to obtain visualization of the boundary layer. A video recorder 607 was provided for recording the results of the experiment.

In experiments performed on the test rig, a turbulent spot was produced upstream of the magnetic boundary layer control device 608 using a mechanical tripping device. It was observed that when the spot entered the control region of the device, turbulence in the boundary layer of plate 609 disappeared under the above conditions. The flow visualization techniques also confirmed qualitatively that reversing the flow of current increased the turbulence in the control region.

Fig. 9 includes three actual prints of the test rig shown in Fig. 8. Fig. 9(a) shows the plate 609 with the boundary layer control device 608 in place. The electrodes 606a are clearly visible. Fig. 9(b) is a print the visualized flow over the plate when a turbulent spot is produced upstream and the tiles are not actuated. The brighter regions evidence unstable flow at the location of the laser sheet at $y^+ = 20$. Fig 9(c) is a print of the visualized flow over the plate under the same conditions as in Fig. 9(b), except that the tiles have been actuated as described above. The bright spots have essentially disappeared, indicating that the flow in the boundary layer has stabilized.

It will be appreciated that magnetic boundary layer control devices such as discussed above could be

- 22 -


provided on any surface upon which it is desired to control the boundary layer, either to prevent or cause separation, or to remove or induce instability.

The present invention provides a device that is simple to manufacture as discrete elements and which could be easily retrofit to craft presently in operation. Accordingly, the magnetic boundary layer control devices could be easily manufactured in large volume and delivered to a site of operation of the craft upon which it is to be installed. The devices could be easily fitted on the inside skin of the craft, for example on a submarine sail, with a minimum amount of time and effort.

Preliminary studies indicate that the power requirements for operational boundary layer control devices would be extremely low. In addition, with the breakthroughs presently taking place with superconductivity, it may be possible to significantly reduce the power requirements of devices incorporating the present invention by the use of superconducting electromagnets.

Of course, it will be appreciated that the invention may take forms other than those specifically described, and the scope of the invention is to be determined solely by the following claims.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

WHAT IS CLAIMED IS:

1. An apparatus for controlling a boundary layer in a flow of a fluid having a predetermined electrical conductivity and moving relative to a surface, said apparatus comprising:

conductivity altering means for providing an electrical conductivity gradient in a near-wall region of the flow proximate to the surface;

a plurality of selectively actuatable control region tiles distributed over the surface, each said tile being bounded by magnetic field generating means for generating in the near-wall region of the fluid a magnetic field $\vec{B}(x,y,z,t)$ having flux lines with a predetermined orientation with respect to the direction of relative movement of the fluid and the surface and electric current generating means for generating in the fluid in the near-wall region an electric current density $\vec{J}(x,y,z,t)$ traversing the magnetic flux lines, wherein actuation of a particular tile generates a magnetic field $\vec{B}$ and electric current density $\vec{J}$ that create force $\vec{L}(x,y,z,t) = \vec{J} \times \vec{B}$ in the near-wall region of the flow and having a component normal to the surface; and

control means for selectively actuating said tiles to create the force $\vec{L}$ in the flow along selected said tiles.

2. An apparatus according to claim 1, wherein the electric current density $\vec{J}$ is spatially constant for an actuated tile.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



3. An apparatus according to claim 2, wherein the magnetic field $\bar{B}$ is spatially constant for an actuated file.
4. An apparatus according to claim 1, wherein the component of the force $\bar{J} \times \bar{B}$ normal to the surface is in a direction toward the surface for stabilizing the boundary layer.
5. An apparatus according to claim 4, wherein the force $\bar{J} \times \bar{B}$ reduces the shear stress in the fluid at the surface.
6. An apparatus according to claim 4, wherein the force $\bar{J} \times \bar{B}$ maintains attached flow over the surface.
7. An apparatus according to claim 1, wherein the component of the force $\bar{J} \times \bar{B}$ normal to the surface of the wall is in a direction away from the surface for destabilizing the boundary layer.
8. An apparatus according to claim 7, wherein the force $\bar{J} \times \bar{B}$ induces turbulent fluid flow in the boundary layer.
9. An apparatus according to claim 7, wherein the force $\bar{J} \times \bar{B}$ induces the boundary layer to separate from the surface.
10. An apparatus according to claim 1, wherein said magnetic field generating means and electric current generating means generate a magnetic field having flux lines perpendicular to the electric current.
11. An apparatus according to claim 1, wherein the surface comprises a lifting surface.





12. An apparatus according to claim 11, wherein said lifting surface is a control surface.
13. An apparatus according to claim 1, wherein the fluid is liquid and said conductivity altering means comprises means for bleeding an electrolyte into the near-wall region of the flow.
14. An apparatus according to claim 1, wherein the fluid is a gas and said conductivity altering means includes means for increasing the concentration of ions in the gas in the near-wall region of the flow.
15. An apparatus according to claim 1, wherein said electric current generating means comprises at least one pair of electrodes disposed with the flux lines of the magnetic field between said electrodes.
16. An apparatus according to claim 1, wherein said magnetic field generating means comprises at least one permanent magnet.
17. An apparatus according to claim 1, wherein said magnetic field generating means comprises at least one electromagnet.
18. An apparatus according to claim 1, further comprising modulating means for varying the density or orientation of at least one of the magnetic field $\vec{B}$ or electric current density $\vec{J}$.
19. An apparatus according to claim 1, further comprising plural said magnetic field generating means and plural said electric current generating means bounding said tiles in a two-dimensional array thereof.

This Sheet Has Been Replaced

THIS SHEET HAS BEEN
REPLACED



AMENDED CLAIMS

[received by the International Bureau on 22 October 1993 (22.10.93); original claims 1,3 and 18 amended; other claims unchanged (3 pages)]

1. An apparatus for controlling a boundary layer in a flow of a fluid having a predetermined electrical conductivity and moving relative to a surface, said apparatus comprising:

conductivity altering means for providing an electrical conductivity gradient in a near-wall region of the flow proximate to the surface;

a plurality of selectively actuatable control region tiles distributed over the surface, each said tile being bounded by magnetic field generating means for generating in the near-wall region of the fluid a magnetic field $\bar{B}(x,y,z,t)$ having flux lines with a predetermined orientation with respect to the direction of relative movement of the fluid and the surface and electric current generating means for generating in the fluid in the near-wall region an electric current density $\bar{J}(x,y,z,t)$ traversing the magnetic flux lines, wherein said magnetic field generating means and said electric current generating means are disposed relative to each other such that actuation of a particular tile generates a magnetic field $\bar{B}$ and electric current density $\bar{J}$ that create force $\bar{L}(x,y,z,t) = \bar{J} \times \bar{B}$ in the near-wall region of the flow and having a component normal to the surface; and

control means for selectively actuating said tiles to create the force $\bar{L}$ in the flow along selected said tiles for controlling the flow.

2. An apparatus according to claim 1, wherein the electric current density $\bar{J}$ is spatially constant for an actuated tile.

3. An apparatus according to claim 2, wherein the magnetic field $\bar{B}$ is spatially constant for an actuated tile.





27

4. An apparatus according to claim 1, wherein the component of the force $\bar{J} \times \bar{B}$ normal to the surface is in a direction toward the surface for stabilizing the boundary layer.

5. An apparatus according to claim 4, wherein the force $\bar{J} \times \bar{B}$ reduces the shear stress in the fluid at the surface.

6. An apparatus according to claim 4, wherein the force $\bar{J} \times \bar{B}$ maintains attached flow over the surface.

7. An apparatus according to claim 1, wherein the component of the force $\bar{J} \times \bar{B}$ normal to the surface of the wall is in a direction away from the surface for destabilizing the boundary layer.

8. An apparatus according to claim 7, wherein the force $\bar{J} \times \bar{B}$ induces turbulent fluid flow in the boundary layer.

9. An apparatus according to claim 7, wherein the force $\bar{J} \times \bar{B}$ induces the boundary layer to separate from the surface.

10. An apparatus according to claim 1, wherein said magnetic field generating means and electric current generating means generate a magnetic field having flux lines perpendicular to the electric current.

11. An apparatus according to claim 1, wherein the surface comprises a lifting surface.

12. An apparatus according to claim 11, wherein said lifting surface is a control surface.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



13. An apparatus according to claim 1, wherein the fluid is liquid and said conductivity altering means comprises means for bleeding an electrolyte into the near-wall region of the flow.

14. An apparatus according to claim 1, wherein the fluid is a gas and said conductivity altering means includes means for increasing the concentration of ions in the gas in the near-wall region of the flow.

15. An apparatus according to claim 1, wherein said electric current generating means comprises at least one pair of electrodes disposed with the flux lines of the magnetic field between said electrodes.

16. An apparatus according to claim 1, wherein said magnetic field generating means comprises at least one permanent magnet.

17. An apparatus according to claim 1, wherein said magnetic field generating means comprises at least one electromagnet.

18. An apparatus according to claim 1, further comprising modulating means for varying at least one of the density and orientation of at least one of the magnetic field $\vec{B}$ and electric current density $\vec{J}$.

19. An apparatus according to claim 1, further comprising plural said magnetic field generating means and plural said electric current generating means bounding said tiles in a two-dimensional array thereof.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED