

9700163-0

Ipos copy

Reference: D 1478

Applicant:

SCHNEIDER ELECTRIC SA

Title of the invention:

Electronic relay

Inventors:

Jean-Marc ROMILLON

Pierre BOUDET

Joël JACQ

This invention relates to a multifunction protective electronic relay including current sensors mounted in series on alternating current supply lines to a load such as a multiphase electric motor.

5 Protective electronic relays with a microprocessor, of the type described in patent EP 0214025 exist. This type of relay can ensure detection and protection functions in the following cases: thermal overload, temperature overshoot, phases absent or out of balance,
10 phase reversals, insulation to earth defects, excessive torque cut-off, running with no load. The sensors situated on each of the power supply phases supply the relay with signals that represent the phase currents. From these signals, the relay can calculate the
15 temperature rise of the windings and of the motor, can detect phase anomalies, etc. It is fitted with separate output relays which allow the alarm or defect information to be utilised. Display of the thermal condition of the motor and of defects is carried out by means of indicator
20 lamps located on the front face or on a remote display module.

These relays are mounted in an ordinary case requiring internal wiring.

25 The aim of this invention is to provide an electronic relay layout that avoids internal wiring and facilitates construction.

In accordance with the invention, the relay is characterised by the fact that it includes at the rear of the case, a power card linked to current sensors and
30 connected by connectors to electronic daughter cards which have lateral terminals with outputs in the lateral

openings in the case and, at the front of the case, a dialogue and communication card that is connected to at least one of the daughter cards.

According to one characteristic, the daughter cards
5 are mounted in the case perpendicular to the power card, the display and communication card being mounted perpendicular to the daughter cards and being connected to the card positioned in the centre.

The invention will now be described in more detail
10 making reference to one embodiment given as an example and shown in the appended drawings in which:

- Figure 1 is a block diagram of the electronic relay according to the invention;
- Figure 2 is a perspective view of the relay;
- 15 - Figure 3 is an exploded perspective view of the relay
- Figure 4 is a view of the back of the power card.

The electronic relay shown in the drawings includes terminals L1, L2, L3 connected to the alternating current
20 power supply lines and the terminals T1, T2, T3 connected to a load, for example, to a motor M. Terminals E and S can be connected to a PTC probe of the temperature sensor type allowing thermal control of the motor.

The case marked 1 in its entirety, is made up of a
25 rear mounting base 11 capable of being fixed to a support (a rail, for example), a box 12 which can be assembled on the mounting base 11 and a front cover 13. It contains a power card C1, an input card C2, a processing card C3, an output card C4 and a dialogue and communication card C5.

30 The power card C1 is housed at the back, on the mounting base 11 of the case and receives all the analog inputs, (currents from the three phases, PTC probe input, inputs from a homopolar magnetic core) and makes these

analog inputs compatible with the inputs of the microcontroller. The card is fitted with a terminal block B4 that allows connection of the analog inputs (homopolar input, PTC probe) and it makes the interconnection with the other cards of the relay by means of removable pin connectors B5, B6, B7, B8. It is fitted with current sensors or transformers I1, I2, I3 which are mounted on the mounting base I1 opposite openings that allow the passage of external wires. The power card C1 can include, at the side of terminals L1, L2, L3, extra terminals suited to different scales of current intensity. In order to keep the drawings simple, only terminals L1, L2 and L3 have been shown.

The input card C2 is housed in the upper part of the case and receives all the logic inputs and makes these logic inputs compatible with the logic inputs of the microcontroller. It is fitted, at the back, with a removable pin connector that connects it at B5 to the power card C1 and, at the front with a terminal block B1 that provides connection of these logic inputs to the external environment. It supports connection and insulation of display circuits. It includes a communication circuit that allows it remote communication, through the use of terminal block B1, with display means located remote from the apparatus.

The processing card C3 is housed in the central part of the case, between the two other cards C2 and C4 and is fitted with a microcontroller. It receives all the logic and analog inputs and manages the outputs. It is fitted, at the rear, with a removable pin connector that connects it at B6, B8 to the power card C1 and, at the front, with a removable pin connector B3 providing connection with the dialogue and communication card C5.

The power supply and output card C4 is housed in the lower part of the case and is fitted with an output relay and the auxiliary power supply. It is fitted, at the back with a removable pin connector that connects it at B7 to the power card C1 and at the front with a terminal block B2 providing connection of the outputs and the power supply to the outside. Via the output relays, it controls a signalling output indicating tripping in the event of a thermal overload, an alarm output indicating if the thermal condition has reached a previously set threshold value, and motor command outputs that allow control of contactors such as a KM1.

The dialogue and communication card C5 is housed at the front of the case and is fitted with components that provide the machine dialogue and the serial connection. It is connected to the processing card C3 by a removable pin connector B3. It carries a serial connector 51 intended for communication with a bus or a computer, a display component 52 that allows the display of the cause of a trip, a first regulating device 53 allowing regulation of the nominal motor current, a second regulating device allowing regulation of the nominal motor current (the sum of the adjustments of 53 and 54 allowing determination of the nominal motor current), a device 55 for regulating the class of trip of the motor, a button 56 that allows to trip the apparatus (test) and a button 57 for resetting it.

The cards C2, C3, C4 are daughter cards assembled inside the case (in which they have slide bars to guide them) so that they are set perpendicular to the power card C1. The dialogue and communication card C5 is mounted on the front face, parallel to the power card C1. The lateral terminal blocks B1 and B2 are set parallel to

the back face of the case with outputs to the outside in the lateral openings 14 of the case. The terminal block B4 also has an output to the outside via an opening in the case.

- 5 . It is of course understood that, without departing from the scope of the invention, variants and means of perfecting the detail of the invention can be devised and the use of equivalent means can similarly be contemplated.



CLAIMS

1. An electronic relay including current sensors (I1, I2, I3) mounted, between terminals (L1, T1, L2, T2, L3, T3), in series on alternating current supply lines to a load (M), characterised by the fact that it includes,
5 at the rear of its case (1) a power card (C1) linked to the current sensors (I1, I2, I3) and connected by connectors to daughter cards (C2, C3, C4) carrying lateral terminal blocks (B1 and B2) with outputs in the lateral openings of the case and, at the front of the
10 case, a communication and dialogue card (C5) connected to at least one of the daughter cards (C3).

2. An electronic relay according to any one of the preceding claims, characterised by the fact that the daughter cards (C2, C3, C4) are mounted in the case
15 perpendicular to the power card (C1), the dialogue and communication card (C5) being mounted perpendicular to the daughter cards (C2, C3, C4) and being connected to the card positioned in the centre (C3).

3. An electronic relay according to any one of the preceding claims, characterised by the fact that the case
20 (1) comprises a rear mounting base (11) capable of being fixed to a support, a box (12) which can be assembled on the mounting base (11) and a front cover (13).

4. An electronic relay according to any one of the preceding claims, characterised by the fact that the
25 first daughter card (C2) mounted laterally and fitted with a terminal block (B1) is a logic input card.



5. An electronic relay according to any one of the preceding claims, characterised by the fact that the second daughter card (C4) mounted laterally and fitted with a terminal block (B2) is an output card.

5 6. An electronic relay according to any one of the preceding claims, characterised by the fact that the daughter card (C3) mounted between the other two cards (C2, C4) is the processing card fitted with a microcontroller.

10 7. An electronic relay according to any one of the preceding claims, characterised by the fact that the dialogue and communication card (C5) positioned at the front is connected by a removable pin connector (B3) to the processing card (C3) and has a communication
15 connector (51) for a bus or a computer.