

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2019/238979 A8

(43) International Publication Date
19 December 2019 (19.12.2019)

WIPO | PCT

- (51) International Patent Classification:
A61M 5/32 (2006.01)
- (21) International Application Number:
PCT/EP2019/068273
- (22) International Filing Date:
08 July 2019 (08.07.2019)
- (25) Filing Language:
English
- (26) Publication Language:
English
- (30) Priority Data:
1809623.0 12 June 2018 (12.06.2018) GB
- (71) Applicant: **NEEDLESMART LTD** [GB/GB]; Suite 3, Stanley Grange, Ormskirk Road, Knowsley Merseyside L34 4AT (GB).
- (72) Inventor: **KIRBY, Clifford**; 3, Old Rectory Green, Sefton Village Merseyside L29 6YD (GB).
- (74) Agent: **HUTCHINSON IP LTD**; 57 Hoghton Street, Southport Merseyside PR9 0PG (GB).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME,

(54) Title: PHLEBOTOMY NEEDLE DESTRUCTION




FIGURE 21

(57) **Abstract:** An apparatus (200) for processing a phlebotomy needle (12) is disclosed. The phlebotomy needle (12) is a double-ended needle (12) with a hub (18) located between its tips (14, 16). The apparatus (200) has a clamping electrode (52) for contacting and clamping one end (14) of the needle (12) between the hub (18) and the tip (14) and a tip electrode (54) for contacting the needle (12) at its tip (14). A voltage (302) is applied between the clamping electrode (52) and the tip electrode (54), to soften/melt the needle via resistive heating, at the same time as the tip electrode (54) is advanced (304) to compress the needle tip (14) and blunt it. The apparatus (200) is characterised by means (208, 210, 216, 218, 224) that allows the needle (12) to be rotated through, say 180 degrees, so that the first tip (14) and the second tip (16) can be blunted. Also disclosed is means for detaching the phlebotomy needle (12) from a main body (20) and/or for removing a cover (22) covering one end (16) of the phlebotomy needle (12). The apparatus (200) enables a Vacutainer-type needle (10) to be disassembled into its various parts (12, 20, 22) and the needle (12) rendered blunt at both ends and non-hazardous.

MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

- *with international search report (Art. 21(3))*
— *with information concerning request for restoration of the right of priority in respect of one or more priority claims (Rules 26bis.3 and 48.2(b)(vii))*

(48) Date of publication of this corrected version:

30 April 2020 (30.04.2020)

(15) Information about Correction:

see Notice of 30 April 2020 (30.04.2020)