

Description

TECHNICAL FIELD

This invention relates to a liquid toner based imaging machine and to a developer electrode therefor.

RELATED APPLICATION

This application is a continuing application of application Serial No. 273,830 filed November 21, 1988. The subject matter in this application is related to the subject matter in copending application Serial No. 273,831 filed November 21, 1988.

BACKGROUND OF THE INVENTION

Liquid toner based copying machines are described in U.S. Patent Nos. 4,286,039, 4,411,976, 4,727,394, and 3,900,003, the disclosures of which are hereby incorporated by reference. In these copying machines, an electrostatic latent image is formed on a photoconductive carrier movable into proximity with a developer electrode held at a voltage intermediate the voltages on the carrier representative of background and information portions of the image. Liquid toner, comprising a dielectric carrier liquid containing charged toner particles, is applied between the photoconductive carrier and the developer electrode. The toner particles, being charged, are drawn to and plate out on information portions of the carrier. In regions on the carrier associated with background, toner particles are drawn toward and tend to plate out on the developer electrode as the regions on the carrier associated with background portions of the image move past the electrode. After development of the image, the carrier moves to a transfer station where the developed image is transferred to a receiving sheet. Thereafter, the carrier is cleared of any residual toner particles, charged to a high voltage at a charging station, and moved to an image transfer station where another image is optically projected onto the carrier. The process described above then repeats.

Substantial amounts of toner particles are likely to remain on the developer electrode from a preceding cycle of operations. Such particles will adhere to the developer electrode when the product of the force attracting the particles to the electrode and the coefficient of friction of the particles on the surface of the electrode is greater than the shear force caused by the flow of toner liquid over the electrode, if such flow is present at all. From a practical standpoint, it is well known that toner particles adhere to the developer electrode and must be removed if good copies of images on the carrier are to be obtained.

U.S. Patent No. 4,168,329 discloses removal of toner particles from a developer electrode by pulsing the electrode with a reverse bias subsequent to de-

velopment of the image, i.e., during an inter-image interval of operation of the machine. This procedure cleans toner particles from the electrode but results in the deposition of the particles onto the carrier necessitating their removal by a further processing operation. This technique is also disclosed in U.S. Patent Nos. 4,041,217, 4,168,329, and 4,423,134.

Other techniques are also known, such as utilizing a conductive roller for the developer electrode (U.S. Patent No. 4,454,833). Toner particles deposited on the roller can be removed by mechanical means, for example, which contact that surface of the roller outside the development region. Other techniques involve placing a high charge on a transverse band on the carrier during the inter-image interval, and passing the charged band over the electrode to deplate toner particles which adhere to the band. This approach, however, also requires further processing of the carrier before the next cycle of operations can begin.

Finally, as disclosed in GB 1,414,335, the developer electrode may be coated with a polymer which inhibits adhesion of toner particles thereto. Polymers disclosed in this patent include a silicone resin, a polytetrafluoroethylene, a polyurethane, a polypropylene, a polyvinyl chloride, a polycarbonate, and a cellulose acetate. According to the patent, the coating has a thickness in the range of from 1-100 μm .

Experiments were performed by the inventors of the present invention to determine if release coatings on developer electrodes have an effect on the image quality. These experiments have established that an electrode coated with a dielectric, such as vinyl polydimethylsiloxane polymer containing a noble metal complex as a catalyst, and a hydrogen functional polymethylsiloxane polymer with thickness of 20 or 40 μm or a polytetrafluoroethylene of 50 μm thicknesses, adversely affect image development. The effect on image development is best demonstrated by producing copies which are uniformly dark. In such case, the optical density of large image areas decrease significantly in the process direction when a development electrode coated in the manner described above is used. This effect is more pronounced for thicker dielectric coatings. This effect is not observed when an uncoated electrode is employed, and is more pronounced for thicker coatings. From this standpoint, coated electrodes known in the prior art and described in GB 1,414,335 are not practical for images which contain large printed areas.

While the techniques of the prior art have been reasonably successful in some respects, all but the approach taken in GB 1,414,335 include a residual cleanup process to remove toner particles that are deplated from the developer electrode before the next copying cycle is carried out. It has also been found that when toners of the type described in example 1 of U.S. Patent No. 4,794,651 are used with coated de-

velopers of the type known in the art, there is a tendency to form a deposit on the developer despite the coating.

It is therefore an object of the present invention to provide a new and improved liquid toner based electro-static imaging machine, and a developer electrode therefor, which eliminates, or substantially reduces, the above-mentioned deficiencies of the prior art.

BRIEF DESCRIPTION OF INVENTION

The present invention provides a liquid toner based imaging machine comprising a movable photoconductive carrier, means for producing an electrostatic latent image on the carrier, and a developing station containing a source of toner liquid that includes charged toner particles. The developing station is operatively associated with the carrier for contacting the same with toner liquid thereby developing the latent image by effecting the transfer of toner particles carried by the liquid to the image.

The developing station includes a developer electrode held at a voltage intermediate the voltages on the carrier representative of background and information portions of the image. As the carrier containing background portions of the image moves relative to an elemental area on the electrode, the resultant electric field is directed toward the elemental area. As a consequence, charged toner particles in the vicinity are attracted to the elemental area. According to the present invention, means are provided for inhibiting the deposition of toner particles on the surface of the electrode during development of the image. Such means for inhibiting deposition of toner particles on the surface of the electrode includes a coating on the surface of the electrode facing the carrier of dielectric material incapable of maintaining a surface charge with a polarity opposite to that of the charge on the toner particles. When the toner is negatively charged, a suitable material is a fluorosilicone polymer, e.g., Dow Corning 730 Solvent Resistant Sealant. In such case the preferred coating thickness is about 20 μm .

Alternatively, coating the developer electrode with fluorosilicone surfactants such as Zonyl (DuPont) has been effective in inhibiting plating out of toner particles, but this expedient inhibits plating-out of toner particles for only a limited period of time.

Where the toner is positively charged, or as an alternative to the use of fluorosilicone polymer for the case of negative charged toner particles, the release material should be slightly conductive. The preferred way in which to achieve this conductivity is to load the fluorosilicone polymer with an additive of conductive material, such as carbon black. Of considerable importance to the success of this embodiment of the invention is the physical size of the particles of carbon black. What is essential is that the size of the carbon

black particles be small enough so that the material is uniformly distributed in the polymer without any significant gaps in the conductivity on the surface of the coating. A preferred additive is Catafor CA100. The preferred amount of conductive material to fluorosilicone polymer is less than about 1% by weight. The preferred range of the additive is between about 0.5% to about 0.75% by weight.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting embodiments of the present invention are disclosed in the accompanying drawings wherein:

Fig. 1 is a schematic side view representation of a liquid toner based electrophotographic copy machine according to the present invention utilizing a photosensitive carrier in the form of a drum;

Fig. 2 is an enlarged sectional view of the drum shown in Fig. 1 associated with a developer electrode for the purpose of illustrating the manner in which plating out of toner particles on both the carrier and the developing electrode occurs;

Fig. 3 is an enlarged view in section of the developing electrode according to one embodiment of the present invention; and

Fig. 4 is a further embodiment of a developing electrode according to the present invention.

DETAILED DESCRIPTION

Referring now to Fig. 1, reference numeral 10 designates a liquid toner based electrophotographic copying machine according to the present invention. The machine includes a movable photoconductive carrier in the form of drum 11 that is rotatably mounted on a support (not shown). Peripheral surface 12 of the drum is photosensitive and capable of being charged to a high voltage at a charging station by discharge device 13 as the drum rotates past the device. Downstream of device 13 is an imaging station at which an optical image is projected onto surface 12 through lens 14 to produce on the surface 12 a latent electrostatic image. Information in the image is associated with highly charged elemental areas on the surface; and background in the image is associated with less charged elemental areas.

After the electrostatic image is produced on the surface of the drum, further rotation brings the surface containing the latent image to developing station 15 where a supply of toner liquid 16 is placed in contact with the surface of the drum. Liquid 16 contains either positively or negatively charged toner particles (not shown) and is kept in contact with the surface of the drum by developer electrode 17 at station 15 which is closely spaced to the drum surface. Electrode 17 is held at a voltage intermediate the voltages

on surface 12 of the drum associated with information and with background in the image. Typically, the surface of the drum is charged to a potential of about 1000 V. with the result that elemental areas on the surface of the drum containing information in the image may be charged to a potential as high as about 1000 V., and elemental areas containing background may be charged to a potential as low as about 100 V. In such case, developer electrode would be held at about 300 V.

A preferred toner for use with the present invention is that produced in accordance with example 1 of U.S. Patent No. 4,794,651, the disclosure of which is included herein by reference. The present invention will also be operative with a variety of other liquid toners.

A schematic representation of a portion of the surface of the drum containing both information and background is shown in Fig. 2, the region containing information being designated by reference numeral 18 and the region containing background being designated by reference numeral 18A. As is well known, the charged toner particles in the toner liquid located between the surface of the drum and the developer electrode are attracted to the information bearing elemental areas on the surface of the drum because the potential on these areas is greater than the potential on the electrode opposite such areas. This effect is indicated schematically in Fig. 2 by arrows 19. However, the potential on background bearing elemental areas on the surface of the drum is lower than the charge on the electrode opposite such areas with the result that toner particles are attracted to the electrode. This effect is indicated schematically in Fig. 2 by arrows 20.

As a consequence of the transfer of toner particles to the surface of the drum, and the movement of the drum relative to the electrode through a predetermined angular displacement, the electrostatic latent image is developed into an image made visible by the presence of toner particles adhering to the surface, and the developer electrode is coated with toner.

Continued rotation of the drum causes the developed image to pass metering station 21 the purpose of which is to remove excess carrier liquid from image and background areas of the image, and then to reach transfer station 25. At station 25, transfer sheet 23 is brought into contact with the surface of the drum and the developed image is transferred from the surface of the drum to the sheet in a known manner. Any toner particles remaining on the drum surface are removed at cleaning station 27 before the drum surface returns to charging station 13 completing a cycle of operation.

The apparatus described above is entirely conventional and is a simplified representation of a liquid toner electrophotographic copying machine, details of which are shown in the patents whose disclosures are incorporated by reference. For example, the in-

vention is applicable to carriers other than drums (e.g., belts), to mechanisms for applying liquid toner other than what is shown schematically in the drawings, to metering other than reverse roller metering, to transfer station configurations other than that shown in the drawings, and for other types of electrostatic imaging machines such as printers utilizing electrostatic masters and laser printers.

The problem with such apparatus is illustrated schematically in Fig. 2 where reference numeral 24 represents toner particles that coat electrode 17 during the developing process effected at station 15. As is well known, particles 24 tend to stick to the electrode even when the developing process utilizes flowing toner liquid. Eventually, the build-up of toner on the electrode seriously affects image quality on the transfer sheet.

According to the present invention, as illustrated schematically in Figs. 3 and 4, electrode 17 is provided with inhibiting means for inhibiting the deposition of toner particles on surface 12 of the drum during the time that the latent image is being developed, i.e., during the time the surface of the drum containing the latent image is operatively associated with the developer electrode of the development station. The inhibiting means may be a layer of release material on the surface of the electrode facing surface 12 of drum 11 in the form of dielectric coating 22. Preferably the coating should be incapable of holding a surface charge at a polarity opposite to the polarity of the toner. Thus an electronegative coating should be used for negatively charged toner and an electropositive material should be used for positive toner. When the charge on the toner is negative, the preferred coating is a fluorosilicone polymer for example, Dow Corning 730 Solvent Resistant Sealant. A coating thickness of about 20 μm is satisfactory, although thicknesses of less than 2 to 100 μm are also operative to inhibit plating. This material is believed to produce the desired result because it is electronegative, that is it naturally develops a negative surface charge and can not carry a positive charge. Thus such material can be defined as having an electrical disaffinity for negatively charged particles and the particles do not stick to the material.

When the charge on the toner particles is positive or as an alternative coating when the toner particles are negatively charged, making the dielectric coating slightly conductive is advantageous. This can be achieved by an additive, such as carbon black, which causes the resistivity of the coating to be in the range of about 10^{13} to about 10^{10} ohm-cm., preferably about 10^{12} to 10^{11} . The physical size of the carbon black particles should be very small to insure uniform surface conductivity on the electrode. That is to say, the surface conductivity should be both uniform and continuous on the surface. Other polymer materials can be used for coating the electrode provided the conduc-

tivity range is as described above.

A suitable additive to the preferred fluorosilicone polymer for this purpose is Catafor CA100, a product currently produced by AMB Chemicals Ltd., Poleacre Lane, Woodley Stockport, Cheshire, England. To obtain this degree of conductivity less than about 1% by weight of the preferred additive is used. The preferred range of additive to dielectric is about 0.5% to about 0.75% by weight. Percentages greater than about 1% by weight are less effective in inhibiting the sticking of toner particles to the electrode.

Developer electrodes made in accordance with the present invention permit copies to be made without gray scale variation in the process direction when copies are made of uniformly gray object. This is a substantial improvement over the prior art.

EXAMPLE I

Toner liquid was prepared by mixing 1000 grams of Elvax II polymer 5720 (manufactured by DuPont Corporation) and 500 grams of Isopar L (manufactured by Exxon Corporation) in a Ross Double Planetary mixer at 90°C. After mixing for about one hour, 250 grams of carbon black (Mogul L) and 500 grams of Isopar L were added; and mixing was continued for about one hour at 90°C. Additional Isopar L was added to provide a mixture of 30% solids and 70% Isopar L; and mixing was continued at the same temperature for about one hour. The material was allowed to come to room temperature with continued mixing for over a period of 3 hours. The material was then diluted with Isopar H to a 13.35% by weight non-volatile solids composition, and the composition was ground with 1/2 inch (1 inch = 25.4 mm) Al_2O_3 cylinders in M-18 Sweco vibratory mill (approximate loading volume, 2 gallons) for about 24 hours at about 40°C. The toner concentrate was then diluted to a 1.5% non-volatiles concentration with Isopar H. Then, 0.6 grams of lecithin (a charge director) dissolved in 5.4 grams of Isopar H was added to 1500 grams of diluted toner dispersion. The toner particles in the toner dispersion were negatively charged in a conventional way to a conventional degree.

A coating of Dow Corning 730 Solvent Resistant Sealant approximately 20 μm thick was applied to half of the developer electrode on a Savin 870 copier such that half the latent image was subject to an electrode according to the invention, and half was not. The conventional back-pulsing (deplating operation) of the developer electrode of the copier was disabled, and a constant +300 V. dc bias was applied to the developer electrode. In addition, the paper feed was disabled; but because the transfer station is downstream of the developer station, this had no effect on the operation of the developer station.

In order to maximize the deposition of toner on the developer electrode, a blank, white document was

copied 2,000 times. After the run was completed, the uncoated half of the electrode was found to be plated with toner particles, and the coated half was free of toner particles. At this point, the paper feed was enabled, and 100 copies of a test document were made. No discernible difference was found either between the two sides of the copies, or as a function of time. This demonstrated that the presence of a coating on the developer electrode does not adversely affect image quality while maintaining the electrode free of toner.

EXAMPLE II

The setup was the same as in EXAMPLE I, but in this case, no background runs were made. The paper feed was enabled, and 150 copies of a test document were made. No discernible difference was found between either the two sides of the document, or as a function of time.

While a specific toner liquid was used in the above examples, it is believed that the results obtained are not dependent on the specific nature of the toner liquid, and that the present invention will operate successfully with conventional liquid toners such as those described in the patents incorporated by reference. In addition, the present invention is applicable to developer electrode voltages other than strictly dc voltages. For example, the invention is applicable to apparatus in which the developer electrode is unidirectional, but time variable.

The advantages and improved results furnished by the method and apparatus of the present invention are apparent from the foregoing description of the preferred embodiment of the invention. Various changes and modifications may be made without departing from the scope of the invention as described in the appended claims.

Claims

1. Liquid toner based imaging apparatus comprising:
 - a) a movable imaging surface (12);
 - b) means for producing (13, 14) an electrostatic latent image on the imaging surface, said image having first and second regions with first and second respective voltages; and
 - c) a developing station (15) having a source of developing liquid (16) that includes charged toner particles, said station being operatively associated with the imaging surface for contacting the same with said liquid thereby developing the latent image by effecting the transfer of toner particles to said image; said developing station including:
 - (1) a developer electrode (17) charged to



tivity range is as described above.

A suitable additive to the preferred fluorosilicone polymer for this purpose is Catafor CA100, a product currently produced by AMB Chemicals Ltd., Poleacre Lane, Woodley Stockport, Cheshire, England. To obtain this degree of conductivity less than about 1% by weight of the preferred additive is used. The preferred range of additive to dielectric is about 0,5% to about 0.75% by weight. Percentages greater than about 1% by weight are less effective in inhibiting the sticking of toner particles to the electrode.

Developer electrodes made in accordance with the present invention permit copies to be made without gray scale variation in the process direction when copies are made of uniformly gray object. This is a substantial improvement over the prior art.

EXAMPLE I

Toner liquid was prepared by mixing 1000 grams of Elvax II polymer 5720 (manufactured by DuPont Corporation) and 500 grams of Isopar L (manufactured by Exxon Corporation) in a Ross Double Planetary mixer at 90°C. After mixing for about one hour, 250 grams of carbon black (Mogul L) and 500 grams of Isopar L were added; and mixing was continued for about for about one hour at 90°C. Additional Isopar L was added to provide a mixture of 30% solids and 70% Isopar L; and mixing was continued at the same temperature for about one hour. The material was allowed to come to room temperature with continued mixing for over a period of 3 hours. The material was then diluted with Isopar H to a 13.35% by weight non-volatile solids composition, and the composition was ground with 1/2 inch (1 inch = 25,4 mm) AL₂O₃ cylinders in M-18 Sweco vibratory mill (approximate loading volume, 2 gallons) for about 24 hours at about 40°C. The toner concentrate was then diluted to a 1.5% non-volatiles concentration with Isopar H. Then, 0.6 grams of lecithin (a charge director) dissolved in 5.4 grams of Isopar H was added to 1500 grams of diluted toner dispersion. The toner particles in the toner dispersion were negatively charged in a conventional way to a conventional degree.

A coating of Dow Corning 730 Solvent Resistant Sealant approximately 20 µm thick was applied to half of the developer electrode on a Savin 870 copier such that half the latent image was subject to an electrode according to the invention, and half was not. The conventional back-pulsing (deplating operation) of the developer electrode of the copier was disabled, and a constant +300 V. dc bias was applied to the developer electrode. In addition, the paper feed was disabled; but because the transfer station is downstream of the developer station, this had no effect on the operation of the developer station.

In order to maximize the deposition of toner on the developer electrode, a blank, white document was

copied 2,000 times. After the run was completed, the uncoated half of the electrode was found to be plated with toner particles, and the coated half was free of toner particles. At this point, the paper feed was enabled, and 100 copies of a test document were made. No discernible difference was found either between the two sides of the copies, or as a function of time. This demonstrated that the presence of a coating on the developer electrode does not adversely affect image quality while maintaining the electrode free of toner.

EXAMPLE II

The setup was the same as in EXAMPLE I, but in this case, no background runs were made. The paper feed was enabled, and 150 copies of a test document were made. No discernible difference was found between either the two sides of the document, or as a function of time.

While a specific toner liquid was used in the above examples, it is believed that the results obtained are not dependent on the specific nature of the toner liquid, and that the present invention will operate successfully with conventional liquid toners such as those described in the patents incorporated by reference. In addition, the present invention is applicable to developer electrode voltages other than strictly dc voltages. For example, the invention is applicable to apparatus in which the developer electrode is unidirectional, but time variable.

The advantages and improved results furnished by the method and apparatus of the present invention are apparent from the foregoing description of the preferred embodiment of the invention. Various changes and modifications may be made without departing from the scope of the invention as described in the appended claims.

Claims

1. Liquid toner based imaging apparatus comprising:
 - a) a movable imaging surface (12);
 - b) means for producing (13, 14) an electrostatic latent image on the imaging surface, said image having first and second regions with first and second respective voltages; and
 - c) a developing station (15) having a source of developing liquid (16) that includes charged toner particles, said station being operatively associated with the imaging surface for contacting the same with said liquid thereby developing the latent image by effecting the transfer of toner particles to said image;
 - said developing station including:
 - (1) a developer electrode (17) charged to



a voltage intermediate said first and second voltages on the imaging surface for attracting particles to said first regions; and

(2) inhibiting means (22) for inhibiting the deposition of toner particles on the surface of the electrode during the development of the image, said inhibiting means including release coating (22) on the surface of the electrode facing the imaging surface,

characterized in that said coating comprises a polymer material and an electrical conductivity increasing additive.

2. A developer electrode (17) for a liquid toner based electrophoretic imaging apparatus having a movable carrier (12) carrying an electrostatic image including background and information portions, and having a developing liquid (16) comprising charged toner particles which is applied between the carrier and the electrode for developing the image by plating out toner particles on information portions of the carrier, said electrode having a surface facing the carrier and inhibition means (22) on said surface for inhibiting the deposition of toner particles on said surface during development of the image, wherein said inhibition means includes a coating (22) on said surface, characterized in that said coating is of a material having an electrical disaffinity for said toner particles.

3. Liquid toner based imaging apparatus comprising:

- a) a movable imaging surface (12);
- b) means for producing (13, 14) an electrostatic latent image on the imaging surface, said image having first and second regions with first and second respective voltages; and
- c) a developing station (15) having a source of developing liquid (16) that includes charged toner particles, said station being operatively associated with the imaging surface for contacting the same with said developing liquid thereby developing the latent image by effecting the transfer of toner particles to said image;

said developing station including a developer electrode (17) according to claim 2, charged to a voltage intermediate said first and second voltages on the imaging surface for attracting particles to said first regions.

4. Apparatus according to claim 3 wherein said release material includes an electrical conductivity increasing additive.

5. Apparatus according to any one of claims 1 or 4 wherein said additive is less than about 1% in weight.

6. Apparatus according to any one of claims 2, 4 or 5 wherein the resistivity of the release material is in the range of 10^{10} to 10^{13} ohm-cm.

7. Apparatus according to claim 6 wherein the resistivity of the release material is in the range of 10^{11} to 10^{12} ohm-cm.

8. Apparatus according to any of the preceding claims wherein said release material is electronegative.

9. Apparatus according to any one of the preceding claims wherein said release material is a fluorosilicone polymer.

10. Apparatus according to any one of the preceding claims wherein said release material is between about 2 and 100 micrometers in thickness.

11. Apparatus according to claim 10 wherein said release material is about 20 micrometers in thickness.

12. A method for electrographic image formation comprising the steps of:

- a) forming on a movable carrier an electrostatic image having first and second regions with first and second voltages respectively;
- b) moving the carrier into proximity with a developer electrode held at a voltage intermediate said first voltages and second voltages;
- c) applying liquid toner containing charged toner particles between the carrier and the developer electrode for plating out toner particles on first portions of the carrier; and
- d) suppressing the plating out of toner particles on the electrode while the toner liquid is applied between the carrier and the developer electrode by coating a release material on the surface thereof facing the carrier,

characterized in that said material has an electrical disaffinity for the toner particles.

13. A method according to claim 12 wherein said release material is electronegative.

14. A method according to claim 12 or 13 wherein said release material comprises a fluorosilicone polymer.

15. A method according to any one of claims 12-14 wherein said release material contains a conductive additive.



Patentansprüche

1. Abbildungsvorrichtung auf Flüssigtonerbasis, welche folgendes aufweist:

a) eine bewegliche Abbildungsfläche (12);
b) eine Einrichtung (13, 14) zum Erzeugen eines elektrostatischen latenten Bildes auf der Abbildungsfläche, wobei das Bild erste und zweite Bereiche mit ersten und zweiten Ladungen jeweils hat; und

c) eine Entwicklungsstation (15), welche einen Vorrat für Flüssigentwickler (16) hat, welcher geladene Tonerpartikel umfaßt, wobei die Station betriebsmäßig mit der Abbildungsfläche zum Kontaktieren derselben mit der Flüssigkeit verbunden ist, wodurch das latente Bild dadurch entwickelt wird, daß die Tonerpartikel auf das Bild übertragen werden;

wobei die Entwicklungsstation folgendes umfaßt:

(1) eine Entwicklungselektrode (17), welche auf eine Spannung zwischen den ersten und zweiten Spannungen der Abbildungsfläche aufgeladen ist, um Partikel an den ersten Bereichen anzuziehen; und

(2) eine Unterdrückungseinrichtung (22), welche die Ablagerung von Tonerpartikeln auf der Oberfläche der Elektrode während der Entwicklung des Bildes unterdrückt, wobei die Unterdrückungseinrichtung einen Trennmittelüberzug (22) auf der Oberfläche der Elektrode umfaßt, die der Abbildungsfläche zugewandt ist,

dadurch gekennzeichnet, daß der Überzug ein Polymermaterial und einen das elektrische Leitvermögen heraufsetzenden Zusatz aufweist.

2. Entwicklungselektrode (17) für eine elektrophoretische Abbildungsvorrichtung auf Flüssigtonerbasis, welche einen beweglichen Träger (22) hat, welcher ein elektrostatisches Bild einschließlich Hintergrunds- und Informationsteilen trägt, und die einen Flüssigentwickler (16) hat, welcher geladene Tonerpartikel aufweist und zwischen dem Träger und der Elektrode zum Entwickeln des Bildes durch Ausbreiten der Tonerpartikel auf die Informationsteile des Trägers aufgebracht wird, wobei die Elektrode eine Oberfläche hat, die dem Träger zugewandt ist, und eine Unterdrückungseinrichtung (22) auf der Fläche zur Unterdrückung der Ablagerung der Tonerpartikel auf der Oberfläche während der Entwicklung des Bildes hat, wobei die Unterdrückungseinrichtung einen Überzug (22) auf der Oberfläche umfaßt, dadurch gekennzeichnet, daß der Überzug aus einem Material besteht, welches eine elektrische Disaffinität für die Tonerpartikel hat.

3. Abbildungsvorrichtung auf Flüssigtonerbasis,

welche folgendes aufweist:

a) eine bewegliche Abbildungsfläche (12);
b) eine Einrichtung (13, 14) zum Erzeugen eines elektrostatischen latenten Bildes auf der Abbildungsfläche, wobei das Bild erste und zweite Bereiche mit ersten und zweiten Spannungen jeweils hat; und

c) eine Entwicklungsstation (15), welche einen Vorrat für Flüssigentwickler (16) hat, welcher geladene Tonerpartikel umfaßt, wobei die Station betriebsmäßig mit der Abbildungsfläche zum Kontaktieren derselben mit der Entwicklerflüssigkeit verbunden ist, wodurch das latente Bild durch die Übertragung der Tonerpartikel auf das Bild entwickelt wird;

wobei die Entwicklungsstation eine Entwicklungselektrode (17) nach Anspruch 2 aufweist, welche auf eine Spannung zwischen den ersten und zweiten Spannungen an der Abbildungsfläche zum Anziehen der Partikel an den ersten Bereichen aufgeladen ist.

4. Vorrichtung nach Anspruch 3, bei der das Trennmittelmaterial einen das elektrische Leitvermögen heraufsetzenden Zusatz umfaßt.
5. Vorrichtung nach einem der Ansprüche 1 oder 4, bei der der Zusatz weniger als etwa 1 Gew.-% ausmacht.
6. Vorrichtung nach einem der Ansprüche 2, 4 oder 5, bei der der spezifische Widerstand des Trennmittelmaterials in einem Bereich von 10^{10} bis 10^{13} Ohm.cm liegt.
7. Vorrichtung nach Anspruch 6, bei der der spezifische Widerstand des Trennmittelmaterials in einem Bereich von 10^{11} bis 10^{12} Ohm.cm liegt.
8. Vorrichtung nach einem der vorangehenden Ansprüche, bei der das Trennmittelmaterial elektronegativ ist.
9. Vorrichtung nach einem der vorangehenden Ansprüche, bei der das Trennmittelmaterial ein Fluorosilikonpolymer ist.
10. Vorrichtung nach einem der vorangehenden Ansprüche, bei der das Trennmittelmaterial eine Dicke zwischen etwa 2 und 100 µm hat.
11. Vorrichtung nach Anspruch 10, bei der das Trennmittelmaterial eine Dicke von etwa 20 µm hat.
12. Verfahren zur Bildung einer elektrographischen Abbildung, welches die folgenden Schritte aufweist:



- a) Ausbilden einer elektrostatischen Abbildung auf einem beweglichen Träger mit ersten und zweiten Bereichen mit ersten und zweiten Spannungen jeweils;
- b) Bewegen des Trägers in die Nähe einer Entwicklungselektrode, welche auf einer Spannung ist, die zwischen den ersten und zweiten Spannungen liegt;
- c) Aufbringen des Flüssigtoners, welcher geladene Tonerpartikel enthält, zwischen den Träger und die Entwicklungselektrode zum Abscheiden von Tonerpartikel auf den ersten Teilen des Trägers; und
- d) Unterdrücken des Ausbreitens der Tonerpartikel auf der Elektrode, währenddem die Tonerflüssigkeit zwischen dem Träger und der Entwicklungselektrode aufgebracht wird, indem ein Trennmittelmaterial als Überzug auf der Oberfläche hiervon vorgesehen wird, welche dem Träger zugewandt ist, dadurch gekennzeichnet, daß das Material eine elektrische Disaffinität für die Tonerpartikel hat.
13. Verfahren nach Anspruch 12, bei der das Trennmittelmaterial elektronegativ ist.
14. Verfahren nach Anspruch 12 oder 13, bei dem das Trennmittelmaterial ein Fluorosiliconpolymer aufweist.
15. Verfahren nach einem der Ansprüche 12 bis 14, bei dem das Trennmittelmaterial einen leitenden Zusatz enthält.

Revendications

1. Appareil de formation d'image à base d'un toner liquide, qui comprend :
- a) une surface mobile (12) de formation d'image;
- b) des moyens (13, 14) pour produire une image électrostatique latente sur la surface de formation d'image, ladite image comprenant des premières et secondes régions avec des première et seconde tensions respectives; et
- c) un poste de révélation (15) comprenant une source de liquide révélateur (16) qui contient des particules de toner chargées, ledit poste étant opérationnellement associé à la surface de formation d'image pour amener ledit liquide en contact avec elle, révélant de ce fait l'image latente en effectuant le transfert des particules de toner sur ladite image;
- ledit poste de révélation comprenant :
- (1) une électrode révélatrice (17) chargée à une tension intermédiaire entre lesdites première et seconde tensions sur la surface de

formation d'image pour attirer des particules vers lesdites premières régions, et

(2) un moyen d'inhibition (22) pour empêcher le dépôt de particules de toner sur la surface de l'électrode pendant la révélation de l'image, ledit moyen d'inhibition comprenant un revêtement de décharge (22) placé sur la surface de l'électrode en vis-à-vis de la surface de formation d'image,

caractérisé en ce que ledit revêtement comprend un matériau polymère et un additif qui augmente la conductivité électrique.

2. Electrode révélatrice (17) destinée à un appareil électrophorétique de formation d'image à partir d'un toner liquide, comprenant un support mobile (12) qui porte une image électrostatique incluant des régions d'information et des régions d'arrière-plan, et comprenant un liquide révélateur (16) qui contient des particules de toner chargées et qui est appliqué entre le support et l'électrode pour révéler l'image par électrodéposition de particules de toner sur les régions d'information du support, ladite électrode ayant une surface en vis-à-vis du support et un moyen d'inhibition (22) sur ladite surface pour empêcher le dépôt de particules de toner sur ladite surface pendant la révélation de l'image, sachant que ledit moyen d'inhibition comprend un revêtement (22) sur ladite surface, caractérisée en ce que ledit revêtement est fait d'un matériau qui présente une répulsion électrique pour lesdites particules de toner.
3. Appareil de formation d'image à base d'un toner liquide, qui comprend :
- a) une surface mobile (12) de formation d'image;
- b) des moyens (13, 14) pour produire une image électrostatique latente sur la surface de formation d'image, ladite image comprenant des premières et secondes régions avec des première et seconde tensions respectives; et
- c) un poste de révélation (15) comprenant une source de liquide révélateur (16) qui contient des particules de toner chargées, ledit poste étant opérationnellement associé à la surface de formation d'image pour amener ledit liquide révélateur en contact avec elle, révélant de ce fait l'image latente en effectuant le transfert des particules de toner sur ladite image;
- ledit poste de révélation comprenant une électrode révélatrice (17) conforme à la revendication 2, chargée à une tension intermédiaire entre lesdites première et seconde tensions sur la surface de formation d'image pour attirer des particules vers lesdites premières régions.
4. Appareil selon la revendication 3, dans lequel le-



- dit matériau de décharge contient un additif qui augmente la conductivité électrique.
5. Appareil selon l'une quelconque des revendications 1 ou 4, dans lequel ledit additif représente moins de 1% en poids environ. 5
 6. Appareil selon l'une quelconque des revendications 2, 4 ou 5, dans lequel la résistivité du matériau de décharge est comprise dans la fourchette 10^{10} à 10^{13} ohm-cm. 10
 7. Appareil selon la revendication 6, dans lequel la résistivité du matériau de décharge est comprise dans la fourchette 10^{11} à 10^{12} ohm-cm. 15
 8. Appareil selon l'une quelconque des précédentes revendications, dans lequel le matériau de décharge est électronégatif. 20
 9. Appareil selon l'une quelconque des précédentes revendications, dans lequel le matériau de décharge est un polymère de type silicone fluoré. 25
 10. Appareil selon l'une quelconque des précédentes revendications, dans lequel le matériau de décharge a une épaisseur comprise entre 2 et 100 micromètres environ. 30
 11. Appareil selon la revendication 10, dans lequel ledit matériau de décharge a une épaisseur d'environ 20 micromètres. 35
 12. Procédé pour former une image électrographique, qui comprend les étapes consistant à : 35
 - a) former, sur un support mobile, une image électrostatique qui comprend des premières et des secondes régions avec respectivement des première et seconde tensions,
 - b) amener le support à proximité d'une électrode révélatrice maintenue à une tension intermédiaire entre lesdites première et seconde tensions, 40
 - c) appliquer un toner liquide qui contient des particules de toner chargées entre le support et l'électrode révélatrice pour déposer des particules de toner sur les premières régions du support; et 45
 - d) supprimer l'électrodéposition des particules de toner sur l'électrode, tandis que le toner liquide est appliqué entre le support et l'électrode révélatrice, par revêtement de la surface de celle-ci qui est en vis-à-vis du support à l'aide d'un matériau de décharge, 50
 caractérisé en ce que ledit matériau présente une répulsion électrique pour les particules de toner. 55

13. Procédé selon la revendication 12, dans lequel

ledit matériau de décharge est électronégatif.

14. Procédé selon la revendication 12 ou 13, dans lequel le matériau de décharge est un polymère de type silicone fluoré.
15. Procédé selon l'une quelconque des revendications 12 à 4, dans lequel le matériau de décharge contient un additif conducteur.