



(43) International Publication Date  
30 May 2013 (30.05.2013)

- (51) International Patent Classification: Not classified
- (21) International Application Number: PCT/IB2012/002906
- (22) International Filing Date:  
14 November 2012 (14.11.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
61/562,420 21 November 2011 (21.11.2011) US  
61/562,416 21 November 2011 (21.11.2011) US  
13/369,231 8 February 2012 (08.02.2012) US  
13/372,296 13 February 2012 (13.02.2012) US
- (71) Applicant: JACKSON GLOBAL PTE. LTD. [SG/SG];  
29 Tai Seng Street, Jackson Design Hub, Singapore  
534120 (SG).
- (72) Inventors: CHOO, Chong, Kun; 29 Tai Seng Street, Jackson Design Hub, Singapore 534120 (SG). TAN, Hong, Seng; 29 Tai Seng Street, Jackson Design Hub, Singapore 534120 (SG).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

(54) Title: MOTOR-DRIVEN CURTAIN OR BLIND ASSEMBLY




FIG. 1

(57) Abstract: Systems and methods for a motor-driven curtain or blind assembly are provided. For example, in some embodiments the motor drive assembly includes a track, a lead runner, and a plurality of sensors. The track can have a plurality of coils that can be electrically activated to generate an electromagnetic field to cause the lead runner to slide along the track. The lead runner may include magnet housing with a magnet to interact with the electromagnetic field. In some embodiments, the plurality of sensors or switches can be disposed between the coils. The sensors can be configured to activate the electromagnetic field locally to cause the lead runner to slide along the track. Examples of the sensors or switches include, but are not limited to, a reed switch, a silicone magnetic switch, an optical switch, a mechanical limit switch, a proximity switch, a magnetic encoder, or an optical encoder.



WO 2013/076584 A2