

**"Improvements Relating to Marking of Smoking-
Article Wrappings"**

This invention relates to the marking of smoking-article wrappings and to smoking articles comprising marked wrappings.

5 The marking of exterior wrappings of cigarettes is a well established practice. For example, brand names are commonly printed in ink on cigarette paper. Such printing usually takes place as part of cigarette manufacture, a printing unit being mounted on the cigarette-making machine. Another common example of the marking
10 of cigarette wrappings is the application to a web of tipping paper of dyes in such a manner as to produce a cork-tipping effect.

It is an object of the present invention to provide a simple and flexible method of marking a wrapping of
15 a smoking article, which method may, if required, be carried out on article-making machinery and which produces the marking otherwise than by printing it in ink.

The invention provides a method of marking a smoking-article having an exterior wrapping consisting of, or
20 incorporating, a substance which causes or undergoes a permanent change of colour under the application of heat, the method being characterised by bringing the article and a heated former means into contact with each other and rolling the smoking article about the longitudinal
25 axis thereof, the former means corresponding to the required marking, whereby heat applied through the former means to the article effects said colour change.

The exterior wrapping may be cigarette paper or the tipping of a cigarette.

30 The degree of colour change caused may then be controlled according to the temperature to which the wrapping is raised by the heated former means.

The method according to the invention may be carried

114

- 2 -

out, if desired, in such manner that the heated former means moulds an impression into the wrapping, as well as causing a colour change of colour-change substance with which the wrapping is provided. When such a moulded
5 impression is required, the wrapping may be one comprising a thermoplastic material, a polyolefin for example.

In the manufacture of filter-tipped cigarettes it is the current practice to assemble in line a double length filter element with two tobacco rods, inner ends
10 of which rods abut respective ends of the filter element.

A tipping wrapper is then applied to such assembly, the wrapping serving to enwrap the full length of the filter element and a short length of each of the tobacco rods and thus to interattach the filter element and the
15 rods. Subsequently, the double cigarette assembly is severed at the central transverse plane of the filter element thus to provide two completed filter tipped cigarettes. These steps are carried out on a machine called a filter-tip assembling machine. In the operation
20 of such machine, a leading end of a discrete tipping wrapping being conveyed on a rotary drum, called a cork drum, is adhered, by adhesive applied to the tipping wrapping, to a rod-filter element-rod assembly being conveyed by another drum, called a transfer drum. The
25 assembly is then transferred onto the cork drum. Disposed in spaced relationship with the cork drum is a curved, heatable rolling plate the purpose of which is to cause each assembly to be rotated about its axis as it is conveyed by the cork drum and thus to cause the tipping wrapping to be wrapped completely about the assembly. In carrying
30 out the method according to the invention, an advantageous location for the heated former means is at or adjacent to the rolling plate.

The colour-change substance with which the wrapping
35 is provided may be incorporated into the "furnish" at the stage of manufacturing the wrapping, but is more

conveniently applied, at the side intended to be the outer side upon incorporation with a smoking article, after manufacture. The substance on the wrapping may, before being caused to change colour, be coloured, white 5 or colourless.

The marking on the wrapping, as for example if it takes the form of a brand name or emblem or similar such indicia, may extend over only a minor proportion of the circumference of the smoking article such that 10 it may be seen in its entirety without the article having to be turned about its axis. On the other hand, the marking may take the form of a decoration or pattern extending or being repeated over the full circumference of the smoking article. Such decoration or pattern 15 may comprise lines extending around or lengthwise of the article. In order to provide such decoration or pattern on a smoking article after manufacture thereof it is necessary to roll the article through a complete revolution in contact with the heated former means.

20 A continuous, ostensibly random pattern, such for example as the well known cork tipping-effect pattern, can be produced using the method according to the present invention.

The present invention also provides a smoking 25 article, a cigarette for example, having a wrapping bearing marking which has been produced by the method according to the invention.

Ways of putting the invention into practice will now be more fully described by way of example with 30 reference to the accompanying daigrammatic drawings in which:

Figure 1 is an end view of part, namely a quadrant of the circumference of the rolling plate of a filter-tipping machine,

35 Figure 2 shows a similar view of an alternative embodiment and

Figure 3 shows a side view of another embodiment

(16)

- 4 -

in which the smoking articles are conveyed linearly. For the present invention a brand-name printing die 1 is let into the rolling face 2 of the rolling plate 3 which coacts with a rotating printing drum, the "cork drum", 6 for producing a double-length cigarette filter cigarette assembly has been referred to above. The contact faces 1' of the dies 1 are flush with the rolling fascia. The dies are separated from the surrounding metal of the plate 3 by a lining 4 of thermal insulating material. Each die 1 is provided with heating means in the form of an electrical resistance heating unit 5. The rolling plate 3 is heated by separate known heating means (not shown), to a lower temperature than the dies, to promote setting of the tipping-wrapping adhesive..

It will be noted that the surface of the drum has shallow flutes 6' at intervals, to which reference will be made hereinafter.

For the use of the apparatus described above, a reel of tipping wrapping was mounted on the filter-tip assembling machine. The fibrous content of this wrapping was substantially wholly composed of cellulosic fibres. The wrapping bore an overall dyed pattern providing a cork-tipping effect. Double-length filter elements and unit-length tobacco rods were fed to the machine, which was operated to interattach the said elements and tobacco rods by means of discrete tipping wrappings severed from the web extending from the aforesaid reel. The double-length cigarettes were then severed by a disc knife of the assembling machine to provide single cigarettes.

It was observed that the tipping of each cigarette, where it had been contacted by one of the heated dies, bore a marking in the form of a distinct, sharp-edged, representation of the brand name. The colour of the

17

5 markings, resulting from heating of the cork-effect dye by the heated printing dies, was significantly darker than that of the surrounding wrapping material which, although having been subjected to heating by the heated rolling plate, had not been raised to a sufficient temperature to cause a colour change of the dye.

Thus, as is usual with such an arrangement, the cigarette or cigarette assembly 7 is caused to roll, in known manner over the surface 2 of the plate 3.

10 - In another test, using the same machine with a tipping wrapping which contained 75% polypropylene fibres and 25% cellulosic fibres was provided with a similar cork-effect appearance. Two brand-name printing dies 1 were let into the rolling plate 3, but the contact
15 face of each die was not flush with the rolling surface 2, but proud of the surface by 1 mm. The tipping wrappings of the cigarettes assembled by the machine each bore a representation of the brand name, but in this case not only was the brand name depicted sharply in colour-
20 changed dye, but also in three dimensions, by virtue of its having been thermally impressed into the wrapping.

These methods according to the invention, when applied to mark tipping wrappings, possess advantages over the current procedure of printing a pattern or
25 decoration onto a tipping wrapping before a reel thereof is mounted on a filter-tip assembling machine. The printing procedure can only be used satisfactorily to print an overall pattern or a decoration continuously along the length of the wrapping web. If discrete
30 markings, emblems for example, were spaced apart at regular intervals along the wrapping web, then in use of that web, the severance thereof to provide discrete tipping wrappings could sometimes take place along a line intersecting an emblem. Because of overlapping

(18)

of the wrapping at the seam therein, the two portions of the emblem could be dislocated and the result unsightly. When, on the other hand, methods according to the present invention are used to produce a marking such as an emblem
5 on tipping wrappings, whether or not the marking is thermally impressed into the wrappings, the marking is applied completely, i.e., without possibility of relative dislocation of portions thereof, even if a
10 portion of the marking extends onto or completely across the lap seam of a tipping wrapping.

When a method according to the present invention is carried out in order to reproduce brand names, emblems or other markings on cigarette papers of assembled cigarettes, it is again significantly advantageous as compared
15 with the known method of utilizing a printing unit mounted on a cigarette-making machine to print markings on the cigarette-paper web upstream of the point of entry thereof into the garniture of the machine. With the printing method, constant attention must be paid
20 to keeping the printing unit clean and clear of build-ups of ink in order to ensure maintenance of distinct printed markings free of smudging. If the cigarette-paper web breaks during operation of the making machine, it may be necessary for the operator to rethread the
25 web around a number of rollers of the printing unit. Adjustments are required from time-to-time to correct for mislocation of the printed marks along the cigarettes. By use of the present invention, defects of the known method
30 are avoided or reduced.

As above described, printing dies 1 were let into the rolling plate 3 of a filter-tip assembling machine and double-length cigarette assemblies 7 were
35 rolled over the dies under action of the rotation of a cork drum 6. As is usual with this arrangement of cork drum and rolling plate, the cigarette assemblies are initially each held in one shallow flute 6' of the

19

drum, possibly under the action of an applied partial vacuum, and roll along the drum surface to be received in a second such flute 6'. In an alternative to this arrangement shown in Figure 2 a drum 6 is provided in the periphery with a series of rollers 8 whose axes are mounted parallel to the axis of the drum. The spacing of these rollers is such that cigarettes or double-length cigarette assemblies 7 can be supported by pairs of adjacent rollers 8. The rollers 8 are positively driven to rotate and cause the cigarettes or assemblies 7 to be rotated as they pass across the faces of or each heated die 1. This alternative form of drum could be mounted on a filter-tip assembling machine or could constitute a separate unit.

15 A further alternative illustrated in Figure 3 is to convey the cigarettes or assemblies 7 in a straight line, not a curved path, as they are rolled into contact with a heated die. An endless belt 9, for example, may be used for the straight-line conveyance.

(20)



- 8 -

CLAIMS:

1. A method of marking a smoking-article having an exterior wrapping consisting of, or incorporating, a substance which causes or undergoes a permanent change of colour under the application of heat, the method
5 being characterised by bringing the article and a heated former means into contact with each other and rolling the smoking article about the longitudinal axis thereof, the former means corresponding to the required marking, whereby heat applied through the former means to the
10 article effects said colour change.
2. A method according to claim.1, wherein said wrapping and heated former means are maintained in contact with each other under pressure.
3. A method according to claim 1 or 2, wherein said
15 former means moulds an impression into said wrapping.
4. A method according to any preceding claim, wherein the method is performed on a filter-tip assembling machine.
5. A method according to any preceding claim, wherein said wrapping is a tipping wrapping.
- 20 6. A method according to any preceding claim, wherein the wrapping is composed substantially wholly of cellulose fibres.
- 25 7. A method according to any one of claims 1 to 5 wherein the wrapping comprises a major proportion of polypropylene fibres and a minor proportion of cellulose fibres.
8. A method of marking a smoking article having an



21

- 9 -

exterior wrapping substantially as hereinbefore described with reference to any of the accompanying drawings.

- 5 9. A smoking article having a wrapping bearing marking which has been produced by a method as claimed in any one of the preceding claims.
-