

SYSTEM AND METHOD FOR INVESTIGATING AND/OR DETERMINING THE CONDITION OR STATE OF A SHIP'S HULL

TECHNICAL FIELD

The present invention relates to a system and a method for investigating and/or determining the condition or the state of a ship's hull.

PRIOR ART

A certain time interval (for example, five years) is specified for ships and after this has elapsed, the ships must be docked for painting, inspection, repair, overhaul, maintenance of the like.

Such obligatory docking of ships after a fixedly predefined time interval has elapsed is associated with high costs for the ship owner. Precisely for such economic reasons, it is in the interest of the ship owner to extend these time intervals if possible, that is, to make them dependent on determining the state of the ship.

The possibility of docking depending on individual circumstances would also be desirable against the background that the waters to be navigated by ships exhibit variable degrees of hardness and pollution and are aggressive to different extents, and consequently affect the ships, in particular the ship's hulls, to different degrees of intensity so that a fixedly predefined painting, inspection, repair, overhaul or maintenance interval usually does not correspond with the actual condition or the actual state of a ship's hull.

DESCRIPTION OF THE PRESENT INVENTION: OBJECT, SOLUTION, ADVANTAGES

Starting from the disadvantages and inadequacies specified hereinbefore and acknowledging the outlined prior art, it is the object of the present invention to provide a system and a method of the type specified initially which allows the docking interval for ships to be selected, in particular to be extended, depending on the condition or the state of the ship's hull.

This object is achieved by a system having the features specified in claim 1 and by a method having the features specified in claim 14.

Advantageous embodiments and appropriate further developments of the present invention are characterised in the dependent claims.

In order to specify the time or the time interval after which a ship such as a cruise ship, a cargo ship or a tanker should be brought into dock for painting, inspection, repair, overhaul, maintenance or similar, the present invention provides a system and a method for the, in particular, automatic investigation, determination and/or measurement of the hull condition or the hull state by means of a floating/submersible investigating/ determining/measuring unit, in particular an underwater vehicle configured in the form of a floating measuring station.

The invention thus provides a system for investigating and/or for determining the condition or the state of a ship's hull, in particular its outer skin, where the system comprises a grid or network having a grid-square division or having individual units which cooperates functionally with at least one floating/submersible investigating/ determining measuring unit for investigating and/or determining the condition or the state of the outer skin of the ship's hull.

The grid or network is divided into individual units which are configured as surface configurations having the same shape, square, rectangular or another geometrical shape.

The units are provided with at least one ordering means or allocating means such as letters, numbers or letter/number combinations.

Furthermore, the grid or network with its individual units and ordering means or allocating means can be scanned, detected optically or detected electronically by means of the investigation/determination unit and converted into measured values.

According to a first embodiment, the outer skin of the ship's hull is provided with the grid or network. In this case, the subdivision of the outer skin can be implemented

- by painting or
- by locatable paint strips applied in particular under the paint of the outer skin.

A second embodiment provides that the grid or network is located in a measuring optical system of the investigating/determining/measuring unit.

A third embodiment provides that the grid or network is constructed visually between the ship's hull and the investigating/determining/measuring unit.

It is particularly advantageous if the grid or network is inserted into the measuring beam transmitted by the investigating/determining/measuring unit onto the ship's hull.

Alternatively to an embodiment as a manned and/or radio-controlled or manually controlled underwater vehicle, in particular a submersible or submarine, the investigation/determination unit can also be configured as a module that can be moved

- along the ship's hull to be investigated and/or
- at a distance, in particular uniformly at a distance, from the ship's hull to be investigated.

Regardless of the specific embodiment of the floating/submersible investigation/determination unit, according to the invention, a special ship skin configuration cooperates functionally, in particular electronically functionally, with the floating/submersible investigation/determination unit.

For the purpose of this cooperation, the investigation/determination unit is preferably provided with investigating/determining means for investigating and/or for determining, in particular for measuring, for example for the photo-optical, photographic or visual detection of the condition or the state, for example of the paint layer thickness and/or the roughness of the ship's hull, in particular the surface of the outer skin of the ship's hull.

These investigating/determining means or measuring devices are configured as

- at least one device for locating the individual units on the ship's hull and/or
- at least one device for scanning the surface of the outer skin in the individual units and/or
- at least one device for measuring the paint layer thickness on the outer skin and/or the roughness of the outer skin.

The invention further relates to a method for investigating and/or for determining the condition or the state of a ship's hull or its outer skin, in particular by means of at least one grid or network which is provided with a subdivision, wherein said subdivision cooperates functionally with at least one floating/submersible investigating/determining/measuring unit for investigating and/or determining the condition or the state of the ship's hull or its outer skin.

A further method for investigating and/or for determining the condition or the state of a ship's hull or its outer skin consists in that a visual grid or network having a grid-square subdivision or individual units provided with ordering means or allocating means in the form of letters, numbers or letter/number combinations, extending in sections or entirely over the outer wall of the ship, is constructed as a pictorial presentation and visualisation on the outer skin of the ship's hull and directed onto the outer skin by a floating/submersible investigating/determining/measuring unit which can navigate parallel to the ship to be checked, so that the individual subdivisions or units are assigned to corresponding areas or sections of the outer skin by which means the condition or the state of the ship's hull or its outer skin is checked by photo-optical, photographic or visual detection.

In addition, the method provides that measured values obtained by means of the investigating/determining/ measuring unit are evaluated and/or these measured values are used to calculate the time at which the ship should be brought into dock, in particular into a dry dock, for painting, inspection, repair, overhaul, maintenance or the like.

The present invention finally relates to the use of at least one floating/submersible investigation/determination unit, in particular at least one underwater vehicle, for example at least one submersible or submarine, for investigating and/or determining the condition or the state of the hull of a ship, for example, a cruise ship, a cargo vessel or a tanker, whose outer

skin, in particular by means of at least one optically visible or invisible grid or network, has a subdivision into units, for example having the same shape.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is explained in detail with reference to exemplary embodiments in the drawings. In the figures:

- Fig. 1 is a perspective partial cross-sectional view of a first exemplary embodiment for a system according to the present invention operating in accordance with the method according to the present invention comprising a fore portion of a ship whose outer skin is provided with a pattern having a framework in the form of plane squares, in a schematic view and comprising a floating/submersible underwater vehicle containing the measuring devices,
- Fig. 2 is a schematic side view of a second exemplary embodiment for a system according to the present invention operating in accordance with the method according to the present invention, comprising an investigation/determination unit which can be moved at a distance along the hull of a ship to be investigated, for example, a cruise ship, a cargo vessel or a tanker, wherein the ship's skin is provided with a pattern comprising a framework in the form of plane squares,
- Fig. 3 is a schematic view of a third exemplary embodiment for a system operating according to the method in accordance with the invention comprising a navigable investigating/determining /measuring unit, wherein the outer skin of a ship's hull is investigated using a visually constructed lattice-work in the form of grid squares.

BEST MODE FOR IMPLEMENTING THE PRESENT INVENTION

As can be deduced from the diagram according to Fig. 1 and according to Fig. 2, the outer skin 12 of this ship's hull 10 is divided into individual plane squares 16 to implement the system 100, 100' according to the invention for the automatic investigation and determination of the condition or the state of a ship's hull 10.

These plane squares 16 are formed by an optically detectable grid or network 14 applied to the ship's skin 12, for example by painting or by strips of paint applied underneath the paint of the ship's skin which can be located by means of a floating/submersible investigation/determination unit 20. It is also possible to apply a grid or network 14 which is not visible externally but can be located, on the side walls of the ship.

The plane square fields 16 can further be provided

- with scannable letters A, B, C, D. ... (see the first exemplary embodiment according to Fig. 1) and/or
- with scannable numbers 1, 2, 3, 4, ... (cf. second exemplary embodiment according to Fig. 2, in particular the enlarged circular diagram in Fig. 2)

as ordering or allocating means 18 in order to ensure an ordered, planned and successive investigation and determination of the condition or state of the ship's hull 10.

In the first exemplary embodiment according to Fig. 1, the second part of the system 100, that is the floating/submersible investigation/determination unit 20, consists of a radio-controlled or manually controlled manned underwater vehicle in the form of a submarine 20 or ship configured as a floating measuring station.

The submarine 20 is, for example, provided with investigation/determination means 22 based on radar and/or for example based on ultrasound, i.e.

- with devices for locating the individual plane squares 16 on the ship's hull 10,
- with devices for scanning the surface of the ships' hull 12 in the individual plane squares 16,
- with devices for measuring the layer thickness of the paint on the ship's skin 12

and similar in order to measure the condition of the state of the surface of the ship's skin 12.

The measured values obtained by means of the reflection (or at least partial reflection) of the detection/measurement beam 24 in the path to the ship's outer skin 12, based for example on radar or for example, on ultrasound are evaluated or these measured values are used to calculate the time at which the ship must come into dry dock for the purpose of painting, inspection, repair, overhaul, maintenance or the like.

The surface condition or the surface state of the ship's skin 12 can be detected visually; in particular the paint layer thickness on the outer skin 12 and the roughness of the outer skin 12 are detected. In this case, the measuring devices are configured so that the surface of the ship's skin 12 can be detected photographically, photo-optically and/or by means of electronic means.

Within the scope of the present invention, it is also feasible that the floating/submersible underwater vehicle 20 in the form of a floating measuring station starts out from a second ship and is received by this again after the

investigation of the ship's hull 10, for example, for paint layer thickness and/or for roughness has been completed.

The second exemplary embodiment of the system 100' illustrated by reference to Fig. 2 is fundamentally based on the same method principle as the first exemplary embodiment of the system 100 according to Fig. 1; however a floating/submersible investigation/determination unit 20' which can be moved along the ship's hull 10 to be investigated (<--> reference numeral DP) is used to detect the condition and the state of the ship's hull.

In this case, the investigation/determination unit 20' can be arranged, for example, on the rail of the ship to be investigated; in particular the investigation/determination unit 20' can be lowered by means of cables 28 on the outer side 12 of the ship's hull 10 and then pulled up again after the investigation has been completed; in particular, the investigation/determination unit 20' can be attached, for example to a mobile suspension device 26, possibly to a rod which can be moved along the ship's rail (<--> reference numeral DP).

In this way, the outer skin 12 of the ship's hull 10 to be investigated can be scanned successively, i.e. in accordance with the sequence 1, 2, 3, 4, .. of the ordering or allocating means 18, for paint layer thickness and roughness.

In a modification of the second exemplary embodiment according to Fig. 2 the investigation/determination unit 20' is not located on the ship to be investigated itself, but at a distance, in particularly uniformly at a distance from the rail of a second ship, in particular an investigating ship.

By moving the investigation/determination unit 20' along this second ship, it is possible to successively scan the outer skin 12 of the ship's hull 10 to be investigated for paint layer thickness and roughness.

A further embodiment of the system according to the invention is shown in Fig. 3. In this embodiment the outer skin 12 of the ship's hull does not have a visible or invisible grid or network in the form of a unit 16 configured as plane-square.

In order to be able to specify the time or the time interval of the docking time of a ship for painting, inspection, repair, overhaul or maintenance, the system provides a floating/submersible investigating/determining/ measuring unit in the form of a boat or submersible and a grid or network 14 which is arranged in a measuring optical system of the investigating/determining/measuring unit 20, 20' or is constructed visually between the ship's hull 10 and the unit 20, 20' (Fig. 3). Thus, the grid or network 14 can also be inserted into the measurement or observation beam transmitted by the unit 20, 20' onto the ship's hull 10. In this case, the size of the grid or network 14 can cover the entire outer skin 12 of the ship's hull 10 but also only sections of the outer skin so that, due to the grid or network 12 co-migrating therefrom as the unit 20, 20' moves parallel to the ship's hull 10, one section after the other of the outer skin can be detected and this can be checked so that by adding the measured section of the ship's hull, a complete monitoring image of the ship's hull or its outer skin 12 is obtained. In this embodiment the grid or network 14 is divided into individual units 16 forming plane squares which are provided with an ordering or allocating means 18 such as letters, numbers or combinations formed of letters and numbers. The use of a visually inserted grid or network 14 or the handling of a visual grid or network 14 has the advantage that the grid or network need not be applied to the outer skin 12 of the ship's hull 10 but can be used in conjunction with the investigating or determining means. Thus, the grid or network can be used, for example, in conjunction with measuring beams or in observation optics.

REFERENCE LIST

- 100 System
100' System
- 10 Ship's hull
12 Outer skin or ship's skin of the ship's hull 10
14 Visible or invisible grid or network on the outer skin of the ship's hull
10
16 Unit formed by grid or network 14, for example, plane square (field)
or plane rectangular (field) on outer skin of the ship's hull 10
18 Ordering or allocating means, for example, scannable letter and/or
scannable number
- 20 Floating/submersible investigation/determination unit, in particular
underwater vehicle
20' Floating/submersible investigation/determination unit,
22 Investigating/determining means of the investigation/determination
unit 20, 20', for example based on radar and/or for example based
on ultrasound
24 Detection/measuring beam of the investigating/ determining means
22
26 Mobile suspension device, in particular movable rod
28 Cable of suspension device 26
- DP Double arrow

CLAIMS

1. A system (100; 100') for investigating and/or determining the condition or the state of a ship's hull (10), in particular its outer skin (12), by means of at least one grid or network (14), which has a subdivision which cooperates functionally with at least one floating/submersible investigating/ determining/measuring unit (20, 20') for investigating and/or for determining the condition or the state of the ship's hull (10).
2. The system (100; 100') for investigating and/or determining the condition or the state of a ship's hull (10), in particular its outer skin (12), according to claim 1, wherein the system comprises a grid or network (14) having a grid-square subdivision (16') or having individual units (16), which cooperates functionally with at least one floating/submersible investigating/determining/ measuring unit (20, 20') for investigating and/or for determining the condition or the state of the outer skin (12) of the ship's hull (10).
3. The system according to claim 1 or 2, characterised in that the grid or network (14) is divided into individual units (16) which are configured as surface configurations, in particular having the same shape, square, rectangular or another geometrical shape.
4. The system according to one of the preceding claims 1 to 3, characterised in that the units (16) are provided with at least one ordering means or allocating means (18) such as letters, numbers or letter/number combinations.

5. The system according to one of the preceding claims 1 to 4, characterised in
that the grid or network (14) with its individual units (16) and ordering means or allocating means (18) can be scanned, detected optically or detected electronically by means of the investigation/determination unit (20; 20') and converted into measured values.
6. The system according to one of the preceding claims 1 to 5, characterised in
that the outer skin (12) of the ship's hull (10) is provided with the grid or network (14).
7. The system according to claim 6, characterised in
that the subdivision of the outer skin (12) is implemented
 - by painting or
 - by locatable paint strips applied in particular under the paint of the outer skin (12).
8. The system according to one of the preceding claims 1 to 4, characterised in
that the grid or network (14) is located in a measuring optical system of the investigating/determining/measuring unit (20, 20').
9. The system according to one of the preceding claims 1 to 5, characterised in
that the grid or network (14) is constructed visually between the ship's hull (10) and the investigating/determining/measuring unit (20; 20').

10. The system according to claim 9,
characterised in
that the grid or network (14) is inserted into a measuring beam
transmitted by the investigating/determining/ measuring unit (20;
20') onto the ship's hull (10).
11. The system according to at least one of claims 1 to 10,
characterised in
that the investigation/determination/measuring unit (20 or 20') is
 - configured as a manned and/or radio-controlled or manually
controlled underwater vehicle, in particular a submersible or
submarine or
 - can be moved along the ship's hull (10) to be investigated
and/or at a distance, in particular uniformly at a distance,
from the ship's hull (10) to be investigated.
12. The system according to at least one of claims 1 to 11,
characterised in
that the investigating/determining/measuring unit (20; 20') is pro-
vided with investigating/determining means (22) or measuring de-
vices for investigation and/or for determining, in particular for meas-
uring, for example for the photo-optical, photographic or visual de-
tection of the condition or the state, for example of the paint layer
thickness and/or the roughness of the ship's hull (10), in particular
the surface of the outer skin (12) of the ship's hull (10).
13. The system according to claim 12,
characterised in
that the investigating/determining means (22) or measuring devices
are configured

- as at least one device for locating the individual units (16) on the ship's hull and/or
 - as at least one device for scanning the surface of the outer skin (12) in the individual units (16) and/or
 - as at least one device for measuring the paint layer thickness on the outer skin (12) and/or the roughness of the outer skin (12).
14. A method for investigating and/or determining the condition or the state of a ship's hull (10) or its outer skin (12), in particular by means of at least one grid or network (14) which is provided with a subdivision, wherein said subdivision cooperates functionally with at least floating/submersible investigating/determining/measuring unit (20, 20') for investigation and/or for determining the condition or the state of the ship's hull (10) or its outer skin (12).
15. A method for investigating and/or determining the condition or the state of a ship's hull (10) or its outer skin (12), characterised in that a visual grid or network (14) having a grid-square subdivision (16') or individual units (16) provided with ordering means or allocating means (18) in the form of letters, numbers or letter/number combinations, extending in sections or entirely over the outer wall of the ship, is constructed as a pictorial presentation and visualisation on the outer skin (12) of the ship's hull (10) and directed onto the outer edge (12) by a floating/submersible investigating/determining/measuring unit (20, 20') which can navigate parallel to the ship to be checked, so that the individual subdivisions (16') or units (16) are assigned to corresponding areas or sections of the outer skin (12) by which means the condition or the state of the ship's hull (10) or its outer skin (12) is checked by photo-optical, photographic or visual detection.

16. The method according to one of claims 14 or 15, characterised in that measured values obtained by means of the investigating/determining/measuring unit (20; 20') are evaluated and/or these measured values are used to calculate the time at which the ship should be brought into dock, in particular into a dry dock, for the purpose of painting, inspection, repair, overhaul, maintenance of the like.
17. Use of at least one floating/submersible investigating/determining/measuring unit (20; 20') for investigating and/or determining the condition or the state of a ship's hull (10) or its outer skin (12), in particular by means of a grid or network (14) provided with a subdivision into units (16), for example having the same shape, having ordering means or allocating means (18) in the form of letters, numbers or letter/number combinations.