



- (51) International Patent Classification: Not classified
- (21) International Application Number:
PCT/US2013/044288
- (22) International Filing Date:
5 June 2013 (05.06.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/656,144 6 June 2012 (06.06.2012) US
- (71) Applicant: FIRESTONE POLYMERS, LLC [US/US];
381 West Wilbeth Road, Akron, Ohio 44301 (US).
- (72) Inventors: NAKATANI, Kenji; 10-1, Kyobashi 1-Chome,
Chuo-Ku, Tokyo 104-8340 (JP). DEDECKER, Mark N.;
8775 Leyland Avenue NW, North Canton, Ohio 44720
(US). PADOLEWSKI, Joseph P.; 165 Hunt Club Drive,
Apt. 3C, Copley, Ohio 44321 (US). PAWLOW, James
H.; 1984 Braewick Drive, Akron, Ohio 44313 (US).
- (74) Agents: HOOKER, Meredith E et al.; 10 East Firestone
Blvd., Akron, Ohio 44317 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: METHOD OF MAKING POLYMERS, POLYMER COMPOSITIONS AND ARTICLES CONTAINING SUCH POLYMERS

FIG.1



(57) Abstract: A method of making a polymer with stable Mooney viscosity and molecular weight is described. A conjugated diolefin is reacted in a hydrocarbon solvent in the presence of an initiator to form a polymer. After forming the polymer, alkoxy silane terminal functionalizing groups are bonded to the polymer. A stabilizing agent having the formula $(R)_{4-n}Si(OH)_n$ wherein R is a C_1 to C_{18} alkyl, C_1 to C_{18} alkyl group containing a heteroatom such as nitrogen or oxygen, C_4 to C_8 cycloalkyl, or C_6 to C_{18} aromatic group is then added to the polymer, optionally in the presence of hydrocarbon oil. The polymer is then desolvating, resulting in a polymer with stable Mooney viscosity and molecular weight, even over prolonged periods of time. Compositions and articles containing the polymer are also described.