



(51) International Patent Classification:
E21B 23/03 (2006.01)

(21) International Application Number:
PCT/NO2010/000450

(22) International Filing Date:
7 December 2010 (07.12.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2009 3485 7 December 2009 (07.12.2009) NO

(71) Applicant (for all designated States except US):
PETROLEUM TECHNOLOGY COMPANY AS [NO/
NO]; Slettestrandveien 13, N-4032 Stavanger (NO).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KLEPPA, Erling**
[NO/NO]; Klovsteinsveien 17, N-4100 Jørpeland (NO).
PETTERSEN, Ståle [NO/NO]; Skaret 3, N-4326
Sandnes (NO).

(74) Agents: **ONSAGERS AS** et al.; P.O.Box 6963 St. Olavs
plass, N-0130 Oslo (NO).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))

(88) Date of publication of the international search report:
1 March 2012

(54) Title: KICK-OVER TOOL

Fig.1.



(57) Abstract: The present invention relates to a kick over tool (5) for manipulating and installing devices into and removing devices from a side pocket mandrel (2), where the kick over tool is designed to enable multiple operations in the same run. The kick over tool comprises a tubular carrier housing (6) adapted for passage through a full opening bore of a production string, at least a first and second setting device (8,9) that is arranged in said carrier housing, the first and second setting device being pivotally connected to a first and second articulated linkage mechanism (12,13) comprising a coupling device for the well bore device.

