

Description

The present invention relates to a solar ray collecting device in accordance with the generic use of claim 1.

The present applicant has previously proposed various kinds of solar ray collecting devices in which solar rays are focused by a lens or the like and guided into an optical conductor cable and further those solar rays are transmitted through the optical conductor cable onto an optional desired place for use in illumination or for other purposes.

Among the solar ray collecting devices proposed by the present applicant, there is one (EP-A-0050189) in which a large number of lenses, (for example, about 2000 lenses) having a diameter equal to or less than about 4 cm, are employed for focusing solar rays. The light-receiving edge of the optical fiber, having a diameter of about 0.1 mm through 0.2 mm, is precisely positioned at the focal point of each of the respective lenses so as to guide the solar rays, focused by each lens, into the optical fiber. Concerning this solar ray collecting device just described, the focal distance is equal to or less than about 4 cm. Therefore it is possible to manufacture a very thin solar ray collecting device.

On the other hand however, the focal position of the lens has to precisely coincide with the light-receiving edge surface of the optical fiber. In the case of using the device in a desert where the ambient temperature varies to a large extent in space, or in a tropical area, the lens and supporting member thermally expand so that the positional relationship between the focus of the lens and the light-receiving edge surface of the optical fiber varies greatly. In such a case it is also possible that the lens and the optical fiber or the like will be destroyed by the extreme heat generated.

In order to settle such a problem as mentioned above, the present applicant has already proposed in the postpublished (EP-A-0128395) a solar ray collecting device which is comprised of a supporting base plate on which a large number of hexagonal recesses are provided and on which a respective optical systems is arranged on each of the recesses, each of the optical systems is comprised of a hexagonal focusing lens of a dimension that is approximately the same as that of the hexagonal recesses and the truncated hexagonal pyramid which extends downward from the light-collecting lens as an upper surface of the recess, an optical conductor whose light-receiving surface is provided on the focus of the light-collecting lens, and the upper internal circumferential surface of the side wall, forming the recess, is so formed that it may be able to move freely on the surface of the hexagonal pyramid.

However the above-mentioned solar ray collecting device was created without taking into account the existence of X-rays, γ-rays and ultra-

violet rays in space, and furthermore without taking into account the special situation related to the effects of thermal energy in space, i.e. the fact that heat generated by radiation is present. For these reasons, the conventional solar ray collecting device was not satisfactory for using it in space.

It is therefore the object of the present invention to provide a solar ray collecting device for use in space, which would effectively absorb the heat expansion of the lens and its supporting member thus preventing them from being destroyed by extreme heat, and which would enable the focus position of each lens to always coincide with the light-receiving edge surface of the optical fiber.

The device as specified in claim 1 solves this object.

Preferred embodiments are disclosed in the depending claims.

The features and advantages of the present invention will become apparent from the following detailed description which goes with the accompanying drawings.

Brief description of the drawings

Fig. 1 is a plane view partly enlarged for explaining an embodiment of the solar ray collecting device previously proposed by the present applicant.

Fig. 2 is a cross-section view of Fig. 1.

Fig. 3 is a cross-sectional view of the main body for explaining an embodiment of the solar ray collecting device according to the present invention.

Fig. 4 is an outlined, cross-sectional view showing the construction of one unit of the solar ray collecting device according to the present invention.

Fig. 5 is a partial view of a combination of lenses constructed by combining several units of the solar ray collecting device according to the present invention.

In order to settle such problems as mentioned above, the present applicant has already proposed a solar ray collecting device as shown in Fig. 1. (Refer to European Patent Application, EP-A-0128395).

In Fig. 2, 10 is an optical system and 20 is a supporting member for supporting it. In practice, a large number of optical systems (for instance, about 60 of them) as shown in Fig. 1 are arranged on the supporting member 20.

Each of the respective optical systems 10, basically consists of a hexagonal lens 11 having a diameter of about 4 cm or less, a truncated hexagonal pyramid 12 on which the lens 11 is mounted, and an optical fiber 13, the light-receiving edge surface of which is precisely positioned at the focus of the lens 11. Solar rays focused by the lens 11 are guided into the optical fiber 13.

A large number of hexagonal recess portions 21 for accommodating the optical systems 10 are formed on the supporting member 20. The upper portion of a side wall 22 forming the recess portion 21 has an inclined surface 23, the inclina-

tion of which is equal to that of the pyramidal surface of the hexagonal pyramid 12.

Consequently, when the lens and the supporting member expand thermally the hexagonal pyramid 12 of the optical system 10 moves upward in a direction A shown by an arrow sliding along the inclined surface 23, and when the lens and the supporting member contract from cooling, the pyramid 12 moves downward in a direction B shown by an arrow and sliding along the same inclined surface because the expansion rate of the lens and the hexagonal pyramid is, in general, larger than that of the other parts. On that occasion, the focal position of the lens 11 scarcely changes and therefore the solar rays are always effectively guided into the optical fiber 13.

Moreover, on that occasion, if the lens expands to a large extent the respective lenses coming into closer contact with each other are apt to collide against each other and to be destroyed. In order to avoid such a problem, a protection bar 24 is set up at each vertex of the side wall's 22 upper surface, i.e. at a location where the respective lenses are apt to be destroyed. Furthermore, the vertex of each lens is provided with a spacing area 11a. In such a manner, destruction of the respective lenses due to mutual collision can be prevented.

As is apparent, in general, there exists no indirect solar rays in space. Direct solar rays are focused by the lens 11 and guided into the optical fiber 13. Consequently, if all of the direct solar rays can be put into the optical fiber, there is no need to worry about the overheating of the supporting base plate.

In practice, however it may be impossible to put all of the rays into the optical fiber and therefore in such a case the supporting base plate would be overheated by the rays that are not guided into the optical fiber. Even if such rays, not guided into it, are utilized in some way, it may turn out to be possible to suppress thermal expansion of the optical system to some extent.

Consequently a transparent material which hardens in high ambient temperatures, for example an acrylic material, is employed as a hexagonal pyramid 12 and on its external circumferential surface aluminum is evaporated in order to form a light-reflecting layer 14 there.

Moreover, a solar battery 15 is installed on the bottom surface portion of the hexagonal pyramid 12 and an optical reaction is caused by the use of optical energy so as to circulate an inductive material 16 for storing energy. In such a manner, the solar rays guided into the hexagonal pyramid 12 are effectively reflected off from the aluminum surface 14 and further those rays are guided onto the bottom surface of the hexagonal pyramid. In the area, the light energy is converted to electrical energy, or otherwise it is stored in the inductive material.

On that occasion, if a fluorescent material is mixed with other materials in the transparent acrylic hexagonal pyramid, it may be possible to convert the rays entering the hexagonal pyramid

to light energy having a wave length capable of most easily reacting to the solar battery or the inductive material therein. Furthermore, the internal circumferential surface of the hexagonal pyramid can be coated with aluminum for forming a reflecting surface therein. In such a manner, since the light rays entering the hexagonal pyramid are reflected and are discharged outside, the rise in temperature of the entire solar ray collecting device can be controlled to some extent.

However, the above-mentioned solar ray collecting device was made without taking into consideration any countermeasures against the existence of other than visible rays (X-rays, γ-rays and ultraviolet rays) in space and furthermore without considering the effects of thermal energy i.e. the fact that the heat caused by radiation is extensive. For these reasons, the conventional solar ray collecting device was not a satisfactory one, especially in the case of using it in space.

Fig. 3 is a partially enlarged cross-sectional view for explaining the construction of an embodiment of the solar ray collecting device according to the present invention. Fig. 4 is a side cross-sectional view showing one unit of the solar ray collecting device according to the present invention. Fig. 5 is a partially outlined, perspective view of a combination of lenses constructed by combining several units of the solar ray collecting device according to the present invention. In Fig. 3, the same reference numeral as in Fig. 2 is attached to the part performing the same function as in Fig. 2.

In the present invention a transparent optically-stable protection cover 30, for instance, a cover 30, made of quartz glass and having the characteristics of being flat, and of not being susceptible to heat distortion, is installed at the light-receiving side of the lens 11. The protective cover 30 is mixed with a filter material capable of weakening X-rays, γ-rays and ultraviolet rays and of letting essentially visible rays pass through. Such a construction prevents some X-rays, γ-rays and ultraviolet rays which exist in space from passing through the optical fiber. Therefore, mainly visible rays are transmitted into the optical fiber 13.

In such a manner, the rays guided into the respective optical fibers 13 are collectively guided into the optical conductor cable 40, and further guided into the space-craft through the optical conductor cable 40.

The present applicant has already proposed a lens coated with an evaporated metal layer 31 for the purpose of obtaining such a filtering effect as already mentioned above. (Refer to the Japanese Patent Application, JP—A—58-22573). Ultraviolet rays or infrared rays can be prevented from passing through the optical system by coating the lens with an evaporated metal layer.

However, when X-rays and ultraviolet rays are prevented from passing through the optical system in such a manner, heat is generated therein as a matter of course. Consequently, the



protective cover and the optical system expand thermally so that they are apt to be destroyed by the heat generated. Furthermore, in space, the temperature difference between the side hit by solar rays and the opposite side is very great and therefore the optical system and other portions thereof may be apt to be destroyed because of the temperature differences.

The present invention was created in order to solve such problems. The protection bar 24 and the supporting member 20 are heat-conductive members, and the tip end portion of the protection bar 24 is connected with the protective cover 30 which has a high heat-conductive efficiency. The heat energy received by the protective cover 30 is transmitted to the rear side of the supporting base plate 20 through the protection bar 24 and the side wall 22 of the supporting member 20, etc.

In such a manner, the heat energy received by the protective cover 30 is transmitted at once to the rear side of the supporting base plate 20 so that the protective cover and the lens, at the light-receiving side are not distorted by the heat generated. In space, the temperature difference between the place hit by the solar rays and the place not hit by them is very great and the property of matter changes in accordance with the temperature differences resulting in the destruction of the components on some occasions. The optical conductor cables are distributed in order to connect them over a comparatively long distance. Consequently, places hit by solar rays and other places not hit by them exist inbetween. The former becomes hot while the latter becomes cold. At such a place as mentioned above, the optical conductor cable is apt to be destroyed because of the temperature differences.

In Fig. 4, 50 is a protective member for covering the side portion and the rear portion of the solar ray collecting unit as mentioned before and 60 is a protective member for covering the optical conductor cable 40. Heat-conductive members 51 and 61, for instance, members like heat pipes, are buried in those protective members. By use of those heat pipes, heat is transmitted at once to the cold place so as to make the temperatures uniform. Extreme temperature differences can thus be prevented.

The embodiment employing the hexagonal pyramid is described heretofore. However, the present invention is not limited only to the embodiment. For instance, the side surface of the supporting member's recessed portion doesn't always have to be in the shape of a hexagonal pyramid. Instead, it may be in the shape of a circular cone.

As is apparent from the foregoing description, according to the present invention it is possible to provide a solar ray collecting device in which the optical system is not destroyed because of thermal expansion and temperature differences and furthermore mainly visible rays can be collected, reducing the reception of harmful rays like ultraviolet rays and X-rays, in space.

Claims

1. A solar ray collecting device comprising a supporting base plate (20) having a large number of hexagonal recesses (21) formed therein, and a large number of optical systems (10) arranged thereon, with one optical system (11) associated to each of said recesses, which optical system comprising a hexagonal focusing lens having a dimension which is approximately equal to the dimension of the associated recess, and an optical conductor (13) having a light-receiving surface which is provided at the focus of the focusing lens characterized by each of the recesses (21) being provided with an inverse truncated pyramid (12), said pyramid facing the base plate at the smaller end thereof, while the outer surface of top end thereof is in sliding engagement with a side wall (23) of the related recess (21), the lens being carried on its outer circumferences by the inverse truncated pyramid at the open top end thereof, and a large number of heat conductive protective bars (24) extending upwardly from the side walls of the recesses and by a protective cover (30, 31) for covering the light-receiving surface side of that supporting base plate (20) and having the function of a filter capable of weakening other than visible rays, said protective bars (24) being in heat conductive contact with said protective cover (30, 31).

2. A solar ray conducting device as defined in claim 1 characterized in that said device comprises a protective frame member (50) for covering the side portion and the rear portion of the supporting base plate (20), said frame member comprising a heat conductive member (51) embedded into said frame member and extending from the light-receiving surface side to its rear surface.

3. A solar ray collecting device as defined in claim 1 or 2, characterized in that the optical conductors are collectively formed into an optical conductor cable (40), the external side of said optical conductor cable being coated with a protective member (60, 61) having a heat conductive member (61).

Patentansprüche

1. Sonnenkollektorstück mit einer Träger-sockelplatte (20), die eine große Anzahl von darin ausgebildeten hexagonalen Vertiefungen (21) und eine große Anzahl von darauf angeordneten optischen Systemen (10) aufweist, wobei jeweils ein optisches System (11) einer Vertiefung zugeordnet ist, wobei das optische System eine hexagonale fokussierende Linse umfaßt, deren Abmessung im wesentlichen der Abmessung der zugeordneten Vertiefung entspricht, und mit einem optischen Leiter (13), der eine Lichtempfangsfläche hat, die im Fokus der fokussierenden Linse angeordnet ist, dadurch gekennzeichnet, daß jede Vertiefung (21) mit einem umgekehrten Pyramidenstumpf (12) versehen ist, wobei das schmale Ende der Pyramide auf die Sockelplatte weist,

protective cover and the optical system expand thermally so that they are apt to be destroyed by the heat generated. Furthermore, in space, the temperature difference between the side hit by solar rays and the opposite side is very great and therefore the optical system and other portions thereof may be apt to be destroyed because of the temperature differences.

The present invention was created in order to solve such problems. The protection bar 24 and the supporting member 20 are heat-conductive members, and the tip end portion of the protection bar 24 is connected with the protective cover 30 which has a high heat-conductive efficiency. The heat energy received by the protective cover 30 is transmitted to the rear side of the supporting base plate 20 through the protection bar 24 and the side wall 22 of the supporting member 20, etc.

In such a manner, the heat energy received by the protective cover 30 is transmitted at once to the rear side of the supporting base plate 20 so that the protective cover and the lens, at the light-receiving side are not distorted by the heat generated. In space, the temperature difference between the place hit by the solar rays and the place not hit by them is very great and the property of matter changes in accordance with the temperature differences resulting in the destruction of the components on some occasions. The optical conductor cables are distributed in order to connect them over a comparatively long distance. Consequently, places hit by solar rays and other places not hit by them exist inbetween. The former becomes hot while the latter becomes cold. At such a place as mentioned above, the optical conductor cable is apt to be destroyed because of the temperature differences.

In Fig. 4, 50 is a protective member for covering the side portion and the rear portion of the solar ray collecting unit as mentioned before and 60 is a protective member for covering the optical conductor cable 40. Heat-conductive members 51 and 61, for instance, members like heat pipes, are buried in those protective members. By use of those heat pipes, heat is transmitted at once to the cold place so as to make the temperatures uniform. Extreme temperature differences can thus be prevented.

The embodiment employing the hexagonal pyramid is described heretofore. However, the present invention is not limited only to the embodiment. For instance, the side surface of the supporting member's recessed portion doesn't always have to be in the shape of a hexagonal pyramid. Instead, it may be in the shape of a circular cone.

As is apparent from the foregoing description, according to the present invention it is possible to provide a solar ray collecting device in which the optical system is not destroyed because of thermal expansion and temperature differences and furthermore mainly visible rays can be collected, reducing the reception of harmful rays like ultraviolet rays and X-rays, in space.

Claims

1. A solar ray collecting device comprising a supporting base plate (20) having a large number of hexagonal recesses (21) formed therein, and a large number of optical systems (10) arranged thereon, with one optical system (11) associated to each of said recesses, which optical system comprising a hexagonal focusing lens having a dimension which is approximately equal to the dimension of the associated recess, and an optical conductor (13) having a light-receiving surface which is provided at the focus of the focusing lens characterized by each of the recesses (21) being provided with an inverse truncated pyramid (12), said pyramid facing the base plate at the smaller end thereof, while the outer surface of top end thereof is in sliding engagement with a side wall (23) of the related recess (21), the lens being carried on its outer circumferences by the inverse truncated pyramid at the open top end thereof, and a large number of heat conductive protective bars (24) extending upwardly from the side walls of the recesses and by a protective cover (30, 31) for covering the light-receiving surface side of that supporting base plate (20) and having the function of a filter capable of weakening other than visible rays, said protective bars (24) being in heat conductive contact with said protective cover (30, 31).

2. A solar ray conducting device as defined in claim 1 characterized in that said device comprises a protective frame member (50) for covering the side portion and the rear portion of the supporting base plate (20), said frame member comprising a heat conductive member (51) embedded into said frame member and extending from the light-receiving surface side to its rear surface.

3. A solar ray collecting device as defined in claim 1 or 2, characterized in that the optical conductors are collectively formed into an optical conductor cable (40), the external side of said optical conductor cable being coated with a protective member (60, 61) having a heat conductive member (61).

Patentansprüche

1. Sonnenkollektorstück mit einer Träger-sockelplatte (20), die eine große Anzahl von darin ausgebildeten hexagonalen Vertiefungen (21) und eine große Anzahl von darauf angeordneten optischen Systemen (10) aufweist, wobei jeweils ein optisches System (11) einer Vertiefung zugeordnet ist, wobei das optische System eine hexagonale fokussierende Linse umfaßt, deren Abmessung im wesentlichen der Abmessung der zugeordneten Vertiefung entspricht, und mit einem optischen Leiter (13), der eine Lichtempfangsfläche hat, die im Fokus der fokussierenden Linse angeordnet ist, dadurch gekennzeichnet, daß jede Vertiefung (21) mit einem umgekehrten Pyramidenstumpf (12) versehen ist, wobei das schmale Ende der Pyramide auf die Sockelplatte weist,



während die äußere Fläche am oberen Ende in Gleiteingriff mit einer Seitenwand (23) der zugeordneten Vertiefung (21) steht, und wobei die Linse an ihrem Außenumfang von dem umgekehrten Pyramidenstumpf an dessen oberem Ende gehalten wird, und mit einer großen Anzahl von wärmeleitenden Schutzarmen (24), die sich nach oben von den Seitenwänden der Vertiefungen erstrecken, und durch eine Schutzabdeckung (30, 31), die die Lichtempfangsflächen der Trägersockelplatte (20) abdeckt, und die als Filter dient, das nicht sichtbare Strahlung schwächt, wobei die Schutzarme (24) in wärmeleitendem Kontakt mit der Schutzabdeckung (30, 31) stehen.

2. Sonnenkollekturvorrichtung nach Anspruch 1, dadurch gekennzeichnet, daß die Vorrichtung einen Schutzrahmen (50) umfaßt, der die Seitenbereiche und den rückwärtigen Bereich der Trägersockelplatte (20) abdeckt, wobei der Rahmen ein wärmeleitendes Element (51) aufweist, das in den Rahmen eingebettet ist, und das sich von der lichtempfangenden Oberfläche zu dessen Rückseite erstreckt.

3. Sonnenkollekturvorrichtung nach Anspruch 1 oder 2, dadurch gekennzeichnet, daß die optischen Leiter gemeinsam zu einem optischen Leiterkabel (40) zusammengefaßt sind, und daß die Außenseite des optischen Leiterkabels mit einem Schutzelement (60, 61) abgedeckt ist, das ein wärmeleitendes Element (61) aufweist.

Revendications

1. Un dispositif collecteur de rayons solaires comprenant une plaque de base portante (20) comportant un grand nombre d'évidements hexagonaux (21) formés dans celle-ci et un grand nombre de systèmes optiques (10) disposés sur celle-ci, avec un système optique (11) associé à chacun des évidements, ledit système optique comprenant une lentille hexagonale de concentration ayant une dimension qui est approximati-

vement égale à la dimension de l'évidement associé, et un conducteur optique (13) comportant une surface réceptrice de lumière qui est placée au foyer de la lentille de concentration, caractérisé en ce que chacun des évidements (21) est pourvu d'une pyramide tronquée inverse (12), ladite pyramide étant dirigée vers la plaque de base par sa petite extrémité tandis que la surface extérieure de son extrémité supérieure est en contact glissant avec une paroi latérale (23) de l'évidement associé (21), la lentille étant supportée sur ses circonférences extérieures par la pyramide tronquée inverse à son extrémité supérieure ouverte, et un grand nombre de barres de protection et de conduction de chaleur (24) s'étendent vers le haut à partir des parois latérales des évidements et il est prévu un couvercle protecteur (30, 31) pour recouvrir le côté superficiel de réception de lumière de ladite plaque de base portante (20), en remplissant la fonction d'un filtre capable d'affaiblir des rayons autres que des rayons visibles, lesdites barres de protection (24) étant en contact de conduction de chaleur avec ledit couvercle protecteur (30, 31).

2. Un dispositif collecteur de rayons solaires tel que défini dans la revendication 1, caractérisé en ce que ledit dispositif comprend un élément structural de protection (50) servant à recouvrir la partie latérale et la partie arrière de la plaque de base portante (20), ledit élément structural comprenant un élément conducteur de chaleur (51) noyé dans ledit élément structural et s'étendant depuis le côté superficiel de réception de lumière jusqu'à sa surface arrière.

3. Un dispositif collecteur de rayons solaires tel que défini dans la revendication 1 ou 2, caractérisé en ce que les conducteurs optiques sont collectivement agencés sous la forme d'un câble conducteur optique (40), le côté extérieur dudit câble conducteur optique étant revêtu d'un élément protecteur (60, 61) comportant un élément conducteur de chaleur (61).

