

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 3/22, B31B 45/00		A1	(11) International Publication Number: WO 99/11526
			(43) International Publication Date: 11 March 1999 (11.03.99)
(21) International Application Number: PCT/JP98/03814			
(22) International Filing Date: 27 August 1998 (27.08.98)			
(30) Priority Data:			
9/245966 ✓	28 August 1997 (28.08.97)	JP	
10/11999 ✓	7 January 1998 (07.01.98)	JP	
10/109804 ✓	20 April 1998 (20.04.98)	JP	
10/126491 ✓	8 May 1998 (08.05.98)	JP	
10/126492 ✓	8 May 1998 (08.05.98)	JP	
10/126493 ✓	8 May 1998 (08.05.98)	JP	
(71) Applicant (for all designated States except US): DAI NIPPON PRINTING CO., LTD. [JP/JP]; 1-1, Ichigaya-kagacho 1-chome, Shinjuku-ku, Tokyo 162-0062 (JP).		(74) Agents: ISHIKAWA, Yasuo et al.; Park Shiba Building, 4F, 17-11, Shiba 2-chome, Minato-ku, Tokyo 105-0014 (JP).	
(72) Inventors; and		(81) Designated States: BR, CA, CN, FI, KR, MX, NO, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(75) Inventors/Applicants (for US only): OKUSHITA, Masataka [JP/JP]; Dai Nippon Printing Co., Ltd., 1-1, Ichigaya-kagacho 1-chome, Shinjuku-ku, Tokyo 162-0062 (JP). YAMADA, Kazuki [JP/JP]; Dai Nippon Printing Co., Ltd., 1-1, Ichigaya-kagacho 1-chome, Shinjuku-ku, Tokyo 162-0062 (JP). HIRAI, Yuichi [JP/JP]; Dai Nippon Printing Co., Ltd., 1-1, Ichigaya-kagacho 1-chome, Shinjuku-ku, Tokyo 162-0062 (JP). MOCHIZUKI, Yoichi [JP/JP]; Dai Nippon Printing Co., Ltd., 1-1, Ichigaya-kagacho		Published <i>With international search report.</i>	

(54) Title: **HEAT-INSULATING CONTAINER AND APPARATUS FOR PRODUCING THE SAME**

(57) Abstract

A heat-insulating container (1) is used for an instant dried food and is excellent in heat-insulating property, design and economy. The container comprises a paper cup body (2) with a bottom (2b), which has an inner surface coated with a polyolefin resin and is provided with an outward curled portion (2c) formed at an upper opening end of the cup body and at least one horizontal rib (2d) formed on a side wall of the cup body so as to project outward therefrom; and an inverse-frustoconical paper sleeve (3) provided with an inward curled portion (3a) formed at a lower end of the sleeve. The cup body and the sleeve are integrally combined with each other so that an upper need of the sleeve is joined to an outer periphery of the side wall of the cup body, which is adjacent to the outward curled portion of the cup body, and an inner surface of the inward curled portion of the sleeve is joined to an outer periphery of a lower portion of the side wall of the cup body.

