



(51) International Patent Classification:

H04L 1/18 (2006.01) *H04W 72/14* (2009.01)
H04L 5/00 (2006.01)

(21) International Application Number:

PCT/SE2011/050929

(22) International Filing Date:

8 July 2011 (08.07.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/389,437 4 October 2010 (04.10.2010) US

(71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ABRAHAMSSON, Richard** [SE/SE]; Åsgatan 45, SE-741 45 Knivsta (SE). **BOSTRÖM, Lisa** [SE/SE]; Slottsvägen 10, SE-169 69 Solna (SE). **LINDSTRÖM, Magnus** [SE/SE]; Turebergs allé 18, Lgh 1101, SE-191 64 Sollentuna (SE). **JÖNGREN, George** [SE/SE]; Karlaviksgatan 15, SE-112 41 Stockholm (SE).

(74) Agent: HASSELGREN, Joakim; Ericsson AB, Patent Unit LTE, Torshamnsgatan 23, S-164 80 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

(54) Title: METHODS AND ARRANGEMENTS IN A TELECOMMUNICATION SYSTEM




Fig. 1a

(57) Abstract: The present invention relates to a method and arrangement for controlling re-transmission in a user equipment supporting uplink spatial multiplexing. The method comprises the steps of - detecting an uplink grant on a physical downlink control channel (102), the uplink grant being valid for at least one transport block; - detecting that at least one transport block is disabled (103), such that no grant is associated with the at least one transport block; and - interpreting (106) the at least one disabled transport block as an acknowledgement, ACK, of previous transmission corresponding to said disabled transport block irrespective of which indication is received on the reception status feedback channel for said previous transmission.