



(51) International Patent Classification:
E21B 21/08 (2006.01)

(21) International Application Number:
PCT/EP2010/063579

(22) International Filing Date:
15 September 2010 (15.09.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/242,772 15 September 2009 (15.09.2009) US

(71) Applicant (for all designated States except US): **MAN-AGED PRESSURE OPERATIONS PTE. LTD** [SG/SG]; 18th Floor, Thong Sia Building, 30 Bideford Road, 229922 (SG).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LEUCHTENBERG, Christian** [DE/BE]; 15 Windmolenberg, B-1200 Brussels (BE).

(74) Agent: **LAWSON, Alison**; Forresters, Chamberlain House, Paradise Place, Birmingham B3 3HP (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: METHOD OF DRILLING A SUBTERRANEAN BOREHOLE




FIG 1

(57) Abstract: A method of drilling a subterranean well bore using a tubular drill string, the method including the steps of injecting a drilling fluid into the well bore via the drill string and removing said drilling fluid from an annular space in the well bore around the drill string via a return line, wherein the method further includes oscillating the pressure of the fluid in the annular space in the well bore, and monitoring the rate of flow of fluid along the return line.