

PROCESS FOR THE REMOVAL OF MERCAPTANS AND HYDROGEN SULFIDE
FROM HYDROCARBON STREAMS

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates generally to a process for
the removal of mercaptans and/or hydrogen sulfide (H_2S)
from petroleum distillate streams. More particularly the
invention relates to a process wherein the petroleum
distillate contains diolefins which are selectively reacted
10 with the mercaptans and/or hydrogen sulfide (H_2S) to form
sulfides. Most particularly the invention relates to a
process wherein the reaction of the mercaptans and/or
hydrogen sulfide (H_2S) with the diolefins is carried out
simultaneously with a fractional distillation to remove the
15 sulfides, and thus the sulfur, from the distillate.


Related Information

Petroleum distillate streams contain a variety of
organic chemical components. Generally the streams are
defined by their boiling ranges which determine the
20 compositions. The processing of the streams also affects
the composition. For instance, products from either
catalytic cracking or thermal cracking processes contain
high concentrations of olefinic materials as well as
saturated (alkanes) materials and polyunsaturated
25 materials (diolefins). Additionally, these components may
be any of the various isomers of the compounds.

The petroleum distillates often contain unwanted
contaminants such as sulfur and nitrogen compounds. These
contaminants often are catalyst poisons or produce
30 undesirable products upon further processing. In
particular the sulfur compounds can be troublesome. The
sulfur compounds are known catalyst inhibitors for naphtha
reforming catalysts and hydrogenation catalysts. The
sulfur compounds present in a stream are dependent upon the
35 boiling range of the distillate. Light naphtha (110-250°F
boiling range) may contain mercaptans as the predominant
sulfur compounds. The most common method for removal of
the H_2S and mercaptans is caustic washing of the organic

streams.

Another method of removal of the sulfur compounds is by hydrodesulfurization (HDS) in which the petroleum distillate is passed over a solid particulate catalyst comprising a hydrogenation metal supported on an alumina base. Additionally copious quantities of hydrogen are included in the feed. The following equations illustrate the reactions in a typical HDS unit:



Typical operating conditions for the HDS reactions are:

15	Temperature, °F	600-780
	Pressure, psig	600-3000
	H ₂ recycle rate, SCF/bbl	1500-3000
	Fresh H ₂ makeup, SCF/bbl	700-1000

As may be seen the emphasis has been upon hydrogenating the sulfur and other contaminating compounds. The sulfur is then removed in the form of gaseous H₂S, which in itself is a pollutant and requires further treatment.

In the production of tertiary amyl methyl ether (TAME) for use as a gasoline additive generally a light cracked naphtha (LCN) is used as the source of the olefins for the etherification reaction. This LCN may contain sulfur as a contaminant in the form of mercaptans in concentrations of up to hundreds wppm. These mercaptans are inhibitors for the hydrogenation catalyst used to hydrogenate dienes in the feed to an etherification or to an alkylation unit. As noted above, one common method has been caustic washing.

SUMMARY OF THE INVENTION

The present invention presents a new process for the removal of mercaptans and/or hydrogen sulfide (H₂S) from aliphatic hydrocarbon streams, containing 4 to 12 carbon atoms. Light cracked stream which is used as a feed to an etherification or alkylation unit is a preferred feed for

this process. The light cracked naphtha contains C₄'s to C₈'s components which may be saturated (alkanes), unsaturated (olefins) and polyunsaturated (diolefins) along with minor amounts of the mercaptans. The light naphtha is generally depentanized in a fractional distillation column to remove that portion containing the C₆ and higher boiling materials (C₆+) as bottoms and the C₅ and lower boiling materials (C₅-) as overheads. One embodiment of the present invention utilizes the upper portion of the depentanizer to react substantially all of the mercaptans and/or hydrogen sulfide (H₂S) contained in the light cracked naphtha with a portion of the diolefins to form sulfides which are higher boiling than the C₅ fraction containing the amylenes which are fed to the etherification and/or alkylation unit. The sulfides are removed as bottoms from the depentanizer column along with the C₆+ fraction and can be simply remixed into the final gasoline fraction.

The catalyst used for the reaction is a reduced nickel, preferably 5 to 70 wt% nickel, such as nickel sulfide on an alumina base which has been configured as a catalytic distillation structure.

Hydrogen is provided as necessary to support the reaction. The distillation column reactor is operated at a pressure such that the reaction mixture is boiling in the bed of catalyst. A "froth level" may be maintained throughout the catalyst bed by control of the bottoms and/or overheads withdrawal rate which may improve the effectiveness of the catalyst thereby decreasing the height of catalyst needed. As may be appreciated the liquid is boiling and the physical state is actually a froth having a higher density than would be normal in a packed distillation column but less than the liquid without the boiling vapors.

The present process preferably operates at overhead pressure of said distillation column reactor in the range between 0 and 250 psig and temperatures within said distillation reaction zone in the range of 100 to 300°F,

preferably 130 to 270°F.

The feed and the hydrogen are preferably fed to the distillation column reactor separately or they may be mixed prior to feeding. A mixed feed is fed below the catalyst bed or at the lower end of the bed. Hydrogen alone is fed below the catalyst bed and the hydrocarbon stream is fed below the bed to about the mid one-third of the bed. The pressure selected is that which maintains catalyst bed temperature between 100°F and 300°F.

BRIEF DESCRIPTION OF THE DRAWING

The figure is a simplified flow diagram of one embodiment of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention provides a process for the reaction of diolefins within a petroleum distillate with the mercaptans and/or hydrogen sulfide (H_2S) within the distillate to form sulfides and concurrent separation of the higher boiling sulfides from the distillate. This requires a distillation column reactor which contains an appropriate catalyst in the form of a catalytic distillation structure.

The C_5 's in the feed to the present unit are contained in a single "light naphtha" cut which may contain everything from C_5 's through C_8 's and higher. This mixture can easily contain 150 to 200 components. Mixed refinery streams often contain a broad spectrum of olefinic compounds. This is especially true of products from either catalytic cracking or thermal cracking processes. Refinery streams are usually separated by fractional distillation, and because they often contain compounds that are very close in boiling points, such separations are not precise. A C_5 stream, for instance, may contain C_4 's and up to C_8 's. These components may be saturated (alkanes), unsaturated (mono-olefins), or polyunsaturated (diolefins). Additionally, the components may be any or all of the various isomers of the individual compounds. Such streams typically contain 15 to 30 weight % of the isoamylenes.

Such refinery streams also contain small amounts of

sulfur which must be removed. The sulfur compounds are generally found in a light cracked naphtha stream as mercaptans and/or hydrogen sulfide (H_2S) which poison the hydrogenation catalyst used to selectively hydrogenate diolefins. Removal of sulfur compounds is generally termed "sweetening" a stream.

Several of the minor components (diolefins) in the feed will react slowly with oxygen during storage to produce "gum" and other undesirable materials. However, these components also react very rapidly in the TAME process to form a yellow, foul smelling gummy material and consume acid in an alkylation unit. Thus it is seen to be desirable to remove these components whether the "light naphtha" cut is to be used only for gasoline blending by itself or as feed to a TAME or alkylation process.

Catalysts which are useful in the mercaptan-diolefin reaction include the Group VIII metals. Generally the metals are deposited as the oxides on an alumina support. The supports are usually small diameter extrudates or spheres. The catalyst must then be prepared in the form of a catalytic distillation structure. The catalytic distillation structure must be able to function as catalyst and as mass transfer medium. The catalyst must be suitably supported and spaced within the column to act as a catalytic distillation structure. In a preferred embodiment the catalyst is contained in a woven wire mesh structure as disclosed in U.S. Patent No. 5,266,546 which is hereby incorporated by reference. Other catalytic distillation structures useful for this purpose are disclosed in U.S. patents 4,731,229 and 5,073,236 which are also incorporated by reference.

A suitable catalyst for the reaction is 58 wt% Ni on 8 to 14 mesh alumina spheres, supplied by Calcat, designated as E-475-SR. Typical physical and chemical properties of the catalyst as provided by the manufacturer are as follows:

TABLE I

	Designation	E-475-SR
	Form	Spheres
	Nominal size	8x14 Mesh
5	Ni wt%	54
	Support	Alumina


The hydrogen rate to the reactor must be sufficient to maintain the reaction, but kept below that which would cause flooding of the column which is understood to be the "effectuating amount of hydrogen" as that term is used herein. Generally the mole ratio of hydrogen to diolefins and acetylenes in the feed is at least 1.0 to 1.0, preferably at least 2.0 to 1.0 and more preferably at least 10 to 1.0.

The catalyst also catalyzes the selective hydrogenation of the polyolefins contained within the light cracked naphtha and to a lesser degree the isomerization of some of the mono-olefins. Generally the relative absorption preference is as follows:

- (1) sulfur compounds
- (2) diolefins
- (3) mono-olefins

If the catalyst sites are occupied by a more strongly absorbed species, reaction of these weaker absorbed species cannot occur.

The reaction of interest is the reaction of the mercaptans and/or hydrogen sulfide (H_2S) with diolefins. In the presence of the catalyst the mercaptans will also react with mono-olefins. However, there is an excess of diolefins to mercaptans and/or hydrogen sulfide (H_2S) in the light cracked naphtha feed and the mercaptans preferentially react with them before reacting with the mono-olefins. The equation of interest which describes the reaction is:



Where R, R₁ and R₂ are independently selected from hydrogen and hydrocarbyl groups of 1 to 20 carbon atoms. This may be compared to the HDS reaction which consumes hydrogen. If there is concurrent hydrogenation of the dienes, then
5 hydrogen will be consumed in that reaction.

Typical of the mercaptan compounds which may be found to a greater or lesser degree in a light cracked naphtha are: methyl mercaptan (b.p. 43°F), ethyl mercaptan (b.p. 99°F), n-propyl mercaptan (b.p. 154°F), iso-propyl mercaptan (b.p.
10 135-140°F), iso-butyl mercaptan (b.p. 190°F), tert-butyl mercaptan (b.p. 147°F), n-butyl mercaptan (b.p. 208°F), sec-butyl mercaptan (b.p. 203°F), iso-amyl mercaptan (b.p. 250°F), n-amyl mercaptan (b.p. 259°F), α-methylbutyl mercaptan (b.p. 234°F), α-ethylpropyl mercaptan (b.p.
15 293°F), n-hexyl mercaptan (b.p. 304°F), 2-mercapto hexane (b.p. 284°F), and 3-mercapto hexane (b.p. 135°F at 20 mm Hg).

Typical diolefins in the C₅ boiling range fraction include: isoprene (2-methyl butadiene-1,3), cis and trans
20 piperylenes (cis and trans 1,3-pentadienes), and minor amounts of butadienes. Analogous dienes exist throughout the range of hydrocarbons useful in the present process.

The present invention carries out the method in a catalyst packed column which can be appreciated to contain
25 a vapor phase ascending and some liquid phase as in any distillation. However since the liquid may be held up within the column by artificial "flooding", it will be appreciated that there may be an increased density over that when the liquid is simply descending because of what
30 would be normal internal reflux.

Referring now to the figure there is depicted a simplified flow diagram of one embodiment of the invention. Light cracked naphtha and hydrogen are fed to a depentanizer configured as a distillation column reactor 10
35 via flow lines 2 and 1 respectively. The C₆ and heavier materials are removed in the lower stripping section 15. The C₅ and lighter material, including the mercaptans, are distilled up into the reaction distillation zone 12

containing the catalytic distillation structure. In the reaction distillation zone 12 substantially all of the mercaptans react with a portion of the diolefins to form higher boiling sulfides which are distilled downward into the stripping section 15 and removed as bottoms via line 8 along with the C₆ and heavier material. A rectifying section 16 is provided to insure separation of the sulfides.

The C₅ and lighter distillate (C₅-), less the mercaptans and/or hydrogen sulfide (H₂S), are removed as overheads via flow line 5 and passed through condenser 13 where the condensible materials are condensed. The liquids sent via line 4 are collected in accumulator 18 where the gaseous materials, including any unreacted hydrogen, are separated and removed via flow line 3. The unreacted hydrogen may be recycled (not shown) if desired. The liquid distillate product is removed via flow line 9. Some of the liquid is recycled to the column 10 as reflux via line 6.

Generally the C₅ and lighter material will be used as feed stock for a etherification unit where the isoamylenes contained therein will be converted to TAME or tertiary amyl ethyl ether (TAE). This TAME or TAE is recombined with the C₆ bottoms and sent to gasoline blending. While the C₆ and heavier materials contain the sulfides, the total sulfur content is still acceptably low.

EXAMPLE

In this Example a one inch diameter column is loaded with 15 ft of the catalyst (E-475-SR) as distillation structure in the upper portion of the column. The catalyst bales are loaded in the column. The column pressure is set at 50 to 150 psig and the column is brought to total reflux with cyclohexane. After reflux is established H₂ is added at 10 SCFH. Periodically water is drained from the reflux drum. After 12 hours the hydrocarbon feed is started. The lower 5 ft. are filled with inert distillation packing. The conditions and results are shown in TABLE II below.

TABLE II

Feed:	C ₄	C ₅		
Hours	6	22	40	80
Mercaptan content, wppm	55	189	189	294
Diolefin/mercaptan wt.	79	21	21	21
Conditions:				
Feed rate, lbs/hr	2.0	2.0	3.0	4.0
H ₂ feed rate, scf	2.0	1.5	2.2	3.5
H ₂ partial press psi	1.3	1.3	1.3	1.3
Overhead pressure, psig	60	75	75	75
Middle cat. bed temp., °F	120	207	205	205
Bottoms rate, lbs/hr	.2	.2	.3	.4
Overheads distillate				
product, lbs/hr	1.5	1.8	2.6	3.5
Internal reflux rate	8.78	7.30	4.50	3.04
Results:				
Mercaptans in overheads				
distillate, wppm	0	8	15	21
Diolefin content, wt %	1.79	.83	.83	---
Diolefin saturation	99.79%	72.2%	55.4%	---
Butene-1/total butenes feed	41%			
Butene-1/total butenes out	32%			
3-MB-1/isoamylenes feed		2.8%	.28%	.28%
3-MB-1/isoamylenes out		2.8%	.28%	.28%
2-MB-2/isoamylenes feed		64.8%	64.8%	64.8%
2-MB-2/isoamylenes out		74.6%	72.6%	70.9%



WO 96/18704

THIS SHEET HAS BEEN
REPLACED

PCT/US95/16193

10

The invention claimed is:

1. A process for removing mercaptans and/or hydrogen sulfide from a hydrocarbon stream, comprising the steps of:

(a) feeding diolefins and a hydrocarbon stream containing sulfur compounds selected from mercaptans, hydrogen sulfide or mixtures thereof to a distillation column reactor into a feed zone;

(b) feeding an effectuating amount of hydrogen to said distillation column reactor

(c) concurrently in said distillation column reactor

(i) contacting the diolefins and said sulfur compounds contained within said hydrocarbon stream in the presence of hydrogen in a distillation reaction zone containing a supported nickel catalyst prepared in the form to act as a catalytic distillation structure thereby reacting a portion of said sulfur compounds with a portion of the diolefins to form sulfide products and a distillate product, having a reduced amount of said sulfur compounds and

(ii) separating said sulfides from said distillate product by fractional distillation;

(d) withdrawing distillate product from said distillation column reactor at a point above said distillation reaction zone, said distillate product having a reduced sulfur compound content; and

(e) withdrawing sulfide products from said distillation column reactor at a point below said distillation reaction zone.

2. The process according to claim 1 wherein said hydrocarbon stream is a light cracked naphtha distillate containing a C₅ and lighter fraction and a C₆ and heavier fraction, said C₅ and lighter fraction is removed as overheads from said distillation column reactor and said C₆ and heavier fraction is removed as bottoms from said distillation column reactor.

3. The process according to claim 1 wherein there is a molar excess of diolefins to sulfur compounds.

4. The process according to claim 3 wherein substantially all of said sulfur compounds are reacted with

This Sheet Has Been Replaced





diolefins to form sulfide products and said distillate product is substantially free of said sulfur compounds.

5. The process according to claim 3 wherein substantially all of said excess of diolefins not reacted with sulfur compounds are hydrogenated to mono-olefins.

6. The process according to claim 1 wherein said diolefins are contained in said hydrocarbon stream.

7. A process for treating a light cracked naphtha distillate for use as an etherification or alkylation feed stock, comprising the steps of:

(a) feeding a light cracked naphtha distillate containing sulfur compounds selected from mercaptans, hydrogen sulfide or mixtures thereof and diolefins to a distillation column reactor having a stripping zone and distillation reaction zone, said light cracked naphtha having a C₆+ fraction and a C₅- fraction;

(b) feeding an effectuating amount of hydrogen to said distillation column reactor;

(c) separating said C₆+ fraction from said C₅- fraction in said stripping zone and distilling said C₅- fraction up into said distillation reaction zone;

(d) concurrently in said distillation reaction zone

(i) contacting the diolefins and sulfur compounds contained within said light cracked naphtha in the presence of hydrogen in a distillation reaction zone containing a reduced nickel catalyst supported on a particulate alumina base prepared in the form to act as a catalytic distillation structure thereby reacting a portion of said sulfur compounds with a portion of the diolefins to form sulfide products and a distillate product,

(ii) selectively hydrogenating any remaining diolefins to mono-olefins, and

(iii) separating said sulfides from said distillate product by fractional distillation;

(e) withdrawing a C₅- distillate product from said distillation column reactor as overheads, said C₅- distillate product having a reduced sulfur compound and diolefin content; and



(f) withdrawing said sulfide products from said distillation column reactor as bottoms along with said C₆+ fraction.

8. The process according to claim 7 wherein there is a molar excess of diolefins to said sulfur compounds within said light cracked naphtha stream.

9. The process according to claim 7 wherein substantially all of said mercaptans react with diolefins to produce sulfide products producing a C₅- distillate product substantially free of said sulfur compounds.

10. A process for treating a light cracked naphtha distillate for use as an etherification and/or alkylation feed stock, comprising the steps of:

(a) feeding a light cracked naphtha distillate containing mercaptans and a molar excess of diolefins to said mercaptans to a distillation column reactor having a stripping zone and distillation reaction zone, said light cracked naphtha having a C₆+ fraction and a C₅- fraction;

(b) feeding an effectuating amount of hydrogen to said distillation column reactor;

(c) separating said C₆+ fraction from said C₅- fraction in said stripping zone and distilling said C₅- fraction up into said distillation reaction zone;

(d) concurrently in said distillation reaction zone

(i) contacting the diolefins, mercaptans and hydrogen sulfide contained within said light cracked naphtha in the presence of hydrogen in a distillation reaction zone containing a nickel sulfide catalyst supported on a particulate alumina base prepared in the form to act as a catalytic distillation structure thereby reacting substantially all of said mercaptans with a portion of the diolefins to form sulfide products and a distillate product,

(ii) selectively hydrogenating the remaining diolefins to mono-olefins, and

(iii) separating said sulfides from said distillate product by fractional distillation;

(e) withdrawing a C₅- distillate product from said



THIS SHEET HAS BEEN
REPLACED


distillation column reactor as overheads, said C₅-distillate product having a substantially reduced mercaptan and diolefin content; and

(f) withdrawing said sulfide products from said distillation column reactor as bottoms along with said C₆+ fraction.

This Sheet Has Been Replaced



1/1



09 JUN 1998

10

The invention claimed is:

1. A process for removing mercaptans and/or hydrogen sulfide from a hydrocarbon stream, comprising the steps of:

(a) feeding diolefins and a hydrocarbon stream containing sulfur compounds selected from mercaptans, hydrogen sulfide or mixtures thereof to a distillation column reactor into a feed zone;

(b) feeding an effectuating amount of hydrogen to said distillation column reactor

(c) concurrently in said distillation column reactor

(i) contacting the diolefins and said sulfur compounds contained within said hydrocarbon stream in the presence of hydrogen in a _____ reaction zone containing a supported nickel catalyst _____

_____ thereby reacting a portion of said sulfur compounds with a portion of the diolefins to form sulfide products and a distillate product, having a reduced amount of said sulfur compounds and

(ii) separating said sulfides from said distillate product by fractional distillation;

(d) withdrawing distillate product from said distillation column reactor at a point above said distillation reaction zone, said distillate product having a reduced sulfur compound content; and

(e) withdrawing sulfide products from said distillation column reactor at a point below said distillation reaction zone.

2. The process according to claim 1 wherein said hydrocarbon stream is a light cracked naphtha distillate containing a C₅ and lighter fraction and a C₆ and heavier fraction, said C₅ and lighter fraction is removed as overheads from said distillation column reactor and said C₆ and heavier fraction is removed as bottoms from said distillation column reactor.

3. The process according to claim 1 wherein there is a molar excess of diolefins to sulfur compounds.


4. The process according to claim 3 wherein substantially all of said sulfur compounds are reacted with




distillation column reactor as overheads, said C₅-distillate product having a substantially reduced mercaptan and diolefin content; and

(f) withdrawing said sulfide products from said distillation column reactor as bottoms along with said C₆+ fraction.

11. The process according to claim 1, 2, 3, 4, 5, or 6 wherein said catalyst is prepared in the form to act as a catalytic distillation structure.



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C10G 45/06, 45/36, C07C 5/03, 7/08, 7/163	A1	(11) International Publication Number: WO 96/18704
		(43) International Publication Date: 20 June 1996 (20.06.96)

(21) International Application Number: **PCT/US95/16193**(22) International Filing Date: **7 December 1995 (07.12.95)**(30) Priority Data:
08/354,593 13 December 1994 (13.12.94) US(71) Applicant: **CHEMICAL RESEARCH & LICENSING COMPANY [US/US]; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US).**(72) Inventors: **HEARN, Dennis; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US). GILDERT, Gary, R.; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US). PUTMAN, Hugh, M.; 10100 Bay Area Boulevard, Pasadena, TX 77507 (US).**(74) Agent: **JOHNSON, Kenneth, H.; P.O. Box 630708, Houston, TX 77263 (US).**(81) Designated States: **AM, AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LT, LU, LV, MD, MG, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TT, UA, UG, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, LS, MW, SD, SZ, UG).****Published***With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*(54) Title: **PROCESS FOR THE REMOVAL OF MERCAPTANS AND HYDROGEN SULFIDE FROM HYDROCARBON STREAMS**

(57) Abstract

A process for treating a light cracked naphtha to be used as an etherification feed stock is disclosed in which mercaptans, hydrogen sulfide and diolefins are removed simultaneously in a distillation column reactor (10) using a reduced nickel catalyst. The mercaptans and hydrogen sulfide are reacted with the diolefins to form sulfides which are higher boiling than that portion of the naphtha which is used as feed to the etherification unit. The higher boiling sulfides are removed as bottoms (8) along with any C₆ and heavier materials. Any diolefins not converted to sulfides are selectively hydrogenated to mono-olefins for use in the etherification process.

