

Capsule system with recognition means and adaptable opening and injection mechanism

Field of the invention

5

The present invention relates to the field of beverage preparation devices using capsules holding beverage ingredients for preparing a beverage upon liquid injection thereto. In particular, the invention relates to a system
10 comprising a beverage preparation device and a capsule, the device being equipped with opening and injection means that are adaptable dependent on a particular capsule inserted into the device.

15 Background and object of the invention

Devices for preparing a beverage upon feeding liquid such as pressurized water into a capsule inserted into a receiving chamber of the device are widely available and well-known on
20 the market. The dedicated capsules are designed for being used with specific machines and usually hold a predefined amount of nutritional ingredients for preparing a single-serve beverage portion such as a coffee beverage upon reconstitution with liquid.

25

EP 1 767 129 discloses a common example for a device for preparing a beverage from a capsule. The device comprises a capsule receiving chamber in which the capsule can be inserted or placed by a consumer. The device further
30 comprises a beverage brewing chamber with two enclosing members that are movable with respect to each other in order to enclose the capsule therebetween. Thereby, an upper enclosing member is equipped with injection means for

piercing and injecting liquid into a first inlet face of the capsule and a lower enclosing member is provided with means for opening a second outlet face of the capsule upon pressure increase with the capsule interior in order to drain the
5 resulting beverage therefrom.

The known beverage preparation devices suffer the drawback that the relative position of the movable capsule enclosing members in their closed position is predefined according to
10 a standard configuration of the device. Accordingly, the pressure exerted by the enclosing members on the capsule as well as the relative location of the injection means with respect to an inlet face will remain constant in every single beverage preparation process with the device.

15 Such an arrangement does however not enable to provide for optimal injection and/or extraction parameters for different capsule configurations, in particular for capsules of different packaging material, of different sizes, of
20 different filling and/or compaction degree and/or of varying granulometry of the nutritional particles such as coffee grinds contained therein.

For example, if the upper enclosing member exerts too much
25 force onto the capsule held within the beverage brewing chamber, the capsule's outlet face may be opened by the opening means of the lower enclosing member too early, which results in a not optimal pressure profile during the beverage preparation process and an overcompaction of the ingredients
30 held in the capsule. Further, if the upper enclosing member does not properly contact the inlet face of the capsule or exerts too little force on the capsule, the capsule's inlet

face may only be partially pierced, which may result in a loss of extraction yield and crema.

5 The present invention thus aims at providing a system and a device for addressing the above-indicated problems. It is particular aimed at providing an enhanced device and system for enabling the provision of optimal injection and/or extraction parameters for different capsule types provided to the device.

10

The present invention seeks to address the above-described problems. The invention also aims at other objects and particularly the solution of other problems as will appear in the rest of the present description.

15

Object and Summary of the invention

In a first aspect, the invention relates to a beverage preparation device for preparing a beverage upon interaction
20 of ingredients provided in a capsule with liquid supplied thereto, the device comprising an injection module comprising a first and a cooperating second enclosing member designed for being moved relatively to each other, the first enclosing member being equipped with capsule opening and
25 injection means for opening a first inlet face of a capsule and inject liquid into the capsule, the first and second enclosing member being designed for being brought into at least a first capsule insertion position for inserting a capsule between the enclosing members and a second capsule
30 enclosing position in which the opening and injection means engage the liquid inlet face of the capsule, the device further comprising control means designed for adapting the capsule enclosing position based on information read from

the capsule and/or based on information provided by a user input.

According to the invention, the respective enclosing
5 position such as in particular a distance between the
respective first and second enclosing members may be adjusted
to the particular capsule inserted to the device. This
enables that the opening and the following beverage injection
10 process can provide for optimal injection and/or extraction
parameters for different capsules comprising for example
different packaging material, different capsule sizes,
different filling and/or compaction degrees and/or
ingredients of different granulometry.

15 In order to provide for different enclosing positions that
may be adapted, i.e. determined and set, based on the capsule
provided to the device and/or based on a user input, the
device is preferably designed for assuming a plurality of
different enclosing positions. Thereby, the different
20 enclosing positions vary preferably at least with regards to
the distance between the respective first and second
enclosing members.

The first and second enclosing member are preferably designed
25 for being moved relatively to each other in linear direction.
Thereby, a distance between the first and second enclosing
member is preferably varied. The first and second enclosing
members may however as well be moved relatively with respect
to each other according to a composite trajectory comprising
30 e.g. a portion of linear motion and a portion wherein the
respective members are at least partially rotated with
respect to each other.

In the first capsule insertion position, the first and second enclosing members are preferably separated by a maximum distance. Accordingly, the capsule inserted into or provided to the beverage preparation device may be received in a free space between the respective first and second enclosing member.

In the second capsule enclosing position, the first and second enclosing members are arranged at closer distance to each other compared to the first capsule insertion position. In this position, the first and second enclosing member engage the capsule, i.e. are arranged adjacent to the respective capsule inlet and outlet face of the capsule. In particular, an inlet face of the capsule is engaged by the opening and injection means of the first enclosing member. In a preferred embodiment, upon bringing the first and second enclosing members into the second capsule enclosing position, the open and injection means open the capsule inlet face such as by piercing, cutting, tearing or the like.

In a preferred embodiment, the control means are designed for further adapting the enclosing position during a beverage preparation process with a capsule in the device based on information read from the capsule and/or based on a user input. In a particular preferred embodiment, the control means are designed for adapting a distance between the first and second enclosing member respectively a penetration depth/force of the opening and injection means into the capsule at least in the capsule enclosing position. Accordingly, the enclosing position and thus the relative position of the first and second enclosing member with respect to each other may be adjusted during the actual beverage preparation process, i.e. before and/or during the

liquid injection into the capsule. Thereby, such adjusting is preferably carried out after an initial opening of the capsule in the enclosing position.

5 In a preferred embodiment, the first and second enclosing member are designed for being brought into at least a third capsule injection position dependent on information read from the capsule and/or based on information provided by a user input. In such position, the distance between the first
10 and second capsule enclosing members is preferably greater than the distance between the enclosing members in the capsule enclosing position.

The capsule injection position is preferably assumed by the
15 first and second enclosing members only during the injection of liquid to the capsule. In such capsule injection position, the opening and injection means are preferably still engaging the inlet face of the capsule. This means that the opening and injection means are still protruding into the opened
20 inlet face of the capsule in sectional side view.

The device according to the invention preferably comprises recognitions means connected to the control means that are designed to read information from the capsule inserted into
25 the device. Notably, such reading of information also encompasses the recognition of a predefined characteristic of the capsule. For this purpose, the recognition means may comprise an optical sensor designed for reading an optical code such as a barcode from a surface of the capsule. The
30 sensor may as well comprise an RFID sensor, a magnetic sensor, an electric, an inductive sensor, a mechanic sensor and/or a CCD sensor suitable for interacting with identification means provided on the capsule and/or for detecting a

characterization of the capsule such as a shape and/or size of the capsule or of one of its constituting parts.

The first enclosing member preferably comprises a shower
5 plate comprising a plurality of protruding hollow piercing
elements such as needles as opening and injection means. The
respective needle elements preferably protrude parallel in
the same direction from the shower plate. The respective
needle elements preferably protrude to the same extent from
10 the shower plate. The piercing elements are preferably all
connected to a joint liquid supply conduit of the enclosing
member.

The second enclosing member preferably comprises a support
15 plate with a plurality of protruding structures such as
pyramids designed to open an outlet face of the capsule upon
pressure increase with the capsule.

The device preferably further comprises means for providing
20 a heated pressurized liquid to the injection module of the
device. In particular, the device preferably comprises a
pump connected to a liquid supply such as a liquid reservoir.
The device preferably further comprises heating means such
as a thermoblock for heating a liquid before being provided
25 to the capsule. The liquid provided to the capsule is
preferably water.

The device preferably further comprises a user interface for
providing information as to the particular capsule or capsule
30 type inserted into the device. Based on this information,
the control means of the device may then adapt the particular
enclosing position of the first and second enclosing member
to the inserted capsule. The user interface may further be

designed for selecting a particular beverage to be prepared and/or the volume of the particular beverage. This further information may as well be used by the control means for adapting the particular enclosing position of the first and
5 second enclosing member. In addition, the control means may adapt also the injection position and/or further parameters of the beverage preparation device based on the information provided by the user input.

10 In a further aspect, the invention relates to a system for preparing a beverage comprising a beverage preparation device as described here-above and at least one capsule containing a predefined amount of beverage ingredients.

15 The ingredients provided in the capsule are preferably designed for reconstituting a single-serve portion of beverage upon interaction with liquid such as water provided to the capsule. The ingredients are preferably ingredients for preparing a coffee beverage such as a ristretto, espresso
20 or lungo coffee beverage. The ingredients are preferably ground coffee particles present in dry powdered form. The ingredients may however as well be present in different form such as in liquid form. The capsule may as well comprise different ingredients such as ingredients suitable for
25 reconstituting a different beverage such as a tea beverage, a soup or the like.

The capsule according to the invention preferably comprises a beverage inlet face and a beverage outlet face enclosing
30 an inner ingredient chamber. The inlet and outlet face of the capsule is preferably formed by a membrane or foil member made e.g. of aluminium. The membrane or foil member of the inlet and outlet face are preferably sealed together at a

circumferentially arranged rim portion of the capsule. The ingredients provided within the capsule are preferably arranged in compressed form. This means that preferably no free space is present within the capsule ingredient chamber, i.e. a free movement of the ingredients particles in the chamber is preferably not enabled.

The capsule preferably comprises an information and/or characterization which can be read by recognition means of the beverage preparation device. The capsule may comprise a code such as an optical code on its outer surface or the like which is designed to be read by a dedicated sensor of the device. The code may comprise information regarding the beverage preparation process parameters and in particular information relating to the respective positions such as the enclosing position to be assumed by the enclosing members of the device when preparing a beverage with the particular capsule. A particular characterization of the capsule may be present by means of its shape and/or size of the capsule which can be recognized by dedicated recognition means of the device. Thereby, dedicated recognition and/or control means of the device are preferably designed to associate information regarding the beverage preparation process parameters and in particular information relating to the respective positions such as the enclosing position to be assumed by the enclosing members of the device to the shape and/or size of the capsule inserted into the beverage preparation device.

The system preferably comprises different types of capsules which differ in their respective shapes and/or sizes, filling degrees, ingredient compaction degree and/or ingredient granulometry. The respective different types of capsule are

preferably equipped with different information and/or characteristics to be read by the beverage preparation device. Accordingly, the respective capsule type comprise dedicated information and/or characteristics which enable the beverage preparation device to read said information from the respective capsule and specifically provide optimal injection and/or extraction parameters for the particular capsule.

10 In a further aspect, the invention relates to a method for preparing a beverage by means of capsule comprising beverage ingredients in a beverage preparation device, the method comprises the steps of:

- inserting a capsule containing a predefined amount of beverage ingredients into the device,
- reading information from the capsule and/or recognizing a characterization of the capsule,
- bringing a first and a cooperating second enclosing member of an injection module of the device from a first capsule insertion position into a second capsule enclosing position in which opening and injection means of the first enclosing member engage and open the liquid inlet face of the capsule, wherein the enclosing position is adapted based on information read from the capsule and/or based on information provided by a user input, and
- injecting liquid into the capsule by means of the opening and injection means.

The step of adapting preferably comprises a determination and a setting of a particular enclosing position by the control means of the device. The determining and setting of the enclosing position may be carried out by directly reading the respective information from the capsule and set a

corresponding capsule enclosing position of the device. Alternatively, the information and/or characteristics read from the capsule may be compared with information provided by the device, such as e.g. in a dedicated memory unit. Based
5 on the result of such comparison, the respective position of the first and second enclosing member may then be set by the control means. Thereby, the memory unit may for example comprise a database or correlation tables that link capsule information and/or characteristics of the capsule with
10 beverage process parameters such as the particular positions of the enclosing members. The memory unit may further comprise additional data and/or parameters for preparing a beverage by means of the particular capsule. Alternatively, the respective parameters may be determined and set based on
15 a provided user input such as a selection of a particular capsule type e.g. by means of a user interface of the device.

The method may additionally comprise the step of further adapting the enclosing position after an initial opening of
20 the inlet face of the capsule and before injection of liquid into the capsule, and/or further adapting the enclosing position during the injection of liquid into the capsule. Accordingly, the enclosing position and thus the relative position of the first and second enclosing member with
25 respect to each other may be adjusted during the actual beverage preparation process, i.e. before and/or during the liquid injection into the capsule.

When adapting the enclosing position before the injection of
30 liquid the first and second enclosing members may be brought into a dedicated capsule injection position. In the capsule injection position, the opening and injection means are preferably still engaged with the first inlet face of the

capsule, i.e. protrude into the inlet face of the capsule when seen in sectional side view.

An adaption of the enclosing position during the injection
5 of liquid into the capsule may be made in order to further
adjust and optimize the injection and/or brewing parameters
such as the injection and/or brewing pressure within the
capsule. Thereby, such adaption may comprise the step of
increasing and/or decreasing a distance between the first
10 and second enclosing members compared to the initial position
in which the capsule is opened and/or compared to the capsule
injection position. The relative position respectively the
distance between the first and second enclosing members may
be continuously varied during beverage injection and/or may
15 be varied to assume different distinct positions during
liquid injection.

The step of adapting is preferably carried out by the control
means of the device dependent on information read from the
20 capsule and/or provided by the user input. As indicated above,
the respective information may be read directly from the
particular capsule and/or may be determined based on
information stored in a dedicated memory unit of the device.

25 In a particular preferred embodiment, the method further
comprises the step of increasing a distance between the first
and second enclosing members after the initial opening of
the capsule. Such increased distance is preferably provided
in the capsule injection position, i.e. in which liquid is
30 then injected into the capsule. The amount by means of which
the distance between the first and second enclosing members
is increased is preferably determined based on the
information read from the capsule and/or by the provided

user input, as indicated above. The increase of the distance is preferably carried out before injection of liquid into the capsule. The distance is preferably only increased by such amount that the opening and injection means of the first enclosing member are still engaged with the first inlet face of the capsule. According to such arrangement, any excess pressure onto the inlet face of the capsule and thus onto the ingredients provided adjacent to said inlet face is reduced to a minimum extent and therefore, a negative effect on the beverage preparation process is avoided.

Brief description of the drawings

Further features, advantages and objects of the present invention will become apparent for a skilled person when reading the following detailed description of embodiments of the present invention, when taken in conjunction with the figures of the enclosed drawings.

Fig. 1 shows a preferred embodiment of an injection module of a beverage preparation device according to the invention in sectional side view.

Fig. 2 shows the injection module according to the invention in closed state.

Fig. 3 shows the injection module according to the invention in which the capsule is sealed by a dedicated engagement means.

Fig. 4 shows the injection module according to the invention in the capsule enclosing position.

Fig. 5 shows the injection module according to the invention in the capsule injection position.

Fig. 6 shows a flow chart relating to a preferred embodiment of the method according to the invention.

Fig. 7 relates to different capsule types of the system according to the invention.

10 Detailed description of the figures

Fig. 1 shows a preferred embodiment of an injection module 10 of a beverage preparation device 100 according to the invention in section side view.

15

The device 100 according to the invention is designed for providing a preferably heated, pressurized liquid to a capsule 5 inserted to the device via the injection module 10. For this purpose, the device comprises a pump, a liquid reservoir and heating means such as a thermoblock (not shown) connected to the injection module 10 in a known manner. The device preferably further comprises user input means such as a touchscreen and/or buttons designed for enabling a user input into the device.

25

The injection module 10 comprises a first and a cooperating second enclosing member 1,2 designed for being moved relatively to each other. The first enclosing member 1 is preferably connected to activation or drive means 4 designed for selectively moving the first enclosing member 1 with respect to the second enclosing member 2. The second enclosing member 2 is preferably fixedly arranged, i.e. not movable within the injection module 10. The first enclosing

30

member 1 may preferably assume a plurality of different positions with respect to the second enclosing member 2.

The first enclosing member 1 comprises capsule opening and injection means 3 for opening a first inlet face 5a of the capsule 5 and inject liquid into the capsule. The first enclosing member 1 preferably comprises a shower plate 1a with a plurality of protruding hollow piercing elements such as needles as opening and injection means 3. The shower plate 1a may comprise an at least partially concave form in order to enclose the preferably conformably shaped inlet face 5a of the capsule 5. The shower plate may alternatively be of essentially planar form.

The second enclosing member 2 preferably comprises a support plate 2a with a plurality of protruding structures such as pyramids designed to open an outlet face 5b of the capsule 5 upon pressure increase with the capsule.

The beverage preparation device 100 further comprises a capsule insertion slot 8 designed to receive the capsule 5 and for feeding the capsule into a receiving chamber 7 arranged between the first and second enclosing member 1,2, e.g. by means of gravity. The insertion slot 8 may be closed by a cover member 9 of the device.

The device further comprises a beverage outflow means 11 fluidly connected to the second enclosing member 2 and designed to collect the resulting beverage drained from the capsule and guide it towards a beverage receptacle such as a cup of the consumer.

The injection module 10 may further comprise sealing means such as a circumferentially arranged sealing ring 12 designed to selectively enclose the capsule 5 in the receiving chamber 7. Notably, the sealing ring 12 may as well be integrally formed with the first enclosing member 1.

The device further comprises control means 13 designed for adapting, i.e. determining and setting, at least a respective capsule enclosing position of the first and second enclosing member 1,2 dependent on information read from the capsule and/or based on information provided by a user input.

The device preferably further comprises recognitions means 14 connected to the control means 13 and which are designed to read information from the capsule 5 inserted into the device. The recognition means 14 may comprise an optical sensor, an RFID sensor, a magnetic sensor, an electric sensor, an inductive sensor, a mechanic sensor and/or a CCD sensor suitable for interacting with identification means 5d provided on the capsule and/or for sensing a characterization of the capsule such as a shape and/or size of the capsule or of one of its constituting parts.

The capsule 5 (see also fig. 7) to be used in conjunction with the device preferably comprises an inlet face 5a and outlet face 5b enclosing an inner ingredient chamber. The inlet and outlet face 5a, 5b are preferably formed by a membrane or foil member made e.g. of aluminum. The membrane or foil member of the inlet and outlet face are preferably sealed together at a circumferentially arranged flange-like rim 5c of the capsule. The ingredients provided within the capsule are preferably arranged in compressed form. This means that preferably no free space is present within the

capsule ingredient chamber, i.e. a free movement of the ingredients particles in the chamber is preferably not enabled. The capsule preferably comprises identification means 5d that can be read by the recognition means 14 of the device. Such identification means 5d may be provided in the form of e.g. an optical code readable by the recognition means 14 of the device. The identification means 5d may however as well be present in the form of a particular characteristics such as e.g. the form and/or shape of the capsule which can be identified by the recognition means 14 of the device. Based on the information provided by the identification means 5d, the control means 13 connected to the recognition means 14 can determine and set beverage process parameters such as at least a particular capsule enclosing position of the first and second enclosing members 1,2.

Fig. 1 relates to a first capsule insertion position of the first and second enclosing members 1,2 with respect to each other. Thereby, the first and second enclosing members 1,2 are preferably arranged at a maximum possible distance d to each other. This position gives enough free space there between in order to provide a capsule to the receiving chamber 7 situated between the enclosing members 1,2.

As shown in fig. 1, a capsule 5 may be inserted via the provided capsule insertion slot 8 by a user in order to provide the capsule to the receiving chamber 7. Thereby, the capsule 5 is preferably held at an intermediate capsule recognition position by means of a dedicated capsule support 15 at which position the recognition means 14 may interact with the identification means 5d and/or the characteristics of the capsule such as to enable a recognition of the

particular capsule 5 inserted into the device. In an alternative embodiment, the recognition of the capsule may take place during insertion into the receiving chamber 7, i.e. without providing an intermediate capsule recognition position.

Alternatively and/or in addition to the above-indicated arrangement, the user may provide information about the inserted capsule via a dedicated user input means of the device. This information may then be used by the control means for adapting the beverage process parameters and/or the particular positions of the first and second enclosing member during the beverage preparation process.

After recognition, the capsule 5 is brought from the intermediate capsule recognition position into the receiving chamber 7. Thereby, the capsule 5 may for example be urged beyond the previously described capsule support 15 by dedicated actuation means such that the capsule 5 proceeds to the receiving chamber 7 by gravity. In a possible alternative, the capsule support 15 will be moved in a retracted position such that the capsule 5 is no longer held by the support and will proceed to the receiving chamber 7 preferably by gravity.

Fig. 2 relates to the position of the capsule in the receiving chamber 7 between the first and second enclosing members 1,2.

In a next step as shown in fig. 3, the capsule 5 is sealingly enclosed in the receiving chamber 7 by means of a circumferentially arranged sealing ring 12. Thereby, a circular front face 12a of the ring 12 will sealingly press

the flange-like rim 5c of the capsule 5 against a preferably circular support face 2b arranged at the respective opposite side of the capsule 5. The sealing pressure applied by the sealing ring 12 onto the flange-like rim 5c of the capsule 5 is preferably equal for every inserted capsule. In a possible variant, the sealing pressure applied by the sealing ring 12 may as well be varied by the control means 13 based on the information read from the inserted capsule and/or based on the information provided by the user input.

10

Next, as shown in fig. 4, the first and second enclosing members 1,2 are brought into the capsule enclosing position in which the opening and injection means 3 of the first enclosing member 1 engage the liquid inlet face 5a of the capsule. Thereby, the opening and injection means 3 open the liquid inlet face 5a preferably by piercing it.

15

In this position, the outlet face 5b is engaged by the second enclosing member 2. Thereby, the outlet face 5b is preferably situated directly adjacent to the support plate 2a with the plurality of protruding structures such as pyramids designed to open the outlet face 5b of the capsule upon pressure increase with the capsule.

20

The indicated capsule enclosing position and in particular a specific distance between the first and second enclosing members 1,2 in this position is determined and set by the control means 13 of the device dependent on the particular capsule 5 inserted to the injection module 10 as described above. Accordingly, the pressure applied onto the inlet face 5a and the outlet face 5b by means of the first and second enclosing member 1,2 in this position can be adapted to the particular capsule inserted. Thereby, also a penetration

25
30

depth/force of the opening and injection means 3 into the capsule can be adapted to the particular capsule.

After the opening of the inlet face 5a of the capsule in the capsule enclosing position as shown in fig. 4 and preferably before any liquid is injected into the capsule, the enclosing member 1,2 may be brought into a capsule injection position as shown in fig. 5. Thereby, the distance d between the first and second enclosing member 1,2 is preferably increased again. Accordingly, the force applied to the inlet face 5a and the outlet face 5b of the capsule is reduced to a minimum extent. In addition, sufficient space is provided for the ingredients within the capsule interior during the liquid injection. Notably, in this capsule injection position, the opening and injection means 3 preferably remain engaged with the inlet face 5a of the capsule, i.e. still protrude into the inlet face 5a when seen in sectional side view. The penetration depth of the opening and injection means 3 is however reduced preferably to a minimum extent.

20

The particular position of the first and second enclosing member 1,2 in the capsule injection position is preferably also determined and set by the control unit of the device based on the information read from the capsule and/or the information provided by the user input.

25

During the following liquid injection by the opening and injection means 3, liquid will interact with the ingredients provided in the capsule 5 in order to form a beverage e.g. by means of extraction and/or dissolution. The increasing pressure within the capsule will lead to an urging of the outlet face 5b against the protruding structures of the support plate 2a, which in turn leads to an opening of the

30

outlet face 5b by tearing and/or perforation. The resulting beverage will then be drained from the capsule 5 via the beverage outflow means 11 of the device and may be collected by a dedicated receptacle such as a cup (not shown).

5

During the liquid injection, the position of the first and second enclosing member 1,2 with respect to each other may remain constant. In an alternative embodiment, the relative position may be further varied by the control means 13 based on the information read from the capsule 5 and/or based on the information provided by the user input. Thereby, the relative position may be continuously varied during beverage injection and/or may be varied to assume different distinct positions during liquid injection.

15

In addition, the control means 13 may be designed to vary further process parameters such as the injection pressure, the liquid temperature and/or the volume of the provided liquid based on the information read from the capsule 5 and/or based on the information provided by the user input. After the beverage preparation process, the first and second enclosing member 1,2 are brought back into the capsule insertion position as shown e.g. in fig. 1. Thereby, the used capsule may be discharged from the receiving chamber 7 by means of a dedicated actuator and/or by means of gravity. The device will then be ready to process a further capsule when inserted into the device.

20

25

Fig. 6 relates to a flow chart describing the steps of a preferred embodiment of the method according to the invention. Thereby, in a first step SI, a capsule 5 is inserted into the beverage preparation device 100 respectively into the injection module 10 of the device.

30

In a second step S2, information is read from the capsule. As previously described, this may be obtained by a recognizing means 14 of the device which interact with
5 identification means 5d of the capsule and/or which recognize a characteristic of the capsule such as a particular size and/or shape. Alternatively, in step S2 a user may provide information about the particular capsule inserted into the device and/or provide a selection of particular process
10 parameters to be applied for this particular capsule.

In a further step S3, at least a specific capsule insertion position of the first and second enclosing member 1,2 is determined based on the read information and/or based on the
15 user input. This is preferably carried out by the control means 13 of the device. In addition, further parameters of the beverage preparation process may be determined based on the provided information and/or the provided user input, such as in particular a specific capsule injection position
20 of the first and second enclosing member 1,2, a volume, a temperature, and/or a pressure for the liquid to be injected into the inserted capsule. The step of determining may encompass a direct determination based on information read from the capsule or information provided via user input or
25 a determination via comparing the read information and/or the user input with information or data stored in a memory unit of the device.

In a further step S4, the capsule is enclosed in the device
30 by the control means 13 setting the determined enclosing position of the first and second enclosing member 1,2. Thereby, an opening of the inlet face 5a of the capsule takes place.

In a further optional step S5, the determined injection position of the first and second enclosing member 1,2 is set by the control means 13. Thereby, a distance between the respective enclosing members 1,2 is preferably increased again while the opening and injection means 3 preferably still maintain engaged with the inlet face 5a of the capsule.

Subsequently, injection of the liquid into the capsule takes place in step S6. In this step, the control means 13 may optionally vary the particular position of the first and second enclosing member 1,2 with respect to each other and/or may set or vary further parameters such as the liquid pressure, temperature and/or volume. The liquid injection leads to the forming of a beverage upon interaction of the capsule ingredients with the liquid and the subsequent draining of the beverage from the capsule.

After the liquid injection, the control means 13 bring back the first and second enclosing member 1,2 into the capsule insertion position respectively into a capsule ejection position, thereby discharging the used capsule from the receiving chamber 7 between the enclosing members (step S7).

Fig. 7 relates to different capsule types 5, 5', 5'' of a system according to the invention. As shown in the figures, the capsule types may comprise different characteristics such as shape and/or size and which may be recognized by the beverage preparation device.

In a preferred embodiment, the capsules 5, 5', 5'' all comprise an equal diameter d_2 of the flange-like rim portion 5c and/or equal diameter d_1 of a central capsule body portion, but differ in their height h, h', h'' . Alternatively or in

addition, the capsules may comprise identification means 5d designed to be recognized and/or read a by the beverage preparation device as previously described. The identification means 5d may for example be a code provided
5 on the outer surface of the capsule.

The different capsule types 5, 5', 5'' as shown in fig. 7 preferably differ in their ingredient filling degree, in the compaction degree of the ingredients and/or in the
10 granulometry of the ingredients provided in the capsule. The capsules may further differ in their packaging material. The beverage process parameters and in particular at least the enclosing position of the respective capsule in the device may thus be specifically adapted to the particular capsule
15 type and its ingredients for providing optimal preparation parameters.

Claims

1. A beverage preparation device (100) for preparing a beverage upon interaction of ingredients provided in a capsule (5) with liquid supplied thereto, the device comprising:

an injection module (10) comprising a first (1) and a cooperating second enclosing member (2) designed for being moved relatively to each other, the first enclosing member being equipped with capsule opening and injection means (3) for opening a first inlet face (5a) of a capsule (5) and inject liquid into the capsule,

the first and second enclosing member (1,2) being designed for being brought into at least a first capsule insertion position for inserting a capsule between the enclosing members (1,2) and a second capsule enclosing position in which the opening and injection means (3) engage the liquid inlet face (5a) of the capsule (5),

characterized in that the device (100) further comprises control means (13) designed for adapting the capsule enclosing position adjusting a distance between the respective first and second enclosing members (1,2) to the capsule (5) inserted to the device (100) based on information read from the capsule and/or based on information provided by a user input.

2. The device according to claim 1, wherein the control means (13) are designed for adapting the enclosing position during a beverage preparation process with a capsule (5) in the device (100) based on information read from the capsule and/or based on information provided by a user input.

3. The device according to claim 1 or 2,
wherein the control means (13) are designed for a
penetration depth of the opening and injection means (3)
into the capsule (5) at least in the capsule enclosing
5 position.
4. The device according to any of the preceding claims,
wherein the first and second enclosing member (1,2) are
designed for being brought into at least a third capsule
10 injection position dependent on information read from the
capsule and/or based on information provided by a user input.
5. The device according to claim 4 or 5,
wherein a distance between the first and second capsule
15 enclosing member (1,2) in the capsule injection position is
greater than the distance (d) between the first and second
capsule enclosing members (1,2) in the capsule enclosing
position.
- 20 6. The device according to any of the preceding claims,
wherein the device comprises recognitions means (14)
connected to the control means (13) that are designed to
read information from the capsule (5) inserted into the
device.
- 25 7. The device according to claim 6,
wherein the recognition means (14) comprise an optical
sensor, an RFID sensor, a magnetic sensor, an electric sensor,
an inductive sensor, a mechanic sensor and/or a CCD sensor
30 suitable for interacting with identification means (5d)
provided on the capsule (5) and/or for sensing a
characterization of the capsule such as a shape and/or size
of the capsule (5) or of one of its constituting parts.

8. The device according to any of the preceding claims,
wherein the device comprises a user interface for
providing information as to the particular capsule type
(5,5',5'') inserted into the device.

5

9. The device according to any of the preceding claims,
wherein the first enclosing member (1) comprises a
shower plate (1a) comprising a plurality of protruding
hollow piercing elements such as needles as opening and
10 injection means (3) and/or wherein the second enclosing
member (2) comprises a support plate (2a) with a
plurality of protruding structures such as pyramids designed
to open an outlet face (5b) of the capsule (5) upon pressure
increase with the capsule.

15

10. A system for preparing a beverage comprising a beverage
preparation device (100) according to any of claim 1 to 9
and a capsule (5) containing a predefined amount of beverage
ingredients.

20

11. The system according to claim 10,
wherein the capsule (5) comprises identification means
(5d) and/or a characteristic designed to be read respectively
recognized by a sensor (14) of the device (100).

25

12. The system according to claim 10 or 11,
wherein the system comprises different types of
capsules (5,5'5'') which differ in their respective shape
and/or sizes, filling degrees, ingredient compaction
30 degree and/or ingredient granulometry, and which comprise
different information, e.g. on dedicated identification
means (5d), and/or comprise different characteristics

designed to be read respectively recognized by the beverage preparation device (100).

13. A method for preparing a beverage by means of capsule
5 (5) comprising beverage ingredients in a beverage preparation device (100), the method comprises the steps of:
- inserting a capsule (5) containing a predefined amount of beverage ingredients into the device (100),
 - 10 - reading information from the capsule (5) and/or recognizing a characteristic of the capsule,
 - bringing a first (1) and a cooperating second enclosing member (2) of an injection module (10) of the device (100) from a first capsule insertion position
15 into a second capsule enclosing position, in which opening and injection means (3) of the first enclosing member (1) engage and open a liquid inlet face (5a) of the capsule (5), wherein the enclosing position is adapted by adjusting a distance between the respective
20 first and second enclosing members (1,2) to the capsule (5) inserted to the device (100) based on information read from the capsule and/or based on information provided by a user input, and
 - injecting liquid into the capsule by means of the
25 opening and injection means (3).

14. The method of claim 13,
wherein the method further comprises the step of further adapting the enclosing position after an initial
30 opening of the inlet face (5a) of the capsule (5) and before injection of liquid into the capsule, and/or further adapting the enclosing position during the injection of liquid into the capsule.

15. The method of claim 13 or 14,
wherein the method further comprises the step of
increasing a distance (d) between the first and second
enclosing members (1,2) after the initial opening of the
5 inlet face (5a) of the capsule (5)